

Package ‘peakPantheR’

October 17, 2020

Title Peak Picking and Annotation of High Resolution Experiments

Version 1.2.0

Date 2020-04-05

Description An automated pipeline for the detection, integration and reporting of predefined features across a large number of mass spectrometry data files.

Depends R (>= 4.0)

Imports foreach (>= 1.4.4), doParallel (>= 1.0.11), ggplot2 (>= 2.2.1), gridExtra (>= 2.3), MSnbase (>= 2.4.0), mzR (>= 2.12.0), stringr (>= 1.2.0), methods (>= 3.4.0), XML (>= 3.98.1.10), minpack.lm (>= 1.2.1), scales(>= 0.5.0), utils

biocViews MassSpectrometry, Metabolomics, PeakDetection

License GPL-3

BugReports <https://github.com/phenomecentre/peakPantheR/issues/new>

URL <https://github.com/phenomecentre/peakPantheR>

Encoding UTF-8

LazyData false

RoxxygenNote 7.1.0

Suggests testthat, faahKO, msdata, knitr, rmarkdown, pandoc, BiocStyle

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/peakPantheR>

git_branch RELEASE_3_11

git_last_commit 2f1eba5

git_last_commit_date 2020-04-27

Date/Publication 2020-10-16

Author Arnaud Wolfer [aut, cre] (<<https://orcid.org/0000-0001-5856-3218>>),
Goncalo Correia [aut] (<<https://orcid.org/0000-0001-8271-9294>>),
Jake Pearce [ctb],
Caroline Sands [ctb]

Maintainer Arnaud Wolfer <adwolfer@gmail.com>

R topics documented:

acquisitionTime,peakPantheRAnnotation-method	3
annotationDiagnosticMultiplot	4
annotationDiagnosticPlots,peakPantheRAnnotation-method	4
annotationParamsDiagnostic,peakPantheRAnnotation-method	5
annotationTable,peakPantheRAnnotation-method	7
cpdID,peakPantheRAnnotation-method	8
cpdMetadata,peakPantheRAnnotation-method	9
cpdName,peakPantheRAnnotation-method	10
dataPoints,peakPantheRAnnotation-method	11
EICs,peakPantheRAnnotation-method	12
extractSignalRawData	13
filename,peakPantheRAnnotation-method	14
filepath,peakPantheRAnnotation-method	15
findTargetFeatures	16
FIR,peakPantheRAnnotation-method	18
fitCurve	19
generateIonChromatogram	20
getAcquisitionDateMzML	20
getTargetFeatureStatistic	21
integrateFIR	22
is.peakPantheR_curveFit	23
isAnnotated,peakPantheRAnnotation-method	23
nbCompounds,peakPantheRAnnotation-method	24
nbSamples,peakPantheRAnnotation-method	25
outputAnnotationDiagnostic,peakPantheRAnnotation-method	26
outputAnnotationParamsCSV,peakPantheRAnnotation-method	27
outputAnnotationResult,peakPantheRAnnotation-method	28
peakFit,peakPantheRAnnotation-method	29
peakPantheR	30
peakPantheRAnnotation	31
peakPantheR_loadAnnotationParamsCSV	36
peakPantheR_parallelAnnotation	37
peakPantheR_plotEICFit	40
peakPantheR_plotPeakwidth	41
peakPantheR_ROIStatistics	43
peakPantheR_singleFileSearch	44
peakTables,peakPantheRAnnotation-method	48
plotEICDetectedPeakwidth	49
plotHistogram	50
predictCurve	51
resetAnnotation,peakPantheRAnnotation-method	51
resetFIR,peakPantheRAnnotation-method	53
ROI,peakPantheRAnnotation-method	54
saveSingleFileMultiEIC	55
skewedGaussian_guess	56
skewedGaussian_minpack.lm	56
skewedGaussian_minpack.lm_objectiveFun	57
skew_erf	57
spectraMetadata,peakPantheRAnnotation-method	58
TIC,peakPantheRAnnotation-method	59

uROI,peakPantheRAnnotation-method	60
uROIExist,peakPantheRAnnotation-method	61
useFIR,peakPantheRAnnotation-method	62
useUROI,peakPantheRAnnotation-method	63
[,peakPantheRAnnotation,ANY,ANY,ANY-method	64

Index

65

acquisitionTime,peakPantheRAnnotation-method

acquisitionTime accessor returns value as *.POSIXct*

Description

acquisitionTime accessor returns value as POSIXct

Usage

```
## S4 method for signature 'peakPantheRAnnotation'  
acquisitionTime(object)
```

Arguments

object peakPantheRAnnotation

Value

(**POSIXct**) A character vector of acquisition date-time (converted from **POSIXct**) or NA

Examples

```

if(requireNamespace('faahKO')){
## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
## compounds

# Paths to spectra files
library(faahKO)
spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
targetFeatTable=targetFeatTable)

```

```
## acquisitionTime can only be extracted from NetCDF files
acquisitionTime(annotation)
# [1] NA NA NA
}
```

annotationDiagnosticMultiplot*Generate a multiplot of all diagnostic plots***Description**

Generate a multiplot of all diagnostic plots (as generated by `annotationDiagnosticPlots()`) for each compound

Usage

```
annotationDiagnosticMultiplot(annotationDiagnosticPlotList)
```

Arguments

```
annotationDiagnosticPlotList
  (list) List of (one per compound) of list of diagnostic plots as generated by
  annotationDiagnosticPlots()
```

Value

A list of multiplots (one per compound)

*annotationDiagnosticPlots,peakPantheRAnnotation-method**Generate fit diagnostic plots***Description**

Generate fit diagnostic plots for each ROI: EICFit the raw data and detected feature fit, rtPeakwidthVert detected peaks retention time apex and peakwidth (vertical and no run order), rtPeakwidthHorzRunOrder detected peaks retention time apex and peakwidth by run order, mzPeakwidthHorzRunOrder detected peaks m/z apex and peakwidth by run order, areaRunOrder detected peaks area by run order, rtHistogram histogram of detected peaks retention time, mzHistogram histogram of detected peaks m/z, areaHistogram histogram of detected peaks area.

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
annotationDiagnosticPlots(object,
  sampleColour, sampling, verbose)
```

Arguments

object	(peakPantheRAnnotation) Annotated peakPantheRAnnotation object
sampleColour	(str) NULL or vector colour for each sample
sampling	(int) Number of points to employ when plotting fittedCurve
verbose	(bool) if TRUE message the plot generation progress

Value

A list (one list per compound) of diagnostic plots: result[[i]]\$EICFit, result[[i]]\$rtPeakwidthVert, result[[i]]\$rtPeakwidthHorzRunOrder, result[[i]]\$mzPeakwidthHorzRunOrder, result[[i]]\$areaRunOrder, result[[i]]\$rtHistogram, result[[i]]\$mzHistogram, result[[i]]\$areaHistogram, result[[i]]\$title

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
                           522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
                           496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
                                      FUN.VALUE=numeric(2))

  emptyAnnotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
                                             targetFeatTable=targetFeatTable)

  annotationDiagnosticPlots(emptyAnnotation)
  # Warning: the object has not been annotated, return an empty diagnostic plot
  # list
  # [[1]]
  # NULL
  # [[2]]
  # NULL
}
```

Description

Set updated ROI (uROI) and Fallback Integration Regions (FIR) based on the annotation results. If the object is not annotated, it is returned untouched. ROI is not modified. If uROI exist they are left untouched, otherwise they are set as the minimum and maximum found peaks limits (+/-5% of ROI in retention time). If FIR are used they are left untouched, otherwise they are set as the median of the found limits (rtMin, rtMax, mzMin, mzMax).

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
annotationParamsDiagnostic(object,
                           verbose)
```

Arguments

object	(peakPantheRAnnotation) Annotated peakPantheRAnnotation object
verbose	(bool) If TRUE message progress of uROI and FIR calculation

Value

(peakPantheRAnnotation) object with updated ROI and FIR set from annotation results

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  emptyAnnotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
                                             targetFeatTable=targetFeatTable)

  annotationParamsDiagnostic(emptyAnnotation, verbose=TRUE)
  # Warning: the object has not been annotated, return the object untouched
  # An object of class peakPantheRAnnotation
  # 2 compounds in 3 samples.
  # updated ROI do not exist (uROI)
  # does not use updated ROI (uROI)
  # does not use fallback integration regions (FIR)
```

```
#  is not annotated
}
```

annotationTable,peakPantheRAnnotation-method
annotationTable accessor

Description

annotationTable returns a dataframe (row samples, col compounds) filled with a specific peakTable column

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
annotationTable(object, column)
```

Arguments

object	peakPantheRAnnotation
column	a peakTable columns

Value

(data.frame) (row samples, col compounds) filled with a specific peakTable column

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values without annotation
  annotationTable(annotation)
```

```

#                               ID-1  ID-2
# C:/R/R-3.6.0/library/faahK0/cdf/K0/ko15.CDF   NA   NA
# C:/R/R-3.6.0/library/faahK0/cdf/K0/ko16.CDF   NA   NA
# C:/R/R-3.6.0/library/faahK0/cdf/K0/ko18.CDF   NA   NA
}

```

cpdID,peakPantheRAnnotation-method
cpdID accessor

Description

cpdID accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
cpdID(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(str) A character vector of compound IDs, of length number of compounds

Examples

```

if(requireNamespace('faahK0')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahK0)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahK0'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin',
      'mz','mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  cpdID(annotation)
}
```

```
# [1] 'ID-1' 'ID-2'
}
```

cpdMetadata,peakPantheRAnnotation-method
cpdMetadata accessor

Description

cpdMetadata accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
cpdMetadata(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(data.frame) A data.frame of compound metadata, with compounds as row and metadata as columns

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values not initialised
  cpdMetadata(annotation)
  # data frame with 0 columns and 2 rows
}
```

cpdName , peakPantheRAnnotation-method
cpdName accessor

Description

cpdName accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
cpdName(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(str) A character vector of compound names, of length number of compounds

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  cpdName(annotation)
  # [1] 'Cpd 1' 'Cpd 2'
}
```

dataPoints,peakPantheRAnnotation-method
dataPoints accessor

Description

dataPoints accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
dataPoints(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

A list of length number of spectra files. Each list element is a *ROIsDataPoint* list of data.frame of raw data points for each ROI/uROI (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row))

Examples

```
if(requireNamespace('faahK0')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahK0)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahK0'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values without annotation
  dataPoints(annotation)
  # [[1]]
  # NULL
  # [[2]]
```

```
# NULL  
# [[3]]  
# NULL  
}
```

EICs,peakPantheRAnnotation-method *EICs accessor*

Description

EICs accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'  
EICs(object, aggregationFunction)
```

Arguments

object peakPantheRAnnotation
aggregationFunction
 (str) Function to use in order to aggregate intensities across mz in each scan.
 One of sum, max, min, mean

Value

(float) Extracted Ion Chromatogram aggregated across mz in each scan

Examples

```

if(requireNamespace('faahKO')){
## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
## compounds

# Paths to spectra files
library(faahKO)
spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
targetFeatTable=targetFeatTable)

```

```
## default values without annotation
EICs(annotation)
# [[1]]
# list()
# [[2]]
# list()
# [[3]]
# list()
}
```

`extractSignalRawData` *Extract signal in a multiple defined mz rt window from a raw data file*

Description

Extract all signal from multiple defined mz rt window from raw data and returns a data.frame. If no rt-mz window is provided, all signal in the raw data file are returned

Usage

```
extractSignalRawData(rawSpec, rt, mz, msLevel = 1L, verbose = TRUE)
```

Arguments

rawSpec	an OnDiskMSnExp-class
rt	(numeric(2) or two-column matrix) the lower and upper retention time range from which the data should be extracted. If a matrix is passed, each row corresponds to a different window. If not provided, the full retention time range will be extracted.
mz	(numeric(2) or two-column matrix) the lower and upper mass range from which the data should be extracted. If a matrix is passed, each row corresponds to a different window. If not provided, the full mass range will be extracted.
msLevel	(int) the MS level at which the data should be extracted (default to MS level 1)
verbose	(bool) If TRUE message progress and warnings

Details

```
## Examples cannot be computed as the function is not exported: ## Use a file form the faahKO package and extract data from a region of ## interest library(faahKO) rawSpec <- MSnbase::readMSData(system.file('cdf/KO/ko15.CDF', package='faahKO'), centroided=TRUE, mode='onDisk') dataPoints <- extractSignalRawData(rawSpec, rt = c(3290., 3410.), mz = c(522.194778, 522.205222), verbose=TRUE) # Reading data from 1 windows dataPoints # [[1]] # rt mz int # 1 3290.115 522.2 1824 # 2 3291.680 522.2 1734 # 3 3293.245 522.2 1572 # 4 3294.809 522.2 1440 # 5 3299.504 522.2 1008 # 6 3301.069 522.2 871 # 7 3302.634 522.2 786 # 8 3304.199 522.2 802 # 9 3305.764 522.2 834 # 10 3307.329 522.2 839 # 11 3315.154 522.2 2187 # 12 3316.719 522.2 3534 # 13 3318.284 522.2 6338 # 14 3319.849 522.2 11718 # 15 3321.414 522.2 21744 # 16 3322.979 522.2 37872 # 17 3324.544 522.2 62424 # 18 3326.109 522.2 98408 # 19 3327.673 522.2 152896 # 20 3329.238 522.2 225984 # 21 3330.803 522.2 308672 # 22 3332.368 522.2 399360 # 23 3333.933 522.2 504000 # 24 3335.498 522.2 614656 # 25 3337.063 522.2 711872 # 26 3338.628 522.2 784704 # 27 3340.193 522.2 836608 # 28 3341.758 522.2
```

```
866304 # 29 3343.323 522.2 882304 # 30 3344.888 522.2 889280 # 31 3346.453 522.2 888256 # 32
3348.018 522.2 866816 # 33 3349.583 522.2 827392 # 34 3351.148 522.2 777728 # 35 3352.713
522.2 727040 # 36 3354.278 522.2 678464 # 37 3355.843 522.2 629120 # 38 3357.408 522.2
578048 # 39 3358.973 522.2 524288 # 40 3360.538 522.2 471040 # 41 3362.102 522.2 416320 #
42 3363.667 522.2 360064 # 43 3365.232 522.2 302400 # 44 3366.797 522.2 249152 # 45 3368.362
522.2 202560 # 46 3369.927 522.2 161024 # 47 3371.492 522.2 123520 # 48 3373.057 522.2 93160
# 49 3374.622 522.2 71856 # 50 3376.187 522.2 58392 # 51 3377.752 522.2 51072 # 52 3379.317
522.2 48376 # 53 3380.882 522.2 49168 # 54 3382.447 522.2 53120 # 55 3384.012 522.2 62488 #
56 3385.577 522.2 78680 # 57 3387.142 522.2 102840 # 58 3388.707 522.2 134656 # 59 3390.272
522.2 173440 # 60 3391.837 522.2 217088 # 61 3393.402 522.2 268864 # 62 3394.966 522.2
330496 # 63 3396.531 522.2 395776 # 64 3398.096 522.2 453376 # 65 3399.661 522.2 499072 #
66 3401.226 522.2 537024 # 67 3402.791 522.2 570304 # 68 3404.356 522.2 592512 # 69 3405.921
522.2 598912 # 70 3407.486 522.2 595008 # 71 3409.051 522.2 588416
```

Value

a list (one entry per window) of data.frame with signal as row and retention time ('rt'), mass ('mz') and intensity ('int') as columns.

filename,peakPantheRAnnotation-method

filename accessor by splitting filepath

Description

filename accessor by splitting filepath

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
filename(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(str) filename

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
```

```

targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
  c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
  'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
  522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
  496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
  FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
  targetFeatTable=targetFeatTable)

filename(annotation)
# [1] 'ko15' 'ko16' 'ko18'
}

```

filepath,peakPantheRAnnotation-method*filepath accessor***Description**

filepath accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
filepath(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(str) A character vector of file paths, of length number of spectra files

Examples

```

if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
    system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
    system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
}
```

```

targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
                        522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
                        496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
                                    FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
                                       targetFeatTable=targetFeatTable)
filepath(annotation)
# [1] 'C:/R/R-3.6.0/library/faahK0/cdf/K0/ko15.CDF'
# [2] 'C:/R/R-3.6.0/library/faahK0/cdf/K0/ko16.CDF'
# [3] 'C:/R/R-3.6.0/library/faahK0/cdf/K0/ko18.CDF'
}

```

findTargetFeatures *Find and integrate target features in each ROI*

Description

For each ROI, fit a curve and integrate the largest feature in the box. Each entry in ROIsDataPoints must match the corresponding row in ROI. The curve shape to employ for fitting can be changed with curveModel while fitting parameters can be changed with params (list with one param per ROI window). rtMin and rtMax are established at 0.5 outward (the window is the ROI width); if after 8 iterations rtMin or rtMax is not found, NA is returned and the peak fit rejected. peakArea is calculated from rtMin to rtMax. mz is the weighted (by intensity) average mz of datapoints falling into the rtMin to rtMax range, mzMin and mzMax are the minimum and maximum mass in these range. If rtMin or rtMax falls outside of ROI (extracted scans), mzMin or mzMax are returned as the input ROI limits and mz is an approximation on the datapoints available (if no scan of the ROI fall between rtMin/rtMax, mz would be NA, the peak is rejected). If any of the two following ratio are superior to maxApexResidualRatio, the fit is rejected: 1) ratio of fit residuals at the apex (predicted apex fit intensity vs measured apex intensity: fit overshoots the apex), 2) ratio of predicted apex fit intensity vs maximum measured peak intensity (fit misses the real apex in the peak).

Usage

```
findTargetFeatures(ROIsDataPoints, ROI, curveModel = "skewedGaussian",
                  params = "guess", sampling = 250, maxApexResidualRatio = 0.2,
                  verbose = FALSE, ...)
```

Arguments

- | | |
|----------------|---|
| ROIsDataPoints | (list) A list (one entry per ROI window) of data.frame with signal as row and retention time ('rt'), mass ('mz') and intensity ('int) as columns. Must match each row of ROI. |
| ROI | (data.frame) A data.frame of compounds to target as rows. Columns: rtMin (float in seconds), rtMax (float in seconds), mzMin (float), mzMax (float) |
| curveModel | (str) Name of the curve model to fit (currently skewedGaussian) |
| params | (list or str) Either 'guess' for automated parametrisation or list (one per ROI windows) of 'guess' or list of curve fit parameters |

sampling	(int) Number of points to employ when subsampling the fittedCurve (rt, rtMin, rtMax, integral calculation)
maxApexResidualRatio	(float) Ratio of maximum allowed fit residual at the peak apex, compared to the fit max intensity. (e.g. 0.2 for a maximum residual of 20% of apex intensity)
verbose	(bool) If TRUE message the time taken and number of features found
...	Passes arguments to fitCurve to alter peak fitting (params)

Details

```
## Examples cannot be computed as the function is not exported: ## Load data library(faahKO) library(MSnbase) netcdfFilePath <- system.file('cdf/KO/ko15.CDF', package = 'faahKO') raw_data <- MSnbase::readMSData(netcdfFilePath,centroided=TRUE,mode='onDisk')

## targetFeatTable targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(), c('cpdID','cpdName','rtMin','mz','mzMax'))), stringsAsFactors=FALSE) targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778, 522.2, 522.205222) targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038, 496.2, 496.204962) targetFeatTable[,3:8] <- vapply(targetFeatTable[,3:8], as.numeric, FUN.VALUE=numeric(2))

ROIsPt <- extractSignalRawData(raw_data, rt=targetFeatTable[,c('rtMin','rtMax')], mz=targetFeatTable[,c('mzMin','mzMax')], verbose=TRUE) # Reading data from 2 windows

foundPeaks <- findTargetFeatures(ROIsPt, targetFeatTable, verbose=TRUE) # Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for # mzMin/mzMax calculation, # approximate mz and returning ROI$mzMin and ROI$mzMax for ROI #1 # Found 2/2 features in 0.07 secs

foundPeaks # $peakTable # found rtMin rt rtMax mzMin mz mzMax peakArea # 1 TRUE 3309.759 3346.828 3385.410 522.1948 522.2 522.2052 26133727 # 2 TRUE 3345.377 3386.529 3428.279 496.2000 496.2 496.2000 35472141 # maxIntMeasured maxIntPredicted # 1 889280 901015.8 # 2 1128960 1113576.7 # # $curveFit # $curveFit[[1]] # $amplitude # [1] 162404.8 # # $center # [1] 3341.888 # # $sigma # [1] 0.07878613 # # $gamma # [1] 0.00183361 # # $fitStatus # [1] 2 # # $curveModel # [1] 'skewedGaussian' # # attr('class') # [1] 'peakPantheR_curveFit' # # $curveFit[[2]] # $amplitude # [1] 199249.1 # # $center # [1] 3382.577 # # $sigma # [1] 0.07490442 # # $gamma # [1] 0.00114719 # # $fitStatus # [1] 2 # # $curveModel # [1] 'skewedGaussian' # # attr('class') # [1] 'peakPantheR_curveFit'
```

Value

A list: list()\$peakTable (*data.frame*) with targeted features as rows and peak measures as columns (see Details), list()\$curveFit (*list*) a list of peakPantheR_curveFit or NA for each ROI.

Details::: The returned *data.frame* is structured as follow:

found	was the peak found
rt	retention time of peak apex (sec)
rtMin	leading edge of peak retention time (sec) determined at 0.5% of apex intensity
rtMax	trailing edge of peak retention time (sec) determined at 0.5% of apex intensity
mz	weighted (by intensity) mean of peak m/z across scans
mzMin	m/z peak minimum (between rtMin, rtMax)
mzMax	m/z peak maximum (between rtMin, rtMax)
peakArea	integrated peak area
maxIntMeasured	maximum peak intensity in raw data
maxIntPredicted	maximum peak intensity based on curve fit (at apex)

FIR,peakPantheRAnnotation-method

FIR accessor returns targetFeatTable with cpdID, cpdName added

Description

FIR accessor returns targetFeatTable with cpdID, cpdName added

Usage

```
## S4 method for signature 'peakPantheRAnnotation'  
FIR(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(data.frame) target feature table with compounds as row and FIR parameters as columns

Examples

```
if(requireNamespace('faahKO')){  
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted  
  ## compounds  
  
  # Paths to spectra files  
  library(faahKO)  
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),  
                    system.file('cdf/K0/ko16.CDF', package = 'faahKO'),  
                    system.file('cdf/K0/ko18.CDF', package = 'faahKO'))  
  
  # targetFeatTable  
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),  
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',  
    'mzMax'))), stringsAsFactors=FALSE)  
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,  
                         522.2, 522.205222)  
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,  
                         496.2, 496.204962)  
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,  
    FUN.VALUE=numeric(2))  
  
  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,  
                                         targetFeatTable=targetFeatTable)  
  
  ## default values without annotation  
  FIR(annotation)  
  #   rtMin rtMax mzMin mzMax cpdID cpdName  
  # 1     NA     NA     NA     NA  ID-1    Cpd 1  
  # 2     NA     NA     NA     NA  ID-2    Cpd 2  
  }
```

fitCurve*Curve fitting using minpack.lm***Description**

Fit different curve models using `minpack`. Fitting parameters can be passed or guessed.

Usage

```
fitCurve(x, y, curveModel = "skewedGaussian", params = "guess")
```

Arguments

<code>x</code>	(numeric) x values (e.g. retention time)
<code>y</code>	(numeric) y observed values (e.g. spectra intensity)
<code>curveModel</code>	(str) name of the curve model to fit (currently <code>skewedGaussian</code>)
<code>params</code>	(list or str) either 'guess' for automated parametrisation or list of initial parameters (<code>\$init_params</code>), lower parameter bounds (<code>\$lower_bounds</code>) and upper parameter bounds (<code>\$upper_bounds</code>)

Details

```
## Examples cannot be computed as the function is not exported: ## x is retention time, y corresponding intensity
input_x <- c(3362.102, 3363.667, 3365.232, 3366.797, 3368.362, 3369.927, 3371.492, 3373.057, 3374.622, 3376.187, 3377.752, 3379.317, 3380.882, 3382.447, 3384.012, 3385.577, 3387.142, 3388.707, 3390.272, 3391.837, 3393.402, 3394.966, 3396.531, 3398.096, 3399.661, 3401.226, 3402.791, 3404.356, 3405.921, 3407.486, 3409.051)
input_y <- c(51048, 81568, 138288, 233920, 376448, 557288, 753216, 938048, 1091840, 1196992, 1261056, 1308992, 1362752, 1406592, 1431360, 1432896, 1407808, 1345344, 1268480, 1198592, 1126848, 1036544, 937600, 849792, 771456, 692416, 614528, 546088, 492752, 446464, 400632)

## Fit fitted_curve <- fitCurve(input_x, input_y, curveModel='skewedGaussian', params='guess')

## Returns the optimal fitting parameters
fitted_curve # # $amplitude # [1] 275371.1 # # $center # [1] 3382.577 # # $sigma # [1] 0.07904697 # # $gamma # [1] 0.001147647 # # $fitStatus # [1] 2 # # $curveModel # [1] 'skewedGaussian' # # attr('class') # [1] 'peakPantheR_curveFit'
```

Value

A 'peakPantheR_curveFit': a list of fitted curve parameters, `fitStatus` from `nls.lm$info` and curve shape name `curveModel`. `fitStatus=0` unsuccessful completion: improper input parameters, `fitStatus=1` successful completion: first convergence test is successful, `fitStatus=2` successful completion: second convergence test is successful, `fitStatus=3` successful completion: both convergence test are successful, `fitStatus=4` questionable completion: third convergence test is successful but should be carefully examined (maximizers and saddle points might satisfy), `fitStatus=5` unsuccessful completion: excessive number of function evaluations/iterations

generateIonChromatogram

Generate ion chromatogram from raw data points

Description

On the input raw data, aggregate intensities across the mz range at each retention time to generate an ion chromatogram: sum for EIC/TIC, max, min or mean. The number of data points returned correspond to the number of unique scans/retention time measurements in the input data

Usage

```
generateIonChromatogram(ROIDataPoint, aggregationFunction = "sum")
```

Arguments

ROIDataPoint	(data.frame) retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row) to use for the ion chromatogram
aggregationFunction	(str) Function to use in order to aggregate intensities across mz in each scan. One of sum, max, min, mean

Details

```
## Examples cannot be computed as the function is not exported: ## Input data points in_rt <- c(3362.102, 3362.102, 3363.667, 3363.667, 3365.232, 3365.232, 3366.797, 3366.797, 3368.362, 3368.362) in_mz <- c(496.2, 497.2, 496.2, 497.2, 496.2, 497.2, 496.2, 497.2, 496.2, 497.2) in_int <- c(39616, 11432, 63344, 18224, 107352, 30936, 182144, 51776, 295232, 81216) input_ROIDataPoints <- data.frame(rt=in_rt, mz=in_mz, int=in_int)

## Aggregate mz to generate EIC EIC <- generateIonChromatogram(input_ROIDataPoints,aggregationFunction='sum')
EIC # rt int # 1 3362.102 51048 # 2 3363.667 81568 # 3 3365.232 138288 # 4 3366.797 233920 #
5 3368.362 376448
```

Value

A data.frame of retention time 'rt' and aggregated intensities 'int'

getAcquisitionDateMzML

Parse acquisition date from a mzML file

Description

Extract acquisition date ("startTimeStamp") from a mzML file. In case of failure (or the file is not a mzML) returns NULL

Usage

```
getAcquisitionDateMzML(mzMLPath, verbose = TRUE)
```

Arguments

mzMLPath	(str) path to mzML raw data file
verbose	(bool) if TRUE message progress

Value

POSIXct or NA

getTargetFeatureStatistic

*Calculate chromatographic peak properties***Description**

Calculate the ppm error, retention time deviation, tailing factor and asymmetry factor for each measured feature.

Usage

```
getTargetFeatureStatistic(fittedCurves, targetFeatTable, foundPeakTable,
                         verbose = FALSE)
```

Arguments

fittedCurves	(list) A list (one entry per ROI window) of peakPantheR_curveFit or NA
targetFeatTable	a data.frame of compounds to target as rows. Columns: cpdID (str), cpdName (str), rtMin (float in seconds), rt (float in seconds, or NA), rtMax (float in seconds), mzMin (float), mz (float or NA), mzMax (float).
foundPeakTable	a data.frame as generated by findTargetFeatures , with features as rows and peak properties as columns. The following columns are mandatory: mzMin, mz, mzMax, rtMin, rt, rtMax
verbose	(bool) if TRUE message when NA scans are removed

Details

```
## Examples cannot be computed as the function is not exported: # fittedCurve cFit1 <- list(amplitude=162404.80579182
center=3341.888, sigma=0.078786133031045896, gamma=0.0018336101984172684, fitStatus=2,
curveModel='skewedGaussian') class(cFit1)<- 'peakPantheR_curveFit' cFit2 <- list(amplitude=199249.10572753669,
center=3382.577, sigma=0.074904415304607966, gamma=0.0011471899372353885, fitStatus=2,
curveModel='skewedGaussian') class(cFit2)<- 'peakPantheR_curveFit' input_fitCurves <- list(cFit1,
cFit2)
# ROI input_ROI <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(), c('cpdID', 'cpdName', 'rt-
Min', 'rt', 'rtMax', 'mzMin', 'mz', 'mzMax'))), stringsAsFactors=FALSE) input_ROI[1,] <- c('ID-
1', 'testCpd 1', 3310., 3344.88, 3390., 522.19, 522.2, 522.21) input_ROI[2,] <- c('ID-2', 'testCpd
2', 3280., 3385.58, 3440., 496.19, 496.2, 496.21) input_ROI[,3:8] <- vapply(input_ROI[,3:8], as.numeric,
FUN.VALUE=numeric(2))
# foundPeakTable input_foundPeakTable <- data.frame(matrix(vector(), 2, 10, dimnames=list(c(),
c('found', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz', 'mzMax', 'peakArea', 'maxIntMeasured','maxIntPredicted'))),
```

```
stringsAsFactors=FALSE) input_foundPeakTable[1,] <- c(TRUE, 3309.758, 3346.827, 3385.410,
522.19, 522.2, 522.21, 26133726, 889280, 901015) input_foundPeakTable[2,] <- c(TRUE, 3345.376,
3386.529, 3428.279, 496.19, 496.2, 496.21, 35472141, 1128960, 1113576) input_foundPeakTable[,1]
<- vapply(input_foundPeakTable[,c(1)], as.logical, FUN.VALUE=logical(1))

# Run peak statistics peakStatistics <- getTargetFeatureStatistic(input_fitCurves, input_ROI, in-
put_foundPeakTable) peakStatistics # found rtMin rt rtMax mzMin mz mzMax peakArea # 1 TRUE
3309.758 3346.827 3385.410 522.19 522.2 522.21 26133726 # 2 TRUE 3345.376 3386.529 3428.279
496.19 496.2 496.21 35472141 # maxIntMeasured maxIntPredicted ppm_error rt_dev_sec tailing-
Factor # 1 889280 901015 0 1.947 1.015385 # 2 1128960 1113576 0 0.949 1.005372 # asymmetry-
Factor # 1 1.026886 # 2 1.009304
```

Value

A `data.frame` with measured compounds as rows and measurements and properties as columns (see Details).

Details::: The returned `data.frame` is structured as follow:

found	was the peak found
rt	retention time of peak apex (sec)
rtMin	leading edge of peak retention time (sec) determined at 0.5% of apex intensity
rtMax	trailing edge of peak retention time (sec) determined at 0.5% of apex intensity
mz	weighted (by intensity) mean of peak m/z across scans
mzMin	m/z peak minimum (between rtMin, rtMax)
mzMax	m/z peak maximum (between rtMin, rtMax)
peakArea	integrated peak area
maxIntMeasured	maximum peak intensity in raw data
maxIntPredicted	maximum peak intensity based on curve fit
ppm_error	difference in ppm between the expected and measured m/z
rt_dev_sec	difference in seconds between the expected and measured rt
tailingFactor	the tailing factor is a measure of peak tailing. It is defined as the distance from the front slope of the p
asymmetryFactor	the asymmetry factor is a measure of peak tailing. It is defined as the distance from the center line of t

integrateFIR

Integrate fallback integration regions

Description

Integrate region defined in FIR if a feature is not found

Usage

```
integrateFIR(rawSpec, FIR, foundPeakTable, verbose = TRUE)
```

Arguments

rawSpec	an OnDiskMSnExp-class
FIR	(data.frame) Fallback Integration Regions (FIR) to integrate when a feature is not found. Compounds as row are identical to the targeted features, columns are <code>rtMin</code> (float in seconds), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mzMax</code> (float)

`foundPeakTable` a `data.frame` as generated by `findTargetFeatures`, with features as rows and peak properties as columns. The following columns are mandatory: `found`, `is_filled`, `mz`, `mzMin`, `mzMax`, `rt`, `rtMin`, `rtMax`, `peakArea`, `maxIntMeasured`, `maxIntPredicted`.

`verbose` (bool) if TRUE message progress

Value

an updated `foundPeakTable` with FIR integration values

`is.peakPantheR_curveFit`

Check if object is of class peakPantheR_curveFit

Description

Check if object is of class `peakPantheR_curveFit`

Usage

`is.peakPantheR_curveFit(x)`

Arguments

`x` object to test

Value

(bool) TRUE or FALSE

`isAnnotated,peakPantheRAnnotation-method`
isAnnotated accessor

Description

isAnnotated accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
isAnnotated(object)
```

Arguments

`object` `peakPantheRAnnotation`

Value

(bool) flag if the annotation has taken place

Examples

```

if(requireNamespace('faahKO')){
## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
## compounds

# Paths to spectra files
library(faahKO)
spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
targetFeatTable=targetFeatTable)

isAnnotated(annotation)
# [1] FALSE
}

```

nbCompounds,peakPantheRAnnotation-method
nbCompounds accessor established on cpdID

Description

nbCompounds accessor established on cpdID

Usage

```

## S4 method for signature 'peakPantheRAnnotation'
nbCompounds(object)

```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(int) number of samples

Examples

```

if(requireNamespace('faahK0')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahK0)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahK0'),
                      system.file('cdf/K0/ko16.CDF', package = 'faahK0'),
                      system.file('cdf/K0/ko18.CDF', package = 'faahK0'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  nbCompounds(annotation)
  # [1] 2
}

```

nbSamples,peakPantheRAnnotation-method

nbSamples accessor established on filepath

Description

nbSamples accessor established on filepath

Usage

```

## S4 method for signature 'peakPantheRAnnotation'
nbSamples(object)

```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(int) number of samples

Examples

```

if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
      'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  nbSamples(annotation)
  # [1] 3
}

```

outputAnnotationDiagnostic,peakPantheRAnnotation-method

Save to disk the annotation parameters as CSV and a diagnostic plot per fitted compound

Description

Save to disk the annotation parameters as CSV (as generated by `outputAnnotationParamsCSV()`) and a diagnostic plot per fitted compound (as generated by `annotationDiagnosticMultiplot()`) if `savePlots` is TRUE

Usage

```

## S4 method for signature 'peakPantheRAnnotation'
outputAnnotationDiagnostic(object,
  saveFolder, savePlots = TRUE, sampleColour = NULL, verbose = TRUE,
  ncores = 0, ...)

```

Arguments

object	(<code>peakPantheRAnnotation</code>) Annotated <code>peakPantheRAnnotation</code> object
saveFolder	(str) Path of folder where <code>annotationParameters_summary.csv</code> and plots will be saved

savePlots	(bool) If TRUE save a diagnostic plot for each compound
sampleColour	(str) NULL or vector colour for each sample
verbose	(bool) If TRUE message progress
ncores	(int) Number of cores to use to save plots in parallel
...	Additional parameters for plotting i.e. sampling for the number of points to employ when plotting fittedCurve

Value

None

Examples

```

if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  emptyAnnotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
                                             targetFeatTable=targetFeatTable)

  # Calculate annotation
  annotation <- peakPantheR_parallelAnnotation(emptyAnnotation, ncores=0,
                                                 getAcquTime=FALSE, verbose=FALSE)$annotation

  # temporary location
  savePath1      <- tempdir()
  outputAnnotationDiagnostic(annotation, saveFolder=savePath1, savePlots=FALSE,
                             verbose=TRUE)
}

```

Description

Save annotation parameters (ROI, uROI and FIR) to disk as a CSV file for editing

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
outputAnnotationParamsCSV(object,
                           saveFolder, verbose)
```

Arguments

object	(peakPantheRAnnotation) Annotated peakPantheRAnnotation object
saveFolder	(str) Path of folder where annotationParameters_summary.csv will be saved
verbose	(bool) If TRUE message progress

Value

None

outputAnnotationResult,peakPantheRAnnotation-method

Save to disk all annotation results as csv files

Description

Save to disk all annotation results as annotationName_csv files: compound metadata (cpdMetadata, cpdID, cpdName) and spectra metadata (spectraMetadata, acquisitionTime, TIC), summary of fit (ratio of peaks found: ratio_peaks_found, ratio of peaks filled: ratio_peaks_filled, mean ppm_error: ppm_error, mean rt_dev_sec: rt_dev_sec), and a file for each column of peakTables (with samples as rows and compounds as columns)

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
outputAnnotationResult(object,
                       saveFolder, annotationName = "annotationResult", verbose = TRUE)
```

Arguments

object	(peakPantheRAnnotation) Annotated peakPantheRAnnotation object
saveFolder	(str) Path of folder where the annotation result csv will be saved
annotationName	(str) name of annotation to use in the saved csv
verbose	(bool) If TRUE message progress

Value

None

Examples

```

if(requireNamespace('faahKO')){
## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
## compounds

# Paths to spectra files
library(faahKO)
spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                   system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
FUN.VALUE=numeric(2))

emptyAnnotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
                                         targetFeatTable=targetFeatTable)

# Calculate annotation
annotation      <- peakPantheR_parallelAnnotation(emptyAnnotation, ncores=0,
                                                 getAcquTime=FALSE, verbose=FALSE)$annotation

# temporary location
savePath1       <- tempdir()
outputAnnotationResult(annotation, saveFolder=savePath1,
                        annotationName='testProject', verbose=TRUE)
}

```

peakFit,peakPantheRAnnotation-method
peakFit accessor

Description

peakFit accessor

Usage

```

## S4 method for signature 'peakPantheRAnnotation'
peakFit(object)

```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

A list of length number of spectra files. Each list element is a *curveFit* list of `peakPantheR_curveFit` or NA for each ROI

Examples

```
if(requireNamespace('faahK0')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahK0)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahK0'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahK0'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values without annotation
  peakFit(annotation)
  # [[1]]
  # NULL
  # [[2]]
  # NULL
  # [[3]]
  # NULL
}
```

Description

peakPantheR detects, integrates and reports pre-defined features in mass spectrometry data files. It enables the real time annotation of multiple compounds in a single file, or the parallel annotation of multiple compounds in multiple files.

Details

The main functions of **peakPantheR** are `peakPantheR_singleFileSearch` for realtime annotation, and `peakPantheR_parallelAnnotation` for parallel annotation. The `peakPantheRAnnotation` object stores parallel annotation results, while reporting functions help assess and the quality of annotation and update fitting parameters. Refer to the vignettes for graphical user interface and command line tutorials.

Author(s)

Maintainer: Arnaud Wolfer <adwolfer@gmail.com> ([ORCID](#))

Authors:

- Goncalo Correia <gscorreia89@gmail.com> ([ORCID](#))

Other contributors:

- Jake Pearce <jake.pearce@gmail.com> [contributor]
- Caroline Sands <caz119@hotmail.co.uk> [contributor]

See Also

Useful links:

- <https://github.com/phenomecentre/peakPantheR>
- Report bugs at <https://github.com/phenomecentre/peakPantheR/issues/new>

`peakPantheRAnnotation` *An S4 class to represent peakPantheR annotation results*

Description

The `peakPantheRAnnotation` class is designed to run and store `peakPantheR` parallel annotation results. Instances of the class are created with the `peakPantheRAnnotation` constructor function, which initialises an object of proper dimension with `spectraPaths` (set samples to process) and `targetFeatTable` (set compounds to target). `spectraPaths` is a character vector of spectra file paths. `targetFeatTable` is a `data.frame` of compounds to target as rows and parameters as columns: `cpdID` (int), `cpdName` (str), `rtMin` (float in seconds), `rt` (float in seconds, or `NA`), `rtMax` (float in seconds), `mzMin` (float), `mz` (float or `NA`), `mzMax` (float).

`peakPantheRAnnotation()`: create an instance of the `peakPantheRAnnotation` class.

Usage

```
peakPantheRAnnotation(spectraPaths = NULL, targetFeatTable = NULL,
                      cpdID = character(), cpdName = character(), ROI = data.frame(rtMin =
                      = numeric(), rt = numeric(), rtMax = numeric(), mzMin = numeric(), mz =
                      numeric(), mzMax = numeric(), stringsAsFactors = FALSE),
                      FIR = data.frame(rtMin = numeric(), rtMax = numeric(), mzMin =
                      numeric(), mzMax = numeric(), stringsAsFactors = FALSE),
                      uROI = data.frame(rtMin = numeric(), rt = numeric(), rtMax = numeric(),
                      mzMin = numeric(), mz = numeric(), mzMax = numeric(), stringsAsFactors =
                      FALSE), filepath = character(), cpdMetadata = data.frame(),
```

```

spectraMetadata = data.frame(), acquisitionTime = character(),
uROIExist = FALSE, useUROI = FALSE, useFIR = FALSE,
TIC = numeric(), peakTables = list(), dataPoints = list(),
peakFit = list(), isAnnotated = FALSE)

peakPantheRAnnotation(spectraPaths = NULL, targetFeatTable = NULL,
cpdID = character(), cpdName = character(), ROI = data.frame(rtMin
= numeric(), rt = numeric(), rtMax = numeric(), mzMin = numeric(), mz =
numeric(), mzMax = numeric(), stringsAsFactors = FALSE),
FIR = data.frame(rtMin = numeric(), rtMax = numeric(), mzMin =
numeric(), mzMax = numeric(), stringsAsFactors = FALSE),
uROI = data.frame(rtMin = numeric(), rt = numeric(), rtMax = numeric(),
mzMin = numeric(), mz = numeric(), mzMax = numeric(), stringsAsFactors =
FALSE), filepath = character(), cpdMetadata = data.frame(),
spectraMetadata = data.frame(), acquisitionTime = character(),
uROIExist = FALSE, useUROI = FALSE, useFIR = FALSE,
TIC = numeric(), peakTables = list(), dataPoints = list(),
peakFit = list(), isAnnotated = FALSE)

```

Arguments

spectraPaths	NULL or a character vector of spectra file paths, to set samples to process
targetFeatTable	NULL or a <code>data.frame</code> of compounds to target as rows and parameters as columns: <code>cpdID</code> (str), <code>cpdName</code> (str), <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or <code>NA</code>), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or <code>NA</code>), <code>mzMax</code> (float). Set compounds to target.
cpdID	A character vector of compound IDs, of length number of compounds
cpdName	A character vector of compound names, of length number of compounds
ROI	A <code>data.frame</code> of Regions Of Interest (ROI) with compounds as row and ROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or <code>NA</code>), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or <code>NA</code>), <code>mzMax</code> (float).
FIR	A <code>data.frame</code> of Fallback Integration Regions (FIR) with compounds as row and FIR parameters as columns: <code>rtMin</code> (float in seconds), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mzMax</code> (float).
uROI	A <code>data.frame</code> of updated Regions Of Interest (uROI) with compounds as row and uROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or <code>NA</code>), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or <code>NA</code>), <code>mzMax</code> (float).
filepath	A character vector of file paths, of length number of spectra files
cpdMetadata	A <code>data.frame</code> of compound metadata, with compounds as row and metadata as columns
spectraMetadata	A <code>data.frame</code> of sample metadata, with samples as row and metadata as columns
acquisitionTime	A character vector of acquisition date-time (converted from <code>POSIXct</code>) or <code>NA</code>
uROIExist	A logical stating if uROI have been set
useUROI	A logical stating if uROI are to be used
useFIR	A logical stating if FIR are to be used
TIC	A numeric vector of TIC or <code>NA</code> , of length number of spectra files

peakTables	A list of peakTable data.frame, of length number of spectra files. Each peakTable data.frame has compounds as rows and peak annotation results as columns.
dataPoints	A list of length number of spectra files. Each list element is a <i>ROIsDataPoint</i> list of data.frame of raw data points for each ROI/uROI (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row))
peakFit	A list of length number of spectra files. Each list element is a <i>curveFit</i> list of peakPantheR_curveFit or NA for each ROI
isAnnotated	A logical stating in the annotation took place

Details

The `validObject` method ensures the conformity of an object to the `peakPantheRAnnotation`-class. The number of compounds is based on `cpdID()` length, and the number of samples is based on `filepath()` length. Slot type is not checked as `setClass` enforces it. `peakTables` and `EICs` type are checked on the first list element. `annotationTable(object, column)` where *column* is a column from *peakTable*, returns a data.frame of values with the samples as rows, ROI as columns.

Value

(`peakPantheRAnnotation`)

Slots

cpdID	A character vector of compound IDs, of length number of compounds
cpdName	A character vector of compound names, of length number of compounds
ROI	A data.frame of Regions Of Interest (ROI) with compounds as row and ROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or NA), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or NA), <code>mzMax</code> (float).
FIR	A data.frame of Fallback Integration Regions (FIR) with compounds as row and FIR parameters as columns: <code>rtMin</code> (float in seconds), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mzMax</code> (float).
uROI	A data.frame of updated Regions Of Interest (uROI) with compounds as row and uROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or NA), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or NA), <code>mzMax</code> (float).
filepath	A character vector of file paths, of length number of spectra files
cpdMetadata	A data.frame of compound metadata, with compounds as row and metadata as columns
spectraMetadata	A data.frame of sample metadata, with samples as row and metadata as columns
acquisitionTime	A character vector of acquisition date-time (converted from POSIXct) or NA
uROIExist	A logical stating if uROI have been set
useUROI	A logical stating if uROI are to be used
useFIR	A logical stating if FIR are to be used
TIC	A numeric vector of TIC or NA, of length number of spectra files
peakTables	A list of peakTable data.frame, of length number of spectra files. Each peakTable data.frame has compounds as rows and peak annotation results as columns.
dataPoints	A list of length number of spectra files. Each list element is a <i>ROIsDataPoint</i> list of data.frame of raw data points for each ROI/uROI (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row))

`peakFit` A list of length number of spectra files. Each list element is a `curveFit` list of `peakPantheR_curveFit` or NA for each ROI

`isAnnotated` A logical stating if the annotation has taken place

Details:: The *peakTables* data.frame are structured as follow:

cpdID	database compound ID
cpdName	compound name
found	was the peak found
rt	retention time of peak apex (sec)
rtMin	leading edge of peak retention time (sec) determined at 0.5% of apex intensity
rtMax	trailing edge of peak retention time (sec) determined at 0.5% of apex intensity
mz	weighted (by intensity) mean of peak m/z across scans
mzMin	m/z peak minimum (between rtMin, rtMax)
mzMax	m/z peak maximum (between rtMin, rtMax)
peakArea	integrated peak area
maxIntMeasured	maximum peak intensity in raw data
maxIntPredicted	maximum peak intensity based on curve fit
is_filled	Logical indicate if the feature was integrated using FIR (Fallback Integration Region)
ppm_error	difference in ppm between the expected and measured m/z
rt_dev_sec	difference in seconds between the expected and measured rt
tailingFactor	the tailing factor is a measure of peak tailing. It is defined as the distance from the front slope of the peak to the baseline.
asymmetryFactor	the asymmetry factor is a measure of peak tailing. It is defined as the distance from the center line of the peak to the baseline.

See Also

Other peakPantheR: [peakPantheR_parallelAnnotation](#), [peakPantheR_singleFileSearch](#)

Other parallelAnnotation: `peakPantheR_parallelAnnotation`, `peakPantheR_singleFileSearch`

Examples

```

annotation
# An object of class peakPantheRAnnotation
# 2 compounds in 3 samples.
# updated ROI do not exist (uROI)
# does not use updated ROI (uROI)
# does not use fallback integration regions (FIR)
# is not annotated

slotNames(annotation)
# [1] 'cpdID'      'cpdName'      'ROI'          'FIR'          'uROI'
# [6] 'filepath'    'cpdMetadata'  'spectraMetadata' 'acquisitionTime'
# [10] 'uROIExist'   'useUROI'     'useFIR'       'TIC'          'peakTables'
# [15] 'dataPoints'  'peakFit'     'isAnnotated'

## Slots shouldn't be accessed directly, accessors are available:
cpdID(annotation)
# [1] 'ID-1' 'ID-2'
cpdName(annotation)
# [1] 'Cpd 1' 'Cpd 2'
ROI(annotation)
#   rtMin      rt rtMax      mz      mzMax cpdID cpdName
# 1 3310 3344.888 3390 522.1948 522.2 522.2052 ID-1 Cpd 1
# 2 3280 3385.577 3440 496.1950 496.2 496.2050 ID-2 Cpd 2
FIR(annotation)
#   rtMin rtMax mzMin mzMax cpdID cpdName
# 1     NA     NA     NA     NA ID-1 Cpd 1
# 2     NA     NA     NA     NA ID-2 Cpd 2
uROI(annotation)
#   rtMin rt rtMax mzMin mz mzMax cpdID cpdName
# 1     NA NA     NA     NA NA     NA ID-1 Cpd 1
# 2     NA NA     NA     NA NA     NA ID-2 Cpd 2
filepath(annotation)
# [1] 'C:/R/R-3.6.0/library/faahKO/cdf/KO/ko15.CDF'
# [2] 'C:/R/R-3.6.0/library/faahKO/cdf/KO/ko16.CDF'
# [3] 'C:/R/R-3.6.0/library/faahKO/cdf/KO/ko18.CDF'
cpdMetadata(annotation)
# data frame with 0 columns and 2 rows
spectraMetadata(annotation)
# data frame with 0 columns and 3 rows
acquisitionTime(annotation)
# [1] NA NA NA
uROIExist(annotation)
# [1] FALSE
useUROI(annotation)
# [1] FALSE
useFIR(annotation)
# [1] FALSE
TIC(annotation)
# [1] NA NA NA
peakTables(annotation)
# [[1]]
# NULL
# [[2]]
# NULL
# [[3]]
# NULL

```

```

dataPoints(annotation)
# [[1]]
# NULL
# [[2]]
# NULL
# [[3]]
# NULL
peakFit(annotation)
# [[1]]
# NULL
# [[2]]
# NULL
# [[3]]
# NULL
isAnnotated(annotation)
# [1] FALSE
}

```

peakPantheR_loadAnnotationParamsCSV*Load fit parameters from CSV***Description**

Initialise a new peakPantheRAnnotation object after loading ROI, uROI and FIR parameters from CSV. spectraPaths, spectraMetadata or cpdMetadata are not initialised and will need to be filled before annotation. useUROI and useFIR are set to FALSE and will need to be set accordingly. uROIEexist is established depending on the uROI columns present in the CSV and will be set to TRUE only if no NA are present

Usage

```
peakPantheR_loadAnnotationParamsCSV(CSVParamPath, verbose = TRUE)
```

Arguments

CSVParamPath	(str) Path to a CSV file of fit parameters as saved by outputAnnotationDiagnostic
verbose	(bool) If TRUE message progress

Value

(peakPantheRAnnotation) Object initialised with ROI, uROI and FIR read from the CSV file

Examples

```

## Input data
input_CSV <- data.frame(matrix(nrow=2, ncol=21, dimnames=list(c(),
c('cpdID', 'cpdName',
'X','ROI_rt', 'ROI_mz', 'ROI_rtMin', 'ROI_rtMax','ROI_mzMin','ROI_mzMax',
'X','uROI_rtMin', 'uROI_rtMax', 'uROI_mzMin', 'uROI_mzMax', 'uROI_rt',
'uROI_mz', 'X', 'FIR_rtMin', 'FIR_rtMax', 'FIR_mzMin', 'FIR_mzMax'))))
input_CSV[1,] <- c('ID-1', 'Cpd 1', '|', 1., 2., 3., 4., 5., 6., '|',

```

```

    7., 8., 9., 10., 11., 12., '|', 13., 14., 15., 16.)
input_CSV[2,] <- c('ID-2', 'Cpd 2', '|', 17., 18., 19., 20., 21., 22., '|',
                  23., 24., 25., 26., 27., 28., '|', 29., 30., 31., 32.)
input_CSV[,-c(1,2,3,10,17)] <- vapply(input_CSV[,-c(1,2,3,10,17)],
                                         as.numeric, FUN.VALUE=numeric(2))

# temporary file location
savePath1 <- tempfile(pattern='file', tmpdir=tempdir(), fileext='.csv')
# save csv
utils::write.csv(input_CSV, file=savePath1, row.names=FALSE)

# Load parameters from CSV
loadedAnnotation <- peakPantheR_loadAnnotationParamsCSV(savePath1,
                                                          verbose=TRUE)
# uROIExist set to TRUE
# New peakPantheRAnnotation object initialised for 2 compounds
# An object of class peakPantheRAnnotation
# 2 compounds in 0 samples.
# updated ROI exist (uROI)
# does not use updated ROI (uROI)
# does not use fallback integration regions (FIR)
# is not annotated

```

peakPantheR_parallelAnnotation*Search, integrate and report targeted features in a multiple spectra***Description**

Integrate all target features in all files defined in the initialised input object and store results. The use of updated ROI and the integration of FIR are controled by the input object slots `useUROI` and `useFIR`. Files are processed in parallel using [peakPantheR_singleFileSearch](#); `ncores` controls the number of cores used for parallelisation, with `ncores=0` corresponding to serial processing. If the processing of a file fails (file does not exist or error during execution) the sample is removed from the outputed object.

Usage

```
peakPantheR_parallelAnnotation(object, ncores = 0, getAcquTime = TRUE,
                               resetWorkers = 1, centroided = TRUE, verbose = TRUE, ...)
```

Arguments

<code>object</code>	(<code>peakPantheRAnnotation</code>) Initialised <code>peakPantheRAnnotation</code> object defining the samples to process and compounds to target. The slots <code>useUROI</code> and <code>useFIR</code> controls if <code>uROI</code> must be used and <code>FIR</code> integrated if a feature is not found
<code>ncores</code>	(int) Number of cores to use for parallelisation. Default 0 for no parallelisation.
<code>getAcquTime</code>	(bool) If TRUE will extract sample acquisition date-time from the mzML metadata (the additional file access will impact run time)
<code>resetWorkers</code>	(int) If 0, the parallel cluster is only initiated once. If >0 the cluster will be reset (and the memory of each worker freed) once <code>ncores * resetWorkers</code> files have been processed. Default value is 1, the cluster is reset once <code>ncores</code> files have

been processed. While potentially impacting performance (need to wait until all ncores * resetWorkers files are processed before restarting the cluster), shutting down the workers processes regularly will ensure the OS can reallocate memory more efficiently. For values >1, ensure sufficient system memory is available

centroided	(bool) use TRUE if the data is centroided, used by readMSData when reading the raw data files
verbose	(bool) If TRUE message calculation progress, time taken, number of features found (total and matched to targets) and failures
...	Passes arguments to findTargetFeatures to alter peak-picking parameters

Value

a list: `list()$result` (*peakPantheRAnnotation*) fully annotated object, `list()$failures` (*list*) list of failed samples and error message

See Also

Other peakPantheR: [peakPantheRAnnotation](#), [peakPantheR_singleFileSearch\(\)](#)

Other parallelAnnotation: [peakPantheRAnnotation](#), [peakPantheR_singleFileSearch\(\)](#)

Examples

```
if(requireNamespace('faahKO')){
  ## Load data
  library(faahKO)

  # 3 files
  input_spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                          system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                          system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # 4 features
  input_ROI      <- data.frame(matrix(vector(), 4, 8,
                                       dimnames=list(c(), c('cpdID', 'cpdName', 'rtMin', 'rt',
                                                       'rtMax', 'mzMin', 'mz', 'mzMax'))),
                                stringsAsFactors=FALSE)
  input_ROI[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
                    522.2, 522.205222)
  input_ROI[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
                    496.2, 496.204962)
  input_ROI[3,] <- c('ID-3', 'Cpd 3', 3420., 3454.435, 3495., 464.195358,
                    464.2, 464.204642)
  input_ROI[4,] <- c('ID-4', 'Cpd 4', 3670., 3701.697, 3745., 536.194638,
                    536.2, 536.205362)
  input_ROI[,c(3:8)] <- vapply(input_ROI[,c(3:8)], as.numeric,
                                 FUN.VALUE=numeric(4))

  # Initialise object
  initAnnotation <- peakPantheRAnnotation(spectraPaths=input_spectraPaths,
                                            targetFeatTable=input_ROI)

  # to use updated ROI:
  # uROIExist=TRUE, useUROI=TRUE, uROI=input_uROI
  # to use FallBack Integration Regions:
  # useFIR=TRUE, FIR=input_FIR
```

```
# Run serially
result_parallelAnnotation <- peakPantheR_parallelAnnotation(initAnnotation,
                                                               ncores=0,
                                                               getAcquTime=FALSE,
                                                               verbose=TRUE)

# Processing 4 compounds in 3 samples:
# uROI:\tFALSE
# FIR:\tFALSE
# ----- ko15 -----
# Polarity can not be extracted from netCDF files, please set manually the
# polarity with the 'polarity' method.
# Reading data from 4 windows
# Data read in: 0.24 secs
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #1
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #3
# Found 4/4 features in 0.06 secs
# Peak statistics done in: 0.02 secs
# Feature search done in: 0.76 secs
# ----- ko16 -----
# Polarity can not be extracted from netCDF files, please set manually the
# polarity with the 'polarity' method.
# Reading data from 4 windows
# Data read in: 0.24 secs
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #1
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #2
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #3
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #4
# Found 4/4 features in 0.08 secs
# Peak statistics done in: 0 secs
# Feature search done in: 0.71 secs
# ----- ko18 -----
# Polarity can not be extracted from netCDF files, please set manually the
# polarity with the 'polarity' method.
# Reading data from 4 windows
# Data read in: 0.25 secs
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #1
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #2
# Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
# mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
# ROI$mzMax for ROI #4
```

```

# Found 4/4 features in 0.06 secs
# Peak statistics done in: 0 secs
# Feature search done in: 0.71 secs
# -----
# Parallel annotation done in: 2.18 secs

# No failures
result_parallelAnnotation$failures

result_parallelAnnotation$annotation
# An object of class peakPantheRAnnotation
# 4 compounds in 3 samples.
#   updated ROI do not exist (uROI)
#   does not use updated ROI (uROI)
#   does not use fallback integration regions (FIR)
#   is annotated
}

```

peakPantheR_plotEICFit*Plot samples raw data and detected feature for a single ROI***Description**

plot a ROI across multiple samples (x axis is RT, y axis is intensity). If curveFit is provided, the fitted curve for each sample is added.

Usage

```
peakPantheR_plotEICFit(ROIDataPointSampleList, curveFitSampleList = NULL,
                      rtMin = NULL, rtMax = NULL, sampling = 250, sampleColour = NULL,
                      verbose = TRUE)
```

Arguments

ROIDataPointSampleList	(list) list of data.frame of raw data points for each sample (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row)).
curveFitSampleList	(list) NULL or a list of peakPantheR_curveFit (or NA) for each sample
rtMin	(float) NULL or vector of detected peak minimum retention time (in sec)
rtMax	(float) NULL or vector of detected peak maximum retention time (in sec)
sampling	(int) Number of points to employ when plotting fittedCurve
sampleColour	(str) NULL or vector colour for each sample (same length as ROIDataPointSampleList, rtMin, rtMax)
verbose	(bool) if TRUE message when NA scans are removed

Value

Grob (ggplot object)

Examples

```

## Input data
# fake sample 1
# ROI data points
rt1           <- seq(990, 1010, by=20/250)
mz1           <- rep(522., length(rt1))
int1          <- (dnorm(rt1, mean=1000, sd=1.5) * 100) + 1
tmp_DataPoints1 <- data.frame(rt=rt1, mz=mz1, int=int1)
# fittedCurve
fit1          <- list(amplitude=37.068916502809756, center=999.3734222573454,
                      sigma=0.58493182568124724, gamma=0.090582029276037035,
                      fitStatus=2, curveModel='skewedGaussian')
class(fit1)    <- 'peakPantheR_curveFit'

# fake sample 2
# ROI data points
rt2           <- seq(990, 1010, by=20/250)
mz2           <- rep(522., length(rt2))
int2          <- (dnorm(rt2, mean=1002, sd=1.5) * 100) + 1
tmp_DataPoints2 <- data.frame(rt=rt2, mz=mz2, int=int2)
# fittedCurve
fit2          <- list(amplitude=37.073067416755556, center=1001.3736564832565,
                      sigma=0.58496485738212201, gamma=0.090553713725151905,
                      fitStatus=2, curveModel='skewedGaussian')
class(fit2)    <- 'peakPantheR_curveFit'

## Plot features in 1 sample without colours
peakPantheR_plotEICFit(ROIDataPointSampleList=list(tmp_DataPoints1),
                       curveFitSampleList=list(fit1),
                       rtMin=995., rtMax=1005.,
                       sampling=250, sampleColour=NULL, verbose=FALSE)

## Plot features in 2 samples with colours
peakPantheR_plotEICFit(
  ROIDataPointSampleList=list(tmp_DataPoints1, tmp_DataPoints2),
  curveFitSampleList=list(fit1, fit2),
  rtMin=c(995., 997.), rtMax=c(1005., 1007.),
  sampling=250, sampleColour=c('blue', 'red'), verbose=FALSE)

```

peakPantheR_plotPeakwidth

Plot peak value and peakwidth by acquisition time or in input order

Description

For a single ROI, plot the peak value and peakwidth (RT, m/z, ...) of detected peaks across multiple samples, by acquisition time or in input order. If `rotateAxis=FALSE` x is run order / plot order, y is the apexValue / widthMin / widthMax, if `rotateAxis=TRUE` x is the measurement values and y the run order.

Usage

```
peakPantheR_plotPeakwidth(apexValue, widthMin = NULL, widthMax = NULL,
                          acquTime = NULL, varName = "variable", sampleColour = NULL,
                          rotateAxis = FALSE, verbose = TRUE)
```

Arguments

apexValue	(float) vector of apex value
widthMin	(float) vector of detected peak minimum peakwidth value or NULL (if NULL no peakwidth)
widthMax	(float) vector of detected peak maximum peakwidth value or NULL (if NULL no peakwidth)
acquTime	(POSIXct) vector of sample acquisition time as POSIXct or NULL (if NULL points are plotted in the order values are passed as input with the first on top or left)
varName	(str) Name of the variable to plot
sampleColour	(str) NULL or vector colour for each sample (same length as apexValue, widthMin, widthMax, acquTime)
rotateAxis	(bool) if TRUE x and y axis are reversed
verbose	(bool) if TRUE message when NA scans are removed

Value

Grob (ggplot object)

Examples

```
## Input data
apexVal <- c(1, 2, 3, 4)
minVal  <- c(0, 0, 2, 2)
maxVal  <- c(2, 4, 4, 5)
acqTime <- as.POSIXct(c('2017-07-13 21:06:14', '2017-07-14 21:06:14',
                       '2017-07-15 21:06:14', '2017-07-16 21:06:14'))

## Plot 4 samples with colour
peakPantheR_plotPeakwidth(apexValue=apexVal, widthMin=minVal, widthMax=maxVal,
                           acquTime=NULL, varName='Test variable 1',
                           sampleColour=c('blue','red','green','orange'),
                           rotateAxis=FALSE, verbose=FALSE)

## Plot 4 samples with colour by acquisition time
peakPantheR_plotPeakwidth(apexValue=apexVal, widthMin=minVal, widthMax=maxVal,
                           acquTime=acqTime, varName='Test variable 2',
                           sampleColour=c('blue','red','green','orange'),
                           rotateAxis=FALSE, verbose=FALSE)

## Plot 4 samples with colour, rotate axis
peakPantheR_plotPeakwidth(apexValue=apexVal, widthMin=minVal, widthMax=maxVal,
                           acquTime=NULL, varName='Test variable 3',
                           sampleColour=c('blue','red','green','orange'),
                           rotateAxis=TRUE, verbose=FALSE)

## Plot 4 samples with colour by acquisition time, rotate axis
```

```
peakPantheR_plotPeakwidth(apexValue=apexVal, widthMin=minVal, widthMax=maxVal,
                          acquTime=acqTime, varName='Test variable 4',
                          sampleColour=c('blue','red','green','orange'),
                          rotateAxis=FALSE, verbose=FALSE)
```

peakPantheR_ROIStatistics*Save to disk each ROI EIC and mean IS RT***Description**

Using reference samples (`referenceSpectraFiles`), save (to `saveFolder`) each ROI EIC (ROI) and reports the mean apex RT for all IS (`IS_ROI`) across samples

Usage

```
peakPantheR_ROIStatistics(referenceSpectraFiles, saveFolder, ROI = NULL,
                           IS_ROI = NULL, sampleColour = NULL, ncores = 0,
                           saveISPlots = TRUE, verbose = TRUE)
```

Arguments

<code>referenceSpectraFiles</code>	(str) A character vector of paths to the reference spectra files
<code>saveFolder</code>	(str) Path to the folder where EICs and IS mean RT (<code>IS_mean_RT.csv</code>) will be saved
<code>ROI</code>	(data.frame) NULL or a data.frame of Regions Of Interest (ROI) with compounds as row and ROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or <code>NA</code>), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or <code>NA</code>), <code>mzMax</code> (float) (if NULL, ROI EICs are not saved)
<code>IS_ROI</code>	(data.frame) NULL or a data.frame of IS ROI with IS as row and ROI parameters as columns: <code>rtMin</code> (float in seconds), <code>rt</code> (float in seconds, or <code>NA</code>), <code>rtMax</code> (float in seconds), <code>mzMin</code> (float), <code>mz</code> (float or <code>NA</code>), <code>mzMax</code> (float) (if NULL IS mean RT is not calculated and saved in <code>IS_mean_RT.csv</code>)
<code>sampleColour</code>	(str) NULL or vector colour for each sample
<code>ncores</code>	(int) Number of cores to use to integrate IS in parallel
<code>saveISPlots</code>	(bool) If TRUE save a diagnostic plot for each IS to <code>saveFolder/IS_search</code> compound
<code>verbose</code>	(bool) If TRUE message progress

Value

None

Examples

```

if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 2 samples and 1 targeted
  ## compound

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/K0/ko16.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 1, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(1))

  # input
  refSpecFiles <- spectraPaths
  input_ROI      <- targetFeatTable
  input_IS_ROI   <- targetFeatTable
  sampleColour   <- c('blue', 'red')

  # temporary saveFolder
  saveFolder1   <- tempdir()

  # Calculate ROI statiscs
  peakPantheR_ROIStatistics(refSpecFiles, saveFolder1, ROI=input_ROI,
    IS_ROI=input_IS_ROI, sampleColour=sampleColour,
    ncores=0, saveISPlots=TRUE, verbose=TRUE)
}

```

peakPantheR_singleFileSearch

Search, integrate and report targeted features in a raw spectra

Description

Report for a raw spectra the TIC, acquisition time, integrated targeted features, fitted curves and datapoints for each region of interest. Optimised to reduce the number of file access. Features not detected can be integrated using fallback integration regions (FIR).

Usage

```

peakPantheR_singleFileSearch(singleSpectraDataPath, targetFeatTable,
  peakStatistic = FALSE, plotEICsPath = NA, getAcquTime = FALSE,
  FIR = NULL, centroided = TRUE, verbose = TRUE, ...)

```

Arguments

singleSpectraDataPath	(str) path to netCDF or mzML raw data file (centroded, only with the channel of interest).
targetFeatTable	a data.frame of compounds to target as rows. Columns: cpdID (str), cpdName (str), rtMin (float in seconds), rt (float in seconds, or NA), rtMax (float in seconds), mzMin (float), mz (float or NA), mzMax (float).
peakStatistic	(bool) If TRUE calculates additional peak statistics: 'ppm_error', 'rt_dev_sec', 'tailing factor' and 'asymmetry factor'
plotEICsPath	(str or NA) If not NA, will save a .png of all ROI EICs at the path provided ('filepath/filename.png' expected). If NA no plot saved
getAcquTime	(bool) If TRUE will extract sample acquisition date-time from the mzML metadata (the additional file access will impact run time)
FIR	(data.frame or NULL) If not NULL, integrate Fallback Integration Regions (FIR) when a feature is not found. Compounds as row are identical to targetFeatTable, columns are rtMin (float in seconds), rtMax (float in seconds), mzMin (float), mzMax (float).
centroded	(bool) use TRUE if the data is centroded, used by readMSData when reading the raw data file
verbose	(bool) If TRUE message calculation progress, time taken and number of features found
...	Passes arguments to findTargetFeatures to alter peak-picking parameters (e.g. curveModel, sampling, params as a list of parameters for each ROI or 'guess',...)

Value

a list: list()\$TIC (*int*) TIC value, list()\$peakTable (*data.frame*) targeted features results (see Details), list()\$curveFit (*list*) list of peakPantheR_curveFit or NA for each ROI, list()\$acquTime (*POSIXct* or *NA*) date-time of sample acquisition from mzML metadata, list()\$ROIsDataPoint (*list*) a list of *data.frame* of raw data points for each ROI (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row)).

Details:: The returned *peakTable* *data.frame* is structured as follow:

cpdID	database compound ID
cpdName	compound name
found	was the peak found
rt	retention time of peak apex (sec)
rtMin	leading edge of peak retention time (sec) determined at 0.5% of apex intensity
rtMax	trailing edge of peak retention time (sec) determined at 0.5% of apex intensity
mz	weighted (by intensity) mean of peak m/z across scans
mzMin	m/z peak minimum (between rtMin, rtMax)
mzMax	m/z peak maximum (between rtMin, rtMax)
peakArea	integrated peak area
maxIntMeasured	maximum peak intensity in raw data
maxIntPredicted	maximum peak intensity based on curve fit
is_filled	Logical indicate if the feature was integrated using FIR (Fallback Integration Region)
ppm_error	difference in ppm between the expected and measured m/z
rt_dev_sec	difference in seconds between the expected and measured rt

tailingFactor the tailing factor is a measure of peak tailing. It is defined as the distance from the front slope of the peak to the center line of the peak.

asymmetryFactor the asymmetry factor is a measure of peak tailing. It is defined as the distance from the center line of the peak to the back slope.

See Also

Other *peakPantheR*: [peakPantheRAnnotation](#), [peakPantheR_parallelAnnotation\(\)](#)

Other parallelAnnotation: [peakPantheRAnnotation](#), [peakPantheR_parallelAnnotation\(\)](#)

Examples

```
if(requireNamespace('faahKO')){
  ## Load data
  library(faahKO)
  netcdfFilePath <- system.file('cdf/K0/ko15.CDF', package = 'faahKO')

  ## targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  res <- peakPantheR_singleFileSearch(netcdfFilePath, targetFeatTable,
    peakStatistic=TRUE)
  # Polarity can not be extracted from netCDF files, please set manually the
  # polarity with the 'polarity' method.
  # Reading data from 2 windows
  # Data read in: 0.16 secs
  # Warning: rtMin/rtMax outside of ROI; datapoints cannot be used for
  # mzMin/mzMax calculation, approximate mz and returning ROI$mzMin and
  # ROI$mzMax for ROI #1
  # Found 2/2 features in 0.05 secs
  # Peak statistics done in: 0 secs
  # Feature search done in: 0.75 secs

  res
  # $TIC
  # [1] 2410533091
  #
  # $peakTable
  #   found      rtMin       rt       rtMax      mzMin      mz       mzMax peakArea
  # 1  TRUE 3309.759 3346.828 3385.410 522.1948 522.2 522.2052 26133727
  # 2  TRUE 3345.377 3386.529 3428.279 496.2000 496.2 496.2000 35472141
  #   maxIntMeasured maxIntPredicted cpdID cpdName is_filled ppm_error
  # 1          889280         901015.8 ID-1   Cpd 1     FALSE 0.02337616
  # 2          1128960        1113576.7 ID-2   Cpd 2     FALSE 0.02460103
  #   rt_dev_sec  tailingFactor  asymmetryFactor
  # 1  1.9397590      1.015357      1.026824
  # 2  0.9518072      1.005378      1.009318
  #
  # $acquTime
```

```
# [1] NA
#
#
# $curveFit
# $curveFit[[1]]
# $amplitude
# [1] 162404.8
#
# $center
# [1] 3341.888
#
# $sigma
# [1] 0.07878613
#
# $gamma
# [1] 0.00183361
#
# $fitStatus
# [1] 2
#
# $curveModel
# [1] 'skewedGaussian'
#
# attr(,'class')
# [1] 'peakPantheR_curveFit'
#
# $curveFit[[2]]
# $amplitude
# [1] 199249.1
#
# $center
# [1] 3382.577
#
# $sigma
# [1] 0.07490442
#
# $gamma
# [1] 0.00114719
#
# $fitStatus
# [1] 2
#
# $curveModel
# [1] 'skewedGaussian'
#
# attr(,'class')
# [1] 'peakPantheR_curveFit'
#
#
# $ROIsDataPoint
# $ROIsDataPoint[[1]]
#       rt     mz    int
# 1 3315.154 522.2   2187
# 2 3316.719 522.2   3534
# 3 3318.284 522.2   6338
# 4 3319.849 522.2  11718
# 5 3321.414 522.2  21744
```

```

# 6 3322.979 522.2 37872
# 7 3324.544 522.2 62424
# 8 3326.109 522.2 98408
# 9 3327.673 522.2 152896
# 10 3329.238 522.2 225984
# ...
#
# $ROIsDataPoint[[2]]
#       rt      mz      int
# 1 3280.725 496.2    1349
# 2 3290.115 496.2   2069
# 3 3291.680 496.2   3103
# 4 3293.245 496.2   5570
# 5 3294.809 496.2  10730
# 6 3296.374 496.2  20904
# 7 3297.939 496.2  38712
# 8 3299.504 496.2  64368
# 9 3301.069 496.2  97096
# 10 3302.634 496.2 136320
# ...
}

```

peakTables,peakPantheRAnnotation-method*peakTables accessor with cpdID and cpdName added back***Description**

peakTables accessor with cpdID and cpdName added back

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
peakTables(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(data.frame) A list of peakTable data.frame, of length number of spectra files. Each peakTable data.frame has compounds as rows and peak annotation results as columns, with added compound ID and name.

Examples

```

if(requireNamespace('faahKO')){
## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
## compounds

# Paths to spectra files
library(faahKO)

```

```

spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                   system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                   system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
  c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
  'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
  522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
  496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
  FUN.VALUE=numeric(2))

annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
  targetFeatTable=targetFeatTable)

## default values without annotation
peakTables(annotation)
# [[1]]
# NULL
# [[2]]
# NULL
# [[3]]
# NULL
}

```

plotEICDetectedPeakwidth*Plot samples raw data and detected feature for a single ROI***Description**

Plot a ROI across multiple samples (x axis is RT, y axis is intensity) with the matching detected peak rt and peakwidth under it. If curveFit is provided, the fitted curve for each compound is added. RT and peakwidth are plotted in the order spectra are passed, with the first spectra on top.

Usage

```
plotEICDetectedPeakwidth(ROIDataPointSampleList, cpdID, cpdName, rt, rtMin,
  rtMax, mzMin, mzMax, ratio = 0.85, sampling = 250,
  curveFitSampleList = NULL, sampleColour = NULL, verbose = TRUE)
```

Arguments

ROIDataPointSampleList	(list) list of data.frame of raw data points for each sample (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row)).
cpdID	(str) Compound ID
cpdName	(str) Compound Name
rt	(float) vector of detected peak apex retention time (in sec)

<code>rtMin</code>	(float) vector of detected peak minimum retention time (in sec)
<code>rtMax</code>	(float) vector of detected peak maximum retention time (in sec)
<code>mzMin</code>	(float) ROI minimum m/z (matching EIC)
<code>mzMax</code>	(float) ROI maximum m/z (matching EIC)
<code>ratio</code>	(float) value between 0 and 1 defining the vertical percentage taken by the EICs subplot
<code>sampling</code>	(int) Number of points to employ when plotting fittedCurve
<code>curveFitSampleList</code>	(list) NULL or a list of <code>peakPantheR_curveFit</code> (or NA) for each sample
<code>sampleColour</code>	(str) NULL or vector colour for each sample (same length as EICs, <code>rt</code> , <code>rtMin</code> , <code>rtMax</code>)
<code>verbose</code>	(bool) if TRUE message when NA scans are removed

Value

Grob (ggplot object)

plotHistogram

Plot variable histogram and density

Description

Plot the histogram and density of the variable

Usage

```
plotHistogram(var, varName = "Variable", density = TRUE, ...)
```

Arguments

<code>var</code>	(float) vector of values to plot
<code>varName</code>	(str) Name of the variable to plot
<code>density</code>	(bool) If TRUE plot overlay the density on the variable
<code>...</code>	Passes arguments to <code>ggplot2::geom_histogram</code> , e.g. <code>bins=20, binwidth=1</code>

Value

Grob (ggplot object)

predictCurve	<i>Predict curve values</i>
--------------	-----------------------------

Description

Evaluate fitted curve values at x data points

Usage

```
predictCurve(fittedCurve, x)
```

Arguments

fittedCurve	(peakPantheR_curveFit) A 'peakPantheR_curveFit': a list of curve fitting parameters, curve shape model curveModel and nls.lm fit status fitStatus.
x	(numeric) values at which to evaluate the fitted curve

Details

```
## Examples cannot be computed as the function is not exported: ## Input a fitted curve fittedCurve
<- list(amplitude=275371.1, center=3382.577, sigma=0.07904697, gamma=0.001147647, fitStatus=2, curveModel='skewedGaussian') class(fittedCurve) <- 'peakPantheR_curveFit' input_x <- c(3290, 3300, 3310, 3320, 3330, 3340, 3350, 3360, 3370, 3380, 3390, 3400, 3410)

## Predict y at each input_x pred_y <- predictCurve(fittedCurve, input_x) pred_y # [1] 2.347729e-08 1.282668e-05 3.475590e-03 4.676579e-01 3.129420e+01 # [6] 1.043341e+03 1.736915e+04 1.447754e+05 6.061808e+05 1.280037e+06 # [11] 1.369651e+06 7.467333e+05 2.087477e+05
```

Value

fitted curve values at x

resetAnnotation,peakPantheRAnnotation-method	<i>Reset a peakPantheRAnnotation and alter samples and compounds information</i>
--	--

Description

Reset a peakPantheRAnnotation (remove results and set isAnnotated=FALSE). If a different number of samples (spectraPaths) or compounds (targetFeatTable) are passed, the object will be initialised to the new size. For input values left as NULL, the slots (filepath (from spectraPaths), ROI, cpdID, cpdName (from targetFeatTable), uROI, FIR, cpdMetadata, spectraMetadata, uROIExist, useUROI and useFIR) will be filled with values from previousAnnotation.

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
resetAnnotation(previousAnnotation,
  spectraPaths = NULL, targetFeatTable = NULL, uROI = NULL,
  FIR = NULL, cpdMetadata = NULL, spectraMetadata = NULL,
  uROIExist = NULL, useUROI = NULL, useFIR = NULL, verbose = TRUE,
  ...)
```

Arguments

previousAnnotation	(peakPantheRAnnotation) object to reset
spectraPaths	NULL or a character vector of spectra file paths, to set samples to process
targetFeatTable	NULL or a data.frame of compounds to target as rows and parameters as columns: cpdID (str), cpdName (str), rtMin (float in seconds), rt (float in seconds, or NA), rtMax (float in seconds), mzMin (float), mz (float or NA), mzMax (float). Set compounds to target.
uROI	NULL or a data.frame of updated Regions Of Interest (uROI) with compounds as row and uROI parameters as columns: rtMin (float in seconds), rt (float in seconds, or NA), rtMax (float in seconds), mzMin (float), mz (float or NA), mzMax (float).
FIR	NULL or a data.frame of Fallback Integration Regions (FIR) with compounds as row and FIR parameters as columns: rtMin (float in seconds), rtMax (float in seconds), mzMin (float), mzMax (float).
cpdMetadata	NULL or a data.frame of compound metadata, with compounds as row and metadata as columns
spectraMetadata	NULL or a data.frame of sample metadata, with samples as row and metadata as columns
uROIExist	NULL or a logical stating if uROI have been set
useUROI	NULL or a logical stating if uROI are to be used
useFIR	NULL or a logical stating if FIR are to be used
verbose	(bool) If TRUE message progress
...	Additional slots and values to set when resetting the object (cpdID, cpdName, ROI, filepath, TIC, acquisitionTime, peakTables, dataPoints, peakFit)

Value

(peakPantheRAnnotation) object reset with previous results removed and slots updated

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
```

```

system.file('cdf/KO/ko16.CDF', package = 'faahKO'))

# targetFeatTable
targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
  c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
  'mzMax'))), stringsAsFactors=FALSE)
targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
  522.2, 522.205222)
targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
  496.2, 496.204962)
targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
  FUN.VALUE=numeric(2))

smallAnnotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
  targetFeatTable=targetFeatTable)
smallAnnotation
# An object of class peakPantheRAnnotation
# 2 compounds in 2 samples.
# updated ROI do not exist (uROI)
# does not use updated ROI (uROI)
# does not use fallback integration regions (FIR)
# is not annotated

# Reset and change number of spectra
newSpectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
  system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
  system.file('cdf/KO/ko18.CDF', package = 'faahKO'))
largerAnnotation <- resetAnnotation(smallAnnotation,
  spectraPaths=newSpectraPaths,
  verbose=TRUE)
largerAnnotation
# An object of class peakPantheRAnnotation
# 2 compounds in 3 samples.
# updated ROI do not exist (uROI)
# does not use updated ROI (uROI)
# does not use fallback integration regions (FIR)
# is not annotated
}

```

resetFIR,peakPantheRAnnotation-method

*Reset FIR windows to uROI or ROI values Reset FIR windows to uROI
(or ROI if uROIEexist=FALSE)*

Description

Reset FIR windows to uROI or ROI values Reset FIR windows to uROI (or ROI if uROIEexist=FALSE)

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
resetFIR(object, verbose)
```

Arguments

- object (peakPantheRAnnotation) object for which FIR are to be reset
 verbose (bool) If TRUE message progress

Value

(peakPantheRAnnotation) object with FIR values reset

Examples

```
## Initialise a peakPantheRAnnotation object with 2 targeted compounds

## targetFeatTable
input_targetFeatTable <- data.frame(matrix(vector(), 2, 8,
                                             dimnames=list(c(), c('cpdID', 'cpdName', 'rtMin',
                                                               'rt', 'rtMax', 'mzMin', 'mz', 'mzMax'))),
                                             stringsAsFactors=FALSE)
input_targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3., 1., 4., 5., 2., 6.)
input_targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 19., 17., 20., 21., 18., 22.)
input_targetFeatTable[,c(3:8)] <- sapply(input_targetFeatTable[,c(3:8)],
                                         as.numeric)

## FIR
input_FIR      <- data.frame(matrix(vector(), 2, 4, dimnames=list(c(),
                                                               c('rtMin', 'rtMax', 'mzMin', 'mzMax'))),
                                         stringsAsFactors=FALSE)
input_FIR[1,]   <- c(13., 14., 15., 16.)
input_FIR[2,]   <- c(29., 30., 31., 32.)

annotation <- peakPantheRAnnotation(targetFeatTable = input_targetFeatTable,
                                       FIR = input_FIR, uROIExist = FALSE)

## Reset FIR with ROI values as uROI are not set
updatedAnnotation <- resetFIR(annotation, verbose=TRUE)
# FIR will be reset with ROI values as uROI values are not set
```

ROI,peakPantheRAnnotation-method

ROI accessor returns targetFeatTable with cpdID, cpdName added

Description

ROI accessor returns targetFeatTable with cpdID, cpdName added

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
ROI(object)
```

Arguments

- object peakPantheRAnnotation

Value

(data.frame) target feature table with compounds as row and ROI parameters as columns

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
      'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ROI(annotation)
  #   rtMin      rt rtMax      mz      mzMax cpdID cpdName
  # 1 3310 3344.888 3390 522.1948 522.2 522.2052 ID-1 Cpd 1
  # 2 3280 3385.577 3440 496.1950 496.2 496.2050 ID-2 Cpd 2
}
```

saveSingleFileMultiEIC

Save to disk a plot of all ROI EIC and detected feature range

Description

Plot and save a .png of all ROI (x is RT, y is intensity), with the matching detected peak rt and peakwidth under it.

Usage

```
saveSingleFileMultiEIC(ROIsDataPoint, curveFit, foundPeakTable, savePath,
  width = 15, height = 15, verbose = TRUE)
```

Arguments

ROIsDataPoint (list) a list of data.frame of raw data points for each ROI (retention time 'rt', mass 'mz' and intensity 'int' (as column) of each raw data points (as row)).

curveFit	(list) a list of peakPantheR_curveFit or NA for each ROI
foundPeakTable	(data.frame) data.frame as generated by findTargetFeatures , with features as rows and peak properties as columns. The following columns are mandatory: cpdID, cpdName, rt, rtmin, rtmax, mzmin, mzmax.
savePath	(str) Full path to save a .png of all ROI EICs, expect 'filepath/filename.png'.
width	(float) Width in cm for a single ROI plot (if more than one plot in total, 2 columns will be used). dpi set to a 100.
height	(float) height in a cm for a single ROI plot. dpi set to 100
verbose	(bool) if TRUE message progress

Value

None

skewedGaussian_guess *Guess function for initial skewed gaussian parameters and bounds*

Description

Guess function for initial skewed gaussian parameters and bounds, at the moment only checks the x position

Usage

skewedGaussian_guess(x, y)

Arguments

x	(numeric) x values (e.g. retention time)
y	(numeric) y observed values (e.g. spectra intensity)

Value

A list of guessed starting parameters list()\$init_params, lower list()\$lower_bounds and upper bounds list()\$upper_bounds (\$gamma, \$center, \$sigma, \$amplitude)

skewedGaussian_minpack.lm

Implementation of the Skewed Gaussian peak shape for use with minpack.lm

Description

Implementation of the Skewed Gaussian peak shape for use with minpack.lm

Usage

skewedGaussian_minpack.lm(params, xx)

Arguments

- params (list) skewed gaussian parameters (params\$gamma, params\$center, params\$sigma, params\$amplitude)
 xx (numeric) values at which to evaluate the skewed gaussian

Value

value of the skewed gaussian evaluated at xx

skewedGaussian_minpack.lm_objectiveFun

Skewed Gaussian minpack.lm objective function

Description

Skewed Gaussian minpack.lm objective function, calculates residuals using the skewed gaussian Peak Shape

Usage

`skewedGaussian_minpack.lm_objectiveFun(params, observed, xx)`

Arguments

- params (list) skewed gaussian parameters (params\$gamma, params\$center, params\$sigma, params\$amplitude)
 observed (numeric) observed y value at xx
 xx (numeric) value at which to evaluate the skewed gaussian

Value

difference between observed and expected skewed gaussian value evaluated at xx

skew_erf

Gaussian Error function

Description

Implementation of the gaussian error function

Usage

`skew_erf(x)`

Arguments

- x (numeric) value at which to evaluate the gaussian error function

Value

Value of the gaussian error function evaluated at x

spectraMetadata,peakPantheRAnnotation-method
spectraMetadata accessor

Description

spectraMetadata accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
spectraMetadata(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(*data.frame*) A *data.frame* of sample metadata, with samples as row and metadata as columns

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values not initialised
  spectraMetadata(annotation)
  # data frame with 0 columns and 3 rows
}
```

TIC,peakPantheRAnnotation-method
TIC accessor

Description

TIC accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
TIC(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(float) A numeric vector of Total Ion Chromatogram or NA, of length number of spectra files

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko16.CDF', package = 'faahKO'),
                     system.file('cdf/K0/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  ## default values without annotation
  TIC(annotation)
  # [1] NA NA NA
}
```

uROI,peakPantheRAnnotation-method

uROI accessor returns targetFeatTable with cpdID, cpdName added

Description

uROI accessor returns targetFeatTable with cpdID, cpdName added

Usage

```
## S4 method for signature 'peakPantheRAnnotation'  
uROI(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(data.frame) target feature table with compounds as row and uROI parameters as columns

Examples

```
if(requireNamespace('faahKO')){  
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted  
  ## compounds  
  
  # Paths to spectra files  
  library(faahKO)  
  spectraPaths <- c(system.file('cdf/K0/ko15.CDF', package = 'faahKO'),  
                    system.file('cdf/K0/ko16.CDF', package = 'faahKO'),  
                    system.file('cdf/K0/ko18.CDF', package = 'faahKO'))  
  
  # targetFeatTable  
  targetFeatTable      <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),  
    c('cpdID', 'cpdName', 'rtMin', 'rt', 'rtMax', 'mzMin', 'mz',  
    'mzMax'))), stringsAsFactors=FALSE)  
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,  
                         522.2, 522.205222)  
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,  
                         496.2, 496.204962)  
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,  
                                     FUN.VALUE=numeric(2))  
  
  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,  
                                         targetFeatTable=targetFeatTable)  
  
  ## default values without annotation  
  uROI(annotation)  
  #   rtMin rt rtMax mzMin mz mzMax cpdID cpdName  
  # 1     NA NA     NA     NA NA     NA ID-1   Cpd 1  
  # 2     NA NA     NA     NA NA     NA ID-2   Cpd 2  
  }
```

uROIExist,peakPantheRAnnotation-method
uROIExist accessor

Description

uROIExist accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
uROIExist(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(bool) flag if uROI have been set

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  uROIExist(annotation)
  # [1] FALSE
}
```

useFIR,peakPantheRAnnotation-method
useFIR accessor

Description

useFIR accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
useFIR(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(bool) flag if FIR are to be used

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  useFIR(annotation)
  # [1] FALSE
}
```

useUROI , peakPantheRAnnotation-method
useUROI accessor

Description

useUROI accessor

Usage

```
## S4 method for signature 'peakPantheRAnnotation'
useUROI(object)
```

Arguments

object	peakPantheRAnnotation
--------	-----------------------

Value

(bool) flag if uROI are to be used

Examples

```
if(requireNamespace('faahKO')){
  ## Initialise a peakPantheRAnnotation object with 3 samples and 2 targeted
  ## compounds

  # Paths to spectra files
  library(faahKO)
  spectraPaths <- c(system.file('cdf/KO/ko15.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko16.CDF', package = 'faahKO'),
                      system.file('cdf/KO/ko18.CDF', package = 'faahKO'))

  # targetFeatTable
  targetFeatTable <- data.frame(matrix(vector(), 2, 8, dimnames=list(c(),
    c('cpdID','cpdName','rtMin','rt','rtMax','mzMin','mz',
    'mzMax'))), stringsAsFactors=FALSE)
  targetFeatTable[1,] <- c('ID-1', 'Cpd 1', 3310., 3344.888, 3390., 522.194778,
    522.2, 522.205222)
  targetFeatTable[2,] <- c('ID-2', 'Cpd 2', 3280., 3385.577, 3440., 496.195038,
    496.2, 496.204962)
  targetFeatTable[,c(3:8)] <- vapply(targetFeatTable[,c(3:8)], as.numeric,
    FUN.VALUE=numeric(2))

  annotation <- peakPantheRAnnotation(spectraPaths=spectraPaths,
    targetFeatTable=targetFeatTable)

  useUROI(annotation)
  # [1] FALSE
}
```

[,peakPantheRAnnotation,ANY,ANY,ANY-method
extract parts of peakPantheRAnnotation class

Description

extract parts of peakPantheRAnnotation class

Usage

```
## S4 method for signature 'peakPantheRAnnotation,ANY,ANY,ANY'  
x[i, j, drop = "missing"]
```

Arguments

x	object from which to extract element(s) or in which to replace element(s).
i	(sample) indices specifying elements to extract or replace
j	(compound) indices specifying elements to extract or replace
drop	not applicable

Value

(peakPantheRAnnotation) object subset

Index

* **parallelAnnotation**
 peakPantheR_parallelAnnotation, 37
 peakPantheR_singleFileSearch, 44
 peakPantheRAnnotation, 31

* **peakPantheR**
 peakPantheR_parallelAnnotation, 37
 peakPantheR_singleFileSearch, 44
 peakPantheRAnnotation, 31

* **realTimeAnnotation**
 peakPantheR_singleFileSearch, 44

[, peakPantheRAnnotation, ANY, ANY, ANY-method,
 64]

[, peakPantheRAnnotation-method
 ([, peakPantheRAnnotation, ANY, ANY, ANY-method],
 11
 64)

_PACKAGE (peakPantheR), 30

acquisitionTime
 (acquisitionTime, peakPantheRAnnotation-method) EICs
 3
 (acquisitionTime, peakPantheRAnnotation-method, EICs, peakPantheRAnnotation-method, 12
 3
 extractSignalRawData, 13

annotationDiagnosticMultiplot, 4

annotationDiagnosticPlots
 (annotationDiagnosticPlots, peakPantheRAnnotation-method) filename
 4
 (annotationDiagnosticPlots, peakPantheRAnnotation-method) fileMethod
 14

annotationDiagnosticPlots, peakPantheRAnnotation-method
 4
 filename
 fileMethod
 14

annotationParamsDiagnostic
 (annotationParamsDiagnostic, peakPantheRAnnotation-method) filepath
 5
 (annotationParamsDiagnostic, peakPantheRAnnotation-method) filename
 15

annotationParamsDiagnostic, peakPantheRAnnotation-method
 5
 filepath
 15

annotationTable
 (annotationTable, peakPantheRAnnotation-method) findTargetFeatures, 16, 21, 23, 56
 7
 (annotationTable, peakPantheRAnnotation-method) FIR
 18

annotationTable, peakPantheRAnnotation-method, FIR, peakPantheRAnnotation-method, 18
 7
 fitCurve, 19

cpdID
 (cpdID, peakPantheRAnnotation-method) generateIonChromatogram, 20
 8
 (cpdID, peakPantheRAnnotation-method) getAcquisitionDatemzML, 20
 getTargetFeatureStatistic, 21

cpdID, peakPantheRAnnotation-method, 8
 integrateFIR, 22

is.peakPantheR_curveFit, 23
 isAnnotated
 (isAnnotated, peakPantheRAnnotation-method), 23
 isAnnotated, peakPantheRAnnotation-method, 23
 nbCompounds
 (nbCompounds, peakPantheRAnnotation-method), 24
 nbCompounds, peakPantheRAnnotation-method, 24
 nbSamples
 (nbSamples, peakPantheRAnnotation-method), 25
 nbSamples, peakPantheRAnnotation-method, 25
 outputAnnotationDiagnostic
 (outputAnnotationDiagnostic, peakPantheRAnnotation-method), 26
 outputAnnotationDiagnostic, peakPantheRAnnotation-method, 26
 outputAnnotationParamsCSV
 (outputAnnotationParamsCSV, peakPantheRAnnotation-method), 27
 outputAnnotationParamsCSV, peakPantheRAnnotation-method, 27
 outputAnnotationResult
 (outputAnnotationResult, peakPantheRAnnotation-method), 28
 outputAnnotationResult, peakPantheRAnnotation-method, 28
 peakFit
 (peakFit, peakPantheRAnnotation-method), 29
 peakFit, peakPantheRAnnotation-method, 29
 peakPantheR, 30
 peakpanther (peakPantheR), 30
 peakPantheR_loadAnnotationParamsCSV,
 36
 peakPantheR_parallelAnnotation, 31, 34,
 37, 46
 peakPantheR_plotEICFit, 40
 peakPantheR_plotPeakwidth, 41
 peakPantheR_ROIStatistics, 43
 peakPantheR_singleFileSearch, 31, 34, 37,
 38, 44
 peakPantheRAnnotation, 31, 38, 46
 peakPantheRAnnotation-class
 (peakPantheRAnnotation), 31
 peakTables
 (peakTables, peakPantheRAnnotation-method),
 48
 peakTables, peakPantheRAnnotation-method,
 48
 plotEICDetectedPeakwidth, 49
 plotHistogram, 50
 predictCurve, 51
 readMSData, 38, 45
 resetAnnotation
 (resetAnnotation, peakPantheRAnnotation-method),
 51
 resetFIR
 (resetFIR, peakPantheRAnnotation-method),
 53
 resetFIR, peakPantheRAnnotation-method,
 53
 ROI (ROI, peakPantheRAnnotation-method),
 54
 skewedGaussian_guess, 56
 skewedGaussian_minpack.lm, 56
 skewedGaussian_minpack.lm_objectiveFun,
 57
 spectraMetadata
 (spectraMetadata, peakPantheRAnnotation-method),
 58
 spectraMetadata, peakPantheRAnnotation-method,
 58
 TIC (TIC, peakPantheRAnnotation-method),
 59
 TIC, peakPantheRAnnotation-method, 59
 uROI
 (uROI, peakPantheRAnnotation-method),
 60
 uROI, peakPantheRAnnotation-method, 60
 uROIExist
 (uROIExist, peakPantheRAnnotation-method),
 61
 uROIExist, peakPantheRAnnotation-method,
 61
 useFIR
 (useFIR, peakPantheRAnnotation-method),
 62
 useFIR, peakPantheRAnnotation-method,
 62

useUROI
 (useUROI,peakPantheRAnnotation-method),
 [63](#)
useUROI,peakPantheRAnnotation-method,
 [63](#)