

Package ‘CRISPRseek’

April 22, 2016

Type Package

Title Design of target-specific guide RNAs in CRISPR-Cas9,
genome-editing systems

Version 1.10.3

Date 2016-03-22

Author Lihua Julie Zhu, Benjamin R. Holmes, Herve Pages, Isana Veksler-
Lublinsky, Victor Ambros, Neil Aronin and Michael Brodsky

Maintainer Lihua Julie Zhu <julie.zhu@umassmed.edu>

Depends R (>= 3.0.1), BiocGenerics, Biostrings

Imports parallel, data.table, seqinr, S4Vectors, IRanges, BSgenome,
BiocParallel

Suggests RUnit, BiocStyle, BSgenome.Hsapiens.UCSC.hg19,
TxDb.Hsapiens.UCSC.hg19.knownGene, org.Hs.eg.db

Description The package includes functions to find potential guide RNAs for input target sequences, optionally filter guide RNAs without restriction enzyme cut site, or without paired guide RNAs, genome-wide search for off-targets, score, rank, fetch flank sequence and indicate whether the target and off-targets are located in exon region or not. Potential guide RNAs are annotated with total score of the top5 and topN off-targets, detailed topN mismatch sites, restriction enzyme cut sites, and paired guide RNAs. If GeneRfold and GeneR are installed (<http://bioconductor.case.edu/bioconductor/2.8/bioc/html/GeneRfold.html>, <http://bioc.ism.ac.jp/packages/2.8/bioc/>) minimum free energy and bracket notation of secondary structure of gRNA and gRNA backbone constant region will be included in the summary file. This package leverages Biostrings and BSgenome packages.

License GPL (>= 2)

LazyLoad yes

biocViews GeneRegulation, SequenceMatching

NeedsCompilation no

R topics documented:

CRISPRseek-package 2

| | |
|--|----|
| annotateOffTargets | 4 |
| buildFeatureVectorForScoring | 6 |
| calculategRNAEfficiency | 7 |
| compare2Sequences | 9 |
| filtergRNAs | 12 |
| filterOffTarget | 14 |
| findgRNAs | 16 |
| foldgRNAs | 18 |
| getOfftargetScore | 19 |
| isPatternUnique | 20 |
| offTargetAnalysis | 21 |
| offTargetAnalysisOfPeakRegions | 26 |
| searchHits | 28 |
| translatePattern | 29 |
| uniqueREs | 30 |
| writeHits | 31 |

Index **33**

| | |
|--------------------|--|
| CRISPRseek-package | <i>Design of target-specific guide RNAs (gRNAs) in CRISPR-Cas9, genome-editing systems</i> |
|--------------------|--|

Description

Design of target-specific gRNAs for the CRISPR-Cas9 system by automatically finding potential gRNAs (paired/not paired), with/without restriction enzyme cut site(s) in a given sequence, searching for off targets with user defined maximum number of mismatches, calculating score of each off target based on mismatch positions in the off target and a penalty weight matrix, filtering off targets with user-defined criteria, and annotating off targets with flank sequences, whether located in exon or not. Summary report is also generated with gRNAs ranked by total topN off target score, annotated with restriction enzyme cut sites, gRNA efficacy and possible paired gRNAs. Detailed paired gRNAs information and restriction enzyme cut sites are stored in separate files in the output directory specified by the user. In total, four tab delimited files are generated in the output directory: OfftargetAnalysis.xls (off target details), Summary.xls (gRNA summary), REcutDetails.xls (restriction enzyme cut sites of each gRNA), and pairedgRNAs.xls (potential paired gRNAs).

Details

| | |
|----------|------------|
| Package: | CRISPRseek |
| Type: | Package |
| Version: | 1.0 |
| Date: | 2013-10-04 |
| License: | GPL (>= 2) |

Function offTargetAnalysis integrates all steps of off target analysis into one function call

Author(s)

Lihua Julie Zhu and Michael Brodsky Maintainer: julie.zhu@umassmed.edu

References

Mali P, Aach J, Stranges PB, Esvelt KM, Moosburner M, Kosuri S, Yang L, Church GM. CAS9 transcriptional activators for target specificity screening and paired nickases for cooperative genome engineering. *Nat Biotechnol.* 2013. 31(9):833-8 Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang. DNA targeting specificity of rNA-guided Cas9 nucleases. *Nat Biotechnol.* 2013. 31:827-834 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. *Plos One* Sept 23rd 2014

See Also

offTargetAnalysis

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
outputDir <- getwd()
inputFilePath <- system.file("extdata", "inputseq.fa", package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa", package = "CRISPRseek")
##### Scenario 1. Target and off-target analysis for paired gRNAs with
##### one of the pairs overlap RE sites
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly=TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly=TRUE,
  BSgenomeName=Hsapiens, txdb=TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 2. Target and off-target analysis for paired gRNAs with or
##### without RE sites
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = FALSE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = TRUE,
  BSgenomeName = Hsapiens, txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 3. Target and off-target analysis for gRNAs overlap RE sites

results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
  BSgenomeName = Hsapiens, txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)
```

```
##### Scenario 4. Off-target analysis for all potential gRNAs, this will
#####be the slowest among the aforementioned scenarios.

results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = FALSE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
  BSgenomeName = Hsapiens, txdb = Txdb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 5. Target and off-target analysis for gRNAs input by user.
gRNAFilePath <- system.file("extdata", "testHsap_GATA1_ex2_gRNA1.fa",
  package="CRISPRseek")
results <- offTargetAnalysis(inputFilePath = gRNAFilePath, findgRNAs = FALSE,
  findgRNAsWithREcutOnly = FALSE, REpatternFile = REpatternFile,
  findPairedgRNAOnly = FALSE, BSgenomeName = Hsapiens,
  txdb = Txdb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, max.mismatch = 1, chromToSearch = "chrX",
  outputDir = outputDir, overwrite = TRUE)

##### Scenario 6. Quick gRNA finding without target and off-target analysis
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = TRUE,
  chromToSearch = "", outputDir = outputDir, overwrite = TRUE)

##### Scenario 7. Quick gRNA finding with gRNA efficacy analysis
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
  REpatternFile = REpatternFile, findPairedgRNAOnly = TRUE,
  BSgenomeName = Hsapiens, annotateExon = FALSE,
  max.mismatch = 0, outputDir = outputDir, overwrite = TRUE)
```

annotateOffTargets *annotate off targets*

Description

annotate off targets to indicate whether it is inside an exon or intron, and the gene id if inside the gene.

Usage

```
annotateOffTargets(scores, txdb, orgAnn)
```

Arguments

scores a data frame output from getOfftargetScore or filterOfftarget. It contains strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd

(end position of the off target),name (gRNA name),gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatch.distance2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches),NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

| | |
|--------|--|
| txdb | TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with Txdb at http://www.bioconductor.org/packages/release/BiocViews.html#___Annotation such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans |
| orgAnn | organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human |

Value

a data frame with off target annotation

Author(s)

Lihua Julie Zhu

References

Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014

See Also

offTargetAnalysis

Examples

```
library(CRISPRseek)
#library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
hitsFile <- system.file("extdata", "hits.txt", package="CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
scores <- getOfftargetScore(featureVectors)
```

```
outputDir <- getwd()
results <- annotateOffTargets(scores,
  txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL)
results
```

```
buildFeatureVectorForScoring
  Build feature vectors
```

Description

Build feature vectors for calculating scores of off targets

Usage

```
buildFeatureVectorForScoring(hits, gRNA.size = 20, canonical.PAM = "NGG")
```

Arguments

| | |
|---------------|--|
| hits | a data frame generated from searchHits, which contains IsMismatch.posX (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1- gRNA.size) representing all positions in the guide RNA, abbreviated as gRNA),strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target),name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (set to 100, and will be calculated in getOfftargetScore) |
| gRNA.size | gRNA size, default 20 |
| canonical.PAM | Canonical PAM, default NGG |

Value

A data frame with hits plus features used for calculating scores and for generating report, including IsMismatch.posX (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1- gRNA.size) representing all positions in the gRNA), strand (strand of the off target, + for plus and - for minus strand),chrom (chromosome of the off target), chromStart (start position of the off target),chromEnd (end position of the off target),name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatche.distance2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA

and off target, e.g.,G.C..... means that this off target aligns with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
hitsFile <- system.file("extdata", "hits.txt", package = "CRISPRseek")
hits <- read.table(hitsFile, sep= "\t", header = TRUE,
  stringsAsFactors = FALSE)
buildFeatureVectorForScoring(hits)
```

calculategRNAEfficiency

Calculate gRNA Efficiency

Description

Calculate gRNA Efficiency for a given set of sequences and feature weight matrix

Usage

```
calculategRNAEfficiency(extendedSequence,
  baseBeforegRNA, featureWeightMatrix, gRNA.size = 20,
  enable.multicore = FALSE)
```

Arguments

extendedSequence

Sequences containing gRNA plus PAM plus flanking sequences. Each sequence should be long enough for building features specified in the featureWeightMatrix

baseBeforegRNA Number of bases before gRNA used for calculating gRNA efficiency, default 4
featureWeightMatrix

a data frame with the first column containing significant features and the second column containing the weight of corresponding features. In the following example, DoenchNBT2014 weight matrix is used. Briefly, features include INTERCEPT, GC_LOW (penalty for low GC content in the gRNA sequence), GC_HIGH (penalty for high GC content in the gRNA sequence), G02 (means G at second position of the extendedSequence), GT02 (means GT di-nucleotides starting at 2nd position of the extendedSequence). To understand how is the feature weight matrix identified, or how to use alternative feature weight matrix file, please see Doench et al., 2014 for details.

`gRNA.size` The size of the gRNA, default 20

`enable.multicore`
 Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE

Value

DNAStrngSet consists of potential gRNAs that can be input to `filtergRNAs` function directly

Author(s)

Lihua Julie Zhu

References

Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. *Nat Biotechnol.* 2014 Sep 3. doi: 10.1038/nbt.3026 <http://www.broadinstitute.org/rnai/public/analysis-tools/sgrna-design>

See Also

`offTargetAnalysis`

Examples

```

extendedSequence <- c("TGGATTGTATAATCAGCATGGATTTGGAAC",
  "TCAACGAGGATATTCTCAGGCTTCAGGTCC",
  "GTTACCTGAATTTGACCTGCTCGGAGGTAA",
  "CTTGGTGTGGCTTCCTTAAGACATGGAGC",
  "CATACAGGCATTGAAGAAGAATTTAGGCCT",
  "AGTACTATACATTTGGCTTAGATTTGGCGG",
  "TTTTCCAGATAGCCGATCTTGGTGTGGCTT",
  "AAGAAGGGAAC TATTCGCTGGTGATGGAGT"
)
featureWeightMatrixFile <- system.file("extdata", "DoenchNBT2014.csv",
  package = "CRISPRseek")
featureWeightMatrix <- read.csv(featureWeightMatrixFile, header=TRUE)
calculategRNAEfficiency(extendedSequence, baseBeforegRNA = 4,
  featureWeightMatrix, gRNA.size = 20)

```

| | |
|-------------------|--|
| compare2Sequences | <i>Compare 2 input sequences/sequence sets for possible guide RNAs (gRNAs)</i> |
|-------------------|--|

Description

Generate all possible guide RNAs (gRNAs) for two input sequences, or two sets of sequences and generate scores for potential off-targets in the other sequence.

Usage

```
compare2Sequences(inputFile1Path, inputFile2Path,
  inputNames=c("Seq1", "Seq2"),
  format = c("fasta", "fasta"), header=FALSE, findgRNAsWithREcutOnly = FALSE,
  searchDirection=c("both", "1to2", "2to1"), BSgenomeName,
  REpatternFile=system.file("extdata", "NEBenzymes.fa", package = "CRISPRseek"),
  minREpatternSize = 6,
  overlap.gRNA.positions = c(17, 18), findPairedgRNAOnly = FALSE,
  min.gap = 0, max.gap = 20, gRNA.name.prefix = "gRNA", PAM.size = 3,
  gRNA.size = 20, PAM = "NGG", PAM.pattern = "N[A|G]G$",
  allowed.mismatch.PAM = 2, max.mismatch = 3,
  outputDir, upstream = 0, downstream = 0,
  weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445,
  0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583),
  overwrite = FALSE, baseBeforegRNA = 4,
  baseAfterPAM = 3, featureWeightMatrixFile = system.file("extdata",
  "DoenchNBT2014.csv", package = "CRISPRseek"), foldgRNAs = TRUE,
  gRNA.backbone="GUUUUAGAGCUAGAAAUAGCAAGUUAUUAAUAAGGCUAGUCCGUUAUCAACUUGAAAAAGUGGCACCGAGUCGGUUCUUUUU
  temperature = 37)
```

Arguments

| | |
|------------------------|---|
| inputFile1Path | Sequence input file 1 path that contains one of the two sequences to be searched for potential gRNAs |
| inputFile2Path | Sequence input file 2 path that contains one of the two sequences to be searched for potential gRNAs |
| inputNames | Name of the input sequences when inputFile1Path and inputFile2Path are DNAS-tringSet instead of file path |
| format | Format of the input files, fasta, fastq and bed format are supported, default fasta |
| header | Indicate whether the input file contains header, default FALSE, only applies to bed format |
| findgRNAsWithREcutOnly | Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern |

| | |
|------------------------|--|
| searchDirection | Indicate whether perform gRNA in both sequences and off-target search against each other (both) or search gRNA in input1 and off-target analysis in input2 (1to2), or vice versa (2to1) |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |
| REpatternFile | File path containing restriction enzyme cut patterns |
| minREpatternSize | Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 6 |
| overlap.gRNA.positions | The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18 |
| findPairedgRNAOnly | Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE |
| min.gap | Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0 |
| max.gap | Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20 |
| gRNA.name.prefix | The prefix used when assign name to found gRNAs, default gRNA, short for guided RNA. |
| PAM.size | PAM length, default 3 |
| gRNA.size | The size of the gRNA, default 20 |
| PAM | PAM sequence after the gRNA, default NGG |
| PAM.pattern | Regular expression of PAM, default N[AIG]G\$ |
| allowed.mismatch.PAM | Number of degenerative bases in the PAM sequence, default to 2 for N[AIG]G PAM |
| max.mismatch | Maximum mismatch allowed to search the off targets in the other sequence, default 3 |
| outputDir | the directory where the sequence comparison results will be written to |
| upstream | upstream offset from the bed input starts to search for gRNA and/or offtargets, default 0 |
| downstream | downstream offset from the bed input ends to search for gRNA and/or offtargets, default 0 |
| weights | numeric vector size of gRNA length, default c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583) which is used in Hsu et al., 2013 cited in the reference section |

| | |
|-------------------------|--|
| overwrite | overwrite the existing files in the output directory or not, default TRUE |
| baseBeforegRNA | Number of bases before gRNA used for calculating gRNA efficiency, default 4 |
| baseAfterPAM | Number of bases after PAM used for calculating gRNA efficiency, default 3 |
| featureWeightMatrixFile | Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details. |
| foldgRNAs | Default TRUE. If set to TRUE, summary file will contain minimum free energy of the secondary structure of gRNA with gRNA backbone from GeneRfold package provided that GeneRfold package has been installed. |
| gRNA.backbone | gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone. |
| temperature | temperature in celsius. Default to 37 celsius. |

Value

Return a data frame with all potential gRNAs from both sequences. In addition, a tab delimited file scoresFor2InputSequences.xls is also saved in the outputDir, sorted by scoreDiff descending.

| | |
|--------------------------|--|
| name | name of the gRNA |
| gRNAPlusPAM | gRNA plus PAM sequence |
| targetInSeq1 | target/off-target sequence including PAM in the 1st input sequence file |
| targetInSeq2 | target/off-target sequence including PAM in the 2nd input sequence file |
| guideAlignment2Offtarget | alignment of gRNA to the other input sequence (off-target sequence) |
| offTargetStrand | strand of the other sequence (off-target sequence) the gRNA align to |
| scoreForSeq1 | score for the target sequence in the 1st input sequence file |
| scoreForSeq2 | score for the target sequence in the 1st input sequence file |
| mismatch.distance2PAM | distances of mismatch to PAM, e.g., 14 means the mismatch is 14 bp away from PAM |
| n.mismatch | number of mismatches between the off-target and the gRNA |
| targetSeqName | the name of the input sequence where the target sequence is located |
| scoreDiff | scoreForSeq1 - scoreForSeq2 |
| bracket.notation | folded gRNA in bracket notation |
| mfe.sgRNA | minimum free energy of sgRNA |
| mfe.diff | mfe.sgRNA-mfe.backbone |
| mfe.backbone | minimum free energy of the gRNA backbone by itself |

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834

See Also

CRISPRseek

Examples

```
library(CRISPRseek)
inputFile1Path <- system.file("extdata", "rs362331T.fa",
                             package = "CRISPRseek")
inputFile2Path <- system.file("extdata", "rs362331C.fa",
                             package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa",
                             package = "CRISPRseek")
seqs <- compare2Sequences(inputFile1Path, inputFile2Path,
                          outputDir = getwd(),
                          REpatternFile = REpatternFile, overwrite = TRUE)
```

 filtergRNAs

Filter gRNAs

Description

Filter gRNAs containing restriction enzyme cut site

Usage

```
filtergRNAs(all.gRNAs, pairOutputFile = "",
            findgRNAsWithREcutOnly = FALSE,
            REpatternFile = system.file("extdata", "NEBenzymes.fa",
                                         package = "CRISPRseek"), format = "fasta",
            minREpatternSize = 4, overlap.gRNA.positions = c(17, 18), overlap.allpos = TRUE)
```

Arguments

`all.gRNAs` gRNAs as DNASTringSet, such as the output from findgRNAs
`pairOutputFile` File path with paired gRNAs

| | |
|------------------------|--|
| findgRNAsWithREcutOnly | Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern |
| REpatternFile | File path containing restriction enzyme cut patterns |
| format | Format of the REpatternFile, default as fasta |
| minREpatternSize | Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 4 |
| overlap.gRNA.positions | The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18 |
| overlap.allpos | Default TRUE, meaning that only gRNAs overlap with all the positions are retained FALSE, meaning that gRNAs overlap with one or both of the positions are retained |

Value

| | |
|------------------|---|
| gRNAs.withRE | gRNAs as DNASTringSet that passed the filter criteria |
| gRNAREcutDetails | a data frame that contains a set of gRNAs annotated with restriction enzyme cut details |

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
all.gRNAs <- findgRNAs(
  inputFilePath = system.file("extdata", "inputseq.fa"),
  package = "CRISPRseek"),
pairOutputFile = "testpairedgRNAs.xls",
findPairedgRNAOnly = TRUE)

gRNAs.RE <- filtergRNAs(all.gRNAs = all.gRNAs,
  pairOutputFile = "testpairedgRNAs.xls", minREpatternSize = 6,
  REpatternFile = system.file("extdata", "NEBenzymes.fa",
  package = "CRISPRseek"), overlap.allpos = TRUE)

gRNAs <- gRNAs.RE$gRNAs.withRE
restriction.enzyme.cut.sites <- gRNAs.RE$gRNAREcutDetails
```

filterOffTarget *filter off targets and generate reports.*

Description

filter off targets that meet the criteria set by users such as minimum score, topN. In addition, off target was annotated with flank sequence, gRNA cleavage efficiency and whether it is inside an exon or not if fetchSequence is set to TRUE and annotateExon is set to TRUE

Usage

```
filterOffTarget(scores, min.score = 0.5, topN = 100,
  topN.OfftargetTotalScore = 10,
  annotateExon = TRUE, txdb, orgAnn, outputDir, oneFilePergRNA = FALSE,
  fetchSequence = TRUE, upstream = 200, downstream = 200, BSgenomeName,
  baseBeforegRNA = 4, baseAfterPAM = 3,
  featureWeightMatrixFile = system.file("extdata", "DoenchNBT2014.csv",
  package = "CRISPRseek"))
```

Arguments

| | |
|--------------------------|--|
| scores | a data frame output from getOfftargetScore. It contains strand (strand of the off target, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target), name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatch.distance.2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches) |
| min.score | minimum score of an off target to included in the final output, default 0.5 |
| topN | top N off targets to be included in the final output, default 100 |
| topN.OfftargetTotalScore | top N off target used to calculate the total off target score, default 10 |
| annotateExon | Choose whether or not to indicate whether the off target is inside an exon or not, default TRUE |
| txdb | TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with Txdb at http://www.bioconductor.org/packages/release/BiocViews.html#___Annotation such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene |

| | |
|-------------------------|--|
| | for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans |
| orgAnn | organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human |
| outputDir | the directory where the off target analysis and reports will be written to |
| oneFilePergrNA | write to one file for each gRNA or not, default to FALSE |
| fetchSequence | Fetch flank sequence of off target or not, default TRUE |
| upstream | upstream offset from the off target start, default 200 |
| downstream | downstream offset from the off target end, default 200 |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |
| baseBeforegrNA | Number of bases before gRNA used for calculating gRNA efficiency, default 4 |
| baseAfterPAM | Number of bases after PAM used for calculating gRNA efficiency, default 3 |
| featureWeightMatrixFile | Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details. |

Value

| | |
|------------|--|
| offtargets | a data frame with off target analysis results |
| summary | a data frame with summary of the off target analysis results |

Author(s)

Lihua Julie Zhu

References

Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. Nat Biotechnol. 2014 Sep 3. doi: 10.1038/nbt.3026 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014

See Also

offTargetAnalysis

Examples

```

library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
hitsFile <- system.file("extdata", "hits.txt", package="CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
scores <- getOfftargetScore(featureVectors)
outputDir <- getwd()
results <- filterOffTarget(scores, BSgenomeName = Hsapiens,
  txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
  orgAnn = org.Hs.egSYMBOL, outputDir = outputDir,
  min.score = 0.1, topN = 10, topN.OfftargetTotalScore = 5)
results$offtargets
results$summary

```

findgRNAs

Find potential gRNAs

Description

Find potential gRNAs for an input file containing sequences in fasta format

Usage

```

findgRNAs(inputFilePath, format = "fasta", PAM = "NGG", PAM.size = 3,
  findPairedgRNAOnly = FALSE, annotatePaired = TRUE, enable.multicore = FALSE,
  gRNA.pattern = "", gRNA.size = 20,
  overlap.gRNA.positions = c(17,18), min.gap = 0, max.gap = 20,
  pairOutputFile, name.prefix = "", featureWeightMatrixFile = system.file("extdata",
  "DoenchNBT2014.csv", package = "CRISPRseek"), baseBeforegRNA = 4,
  baseAfterPAM = 3, calculategRNAEfficacy = FALSE, efficacyFile)

```

Arguments

| | |
|--------------------|--|
| inputFilePath | Sequence input file path or a DNASTringSet object that contains sequences to be searched for potential gRNAs |
| format | Format of the input file, fasta and fastq are supported, default fasta |
| PAM | protospacer-adjacent motif (PAM) sequence after the gRNA, default NGG |
| PAM.size | PAM length, default 3 |
| findPairedgRNAOnly | Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE |
| annotatePaired | Indicate whether to output paired information, default TRUE |

| | |
|--------------------------------------|--|
| <code>enable.multicore</code> | Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE |
| <code>gRNA.pattern</code> | Regular expression or IUPAC Extended Genetic Alphabet to represent gRNA pattern, default is no restriction. To specify that the gRNA must start with GG for example, then set it to <code>^GG</code> . Please see <code>help(translatePattern)</code> for a list of IUPAC Extended Genetic Alphabet. |
| <code>gRNA.size</code> | The size of the gRNA, default 20 |
| <code>overlap.gRNA.positions</code> | The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18 |
| <code>min.gap</code> | Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0 |
| <code>max.gap</code> | Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20 |
| <code>pairOutputFile</code> | The output file for writing paired gRNA information to |
| <code>name.prefix</code> | The prefix used when assign name to found gRNAs, default gRNA, short for guided RNA. |
| <code>baseBeforegRNA</code> | Number of bases before gRNA used for calculating gRNA efficiency, default 4 |
| <code>baseAfterPAM</code> | Number of bases after PAM used for calculating gRNA efficiency, default 3 |
| <code>featureWeightMatrixFile</code> | Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details. |
| <code>calculategRNAEfficiency</code> | Default to FALSE, not to calculate gRNA efficacy |
| <code>efficacyFile</code> | File path to write gRNA efficacies |

Details

If users already has a fasta file that contains a set of potential gRNAs, then users can call `filtergRNAs` directly although the easiest way is to call the one-stop-shopping function `OffTargetAnalysis` with `findgRNAs` set to FALSE.

Value

`DNAStrngSet` consists of potential gRNAs that can be input to `filtergRNAs` function directly

Note

If the input sequence file contains multiple >300 bp sequences, suggest create one input file for each sequence and run the `OffTargetAnalysis` separately.

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
findgRNAs(inputFilePath = system.file("extdata",
  "inputseq.fa", package = "CRISPRseek"),
  pairOutputFile = "testpairedgRNAs.xls",
  findPairedgRNAOnly = TRUE)
```

foldgRNAs

*Fold gRNAs with the gRNA backbone constant region***Description**

Fold gRNAs with the gRNA backbone constant region and output minimum free energy and the folded structure in bracket notation using GeneRfold package

Usage

```
foldgRNAs(gRNAs.withoutPAM,
  gRNA.backbone="GUUUUAGAGCUAGAAAUAGCAAGUUAAAAUAAGGCUAGUCCGUUAUCAACUUGAAAAAGUGGCACCGAGUCGGUCUUUUU
  temperature = 37)
```

Arguments

| | |
|------------------|--|
| gRNAs.withoutPAM | gRNAs as character, without PAM sequence. |
| gRNA.backbone | gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone. |
| temperature | temperature in celsius. Default to 37 celsius. |

Value

a data frame that contains a set of gRNAs annotated with bracket.notation (folded sgRNA in bracket notation), mfe.sgRNA (minimum free energy of sgRNA:gRNA plus backbone), mfe.diff (mfe.sgRNA-mfe.backbone), mfe.backbone (minimum free energy of the gRNA backbone by itself).

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
gRNAs.withoutPAM <- c("AACCTTGGGGTTACTGAAAG", "ATCCTGGAGCTTAGTCATAG")
mfe <- foldgRNAs(gRNAs.withoutPAM)
```

| | |
|--------------------------------|--|
| <code>getOfftargetScore</code> | <i>Calculate score for each off target</i> |
|--------------------------------|--|

Description

Calculate score for each off target with given feature vectors and weights vector

Usage

```
getOfftargetScore(featureVectors,
  weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508,
  0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583))
```

Arguments

featureVectors a data frame generated from `buildFeatureVectorForScoring`. It contains `IsMismatch.posX` (Indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1- gRNA.size) representing all positions in the gRNA), `strand` (strand of the off target, + for plus and - for minus strand), `chrom` (chromosome of the off target), `chromStart` (start position of the off target), `chromEnd` (end position of the off target), `name` (gRNA name), `gRNAPlusPAM` (gRNA sequence with PAM sequence concatenated), `OffTargetSequence` (the genomic sequence of the off target), `n.mismatch` (number of mismatches between the off target and the gRNA), `forViewInUCSC` (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), `score` (score of the off target), `mismatch.distance2PAM` (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), `alignment` (alignment between gRNA and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches), `NGG` (this off target contains canonical PAM or not, 1 for yes and 0 for no) `mean.neighbor.distance.mismatch` (mean distance between neighboring mismatches)

weights a numeric vector size of gRNA length, default `c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583)` which is used in Hsu et al., 2013 cited in the reference section

Details

score is calculated using the weights and algorithm by Hsu et al., 2013 cited in the reference section

Value

a data frame containing strand (strand of the match, + for plus and - for minus strand), chrom (chromosome of the off target), chromStart (start position of the off target), chromEnd (end position of the off target), name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (score of the off target), mismatch.distance2PAM (a comma separated distances of all mismatches to PAM, e.g., 14,11 means one mismatch is 14 bp away from PAM and the other mismatch is 11 bp away from PAM), alignment (alignment between gRNA and off target, e.g.,G..C..... means that this off target aligns with gRNA except that G and C are mismatches), NGG (this off target contains canonical PAM or not, 1 for yes and 0 for no) mean.neighbor.distance.mismatch (mean distance between neighboring mismatches)

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834

See Also

offTargetAnalysis

Examples

```
hitsFile <- system.file("extdata", "hits.txt",
  package = "CRISPRseek")
hits <- read.table(hitsFile, sep = "\t", header = TRUE,
  stringsAsFactors = FALSE)
featureVectors <- buildFeatureVectorForScoring(hits)
getOfftargetScore(featureVectors)
```

isPatternUnique

Output whether the input patterns occurs only once in the sequence

Description

Input a sequence and a list of patterns and determine if the patterns occurs only once in the sequence. Used for determining whether a RE site in gRNA also occurs in the flanking region.

Usage

```
isPatternUnique(seq, patterns)
```

Arguments

```
seq          flanking sequence of a gRNA
patterns     patterns as DNASTringSet, such as a list of RE sites
```

Value

returns a character vectors containing the uniqueness of each pattern/RE site

Author(s)

Lihua Julie Zhu

Examples

```
seq <- "TGGATTGTATAATCAGCATGGATTTGGAAC"
patterns <- DNASTringSet(c("TGG", "TGGA", "TGGATA", "TTGGAAC", ""))
isPatternUnique(seq, patterns)
isPatternUnique(seq)
isPatternUnique(patterns)
```

| | |
|-------------------|--|
| offTargetAnalysis | <i>Design of target-specific guide RNAs for CRISPR-Cas9 system in one function</i> |
|-------------------|--|

Description

Design of target-specific guide RNAs (gRNAs) for CRISPR-Cas9 system by automatically calling findgRNAs, filtergRNAs, searchHits, buildFeatureVectorForScoring, getOfftargetScore, filterOfftarget, calculating gRNA cleavage efficiency and generate reports.

Usage

```
offTargetAnalysis(inputFilePath, format = "fasta", header = FALSE,
  gRNAoutputName, findgRNAs = TRUE,
  exportAllgRNAs = c("all", "fasta", "genbank", "no"),
  findgRNAsWithREcutOnly = FALSE,
  REpatternFile = system.file("extdata", "NEBenzymes.fa",
    package = "CRISPRseek"), minREpatternSize = 4,
  overlap.gRNA.positions = c(17, 18), findPairedgRNAOnly = FALSE,
  annotatePaired = TRUE, enable.multicore = FALSE,
  min.gap = 0, max.gap = 20, gRNA.name.prefix = "", PAM.size = 3,
  gRNA.size = 20, PAM = "NGG", BSgenomeName, chromToSearch = "all",
  chromToExclude = c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1",
```

```

"chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_qbl_hap6",
"chr6_ssto_hap7"),
  max.mismatch = 3, PAM.pattern = "N[A|G]G$", allowed.mismatch.PAM = 2,
  gRNA.pattern = "", min.score = 0.5, topN = 100,
  topN.OfftargetTotalScore = 10, annotateExon = TRUE,
txdb, orgAnn, outputDir, fetchSequence = TRUE, upstream = 200, downstream = 200,
upstream.search = 0, downstream.search = 0,
weights = c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508,
0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583),
baseBeforegRNA = 4, baseAfterPAM = 3,
featureWeightMatrixFile = system.file("extdata", "DoenchNBT2014.csv",
package = "CRISPRseek"), useScore = TRUE, useEfficacyFromInputSeq = FALSE,
outputUniqueREs = TRUE, foldgRNAs = TRUE,
gRNA.backbone="GUUUUAGAGCUAGAAAUAGCAAGUUAUUAAUAAGGCUAGUCCGUUAUCAACUUGAAAAAGUGGCACCGAGUCGGUGCUUUUU
temperature = 37,
overwrite = FALSE)

```

Arguments

| | |
|------------------------|--|
| inputFilePath | Sequence input file path or a DNASTringSet object that contains sequences to be searched for potential gRNAs |
| format | Format of the input file, fasta, fastq and bed are supported, default fasta |
| header | Indicate whether the input file contains header, default FALSE, only applies to bed format |
| gRNAoutputName | Specify the name of the gRNA output file when inputFilePath is DNASTringSet object instead of file path |
| findgRNAs | Indicate whether to find gRNAs from the sequences in the input file or skip the step of finding gRNAs, default TRUE. Set it to FALSE if the input file contains user selected gRNAs plus PAM already. |
| exportAllgRNAs | Indicate whether to output all potential gRNAs to a file in fasta format, genbank format or both. Default to both. |
| findgRNAsWithREcutOnly | Indicate whether to find gRNAs overlap with restriction enzyme recognition pattern |
| REpatternFile | File path containing restriction enzyme cut patterns |
| minREpatternSize | Minimum restriction enzyme recognition pattern length required for the enzyme pattern to be searched for, default 4 |
| overlap.gRNA.positions | The required overlap positions of gRNA and restriction enzyme cut site, default 17 and 18 |
| findPairedgRNAOnly | Choose whether to only search for paired gRNAs in such an orientation that the first one is on minus strand called reverse gRNA and the second one is on plus strand called forward gRNA. TRUE or FALSE, default FALSE |
| annotatePaired | Indicate whether to output paired information, default TRUE |

| | |
|--------------------------|--|
| min.gap | Minimum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 0 |
| enable.multicore | Indicate whether enable parallel processing, default FALSE. For super long sequences with lots of gRNAs, suggest set it to TRUE |
| max.gap | Maximum distance between two oppositely oriented gRNAs to be valid paired gRNAs. Default 20 |
| gRNA.name.prefix | The prefix used when assign name to found gRNAs, default gRNA, short for guided RNA. |
| PAM.size | PAM length, default 3 |
| gRNA.size | The size of the gRNA, default 20 |
| PAM | PAM sequence after the gRNA, default NGG |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |
| chromToSearch | Specify the chromosome to search, default to all, meaning search all chromosomes. For example, chrX indicates searching for matching in chromosome X only |
| chromToExclude | Specify the chromosome not to search. If specified as "", meaning to search chromosomes specified by chromToSearch. By default, to exclude haplotype blocks from offtarget search in hg19, i.e., chromToExclude = c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1", "chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_qbl", "chr6_ssto_hap7") |
| max.mismatch | Maximum mismatch allowed in off target search, default 3. Warning: will be considerably slower if set > 3 |
| PAM.pattern | Regular expression of protospacer-adjacent motif (PAM), default N[AIG]G\$ |
| allowed.mismatch.PAM | Number of degenerative bases in the PAM sequence, default to 2 for N[AIG]G PAM |
| gRNA.pattern | Regular expression or IUPAC Extended Genetic Alphabet to represent gRNA pattern, default is no restriction. To specify that the gRNA must start with GG for example, then set it to ^GG. Please see help(translatePattern) for a list of IUPAC Extended Genetic Alphabet. |
| min.score | minimum score of an off target to included in the final output, default 0.5 |
| topN | top N off targets to be included in the final output, default 100 |
| topN.OfftargetTotalScore | top N off target used to calculate the total off target score, default 10 |
| annotateExon | Choose whether or not to indicate whether the off target is inside an exon or not, default TRUE |

| | |
|-------------------------|--|
| txdb | TxDb object, for creating and using TxDb object, please refer to GenomicFeatures package. For a list of existing TxDb object, please search for annotation package starting with Txdb at http://www.bioconductor.org/packages/release/BiocViews.html#___Annotation such as TxDb.Rnorvegicus.UCSC.rn5.refGene for rat, TxDb.Mmusculus.UCSC.mm10.knownGene for mouse, TxDb.Hsapiens.UCSC.hg19.knownGene for human, TxDb.Dmelanogaster.UCSC.dm3.ensGene for Drosophila and TxDb.Celegans.UCSC.ce6.ensGene for C.elegans |
| orgAnn | organism annotation mapping such as org.Hs.egSYMBOL in org.Hs.eg.db package for human |
| outputDir | the directory where the off target analysis and reports will be written to |
| fetchSequence | Fetch flank sequence of off target or not, default TRUE |
| upstream | upstream offset from the off target start, default 200 |
| downstream | downstream offset from the off target end, default 200 |
| upstream.search | upstream offset from the bed input starts to search for gRNAs, default 0 |
| downstream.search | downstream offset from the bed input ends to search for gRNAs, default 0 |
| weights | a numeric vector size of gRNA length, default c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583) which is used in Hsu et al., 2013 cited in the reference section |
| baseBeforegRNA | Number of bases before gRNA used for calculating gRNA efficiency, default 4 |
| baseAfterPAM | Number of bases after PAM used for calculating gRNA efficiency, default 3 |
| featureWeightMatrixFile | Feature weight matrix file used for calculating gRNA efficiency. By default DoenchNBT2014 weight matrix is used. To use alternative weight matrix file, please input a csv file with first column containing significant features and the second column containing the corresponding weights for the features. Please see Doench et al., 2014 for details. |
| useScore | Default TRUE, display in gray scale with the darkness indicating the gRNA efficacy. The taller bar shows the Cas9 cutting site. If set to False, efficacy will not show. Instead, gRNAs in plus strand will be colored red and gRNAs in negative strand will be colored green. |
| useEfficacyFromInputSeq | Default FALSE. If set to TRUE, summary file will contain gRNA efficacy calculated from input sequences instead of from off-target analysis. Set it to TRUE if the input sequence is from a different species than the one used for off-target analysis. |
| outputUniqueREs | Default TRUE. If set to TRUE, summary file will contain REs unique to the cleavage site within 100 or 200 bases surrounding the gRNA sequence. |
| foldgRNAs | Default TRUE. If set to TRUE, summary file will contain minimum free energy of the secondary structure of gRNA with gRNA backbone from GeneRfold package provided that GeneRfold package has been installed. |
| gRNA.backbone | gRNA backbone constant region sequence. Default to the sequence in Sp gRNA backbone. |
| temperature | temperature in celsius. Default to 37 celsius. |
| overwrite | overwrite the existing files in the output directory or not, default FALSE |

Value

Four tab delimited files are generated in the output directory: OfftargetAnalysis.xls (detailed information of off targets), Summary.xls (summary of the gRNAs), REcutDetails.xls (restriction enzyme cut sites of each gRNA), and pairedgRNAs.xls (potential paired gRNAs)

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. *Nature Biotechnology* 31:827-834 Doench JG, Hartenian E, Graham DB, Tothova Z, Hegde M, Smith I, Sullender M, Ebert BL, Xavier RJ, Root DE. Rational design of highly active sgRNAs for CRISPR-Cas9-mediated gene inactivation. *Nat Biotechnol.* 2014 Sep 3. doi: 10.1038 nbt.3026 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. *Plos One* Sept 23rd 2014

See Also

CRISPRseek

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(org.Hs.eg.db)
outputDir <- getwd()
inputFilePath <- system.file("extdata", "inputseq.fa",
                             package = "CRISPRseek")
REpatternFile <- system.file("extdata", "NEBenzymes.fa",
                             package = "CRISPRseek")
results <- offTargetAnalysis(inputFilePath, findgRNAsWithREcutOnly = TRUE,
                             REpatternFile = REpatternFile, findPairedgRNAOnly = FALSE,
                             annotatePaired = FALSE,
                             BSgenomeName = Hsapiens, chromToSearch = "chrX",
                             txdb = TxDb.Hsapiens.UCSC.hg19.knownGene,
                             orgAnn = org.Hs.egSYMBOL, max.mismatch = 1,
                             outputDir = outputDir, overwrite = TRUE)
```

offTargetAnalysisOfPeakRegions

Finding offtargets in given regions

Description

Finding offtargets in given regions, such as peaks from GUIDE-seq

Usage

```
offTargetAnalysisOfPeakRegions(gRNA, peaks,
  format=c("fasta", "bed"),
  peaks.withHeader = FALSE, BSgenomeName,
  upstream = 50, downstream =50, PAM.size = 3, gRNA.size = 20,
  PAM = "NGG", PAM.pattern = "NNN$", max.mismatch = 6,
  outputDir, allowed.mismatch.PAM = 3, overwrite = TRUE,
  weights = c(0, 0, 0.014, 0, 0, 0.395,
  0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615,
  0.804, 0.685, 0.583)
)
```

Arguments

| | |
|----------------------|--|
| gRNA | gRNA input file path or a DNASTringSet object that contains gRNA plus PAM sequences used for genome editing |
| peaks | peak input file path or a GenomicRanges object that contains genomic regions to be searched for potential offtargets |
| format | Format of the gRNA and peak input file. Currently, fasta and bed are supported for gRNA and peak input file respectively |
| peaks.withHeader | Indicate whether the peak input file contains header, default FALSE |
| PAM.size | PAM length, default 3 |
| gRNA.size | The size of the gRNA, default 20 |
| PAM | PAM sequence after the gRNA, default NGG |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |
| max.mismatch | Maximum mismatch allowed in off target search, default 6 |
| PAM.pattern | Regular expression of protospacer-adjacent motif (PAM), default N[AIG]G\$ |
| allowed.mismatch.PAM | Number of degenerative bases in the PAM sequence, default to 2 for N[AIG]G PAM |

| | |
|------------|--|
| outputDir | the directory where the off target analysis and reports will be written to |
| upstream | upstream offset from the peak start, default 50 |
| downstream | downstream offset from the peak end, default 50 |
| weights | a numeric vector size of gRNA length, default c(0, 0, 0.014, 0, 0, 0.395, 0.317, 0, 0.389, 0.079, 0.445, 0.508, 0.613, 0.851, 0.732, 0.828, 0.615, 0.804, 0.685, 0.583) which is used in Hsu et al., 2013 cited in the reference section |
| overwrite | overwrite the existing files in the output directory or not, default FALSE |

Value

Same as compare2Sequences with one more tab-delimited file offTargetsInPeakRegions.xls containing all input peaks with potential gRNA binding sites, mismatch number and positions, and predicted cleavage score.

Author(s)

Lihua Julie Zhu

References

Patrick D Hsu, David A Scott, Joshua A Weinstein, F Ann Ran, Silvana Konermann, Vineeta Agarwala, Yinqing Li, Eli J Fine, Xuebing Wu, Ophir Shalem, Thomas J Cradick, Luciano A Marraffini, Gang Bao & Feng Zhang (2013) DNA targeting specificity of rNA-guided Cas9 nucleases. Nature Biotechnology 31:827-834 Lihua Julie Zhu, Benjamin R. Holmes, Neil Aronin and Michael Brodsky. CRISPRseek: a Bioconductor package to identify target-specific guide RNAs for CRISPR-Cas9 genome-editing systems. Plos One Sept 23rd 2014

See Also

CRISPRseek

Examples

```
library(CRISPRseek)
library("BSgenome.Hsapiens.UCSC.hg19")
peaks <- system.file("extdata", "T2plus1000offTargets.bed",
  package = "CRISPRseek")
gRNAs <- system.file("extdata", "T2.fa",
  package = "CRISPRseek")
outputDir = getwd()
offTargets <- offTargetAnalysisOfPeakRegions(gRNA = gRNAs, peaks = peaks,
  format=c("fasta", "bed"),
  peaks.withHeader = TRUE, BSgenomeName = Hsapiens,
  upstream = 50, downstream =50, PAM.size = 3, gRNA.size = 20,
  PAM = "NGG", PAM.pattern = "NNN$", max.mismatch = 8,
  outputDir = outputDir,
  allowed.mismatch.PAM = 3, overwrite = TRUE
)
```

searchHits *Search for off targets*

Description

Search for off targets for given gRNAs, BSgenome and maximum mismatches

Usage

```
searchHits(gRNAs, BSgenomeName, chromToSearch = "all", chromToExclude = "",
           max.mismatch = 3,
           PAM.size = 3, gRNA.size = 20, PAM = "N[A|G]G$", allowed.mismatch.PAM = 2)
```

Arguments

| | |
|----------------------|---|
| gRNAs | DNAStringSet object containing a set of gRNAs. Please note the sequences must contain PAM appended after gRNAs, e.g., ATCGAAATTCGAGCCAATCCGG where ATCGAAATTCGAGCCAATCC is the gRNA and CGG is the PAM |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |
| chromToSearch | Specify the chromosome to search, default to all, meaning search all chromosomes. For example, chrX indicates searching for matching in chromosome X only |
| chromToExclude | Specify the chromosome not to search, default to none, meaning to search chromosomes specified by chromToSearch. For example, to exclude haplotype blocks from offtarget search in hg19, set chromToExclude to c("chr17_ctg5_hap1", "chr4_ctg9_hap1", "chr6_apd_hap1", "chr6_cox_hap2", "chr6_dbb_hap3", "chr6_mann_hap4", "chr6_mcf_hap5", "chr6_qbl", "chr6_ssto_hap7") |
| max.mismatch | Maximum mismatch allowed in off target search, default 3. Warning: will be considerably slower if it is set to greater than 3 |
| PAM.size | Size of PAM, default 3 |
| gRNA.size | Size of gRNA, default 20 |
| PAM | Regular expression of PAM, default N[A G]G\$ |
| allowed.mismatch.PAM | Number of degenerative bases in the PAM sequence, default to 2 for N[A G]G PAM |

Value

a data frame contains IsMismatch.posX (indicator variable indicating whether this position X is mismatch or not, 1 means yes and 0 means not, X = 1 to gRNA.size) representing all positions in the gRNA), strand (strand of the match, + for plus and - for minus strand), chrom (chromosome of the off

target), chromStart (start position of the off target), chromEnd (end position of the off target), name (gRNA name), gRNAPlusPAM (gRNA sequence with PAM sequence concatenated), OffTargetSequence (the genomic sequence of the off target), n.mismatch (number of mismatches between the off target and the gRNA), forViewInUCSC (string for viewing in UCSC genome browser, e.g., chr14:31665685-31665707), score (set to 100, and will be updated in getOfftargetScore)

Author(s)

Lihua Julie Zhu

See Also

offTargetAnalysis

Examples

```
all.gRNAs <- findgRNAs(inputFilePath =
  system.file("extdata", "inputseq.fa", package = "CRISPRseek"),
  pairOutputFile = "pairedgRNAs.xls",
  findPairedgRNAOnly = TRUE)

library("BSgenome.Hsapiens.UCSC.hg19")
### for speed reason, use max.mismatch = 0 for finding all targets with
### all variants of PAM
hits <- searchHits(all.gRNAs[1], BSgenomeName = Hsapiens,
  max.mismatch = 0, chromToSearch = "chrX")
colnames(hits)
```

| | |
|------------------|---|
| translatePattern | <i>translate pattern from IUPAC Extended Genetic Alphabet to regular expression</i> |
|------------------|---|

Description

translate pattern containing the IUPAC nucleotide ambiguity codes to regular expression. For example, Y->[C|T], R-> [A|G], S-> [G|C], W-> [A|T], K-> [T|U|G], M-> [A|C], B-> [C|G|T], D-> [A|G|T], H-> [A|C|T], V-> [A|C|G] and N-> [A|C|T|G].

Usage

```
translatePattern(pattern)
```

Arguments

pattern a character vector with the IUPAC nucleotide ambiguity codes

Value

a character vector with the pattern represented as regular expression

Author(s)

Lihua Julie Zhu

Examples

```
pattern1 <- "AACCNWМК"
translatePattern(pattern1)
```

| | |
|-----------|---|
| uniqueREs | <i>Output restriction enzymes that recognize only the gRNA cleavage sites</i> |
|-----------|---|

Description

For each identified gRNA, output restriction enzymes that recognize only the gRNA cleavage sites.

Usage

```
uniqueREs(REcutDetails, summary, offTargets, scanUpstream = 100,
          scanDownstream = 100, BSgenomeName)
```

Arguments

| | |
|----------------|--|
| REcutDetails | REcutDetails stored in the REcutDetails.xls |
| summary | summary stored in the summary.xls |
| offTargets | offTargets stored in the offTargets.xls |
| scanUpstream | upstream offset from the gRNA start, default 100 |
| scanDownstream | downstream offset from the gRNA end, default 100 |
| BSgenomeName | BSgenome object. Please refer to available.genomes in BSgenome package. For example, BSgenome.Hsapiens.UCSC.hg19 for hg19, BSgenome.Mmusculus.UCSC.mm10 for mm10, BSgenome.Celegans.UCSC.ce6 for ce6, BSgenome.Rnorvegicus.UCSC.rn5 for rn5, BSgenome.Drerio.UCSC.danRer7 for Zv9, and BSgenome.Dmelanogaster.UCSC.dm3 for dm3 |

Value

returns the RE sites that recognize only the gRNA cleavage sites for each gRNA.

Author(s)

Lihua Julie Zhu

Examples

```
library("BSgenome.Hsapiens.UCSC.hg19")
load(system.file("extdata", "ForTestinguniqueREs.RData",
  package = "CRISPRseek"))
uniqueREs(results$REcutDetails, results$summary, results$offtarget,
scanUpstream = 50,
  scanDownstream = 50, BSgenomeName = Hsapiens)
```

writeHits

Write the hits of sequence search to a file

Description

write the hits of sequence search to a file, internal function used by searchHits

Usage

```
writeHits(gRNA, seqname, matches, strand, file, gRNA.size = 20,
  PAM = "N[A|G]G$", max.mismatch = 4, chrom.len, append = FALSE)
```

Arguments

| | |
|--------------|--|
| gRNA | DNASTring object with gRNA sequence with PAM appended immediately after, e.g., ACGTACGTACGTACTGACGTCGG with 20bp gRNA sequence plus 3bp PAM sequence CCG |
| seqname | chromosome name as character, e.g., chr1 |
| matches | XStringViews object storing matched chromosome locations |
| strand | strand of the match, + for plus strand and - for minus strand |
| file | file path where the hits is written to |
| gRNA.size | gRNA size, default 20 |
| PAM | PAM as regular expression for filtering the hits, default N[A G]G\$ |
| max.mismatch | maximum mismatch allowed within the gRNA (excluding PAM portion) for filtering the hits, default 4 |
| chrom.len | length of the matched chromosome |
| append | TRUE if append to existing file, false if start a new file |

Value

results are saved in the file specified by file

Author(s)

Lihua Julie Zhu

References

<http://bioconductor.org/packages/2.8/bioc/vignettes/BSgenome/inst/doc/GenomeSearching.pdf>

See Also

offTargetAnalysis

Examples

```
gRNAPlusPAM <- DNASTring("ACGTACGTACGTAAGTACGTCGG")
x <- DNASTring("AAGCGGATATGACGTACGTACGTAAGTACGTCGG")
chrom.len <- nchar(as.character(x))
m <- matchPattern(gRNAPlusPAM, x)
names(m) <- "testing"
writeHits(gRNA = gRNAPlusPAM, seqname = "chr1",
          matches = m, strand = "+", file = "exampleWriteHits.txt",
          chrom.len = chrom.len, append = FALSE)
```

Index

*Topic **misc**

- annotateOffTargets, 4
- buildFeatureVectorForScoring, 6
- calculategRNAEfficiency, 7
- compare2Sequences, 9
- filtergRNAs, 12
- filterOffTarget, 14
- findgRNAs, 16
- foldgRNAs, 18
- getOfftargetScore, 19
- isPatternUnique, 20
- offTargetAnalysis, 21
- offTargetAnalysisOfPeakRegions, 26
- searchHits, 28
- translatePattern, 29
- uniqueREs, 30
- writeHits, 31

*Topic **package**

- CRISPRseek-package, 2

annotateOffTargets, 4

buildFeatureVectorForScoring, 6

calculategRNAEfficiency, 7

compare2Sequences, 9

CRISPRseek (CRISPRseek-package), 2

CRISPRseek-package, 2

filtergRNAs, 12

filterOffTarget, 14

findgRNAs, 16

foldgRNAs, 18

getOfftargetScore, 19

isPatternUnique, 20

offTargetAnalysis, 21

offTargetAnalysisOfPeakRegions, 26

searchHits, 28

translatePattern, 29

uniqueREs, 30

writeHits, 31