

Package ‘MmPalateMiRNA’

April 12, 2018

Type Package

Title Murine Palate miRNA Expression Analysis

Version 1.28.0

Date 2012-11-06

Author Guy Brock <guy.brock@louisville.edu>, Partha Mukhopadhyay

<p0mukh01@louisville.edu>, Vasyl Pihur

<vasyl.pihur@louisville.edu>, Robert M. Greene

<Dr.Bob.Greene@gmail.com>, and M. Michele Pisano

<mmpisa01@louisville.edu>

Maintainer Guy Brock <guy.brock@louisville.edu>

Depends R (>= 2.13.0), methods, Biobase, xtable, limma, statmod,
lattice, vsn

Imports limma, lattice, Biobase

Suggests GOstats, graph, Category, org.Mm.eg.db, microRNA,
targetscan.Mm.eg.db, RSQLite, DBI, AnnotationDbi, clValid,
class, cluster, multtest, RColorBrewer, latticeExtra

Description R package compendium for the analysis of murine palate
miRNA two-color expression data.

License GPL-3

LazyLoad yes

Collate MmPalateMiRNA-Methods.R MmPalateMiRNA-functions.R

biocViews Microarray, TwoChannel, QualityControl, Preprocessing,
DifferentialExpression, MultipleComparison, Clustering, GO,
Pathways, ReportWriting, SequenceMatching

NeedsCompilation no

R topics documented:

MmPalateMiRNA-package	2
checkMVs	3
checkOutliers	4
clustPlot	5
densityplot	6
filterArray	7

fixMVs	8
fixOutliers	9
imputeKNN	10
levelplot	11
MADvsMedianPlot	12
MAplot	13
PalateData	15

Index**17**

MmPalateMiRNA-package *R package compendium for the analysis of murine palate two-color miRNA expression data*

Description

R package compendium for the analysis of two-color miRNA expression data, during the period of murine embryonic palate development (gestational days (GD) 12, 13, and 14). Samples were hybridized to Miltenyi Biotech miRXplore Microarrays. The compendium covers a wide range of steps which occur in a typical miRNA microarray data analysis, including pre-processing, normalization, differential expression analysis, clustering, target identification, and gene-set enrichment analysis.

Details

Package:	MmPalateMiRNA
Type:	Package
Version:	1.0
Date:	2011-09-14
License:	LGPL
LazyLoad:	yes

The package contains several functions which are helpful during the pre-processing steps of array data, which are specific to `RGList` objects and, in the case of the `fixOutliers` and `fixMVs` functions, depend on the replicated structure of Miltenyi Biotech miRXplore Microarrays. Additionally, methods are available to produce diagnostic plots for `RGList` objects and lists of normalized data sets (`MAList` and / or `NChannelSet` objects), which build on the generic functions in `lattice`. Lastly, the main focus of the package is the package vignette "MmPalateMiRNA", which contains an extended example covering the typical steps in an miRNA microarray data analysis.

Author(s)

Guy Brock, Partha Mukhopadhyay, Vasyl Pihur, Bob Green, M. Michele Pisano Maintainer: Guy Brock <guy.brock@louisville.edu>

References

P. Mukhopadhyay, G. Brock, V. Pihur, C. Webb, M.M. Pisano, and R.M. Greene. Developmental microRNA expression profiling of murine embryonic orofacial tissue. Birth Defects Res A Clin Mol Teratol, 88(7):511-34, 2010.

R. Gentleman. Reproducible research: a bioinformatics case study. *Stat Appl Genet Mol Biol*, 4:Article2, 2005.

D. Sarkar, R. Parkin, S. Wyman, A. Bendoraitė, C. Sather, J. Delrow, A. K. Godwin, C. Drescher, W. Huber, R. Gentleman, and M. Tewari. Quality assessment and data analysis for microRNA expression arrays. *Nucleic Acids Res*, 37(2):e17, 2009.

checkMVs

Check an [RGList](#) object for missing values

Description

Checks each of the red and green foreground and background channels in an [RGList](#) object for missing values.

Usage

```
checkMVs(obj)
## S4 method for signature 'RGList'
checkMVs(obj)
```

Arguments

obj An [RGList](#) object

Value

Returns a list with the following components

R.na	index of missing values in the red channel (<code>obj\$R</code>)
Rb.na	index of missing values in the red background channel (<code>obj\$Rb</code>)
G.na	index of missing values in the green channel (<code>obj\$G</code>)
Gb.na	index of missing values in the green background channel (<code>obj\$Gb</code>)

Methods

`signature(obj = "RGList")`

See Also

[fixMVs](#), [checkOutliers](#), [fixOutliers](#)

Examples

```
data(PalateData)
mvs <- checkMVs(PalateData)
```

checkOutliers *Check RGList object for outlying values*

Description

Checks each of the red and green foreground and background channels in an [RGList](#) for outlying values.

Usage

```
checkOutliers(obj)
## S4 method for signature 'RGList'
checkOutliers(obj)
```

Arguments

obj	An RGList object
-----	----------------------------------

Details

Detects outliers outside range of mean +/- 2.665 standard deviations. Returns the indexes of outlying observations in each channel (R,Rb and G,Gb).

Value

Returns a list with the following components

Rout	index of outliers in the red channel (obj\$R)
Rbout	index of outliers in the red background channel (obj\$Rb)
Gout	index of outliers in the green channel (obj\$G)
Gbout	index of outliers in the green background channel (obj\$Gb)

Methods

```
signature(obj = "RGList")
```

See Also

[fixOutliers](#), [checkMVs](#), [fixMVs](#)

Examples

```
data(PalateData)
outliers <- checkOutliers(PalateData)
```

clustPlot	<i>Plot expression profiles</i>
-----------	---------------------------------

Description

Produces plots of clustered expression profiles, with separate plots for each cluster. The average expression profile for each cluster is superimposed as well.

Usage

```
clustPlot(cl, mat, nrow, ncol)
```

Arguments

cl	integer vector giving the cluster membership for each item
mat	matrix of values to be plotted
nrow	number of rows to use for plotting
ncol	number of columns to use for plotting

Details

The figure region will be subdivided into nrow by ncol separate plots, using `mffrow`. The average expression profile and the number of genes belonging to each cluster is superimposed on each of the plots.

References

G.N. Brock, V. Pihur, S. Datta, and S. Datta. clValid, an R package for cluster validation. *Journal of Statistical Software*, 25, 2008.

See Also

See the package vignette for illustration on usage

Examples

```
## generate some fake data and cluster
set.seed(101)
mat <- matrix(rnorm(500), nrow=100, ncol=5)
clusts <- hclust(dist(mat))
cl <- cutree(clusts, 6)
clustPlot(cl, mat, 3, 2)
```

densityplot*Density plots of log2 intensity values*

Description

Plots the estimated density of log2 intensity values for two-color microarrays

Usage

```
## S4 method for signature 'RGList,missing'
densityplot(
  x,
  channel=c("G", "R"),
  group=NULL,
  subset=NULL,
  ...)

## S4 method for signature 'list,missing'
densityplot(
  x,
  channel=c("G", "R"),
  group=NULL,
  subset=NULL,
  ...)
```

Arguments

<code>x</code>	Either an RGList object, or a list containing MAList and/or NChannelSet objects
<code>channel</code>	The channel to use for calculating distances, one of either "G" (green or control channel) or "R" (red or experimental channel)
<code>group</code>	An optional character string specifying the name of a factor to create separate panel displays, which must be in <code>x\$genes</code> (for RGList objects)
<code>subset</code>	An optional character vector specifying the which levels of <code>group</code> to use in creating separate panel displays
<code>...</code>	arguments to pass to densityplot

Methods

```
signature(x = "RGList", data = "missing") For RGList objects, separate panel displays can
be produced for different types of probes, as determined by the group argument.

signature(x = "list", data = "missing") The method for list objects is intended to work
with lists of normalized data sets, as either MAList or NChannelSet objects. This method will
produce separate panel displays for each normalized data set, additionally subsetted by the
group argument if supplied. The useOuterStrips function in the latticeExtra package can
be used for 'outer' strip labels in the latter case.
```

References

D. Sarkar, R. Parkin, S. Wyman, A. Bendoraitė, C. Sather, J. Delrow, A. K. Godwin, C. Drescher, W. Huber, R. Gentleman, and M. Tewari. Quality assessment and data analysis for microRNA expression arrays. *Nucleic Acids Res.*, 37(2):e17, 2009.

See Also

[levelplot](#) for pairwise distance plots between arrays, [MADvsMedianPlot](#) for median absolute deviation versus median plots, and [MAplot](#) for MA plots

Examples

```
data(PalateData)
res <- densityplot(PalateData, channel="G", group="probe.type",
                     subset = c("Other miRNAs", "MMU miRNAs", "Control"),
                     col=rep(1:3, each=3), lty=rep(1:3, 3),
                     key = list(lines=list(col=rep(1:3, each=3), lty=rep(1:3, 3)),
                                columns=3))
print(res)
```

filterArray

Filter an [RGList](#) object to remove probes

Description

Filters an [RGList](#) object to remove probes with foreground intensities not sufficiently above the background intensity. Additionally can filter probes based on character strings, to remove e.g. control probes.

Usage

```
filterArray (obj, ...)
## S4 method for signature 'RGList'
filterArray(obj, keep, frac, number, reps)
```

Arguments

obj	An RGList object
keep	Character vector to be used as a text filter. Only gene names (as contained in <code>obj\$genes\$Name</code>) which contain these text strings will be retained.
frac	Fraction to use as a background filter. Only those probes with foreground values (both red and green) greater than 'frac' times the background values pass the filter.
number	The number of samples required to pass the background filter for each probe.
reps	The number of replicates for each probe required to pass the filtering step.
...	allows additional arguments to be passed to specific methods

Value

Returns an [RGList](#) object identical in structure to the input object, but with reduced dimension according to the filtering steps.

Methods

```
signature(obj = "RGList")
```

See Also

[checkMVs](#), [fixMVs](#), [checkOutliers](#), [fixOutliers](#)

Examples

```
data(PalateData)
reducedSet <- filterArray(PalateData, keep=c("MIR", "LET", "POSCON", "CALIB"),
                           frac=1.1, number=3, reps=4)
```

fixMVs

'Fix' an RGList object with missing values.

Description

Imputes missing values in one of the red foreground, red background, green foreground, or green background matrices of an RGList object created from Miltenyi Biotech miRXplore Microarrays. Uses the replicate structure of the array to impute the missing values. Implicit assumption is that only one of the four replicated values for a probe is a missing value.

Usage

```
fixMVs(mat, idx, gene.ids)
```

Arguments

mat	One of the red foreground (R), red background (Rb), green foreground (G), or green background (Gb) matrices in an RGList object, which contains missing values.
idx	Index of missing values, as returned by the checkMVs function. See examples for usage.
gene.ids	Vector of gene IDs for each probe. See examples for usage.

Details

The function is specific to RGList objects which were created from Miltenyi Biotech miRXplore Microarrays, since it depends on the replicated structure of that array (probes spotted in quadruplicate) to impute the missing probe values.

Value

Returns a matrix with the missing probe values imputed.

See Also

[checkMVs](#), [checkOutliers](#), [fixOutliers](#)

Examples

```
data(PalateData)
mvs <- checkMVs(PalateData)
PalateData$Rb <- fixMVs(PalateData$Rb, mvs$Rb.na, PalateData$genes$Gene)
```

fixOutliers

'Fix' an RGList object with outlying values.

Description

Imputes outlying values in one of the red foreground, red background, green foreground, or green background matrices of an RGList object created from Miltenyi Biotech miRXplore Microarrays. Uses the replicate structure of the array to impute the outlying values. Implicit assumption is that only one of the four replicated values for a probe is an outlying value.

Usage

```
fixOutliers(mat, idx, gene.ids)
```

Arguments

mat	One of the red foreground (R), red background (Rb), green foreground (G), or green background (Gb) matrices in an RGList object, which contains outlying values.
idx	Index of outlying values, as returned by the checkOutliers function. See examples for usage.
gene.ids	Vector of gene IDs for each probe. See examples for usage.

Details

The function is specific to RGList objects which were created from Miltenyi Biotech miRXplore Microarrays, since it depends on the replicated structure of that array (probes spotted in quadruplicate) to impute the outlying probe values.

Value

Returns a matrix with the outlying probe values imputed.

See Also

[checkOutliers](#), [checkMVs](#), [fixMVs](#)

Examples

```
data(PalateData)
outliers <- checkOutliers(PalateData)
PalateData$R <- fixOutliers(PalateData$R, outliers$Rout, PalateData$genes$Gene)
```

imputeKNN*Impute missing values*

Description

Imputes missing values in a data matrix using the K-nearest neighbor algorithm.

Usage

```
imputeKNN(data, k = 10, distance = "euclidean", rm.na = TRUE, rm.nan =  
TRUE, rm.inf = TRUE )
```

Arguments

data	a data matrix
k	number of neighbors to use
distance	distance metric to use, one of "euclidean" or "correlation"
rm.na	should NA values be imputed?
rm.nan	should NaN values be imputed?
rm.inf	should Inf values be imputed?

Details

Uses the K-nearest neighbor algorithm, as described in Troyanskaya et al., 2001, to impute missing values in a data matrix. Elements are imputed row-wise, so that neighbors are selected based on the rows which are closest in distance to the row with missing values. There are two choices for a distance metric, either Euclidean (the default) or a correlation 'metric'. If the latter is selected, matrix values are first row-normalized to mean zero and standard deviation one to select neighbors. Values are 'un'-normalized by applying the inverse transformation prior to returning the imputed data matrix.

Value

A data matrix with missing values imputed.

Author(s)

Guy Brock

References

- O. Troyanskaya, M. Cantor, G. Sherlock, P. Brown, T. Hastie, R. Tibshirani, D. Botstein, and R. B. Altman. Missing value estimation methods for dna microarrays. *Bioinformatics*, 17(6):520-5, 2001.
- G.N. Brock, J.R. Shaffer, R.E. Blakesley, M.J. Lotz, and G.C. Tseng. Which missing value imputation method to use in expression profiles: a comparative study and two selection schemes. *BMC Bioinformatics*, 9:12, 2008.

See Also

See the package vignette for illustration on usage.

Examples

```
## generate some fake data and impute MVs
set.seed(101)
mat <- matrix(rnorm(500), nrow=100, ncol=5)
idx.mv <- sample(1:length(mat), 50, replace=FALSE)
mat[idx.mv] <- NA
imputed <- imputeKNN(mat)
```

levelplot

Pairwise distance between arrays

Description

Calculates and plots the pairwise distance between arrays, as measured by the median of the absolute differences in log2 intensity values.

Usage

```
## S4 method for signature 'RGList,missing'
levelplot(
  x,
  channel=c("G", "R"),
  group=NULL,
  subset=NULL,
  ...)

## S4 method for signature 'list,missing'
levelplot(
  x,
  channel=c("G", "R"),
  order=NULL,
  ...)
```

Arguments

x	Either an RGList object, or a list containing MAList and/or NChannelSet objects
channel	The channel to use for calculating distances, one of either "G" (green or control channel) or "R" (red or experimental channel)
group	An optional character string specifying the name of a factor to create separate panel displays, which must be in x\$genes (for RGList objects)
subset	An optional character vector specifying the which levels of group to use in creating separate panel displays
order	An optional numeric vector specifying the order of the arrays to use in producing the distance plots, i.e. for grouping certain arrays together
...	arguments to pass to levelplot

Methods

`signature(x = "RGList", data = "missing")` For `RGList` objects, separate panel displays can be produced for different types of probes, as determined by the `group` argument.

`signature(x = "list", data = "missing")` The method for `list` objects is intended to work with lists of normalized data sets, as either `MAList` or `NChannelSet` objects. This method will produce separate panel displays for each normalized data set.

References

D. Sarkar, R. Parkin, S. Wyman, A. Bendoraitė, C. Sather, J. Delrow, A. K. Godwin, C. Drescher, W. Huber, R. Gentleman, and M. Tewari. Quality assessment and data analysis for microRNA expression arrays. *Nucleic Acids Res*, 37(2):e17, 2009.

See Also

`densityplot` for density plots of log2 intensity values, `MADvsMedianPlot` for median absolute deviation versus median plots, and `MAplot` for MA plots

Examples

```
data(PalateData)
res <- levelplot(PalateData[, c(1,5,9,2:4,6:8)],
                  channel="G", group="probe.type",
                  subset=c("MMU miRNAs", "Other miRNAs", "Control", "Empty"),
                  scales = list(rot=c(45, 45)))
print(res)
```

`MADvsMedianPlot`

Spread vs location of probe intensities

Description

Plots of the spread (median absolute deviation) versus the location (median) of probe intensity levels.

Usage

```
MADvsMedianPlot(x, ...)

## S4 method for signature 'list'
MADvsMedianPlot(
  x,
  channel=c("G", "R"),
  group=NULL,
  subset=NULL,
  ...)
```

Arguments

x	A list containing <code>MAList</code> and/or <code>NChannelSet</code> objects
channel	The channel to use for calculating distances, one of either "G" (green or control channel) or "R" (red or experimental channel)
group	An optional character string specifying the name of a factor to create separate panel displays, which must be in x\$genes (for <code>RGList</code> objects)
subset	An optional character vector specifying the which levels of group to use in creating separate panel displays
...	arguments to pass to <code>densityplot</code>

Methods

`signature(x = "list")` The method for `list` objects is intended to work with lists of normalized data sets, as either `MAList` or `NChannelSet` objects. This method will produce separate panel displays for each normalized data set, additionally color-coded by the `group` argument if supplied.

References

D. Sarkar, R. Parkin, S. Wyman, A. Bendoraitė, C. Sather, J. Delrow, A. K. Godwin, C. Drescher, W. Huber, R. Gentleman, and M. Tewari. Quality assessment and data analysis for microRNA expression arrays. *Nucleic Acids Res*, 37(2):e17, 2009.

See Also

`levelplot` for pairwise distance plots between arrays, `densityplot` for density plots of log2 intensity values, and `MAplot` for MA plots.

Examples

```
data(PalateData)
reducedSet <- filterArray(PalateData, keep=c("MIR", "LET", "POSCON", "CALIB"),
                           frac=1.1, number=3, reps=4)
ndata.none <- normalizeWithinArrays(reducedSet, method="none")
ndata.median <- normalizeWithinArrays(reducedSet, method="median")
ndata.loess <- normalizeWithinArrays(reducedSet, method="loess")
ndata.quantile <- normalizeBetweenArrays(reducedSet, method="quantile")
ndata.all <- list(ndata.none, ndata.median, ndata.loess,
                  ndata.quantile)
res <- MADvsMedianPlot(ndata.all, channel="R", group="probe.type",
                       subset=c("MMU miRNAs", "Other miRNAs", "Control"))
print(res)
```

Description

Plots of the log2 expression ratios (M values) versus the mean log2 expression values (A values) for each probe for each array.

Usage

```
MApplot(x, ...)

## S4 method for signature 'MAList'
MAplot(
  x,
  ...)

## S4 method for signature 'NChannelSet'
MAplot(
  x,
  ...)
```

Arguments

<code>x</code>	Either an MAList object or an NChannelSet object
<code>...</code>	arguments to pass to xyplot

Details

The so-called "MA" plot can be used to evaluate whether there is a bias associated with overall intensity level for each array. Loess smoothed regression lines are superimposed on each plot to demonstrate the trend.

Methods

<code>signature(x = "MAList")</code>	<code>M</code> and <code>A</code> values are stored as matrices in <code>x</code>
<code>signature(x = "NChannelSet")</code>	<code>M</code> and <code>A</code> values are calculated from the <code>R</code> and <code>G</code> matrices returned by <code>assayData(x)</code>

See Also

[densityplot](#) for density plots of log2 intensity values, [levelplot](#) for pairwise distance plots between arrays, and [MADvsMedianPlot](#) for median absolute deviation versus median plots.

Examples

```
data(PalateData)
reducedSet <- filterArray(PalateData, keep=c("MIR", "LET", "POSCON", "CALIB"),
                           frac=1.1, number=3, reps=4)
ndata.quantile <- normalizeBetweenArrays(reducedSet, method="quantile")
res <- MApplot(ndata.quantile)
print(res)
```

PalateData

Murine Secondary Palate Development miRNA Expression Data

Description

This data set contains two-color miRNA microarray expression data obtained from mouse embryonic tissue during gestational days (GD) 12, 13, and 14, which represents the critical period of palate development in the mouse.

Usage

```
data(PalateData)
```

Format

The data are in the format of an "[RGList](#)", which in this case is a list with the following 9 elements:

R matrix of dimension 6336 x 9 which contains the red channel foreground measurements
G matrix of dimension 6336 x 9 which contains the green channel foreground measurements
Rb matrix of dimension 6336 x 9 which contains the red channel background measurements
Gb matrix of dimension 6336 x 9 which contains the green channel background measurements
source source of the images, here "imagene"
Field.Dimensions numeric vector giving the field dimensions of the array (Metarows, Metacols, Rows and Cols)
weights matrix of dimension 6336 x 9 which contains the quality weights associated with each spot on the arrays
printer list containing information on the process used to print the spots on the arrays (number of grid rows / columns and number of spot rows / columns per grid - coincides with Field.Dimensions)
genes A data.frame containing information on each probe. Has the following columns:
Field field position for the probe
Meta Row meta row position for the probe
Meta Column meta column position for the probe
Row row position for the probe
Column column position for the probe
Gene ID unique gene identifier provided by Miltenyi Biotec
ID unique probe identifier constructed by concatenating the "Gene ID" with "Meta Row", "Meta Column", "Row", and "Column" information
Name name of the microRNA
Name.stem base name of the microRNA
probe.type type of probe, "MMU miRNAs", "Other miRNAs", "Control", "Empty", and "Other"

Details

RNA samples were isolated from mouse embryonic orofacial tissues (GD-12 - GD-14) and fluorescently labeled with Hy5 (red). Control samples (miRXplore Universal Reference) were labeled with Hy3 (green). The two sets of samples were hybridized to miRXplore Microarrays (Miltenyi Biotec) using the a-Hyb Hybridization Station (Miltenyi Biotec). Probes for a total of 1336 mature miRNAs (from human, mouse, rat and virus), including positive control and calibration probes, were spotted in quadruplicate on each microarray. Each array included probes for 588 murine miRNAs.

Source

P. Mukhopadhyay, G. Brock, V. Pihur, C. Webb, M.M. Pisano, and R.M. Greene. Developmental microRNA expression profiling of murine embryonic orofacial tissue. Birth Defects Res A Clin Mol Teratol, 88(7):511-34, 2010.

Examples

```
data(PalateData)
```

Index

*Topic **cluster**
 clustPlot, 5

*Topic **datasets**
 PalateData, 15

*Topic **hplot**
 densityplot, 6
 levelplot, 11
 MADvsMedianPlot, 12
 MAplot, 13

*Topic **manip**
 checkMVs, 3
 checkOutliers, 4
 filterArray, 7
 fixMVs, 8
 fixOutliers, 9
 imputeKNN, 10
 MmPalateMiRNA-package, 2

*Topic **methods**
 checkMVs, 3
 checkOutliers, 4
 densityplot, 6
 filterArray, 7
 levelplot, 11
 MADvsMedianPlot, 12
 MAplot, 13

*Topic **package**
 MmPalateMiRNA-package, 2

 checkMVs, 3, 4, 8, 9
 checkMVs, RGLList-method (checkMVs), 3
 checkMVs-methods (checkMVs), 3
 checkOutliers, 3, 4, 8, 9
 checkOutliers, RGLList-method
 (checkOutliers), 4
 checkOutliers-methods (checkOutliers), 4
 clustPlot, 5

 densityplot, 6, 6, 12–14
 densityplot, list, missing-method
 (densityplot), 6
 densityplot, RGLList, missing-method
 (densityplot), 6
 densityplot-methods (densityplot), 6

 filterArray, 7
 filterArray, RGLList-method
 (filterArray), 7
 filterArray-methods (filterArray), 7
 fixMVs, 2–4, 8, 8, 9
 fixOutliers, 2–4, 8, 9

 imputeKNN, 10

 lattice, 2
 levelplot, 7, 11, 11, 13, 14
 levelplot, list, missing-method
 (levelplot), 11
 levelplot, RGLList, missing-method
 (levelplot), 11
 levelplot-methods (levelplot), 11

 MADvsMedianPlot, 7, 12, 12, 14
 MADvsMedianPlot, list-method
 (MADvsMedianPlot), 12
 MADvsMedianPlot-methods
 (MADvsMedianPlot), 12

 MAList, 2, 6, 11–14
 MAplot, 7, 12, 13, 13
 MAplot, MAList-method (MAplot), 13
 MAplot, NChannelSet-method (MAplot), 13
 MAplot-methods (MAplot), 13

 MmPalateMiRNA (MmPalateMiRNA-package), 2
 MmPalateMiRNA-package, 2

 NChannelSet, 2, 6, 11–14

 PalateData, 15

 RGLList, 2–4, 6, 7, 11–13, 15

 xyplot, 14