

Package ‘splatter’

April 12, 2018

Type Package

Title Simple Simulation of Single-cell RNA Sequencing Data

Version 1.2.2

Date 2018-03-27

Author Luke Zappia

Maintainer Luke Zappia <luke.zappia@mcri.edu.au>

Description Splatter is a package for the simulation of single-cell RNA sequencing count data. It provides a simple interface for creating complex simulations that are reproducible and well-documented. Parameters can be estimated from real data and functions are provided for comparing real and simulated datasets.

License GPL-3 + file LICENSE

LazyData TRUE

Depends R (>= 3.4), scater, SingleCellExperiment

Imports akima, BiocGenerics, BiocParallel, checkmate, edgeR, fitdistrplus, ggplot2, locfit, matrixStats, methods, scales, stats, SummarizedExperiment, utils

Suggests BiocStyle, covr, cowplot, knitr, limSolve, lme4, progress, pscl, testthat, rmarkdown, S4Vectors, scDD, scran, mfa, phenopath, zinbwave, BASiCS

biocViews SingleCell, RNASeq, Transcriptomics, GeneExpression, Sequencing, Software

URL <https://github.com/Oshlack/splatter>

BugReports <https://github.com/Oshlack/splatter/issues>

RoxygenNote 6.0.1

VignetteBuilder knitr

NeedsCompilation no

R topics documented:

addFeatureStats	3
addGeneLengths	4
BASiCSEstimate	5

BASiCSParams	6
BASiCSSimulate	7
bridge	8
compareSCEs	8
diffSCEs	9
expandParams	11
getLNormFactors	11
getParam	12
getParams	12
getPathOrder	13
listSims	13
logistic	14
lun2Estimate	14
Lun2Params	15
lun2Simulate	16
lunEstimate	17
LunParams	18
lunSimulate	18
makeCompPanel	19
makeDiffPanel	20
makeOverallPanel	21
mfaEstimate	21
MFAParams	22
mfaSimulate	23
newParams	24
Params	24
phenoEstimate	25
PhenoParams	26
phenoSimulate	26
rbindMatched	27
scDDEstimate	27
SCDDParams	29
scDDSimulate	29
setParam	30
setParams	31
setParamsUnchecked	32
setParamUnchecked	33
showPP	33
simpleEstimate	34
SimpleParams	34
simpleSimulate	35
splatEstBCV	36
splatEstDropout	36
splatEstimate	37
splatEstLib	37
splatEstMean	38
splatEstOutlier	38
SplatParams	39
splatSimBatchCellMeans	40
splatSimBatchEffects	41
splatSimBCVMeans	41
splatSimCellMeans	42

<i>addFeatureStats</i>	3
------------------------	---

splatSimDE	42
splatSimDropout	43
splatSimGeneMeans	43
splatSimLibSizes	44
splatSimTrueCounts	44
splatSimulate	45
splatter	47
summariseDiff	47
winsorize	48
zinbEstimate	48
ZINBParams	49
zinbSimulate	50

Index	51
--------------	----

addFeatureStats	<i>Add feature statistics</i>
------------------------	-------------------------------

Description

Add additional feature statistics to a SingleCellExperiment object

Usage

```
addFeatureStats(sce, value = c("counts", "cpm", "tpm", "fpkm"), log = FALSE,  
offset = 1, no.zeros = FALSE)
```

Arguments

sce	SingleCellExperiment to add feature statistics to.
value	the expression value to calculate statistics for. Options are "counts", "cpm", "tpm" or "fpkm". The values need to exist in the given SingleCellExperiment.
log	logical. Whether to take log2 before calculating statistics.
offset	offset to add to avoid taking log of zero.
no.zeros	logical. Whether to remove all zeros from each feature before calculating statistics.

Details

Currently adds the following statistics: mean, variance, coefficient of variation, median and median absolute deviation. Statistics are added to the `rowData` slot and are named `Stat[Log]Value[No0]` where Log and No0 are added if those arguments are true. UpperCamelCase is used to differentiate these columns from those added by analysis packages.

Value

SingleCellExperiment with additional feature statistics

`addGeneLengths` *Add gene lengths*

Description

Add gene lengths to an `SingleCellExperiment` object

Usage

```
addGeneLengths(sce, method = c("generate", "sample"), loc = 7.9,
               scale = 0.7, lengths = NULL)
```

Arguments

<code>sce</code>	SingleCellExperiment to add gene lengths to.
<code>method</code>	Method to use for creating lengths.
<code>loc</code>	Location parameter for the generate method.
<code>scale</code>	Scale parameter for the generate method.
<code>lengths</code>	Vector of lengths for the sample method.

Details

This function adds simulated gene lengths to the `rowData` slot of a `SingleCellExperiment` object that can be used for calculating length normalised expression values such as TPM or FPKM. The `generate` method simulates lengths using a (rounded) log-normal distribution, with the default `loc` and `scale` parameters based on human protein-coding genes. Alternatively the `sample` method can be used which randomly samples lengths (with replacement) from a supplied vector.

Value

`SingleCellExperiment` with added gene lengths

Examples

```
# Default generate method
sce <- simpleSimulate()
sce <- addGeneLengths(sce)
head(rowData(sce))
# Sample method (human coding genes)
## Not run:
library(TxDb.Hsapiens.UCSC.hg19.knownGene)
library(GenomicFeatures)
txdb <- TxDb.Hsapiens.UCSC.hg19.knownGene
tx.lens <- transcriptLengths(txdb, with.cds_len = TRUE)
tx.lens <- tx.lens[tx.lens$cds_len > 0, ]
gene.lens <- max(splitAsList(tx.lens$tx_len, tx.lens$gene_id))
sce <- addGeneLengths(sce, method = "sample", lengths = gene.lens)

## End(Not run)
```

BASiCSEstimate	<i>Estimate BASiCS simulation parameters</i>
-----------------------	--

Description

Estimate simulation parameters for the BASiCS simulation from a real dataset.

Usage

```
BASiCSEstimate(counts, spike.info = NULL, batch = NULL, n = 20000,
  thin = 10, burn = 5000, params = newBASiCSParams(), verbose = TRUE,
  progress = TRUE, ...)

## S3 method for class 'SCESet'
BASiCSEstimate(counts, spike.info = NULL, batch = NULL,
  n = 20000, thin = 10, burn = 5000, params = newBASiCSParams(),
  verbose = TRUE, progress = TRUE, ...)

## S3 method for class 'matrix'
BASiCSEstimate(counts, spike.info = NULL, batch = NULL,
  n = 20000, thin = 10, burn = 5000, params = newBASiCSParams(),
  verbose = TRUE, progress = TRUE, ...)
```

Arguments

counts	either a counts matrix or an SCESet object containing count data to estimate parameters from.
spike.info	data.frame describing spike-ins with two columns: "Name" giving the names of the spike-in features (must match rownames(counts)) and "Input" giving the number of input molecules.
batch	vector giving the batch that each cell belongs to.
n	total number of MCMC iterations. Must be $\geq \max(4, \text{thin})$ and a multiple of thin.
thin	thining period for the MCMC sampler. Must be ≥ 2 .
burn	burn-in period for the MCMC sampler. Must be in the range $1 \leq \text{burn} < n$ and a multiple of thin.
params	BASiCSParams object to store estimated values in.
verbose	logical. Whether to print progress messages.
progress	logical. Whether to print additional BASiCS progress messages.
...	Optional parameters passed to BASiCS_MCMC .

Details

This function is just a wrapper around [BASiCS_MCMC](#) that takes the output and converts it to a BASiCSParams object. Either a set of spike-ins or batch information (or both) must be supplied. If only batch information is provided there must be at least two batches. See [BASiCS_MCMC](#) for details.

Value

BASiCSParams object containing the estimated parameters.

Examples

```
## Not run:
data("sc_example_counts")
spike.info <- data.frame(Name = rownames(sc_example_counts)[1:10],
                         Input = rnorm(10, 500, 200),
                         stringsAsFactors = FALSE)
params <- BASiCSEstimate(sc_example_counts[1:50, 1:20],
                         spike.info)
params

## End(Not run)
```

Description

S4 class that holds parameters for the BASiCS simulation.

Parameters

The BASiCS simulation uses the following parameters:

nGenes The number of genes to simulate.

nCells The number of cells to simulate.

[seed] Seed to use for generating random numbers.

Batch parameters **nBatches** Number of batches to simulate.

batchCells Number of cells in each batch.

Gene parameters **gene.params** A `data.frame` containing gene parameters with two coloumns:
Mean (mean expression for each biological gene) and Delta (cell-to-cell heterogeneity
for each biological gene).

Spike-in parameters **nSpikes** The number of spike-ins to simulate.

spike.means Input molecules for each spike-in.

Cell parameters **cell.params** A `data.frame` containing gene parameters with two coloumns:
Phi (mRNA content factor for each cell, scaled to sum to the number of cells in each
batch) and S (capture efficient for each cell).

Variability parameters **theta** Technical variability parameter for each batch.

The parameters not shown in brackets can be estimated from real data using `BASiCSEstimate`. For
details of the BASiCS simulation see `BASiCSSimulate`.

BASICSSimulate	<i>BASiCS simulation</i>
----------------	--------------------------

Description

Simulate counts using the BASiCS method.

Usage

```
BASICSSimulate(params = newBASICSPParams(), verbose = TRUE, ...)
```

Arguments

params	BASICSPParams object containing simulation parameters.
verbose	logical. Whether to print progress messages
...	any additional parameter settings to override what is provided in params.

Details

This function is just a wrapper around [BASICSSim](#) that takes a `BASICSPParams`, runs the simulation then converts the output to an `SCESet` object. See [BASICSSim](#) for more details of how the simulation works.

Value

SingleCellExperiment containing simulated counts

References

Vallejos CA, Marioni JC, Richardson S. BASiCS: Bayesian Analysis of Single-Cell Sequencing data. PLoS Comput. Biol. (2015).

Paper: [10.1371/journal.pcbi.1004333](https://doi.org/10.1371/journal.pcbi.1004333)

Code: <https://github.com/catavallejos/BASiCS>

Examples

```
sim <- BASICSSimulate()
```

bridge	<i>Brownian bridge</i>
--------	------------------------

Description

Calculate a smoothed Brownian bridge between two points. A Brownian bridge is a random walk with fixed end points.

Usage

```
bridge(x = 0, y = 0, N = 5, n = 100, sigma.fac = 0.8)
```

Arguments

x	starting value.
y	end value.
N	number of steps in random walk.
n	number of points in smoothed bridge.
sigma.fac	multiplier specifying how extreme each step can be.

Value

Vector of length n following a path from x to y.

compareSCEs	<i>Compare SingleCellExperiment objects</i>
-------------	---

Description

Combine the data from several SingleCellExperiment objects and produce some basic plots comparing them.

Usage

```
compareSCEs(sces, point.size = 0.1, point.alpha = 0.1, fits = TRUE,
            colours = NULL)
```

Arguments

sces	named list of SingleCellExperiment objects to combine and compare.
point.size	size of points in scatter plots.
point.alpha	opacity of points in scatter plots.
fits	whether to include fits in scatter plots.
colours	vector of colours to use for each dataset.

Details

The returned list has three items:

FeatureData Combined feature data from the provided SingleCellExperiments.

PhenoData Combined pheno data from the provided SingleCellExperiments.

Plots Comparison plots

Means Boxplot of mean distribution.

Variances Boxplot of variance distribution.

MeanVar Scatter plot with fitted lines showing the mean-variance relationship.

LibraySizes Boxplot of the library size distribution.

ZerosGene Boxplot of the percentage of each gene that is zero.

ZerosCell Boxplot of the percentage of each cell that is zero.

MeanZeros Scatter plot with fitted lines showing the mean-zeros relationship.

The plots returned by this function are created using [ggplot](#) and are only a sample of the kind of plots you might like to consider. The data used to create these plots is also returned and should be in the correct format to allow you to create further plots using [ggplot](#).

Value

List containing the combined datasets and plots.

Examples

```
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
comparison <- compareSCEs(list(Splat = sim1, Simple = sim2))
names(comparison)
names(comparison$Plots)
```

diffSCEs

Diff SingleCellExperiment objects

Description

Combine the data from several SingleCellExperiment objects and produce some basic plots comparing them to a reference.

Usage

```
diffSCEs(sces, ref, point.size = 0.1, point.alpha = 0.1, fits = TRUE,
colours = NULL)
```

Arguments

sces	named list of SingleCellExperiment objects to combine and compare.
ref	string giving the name of the SingleCellExperiment to use as the reference
point.size	size of points in scatter plots.
point.alpha	opacity of points in scatter plots.
fits	whether to include fits in scatter plots.
colours	vector of colours to use for each dataset.

Details

This function aims to look at the differences between a reference SingleCellExperiment and one or more others. It requires each SingleCellExperiment to have the same dimensions. Properties are compared by ranks, for example when comparing the means the values are ordered and the differences between the reference and another dataset plotted. A series of Q-Q plots are also returned.

The returned list has five items:

Reference The SingleCellExperiment used as the reference.

FeatureData Combined feature data from the provided SingleCellExperiments.

PhenoData Combined pheno data from the provided SingleCellExperiments.

Plots Difference plots

Means Boxplot of mean differences.

Variances Boxplot of variance differences.

MeanVar Scatter plot showing the difference from the reference variance across expression ranks.

LibrarySizes Boxplot of the library size differences.

ZerosGene Boxplot of the differences in the percentage of each gene that is zero.

ZerosCell Boxplot of the differences in the percentage of each cell that is zero.

MeanZeros Scatter plot showing the difference from the reference percentage of zeros across expression ranks.

QQPlots Quantile-Quantile plots

Means Q-Q plot of the means.

Variances Q-Q plot of the variances.

LibrarySizes Q-Q plot of the library sizes.

ZerosGene Q-Q plot of the percentage of zeros per gene.

ZerosCell Q-Q plot of the percentage of zeros per cell.

The plots returned by this function are created using [ggplot](#) and are only a sample of the kind of plots you might like to consider. The data used to create these plots is also returned and should be in the correct format to allow you to create further plots using [ggplot](#).

Value

List containing the combined datasets and plots.

Examples

```
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
difference <- diffSCEs(list(Splat = sim1, Simple = sim2), ref = "Simple")
names(difference)
names(difference$Plots)
```

expandParams	<i>Expand parameters</i>
--------------	--------------------------

Description

Expand the parameters that can be vectors so that they are the same length as the number of groups.

Usage

```
expandParams(object, ...)

## S4 method for signature 'BASiCSPParams'
expandParams(object)

## S4 method for signature 'LunParams'
expandParams(object)

## S4 method for signature 'SplatParams'
expandParams(object)
```

Arguments

object	object to expand.
...	additional arguments.

Value

Expanded object.

getLNormFactors	<i>Get log-normal factors</i>
-----------------	-------------------------------

Description

Randomly generate multiplication factors from a log-normal distribution.

Usage

```
getLNormFactors(n.facs, sel.prob, neg.prob, fac.loc, fac.scale)
```

Arguments

n.facs	Number of factors to generate.
sel.prob	Probability that a factor will be selected to be different from 1.
neg.prob	Probability that a selected factor is less than one.
fac.loc	Location parameter for the log-normal distribution.
fac.scale	Scale factor for the log-normal distribution.

Value

Vector containing generated factors.

`getParam`*Get a parameter***Description**

Accessor function for getting parameter values.

Usage

```
getParam(object, name)

## S4 method for signature 'Params'
getParam(object, name)
```

Arguments

<code>object</code>	object to get parameter from.
<code>name</code>	name of the parameter to get.

Value

The extracted parameter value

Examples

```
params <- newSimpleParams()
getParam(params, "nGenes")
```

`getParams`*Get parameters***Description**

Get multiple parameter values from a Params object.

Usage

```
getParams(params, names)
```

Arguments

<code>params</code>	Params object to get values from.
<code>names</code>	vector of names of the parameters to get.

Value

List with the values of the selected parameters.

Examples

```
params <- newSimpleParams()  
getParams(params, c("nGenes", "nCells", "mean.rate"))
```

getPathOrder*Get path order***Description**

Identify the correct order to process paths so that preceding paths have already been simulated.

Usage

```
getPathOrder(path.from)
```

Arguments

`path.from` vector giving the path endpoints that each path originates from.

Value

Vector giving the order to process paths in.

listSims*List simulations***Description**

List all the simulations that are currently available in Splatter with a brief description.

Usage

```
listSims(print = TRUE)
```

Arguments

`print` logical. Whether to print to the console.

Value

Invisibly returns a data.frame containing the information that is displayed.

Examples

```
listSims()
```

logistic *Logistic function*

Description

Implementation of the logistic function

Usage

```
logistic(x, x0, k)
```

Arguments

x	value to apply the function to.
x0	midpoint parameter. Gives the centre of the function.
k	shape parameter. Gives the slope of the function.

Value

Value of logistic function with given parameters

lun2Estimate *Estimate Lun2 simulation parameters*

Description

Estimate simulation parameters for the Lun2 simulation from a real dataset.

Usage

```

lun2Estimate(counts, plates, params = newLun2Params(), min.size = 200,
              verbose = TRUE, BPPARAM = SerialParam())

## S3 method for class 'SingleCellExperiment'
lun2Estimate(counts, plates,
              params = newLun2Params(), min.size = 200, verbose = TRUE,
              BPPARAM = SerialParam())

## S3 method for class 'matrix'
lun2Estimate(counts, plates, params = newLun2Params(),
              min.size = 200, verbose = TRUE, BPPARAM = SerialParam())

```

Arguments

counts	either a counts matrix or a SingleCellExperiment object containing count data to estimate parameters from.
plates	integer vector giving the plate that each cell originated from.
params	Lun2Params object to store estimated values in.
min.size	minimum size of clusters when identifying group of cells in the data.
verbose	logical. Whether to show progress messages.
BPPARAM	A BiocParallelParam instance giving the parallel back-end to be used. Default is SerialParam which uses a single core.

Details

See [Lun2Params](#) for more details on the parameters.

Value

LunParams object containing the estimated parameters.

Examples

```
## Not run:
data("sc_example_counts")
data("sc_example_cell_info")
plates <- factor(sc_example_cell_info$Mutation_Status)
params <- lun2Estimate(sc_example_counts, plates, min.size = 20)
params

## End(Not run)
```

Description

S4 class that holds parameters for the Lun2 simulation.

Parameters

The Lun2 simulation uses the following parameters:

nGenes The number of genes to simulate.

nCells The number of cells to simulate.

[seed] Seed to use for generating random numbers.

Gene parameters gene.params A data.frame containing gene parameters with two columns:
Mean (mean expression for each gene) and Disp (dispersion for each gene).

zi.params A data.frame containing zero-inflated gene parameters with three columns:
Mean (mean expression for each gene), Disp (dispersion for each gene), and Prop (zero proportion for each gene).

[nPlates] The number of plates to simulate.

Plate parameters plate.ingroup Character vector giving the plates considered to be part of the "ingroup".

plate.mod Plate effect modifier factor. The plate effect variance is divided by this value.

plate.var Plate effect variance.

Cell parameters cell.plates Factor giving the plate that each cell comes from.

cell.libSizes Library size for each cell.

cell.libMod Modifier factor for library sizes. The library sizes are multiplied by this value.

Differential expression parameters de.nGenes Number of differentially expressed genes.

de.fc Fold change for differentially expressed genes.

The parameters not shown in brackets can be estimated from real data using [lun2Estimate](#). For details of the Lun2 simulation see [lun2Simulate](#).

lun2Simulate

Lun2 simulation

Description

Simulate single-cell RNA-seq count data using the method described in Lun and Marioni "Overcoming confounding plate effects in differential expression analyses of single-cell RNA-seq data".

Usage

```
lun2Simulate(params = newLun2Params(), zinb = FALSE, verbose = TRUE, ...)
```

Arguments

params	Lun2Params object containing simulation parameters.
zinb	logical. Whether to use a zero-inflated model.
verbose	logical. Whether to print progress messages
...	any additional parameter settings to override what is provided in params.

Details

The Lun2 simulation uses a negative-binomial distribution where the means and dispersions have been sampled from a real dataset (using [lun2Estimate](#)). The other core feature of the Lun2 simulation is the addition of plate effects. Differential expression can be added between two groups of plates (an "ingroup" and all other plates). Library size factors are also applied and optionally a zero-inflated negative-binomial can be used.

If the number of genes to simulate differs from the number of provided gene parameters or the number of cells to simulate differs from the number of library sizes the relevant parameters will be sampled with a warning. This allows any number of genes or cells to be simulated regardless of the number in the dataset used in the estimation step but has the downside that some genes or cells may be simulated multiple times.

Value

SingleCellExperiment containing simulated counts.

References

Lun ATL, Marioni JC. Overcoming confounding plate effects in differential expression analyses of single-cell RNA-seq data. *Biostatistics* (2017).

Paper: dx.doi.org/10.1093/biostatistics/kxw055

Code: <https://github.com/MarioniLab/PlateEffects2016>

Examples

```
sim <- lun2Simulate()
```

lunEstimate	<i>Estimate Lun simulation parameters</i>
-------------	---

Description

Estimate simulation parameters for the Lun simulation from a real dataset.

Usage

```
lunEstimate(counts, params = newLunParams())

## S3 method for class 'SingleCellExperiment'
lunEstimate(counts, params = newLunParams())

## S3 method for class 'matrix'
lunEstimate(counts, params = newLunParams())
```

Arguments

counts either a counts matrix or an SingleCellExperiment object containing count data to estimate parameters from.
params LunParams object to store estimated values in.

Details

The nGenes and nCells parameters are taken from the size of the input data. No other parameters are estimated. See [LunParams](#) for more details on the parameters.

Value

LunParams object containing the estimated parameters.

Examples

```
data("sc_example_counts")
params <- lunEstimate(sc_example_counts)
params
```

LunParams

*The LunParams class***Description**

S4 class that holds parameters for the Lun simulation.

Parameters

The Lun simulation uses the following parameters:

nGenes The number of genes to simulate.

nCells The number of cells to simulate.

[nGroups] The number of groups to simulate.

[groupCells] Vector giving the number of cells in each simulation group/path.

[seed] Seed to use for generating random numbers.

Mean parameters **[mean.shape]** Shape parameter for the mean gamma distribution.

[mean.rate] Rate parameter for the mean gamma distribution.

Counts parameters **[count.disp]** The dispersion parameter for the counts negative binomial distribution.

Differential expression parameters **[de.nGenes]** The number of genes that are differentially expressed in each group

[de.upProp] The proportion of differentially expressed genes that are up-regulated in each group

[de.upFC] The fold change for up-regulated genes

[de.downFC] The fold change for down-regulated genes

The parameters not shown in brackets can be estimated from real data using [lunEstimate](#). For details of the Lun simulation see [lunSimulate](#).

lunSimulate

*Lun simulation***Description**

Simulate single-cell RNA-seq count data using the method described in Lun, Bach and Marioni "Pooling across cells to normalize single-cell RNA sequencing data with many zero counts".

Usage

```
lunSimulate(params = newLunParams(), verbose = TRUE, ...)
```

Arguments

params LunParams object containing Lun simulation parameters.

verbose logical. Whether to print progress messages.

... any additional parameter settings to override what is provided in **params**.

Details

The Lun simulation generates gene mean expression levels from a gamma distribution with `shape = mean.shape` and `rate = mean.rate`. Counts are then simulated from a negative binomial distribution with `mu = means` and `size = 1 / bcv.common`. In addition each cell is given a size factor ($2^{\wedge} rnorm(nCells, mean = 0, sd = 0.1)$) and differential expression can be simulated with fixed fold changes.

See [LunParams](#) for details of the parameters.

Value

`SingleCellExperiment` object containing the simulated counts and intermediate values.

References

Lun ATL, Bach K, Marioni JC. Pooling across cells to normalize single-cell RNA sequencing data with many zero counts. *Genome Biology* (2016).

Paper: [dx.doi.org/10.1186/s13059-016-0947-7](https://doi.org/10.1186/s13059-016-0947-7)

Code: <https://github.com/MarioniLab/Deconvolution2016>

Examples

```
sim <- lunSimulate()
```

`makeCompPanel`

Make comparison panel

Description

Combine the plots from `compareSCEs` into a single panel.

Usage

```
makeCompPanel(comp, title = "Comparison", labels = c("Means", "Variance",
  "Mean-variance relationship", "Library size", "Zeros per gene",
  "Zeros per cell", "Mean-zeros relationship"))
```

Arguments

- | | |
|---------------------|--|
| <code>comp</code> | list returned by compareSCEs . |
| <code>title</code> | title for the panel. |
| <code>labels</code> | vector of labels for each of the seven plots. |

Value

Combined panel plot

Examples

```
## Not run:
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
comparison <- compareSCEs(list(Splat = sim1, Simple = sim2))
panel <- makeCompPanel(comparison)

## End(Not run)
```

makeDiffPanel

Make difference panel

Description

Combine the plots from diffSCEs into a single panel.

Usage

```
makeDiffPanel(diff, title = "Difference comparison", labels = c("Means",
  "Variance", "Library size", "Zeros per cell", "Zeros per gene",
  "Mean-variance relationship", "Mean-zeros relationship"))
```

Arguments

- diff** list returned by [diffSCEs](#).
- title** title for the panel.
- labels** vector of labels for each of the seven sections.

Value

Combined panel plot

Examples

```
## Not run:
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
difference <- diffSCEs(list(Splat = sim1, Simple = sim2), ref = "Simple")
panel <- makeDiffPanel(difference)

## End(Not run)
```

<code>makeOverallPanel</code>	<i>Make overall panel</i>
-------------------------------	---------------------------

Description

Combine the plots from `compSCEs` and `diffSCEs` into a single panel.

Usage

```
makeOverallPanel(comp, diff, title = "Overall comparison",
  row.labels = c("Means", "Variance", "Mean-variance relationship",
  "Library size", "Zeros per cell", "Zeros per gene",
  "Mean-zeros relationship"))
```

Arguments

<code>comp</code>	list returned by <code>compareSCEs</code> .
<code>diff</code>	list returned by <code>diffSCEs</code> .
<code>title</code>	title for the panel.
<code>row.labels</code>	vector of labels for each of the seven rows.

Value

Combined panel plot

Examples

```
## Not run:
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
comparison <- compSCESets(list(Splat = sim1, Simple = sim2))
difference <- diffSCESets(list(Splat = sim1, Simple = sim2), ref = "Simple")
panel <- makeOverallPanel(comparison, difference)

## End(Not run)
```

<code>mfaEstimate</code>	<i>Estimate mfa simulation parameters</i>
--------------------------	---

Description

Estimate simulation parameters for the mfa simulation from a real dataset.

Usage

```
mfaEstimate(counts, params = newMFAParams())

## S3 method for class 'SingleCellExperiment'
mfaEstimate(counts, params = newMFAParams())

## S3 method for class 'matrix'
mfaEstimate(counts, params = newMFAParams())
```

Arguments

- counts** either a counts matrix or a SingleCellExperiment object containing count data to estimate parameters from.
- params** MFAParams object to store estimated values in.

Details

The nGenes and nCells parameters are taken from the size of the input data. The dropout lambda parameter is estimate using [empirical_lambda](#). See [MFAParams](#) for more details on the parameters.

Value

MFAParams object containing the estimated parameters.

Examples

```
data("sc_example_counts")
params <- mfaEstimate(sc_example_counts)
params
```

MFAParams

The MFAParams class

Description

S4 class that holds parameters for the mfa simulation.

Parameters

The mfa simulation uses the following parameters:

nGenes The number of genes to simulate.

nCells The number of cells to simulate.

[seed] Seed to use for generating random numbers.

[trans.prop] Proportion of genes that show transient expression. These genes are briefly up or down-regulated before returning to their initial state

[zero.neg] Logical. Whether to set negative expression values to zero. This will zero-inflate the data.

[dropout.present] Logical. Whether to simulate dropout.

dropout.lambda Lambda parameter for the exponential dropout function.

The parameters not shown in brackets can be estimated from real data using [mfaEstimate](#). See [create_synthetic](#) for more details about the parameters. For details of the Splatter implementation of the mfa simulation see [mfaSimulate](#).

mfaSimulate*MFA simulation*

Description

Simulate a bifurcating pseudotime path using the mfa method.

Usage

```
mfaSimulate(params = newMFAParams(), verbose = TRUE, ...)
```

Arguments

params	MFAParams object containing simulation parameters.
verbose	Logical. Whether to print progress messages.
...	any additional parameter settings to override what is provided in params.

Details

This function is just a wrapper around [create_synthetic](#) that takes a [MFAParams](#), runs the simulation then converts the output from log-expression to counts and returns a [SingleCellExperiment](#) object. See [create_synthetic](#) and the mfa paper for more details about how the simulation works.

Value

SingleCellExperiment containing simulated counts

References

Campbell KR, Yau C. Probabilistic modeling of bifurcations in single-cell gene expression data using a Bayesian mixture of factor analyzers. Wellcome Open Research (2017).

Paper: [10.12688/wellcomeopenres.11087.1](https://doi.org/10.12688/wellcomeopenres.11087.1)

Code: <https://github.com/kieranrcampbell/mfa>

Examples

```
sim <- mfaSimulate()
```

`newParams`*New Params***Description**

Create a new Params object. Functions exist for each of the different Params subtypes.

Usage

```
newBASiCSPParams(...)  
newLun2Params(...)  
newLunParams(...)  
newMFAPParams(...)  
newPhenoParams(...)  
newSCDDParams(...)  
newSimpleParams(...)  
newSplatParams(...)  
newZINBParams(...)
```

Arguments

... additional parameters passed to [setParams](#).

Value

New Params object.

Examples

```
params <- newSimpleParams()  
params <- newSimpleParams(nGenes = 200, nCells = 10)
```

`Params`*The Params virtual class***Description**

Virtual S4 class that all other Params classes inherit from.

Parameters

The Params class defines the following parameters:

nGenes The number of genes to simulate.
nCells The number of cells to simulate.
[seed] Seed to use for generating random numbers.

The parameters not shown in brackets can be estimated from real data.

phenoEstimate	<i>Estimate PhenoPath simulation parameters</i>
---------------	---

Description

Estimate simulation parameters for the PhenoPath simulation from a real dataset.

Usage

```
phenoEstimate(counts, params = newPhenoParams())  
  
## S3 method for class 'SingleCellExperiment'  
phenoEstimate(counts,  
               params = newPhenoParams())  
  
## S3 method for class 'matrix'  
phenoEstimate(counts, params = newPhenoParams())
```

Arguments

counts either a counts matrix or an SingleCellExperiment object containing count data to estimate parameters from.
params PhenoParams object to store estimated values in.

Details

The nGenes and nCells parameters are taken from the size of the input data. The total number of genes is evenly divided into the four types. See [PhenoParams](#) for more details on the parameters.

Value

PhenoParams object containing the estimated parameters.

Examples

```
data("sc_example_counts")  
params <- phenoEstimate(sc_example_counts)  
params
```

PhenoParams

*The PhenoParams class***Description**

S4 class that holds parameters for the PhenoPath simulation.

Parameters

The PhenoPath simulation uses the following parameters:

`nGenes` The number of genes to simulate.

`nCells` The number of cells to simulate.

`[seed]` Seed to use for generating random numbers.

`[n.de]` Number of genes to simulate from the differential expression regime

`[n.pst]` Number of genes to simulate from the pseudotime regime

`[n.pst.beta]` Number of genes to simulate from the pseudotime + beta interactions regime

`[n.de.pst.beta]` Number of genes to simulate from the differential expression + pseudotime + interactions regime

The parameters not shown in brackets can be estimated from real data using [phenoEstimate](#). For details of the PhenoPath simulation see [phenoSimulate](#).

phenoSimulate

*PhenoPath simulation***Description**

Simulate counts from a pseudotime trajectory using the PhenoPath method.

Usage

```
phenoSimulate(params = newPhenoParams(), verbose = TRUE, ...)
```

Arguments

- | | |
|----------------------|---|
| <code>params</code> | PhenoParams object containing simulation parameters. |
| <code>verbose</code> | logical. Whether to print progress messages |
| <code>...</code> | any additional parameter settings to override what is provided in <code>params</code> . |

Details

This function is just a wrapper around [simulate_phenopath](#) that takes a `PhenoParams`, runs the simulation then converts the output from log-expression to counts and returns a `SingleCellExperiment` object. The original simulated log-expression values are returned in the `LogExprs` assay. See [simulate_phenopath](#) and the PhenoPath paper for more details about how the simulation works.

Value

SingleCellExperiment containing simulated counts

References

Campbell K, Yau C. Uncovering genomic trajectories with heterogeneous genetic and environmental backgrounds across single-cells and populations. bioRxiv (2017).

Paper: [10.1101/159913](https://doi.org/10.1101/159913)

Code: <https://github.com/kieranrcampbell/phenopath>

Examples

```
sim <- phenoSimulate()
```

rbindMatched	<i>Bind rows (matched)</i>
--------------	----------------------------

Description

Bind the rows of two data frames, keeping only the columns that are common to both.

Usage

```
rbindMatched(df1, df2)
```

Arguments

df1	first data.frame to bind.
df2	second data.frame to bind.

Value

data.frame containing rows from df1 and df2 but only common columns.

scDDEstimate	<i>Estimate scDD simulation parameters</i>
--------------	--

Description

Estimate simulation parameters for the scDD simulation from a real dataset.

Usage

```
scDDEstimate(counts, params = newSCDDParams(), verbose = TRUE,
             BPPARAM = SerialParam(), ...)

## S3 method for class 'matrix'
scDDEstimate(counts, params = newSCDDParams(),
             verbose = TRUE, BPPARAM = SerialParam(), conditions, ...)

## S3 method for class 'SingleCellExperiment'
scDDEstimate(counts, params = newSCDDParams(),
             verbose = TRUE, BPPARAM = SerialParam(), condition = "condition", ...)

## Default S3 method:
scDDEstimate(counts, params = newSCDDParams(),
             verbose = TRUE, BPPARAM = SerialParam(), condition, ...)
```

Arguments

counts	either a counts matrix or a SingleCellExperiment object containing count data to estimate parameters from.
params	SCDDParams object to store estimated values in.
verbose	logical. Whether to show progress messages.
BPPARAM	A BiocParallelParam instance giving the parallel back-end to be used. Default is SerialParam which uses a single core.
...	further arguments passed to or from other methods.
conditions	Vector giving the condition that each cell belongs to. Conditions can be 1 or 2.
condition	String giving the column that represents biological group of interest.

Details

This function applies [preprocess](#) to the counts then uses [scDD](#) to estimate the numbers of each gene type to simulate. The output is then converted to a SCDDParams object. See [preprocess](#) and [scDD](#) for details.

Value

SCDDParams object containing the estimated parameters.

Examples

```
## Not run:
data("sc_example_counts")
conditions <- sample(1:2, ncol(sc_example_counts), replace = TRUE)
params <- scDDEstimate(sc_example_counts, conditions = conditions)
params

## End(Not run)
```

SCDDParams*The SCDDParams class*

Description

S4 class that holds parameters for the scDD simulation.

Parameters

The SCDD simulation uses the following parameters:

nGenes The number of genes to simulate (not used).
 nCells The number of cells to simulate in each condition.
 [seed] Seed to use for generating random numbers.
 SCdat [SingleCellExperiment](#) containing real data.
 nDE Number of DE genes to simulate.
 nDP Number of DP genes to simulate.
 nDM Number of DM genes to simulate.
 nDB Number of DB genes to simulate.
 nEE Number of EE genes to simulate.
 nEP Number of EP genes to simulate.
 [sd.range] Interval for fold change standard deviations.
 [modeFC] Values for DP, DM and DB mode fold changes.
 [varInflation] Variance inflation factors for each condition. If all equal to 1 will be set to NULL (default).
 [condition] String giving the column that represents biological group of interest.

The parameters not shown in brackets can be estimated from real data using [scDDEstimate](#). See [simulateSet](#) for more details about the parameters. For details of the Splatter implementation of the scDD simulation see [scDDSimulate](#).

scDDSimulate

scDD simulation

Description

Simulate counts using the scDD method.

Usage

```
scDDSimulate(params = newSCDDParams(), plots = FALSE, plot.file = NULL,
             verbose = TRUE, BPPARAM = SerialParam(), ...)
```

Arguments

<code>params</code>	SCDDParams object containing simulation parameters.
<code>plots</code>	logical. whether to generate scDD fold change and validation plots.
<code>plot.file</code>	File path to save plots as PDF.
<code>verbose</code>	logical. Whether to print progress messages
<code>BPPARAM</code>	A <code>BiocParallelParam</code> instance giving the parallel back-end to be used. Default is <code>SerialParam</code> which uses a single core.
...	any additional parameter settings to override what is provided in <code>params</code> .

Details

This function is just a wrapper around `simulateSet` that takes a `SCDDParams`, runs the simulation then converts the output to a `SingleCellExperiment` object. See `simulateSet` for more details about how the simulation works.

Value

`SingleCellExperiment` containing simulated counts

References

Korthauer KD, Chu L-F, Newton MA, Li Y, Thomson J, Stewart R, et al. A statistical approach for identifying differential distributions in single-cell RNA-seq experiments. *Genome Biology* (2016).

Paper: [10.1186/s13059-016-1077-y](https://doi.org/10.1186/s13059-016-1077-y)

Code: <https://github.com/kdkorthauer/scDD>

Examples

```
## Not run:  
sim <- scDDSimulate()  
  
## End(Not run)
```

`setParam`

Set a parameter

Description

Function for setting parameter values.

Usage

```
setParam(object, name, value)  
  
## S4 method for signature 'BASiCSParams'  
setParam(object, name, value)  
  
## S4 method for signature 'Lun2Params'  
setParam(object, name, value)
```

```
## S4 method for signature 'LunParams'
setParam(object, name, value)

## S4 method for signature 'Params'
setParam(object, name, value)

## S4 method for signature 'PhenoParams'
setParam(object, name, value)

## S4 method for signature 'SCDDParams'
setParam(object, name, value)

## S4 method for signature 'SplatParams'
setParam(object, name, value)

## S4 method for signature 'ZINBParams'
setParam(object, name, value)
```

Arguments

- object object to set parameter in.
 name name of the parameter to set.
 value value to set the parameter to.

Value

Object with new parameter value.

Examples

```
params <- newSimpleParams()
setParam(params, "nGenes", 100)
```

setParams

Set parameters

Description

Set multiple parameters in a Params object.

Usage

```
setParams(params, update = NULL, ...)
```

Arguments

- params Params object to set parameters in.
 update list of parameters to set where names(update) are the names of the parameters to set and the items in the list are values.
 ... additional parameters to set. These are combined with any parameters specified in update.

Details

Each parameter is set by a call to `setParam`. If the same parameter is specified multiple times it will be set multiple times. Parameters can be specified using a list via update (useful when collecting parameter values in some way) or individually (useful when setting them manually), see examples.

Value

Params object with updated values.

Examples

```
params <- newSimpleParams()
params
# Set individually
params <- setParams(params, nGenes = 1000, nCells = 50)
params
# Set via update list
params <- setParams(params, list(mean.rate = 0.2, mean.shape = 0.8))
params
```

`setParamsUnchecked` *Set parameters UNCHECKED*

Description

Set multiple parameters in a Params object.

Usage

```
setParamsUnchecked(params, update = NULL, ...)
```

Arguments

<code>params</code>	Params object to set parameters in.
<code>update</code>	list of parameters to set where <code>names(update)</code> are the names of the parameters to set and the items in the list are values.
<code>...</code>	additional parameters to set. These are combined with any parameters specified in <code>update</code> .

Details

Each parameter is set by a call to `setParam`. If the same parameter is specified multiple times it will be set multiple times. Parameters can be specified using a list via update (useful when collecting parameter values in some way) or individually (useful when setting them manually), see examples.
THE FINAL OBJECT IS NOT CHECKED FOR VALIDITY!

Value

Params object with updated values.

setParamUnchecked	<i>Set a parameter UNCHECKED</i>
-------------------	----------------------------------

Description

Function for setting parameter values. THE OUTPUT IS NOT CHECKED FOR VALIDITY!

Usage

```
setParamUnchecked(object, name, value)  
## S4 method for signature 'Params'  
setParamUnchecked(object, name, value)
```

Arguments

object	object to set parameter in.
name	name of the parameter to set.
value	value to set the paramter to.

Value

Object with new parameter value.

showPP	<i>Show pretty print</i>
--------	--------------------------

Description

Function used for pretty printing params object.

Usage

```
showPP(params, pp)
```

Arguments

params	object to show.
pp	list specifying how the object should be displayed.

Value

Print params object to console

<code>simpleEstimate</code>	<i>Estimate simple simulation parameters</i>
-----------------------------	--

Description

Estimate simulation parameters for the simple simulation from a real dataset.

Usage

```
simpleEstimate(counts, params = newSimpleParams())

## S3 method for class 'SingleCellExperiment'
simpleEstimate(counts,
               params = newSimpleParams()

## S3 method for class 'matrix'
simpleEstimate(counts, params = newSimpleParams())
```

Arguments

<code>counts</code>	either a counts matrix or a <code>SingleCellExperiment</code> object containing count data to estimate parameters from.
<code>params</code>	SimpleParams object to store estimated values in.

Details

The `nGenes` and `nCells` parameters are taken from the size of the input data. The mean parameters are estimated by fitting a gamma distribution to the library size normalised mean expression level using `fitdist`. See [SimpleParams](#) for more details on the parameters.

Value

SimpleParams object containing the estimated parameters.

Examples

```
data("sc_example_counts")
params <- simpleEstimate(sc_example_counts)
params
```

<code>SimpleParams</code>	<i>The SimpleParams class</i>
---------------------------	-------------------------------

Description

S4 class that holds parameters for the simple simulation.

Parameters

The simple simulation uses the following parameters:

`nGenes` The number of genes to simulate.
`nCells` The number of cells to simulate.
[`seed`] Seed to use for generating random numbers.
`mean.shape` The shape parameter for the mean gamma distribution.
`mean.rate` The rate parameter for the mean gamma distribution.
[`count.disp`] The dispersion parameter for the counts negative binomial distribution.

The parameters not shown in brackets can be estimated from real data using [simpleEstimate](#). For details of the simple simulation see [simpleSimulate](#).

simpleSimulate

Simple simulation

Description

Simulate counts from a simple negative binomial distribution without simulated library sizes, differential expression etc.

Usage

```
simpleSimulate(params = newSimpleParams(), verbose = TRUE, ...)
```

Arguments

`params` SimpleParams object containing simulation parameters.
`verbose` logical. Whether to print progress messages
... any additional parameter settings to override what is provided in `params`.

Details

Gene means are simulated from a gamma distribution with `shape = mean.shape` and `rate = mean.rate`. Counts are then simulated from a negative binomial distribution with `mu = means` and `size = 1 / count.disp`. See [SimpleParams](#) for more details of the parameters.

Value

SingleCellExperiment containing simulated counts

Examples

```
sim <- simpleSimulate()  
# Override default parameters  
sim <- simpleSimulate(nGenes = 1000, nCells = 50)
```

splatEstBCV*Estimate Splat Biological Coefficient of Variation parameters***Description**

Parameters are estimated using the [estimateDisp](#) function in the edgeR package.

Usage

```
splatEstBCV(counts, params)
```

Arguments

- | | |
|--------|--|
| counts | counts matrix to estimate parameters from. |
| params | SplatParams object to store estimated values in. |

Details

The [estimateDisp](#) function is used to estimate the common dispersion and prior degrees of freedom. See [estimateDisp](#) for details. When estimating parameters on simulated data we found a broadly linear relationship between the true underlying common dispersion and the edgR estimate, therefore we apply a small correction, $\text{disp} = 0.1 + 0.25 * \text{edgeR.disp}$.

Value

SplatParams object with estimated values.

splatEstDropout*Estimate Splat dropout parameters***Description**

Estimate the midpoint and shape parameters for the logistic function used when simulating dropout.

Usage

```
splatEstDropout(norm.counts, params)
```

Arguments

- | | |
|-------------|--|
| norm.counts | library size normalised counts matrix. |
| params | SplatParams object to store estimated values in. |

Details

Logistic function parameters are estimated by fitting a logistic function to the relationship between log2 mean gene expression and the proportion of zeros in each gene. See [nls](#) for details of fitting.

Value

SplatParams object with estimated values.

<code>splatEstimate</code>	<i>Estimate Splat simulation parameters</i>
----------------------------	---

Description

Estimate simulation parameters for the Splat simulation from a real dataset. See the individual estimation functions for more details on how this is done.

Usage

```
splatEstimate(counts, params = newSplatParams())

## S3 method for class 'SingleCellExperiment'
splatEstimate(counts,
  params = newSplatParams()

## S3 method for class 'matrix'
splatEstimate(counts, params = newSplatParams())
```

Arguments

<code>counts</code>	either a counts matrix or a SingleCellExperiment object containing count data to estimate parameters from.
<code>params</code>	SplatParams object to store estimated values in.

Value

SplatParams object containing the estimated parameters.

See Also

[splatEstMean](#), [splatEstLib](#), [splatEstOutlier](#), [splatEstBCV](#), [splatEstDropout](#)

Examples

```
data("sc_example_counts")
params <- splatEstimate(sc_example_counts)
params
```

<code>splatEstLib</code>	<i>Estimate Splat library size parameters</i>
--------------------------	---

Description

A log-normal distribution is fitted to the library sizes and the estimated parameters are added to the `params` object. See [fitdist](#) for details on the fitting.

Usage

```
splatEstLib(counts, params)
```

Arguments

- `counts` counts matrix to estimate parameters from.
`params` splatParams object to store estimated values in.

Value

splatParams object with estimated values.

<code>splatEstMean</code>	<i>Estimate Splat mean parameters</i>
---------------------------	---------------------------------------

Description

Estimate rate and shape parameters for the gamma distribution used to simulate gene expression means.

Usage

```
splatEstMean(norm.counts, params)
```

Arguments

- `norm.counts` library size normalised counts matrix.
`params` SplatParams object to store estimated values in.

Details

Parameter for the gamma distribution are estimated by fitting the mean normalised counts using [fitdist](#). The 'maximum goodness-of-fit estimation' method is used to minimise the Cramer-von Mises distance. This can fail in some situations, in which case the 'method of moments estimation' method is used instead. Prior to fitting the means are winsorized by setting the top and bottom 10 percent of values to the 10th and 90th percentiles.

Value

SplatParams object with estimated values.

<code>splatEstOutlier</code>	<i>Estimate Splat expression outlier parameters</i>
------------------------------	---

Description

Parameters are estimated by comparing means of individual genes to the median mean expression level.

Usage

```
splatEstOutlier(norm.counts, params)
```

Arguments

- norm.counts library size normalised counts matrix.
- params SplatParams object to store estimated values in.

Details

Expression outlier genes are detected using the Median Absolute Deviation (MAD) from median method. If the log2 mean expression of a gene is greater than two MADs above the median log2 mean expression it is designated as an outlier. The proportion of outlier genes is used to estimate the outlier probability. Factors for each outlier gene are calculated by dividing mean expression by the median mean expression. A log-normal distribution is then fitted to these factors in order to estimate the outlier factor location and scale parameters using [fitdist](#).

Value

SplatParams object with estimated values.

SplatParams

The SplatParams class

Description

S4 class that holds parameters for the Splatter simulation.

Parameters

The Splatter simulation requires the following parameters:

nGenes The number of genes to simulate.

nCells The number of cells to simulate.

[seed] Seed to use for generating random numbers.

Batch parameters [nBatches] The number of batches to simulate.

[batchCells] Vector giving the number of cells in each batch.

[batch.facLoc] Location (meanlog) parameter for the batch effect factor log-normal distribution. Can be a vector.

[batch.facScale] Scale (sdlog) parameter for the batch effect factor log-normal distribution. Can be a vector.

Mean parameters mean.shape Shape parameter for the mean gamma distribution.

mean.rate Rate parameter for the mean gamma distribution.

Library size parameters lib.loc Location (meanlog) parameter for the library size log-normal distribution.

lib.scale Scale (sdlog) parameter for the library size log-normal distribution.

Expression outlier parameters out.prob Probability that a gene is an expression outlier.

out.facLoc Location (meanlog) parameter for the expression outlier factor log-normal distribution.

out.facScale Scale (sdlog) parameter for the expression outlier factor log-normal distribution.

Group parameters [nGroups] The number of groups or paths to simulate.
 [group.prob] Probability that a cell comes from a group.

Differential expression parameters [de.prob] Probability that a gene is differentially expressed in a group. Can be a vector.
 [de.loProb] Probability that a differentially expressed gene is down-regulated. Can be a vector.
 [de.facLoc] Location (meanlog) parameter for the differential expression factor log-normal distribution. Can be a vector.
 [de.facScale] Scale (sdlog) parameter for the differential expression factor log-normal distribution. Can be a vector.

Biological Coefficient of Variation parameters bcv.common Underlying common dispersion across all genes.
 bcv.df Degrees of Freedom for the BCV inverse chi-squared distribution.

Dropout parameters dropout.present Logical. Whether to simulate dropout.
 dropout.mid Midpoint parameter for the dropout logistic function.
 dropout.shape Shape parameter for the dropout logistic function.

Differentiation path parameters [path.from] Vector giving the originating point of each path. This allows path structure such as a cell type which differentiates into an intermediate cell type that then differentiates into two mature cell types. A path structure of this form would have a "from" parameter of c(0, 1, 1) (where 0 is the origin). If no vector is given all paths will start at the origin.
 [path.length] Vector giving the number of steps to simulate along each path. If a single value is given it will be applied to all paths.
 [path.skew] Vector giving the skew of each path. Values closer to 1 will give more cells towards the starting population, values closer to 0 will give more cells towards the final population. If a single value is given it will be applied to all paths.
 [path.nonlinearProb] Probability that a gene follows a non-linear path along the differentiation path. This allows more complex gene patterns such as a gene being equally expressed at the beginning an end of a path but lowly expressed in the middle.
 [path.sigmaFac] Sigma factor for non-linear gene paths. A higher value will result in more extreme non-linear variations along a path.

The parameters not shown in brackets can be estimated from real data using [splatEstimate](#). For details of the Splatter simulation see [splatSimulate](#).

splatSimBatchCellMeans
Simulate batch means

Description

Simulate a mean for each gene in each cell incorporating batch effect factors.

Usage

`splatSimBatchCellMeans(sim, params)`

Arguments

- sim SingleCellExperiment to add batch means to.
params SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated batch means.

splatSimBatchEffects *Simulate batch effects*

Description

Simulate batch effects. Batch effect factors for each batch are produced using [getLNormFactors](#) and these are added along with updated means for each batch.

Usage

```
splatSimBatchEffects(sim, params)
```

Arguments

- sim SingleCellExperiment to add batch effects to.
params SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated batch effects.

splatSimBCVMeans *Simulate BCV means*

Description

Simulate means for each gene in each cell that are adjusted to follow a mean-variance trend using Biological Coefficient of Variation taken from and inverse gamma distribution.

Usage

```
splatSimBCVMeans(sim, params)
```

Arguments

- sim SingleCellExperiment to add BCV means to.
params SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated BCV means.

`splatSimCellMeans` *Simulate cell means*

Description

Simulate a gene by cell matrix giving the mean expression for each gene in each cell. Cells start with the mean expression for the group they belong to (when simulating groups) or cells are assigned the mean expression from a random position on the appropriate path (when simulating paths). The selected means are adjusted for each cell's expected library size.

Usage

```
splatSimSingleCellMeans(sim, params)

splatSimGroupCellMeans(sim, params)

splatSimPathCellMeans(sim, params)
```

Arguments

<code>sim</code>	SingleCellExperiment to add cell means to.
<code>params</code>	SplatParams object with simulation parameters.

Value

SingleCellExperiment with added cell means.

`splatSimDE` *Simulate group differential expression*

Description

Simulate differential expression. Differential expression factors for each group are produced using `getLNormFactors` and these are added along with updated means for each group. For paths care is taken to make sure they are simulated in the correct order.

Usage

```
splatSimGroupDE(sim, params)

splatSimPathDE(sim, params)
```

Arguments

<code>sim</code>	SingleCellExperiment to add differential expression to.
<code>params</code>	SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated differential expression.

splatSimDropout	<i>Simulate dropout</i>
-----------------	-------------------------

Description

A logistic function is used to form a relationship between the expression level of a gene and the probability of dropout, giving a probability for each gene in each cell. These probabilities are used in a Bernoulli distribution to decide which counts should be dropped.

Usage

```
splatSimDropout(sim, params)
```

Arguments

sim	SingleCellExperiment to add dropout to.
params	SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated dropout and observed counts.

splatSimGeneMeans	<i>Simulate gene means</i>
-------------------	----------------------------

Description

Simulate gene means from a gamma distribution. Also simulates outlier expression factors. Genes with an outlier factor not equal to 1 are replaced with the median mean expression multiplied by the outlier factor.

Usage

```
splatSimGeneMeans(sim, params)
```

Arguments

sim	SingleCellExperiment to add gene means to.
params	SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated gene means.

`splatSimLibSizes` *Simulate library sizes*

Description

Simulate expected library sizes from a log-normal distribution

Usage

```
splatSimLibSizes(sim, params)
```

Arguments

<code>sim</code>	SingleCellExperiment to add library size to.
<code>params</code>	SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated library sizes.

`splatSimTrueCounts` *Simulate true counts*

Description

Simulate a true counts matrix. Counts are simulated from a poisson distribution where Each gene in each cell has it's own mean based on the group (or path position), expected library size and BCV.

Usage

```
splatSimTrueCounts(sim, params)
```

Arguments

<code>sim</code>	SingleCellExperiment to add true counts to.
<code>params</code>	SplatParams object with simulation parameters.

Value

SingleCellExperiment with simulated true counts.

splatSimulate	<i>Splat simulation</i>
---------------	-------------------------

Description

Simulate count data from a fictional single-cell RNA-seq experiment using the Splat method.

Usage

```
splatSimulate(params = newSplatParams(), method = c("single", "groups",
  "paths"), verbose = TRUE, ...)

splatSimulateSingle(params = newSplatParams(), verbose = TRUE, ...)

splatSimulateGroups(params = newSplatParams(), verbose = TRUE, ...)

splatSimulatePaths(params = newSplatParams(), verbose = TRUE, ...)
```

Arguments

params	SplatParams object containing parameters for the simulation. See SplatParams for details.
method	which simulation method to use. Options are "single" which produces a single population, "groups" which produces distinct groups (eg. cell types) or "paths" which selects cells from continuous trajectories (eg. differentiation processes).
verbose	logical. Whether to print progress messages.
...	any additional parameter settings to override what is provided in params.

Details

Parameters can be set in a variety of ways. If no parameters are provided the default parameters are used. Any parameters in `params` can be overridden by supplying additional arguments through a call to [setParams](#). This design allows the user flexibility in how they supply parameters and allows small adjustments without creating a new SplatParams object. See examples for a demonstration of how this can be used.

The simulation involves the following steps:

1. Set up simulation object
2. Simulate library sizes
3. Simulate gene means
4. Simulate groups/paths
5. Simulate BCV adjusted cell means
6. Simulate true counts
7. Simulate dropout
8. Create final dataset

The final output is a [SingleCellExperiment](#) object that contains the simulated counts but also the values for various intermediate steps. These are stored in the `colData` (for cell specific information), `rowData` (for gene specific information) or `assays` (for gene by cell matrices) slots. This additional information includes:

phenoData Cell Unique cell identifier.

Group The group or path the cell belongs to.

ExpLibSize The expected library size for that cell.

Step (paths only) how far along the path each cell is.

featureData Gene Unique gene identifier.

BaseGeneMean The base expression level for that gene.

OutlierFactor Expression outlier factor for that gene. Values of 1 indicate the gene is not an expression outlier.

GeneMean Expression level after applying outlier factors.

BatchFac[Batch] The batch effects factor for each gene for a particular batch.

DEFac[Group] The differential expression factor for each gene in a particular group. Values of 1 indicate the gene is not differentially expressed.

SigmaFac[Path] Factor applied to genes that have non-linear changes in expression along a path.

assayData BatchCellMeans The mean expression of genes in each cell after adding batch effects.

BaseCellMeans The mean expression of genes in each cell after any differential expression and adjusted for expected library size.

BCV The Biological Coefficient of Variation for each gene in each cell.

CellMeans The mean expression level of genes in each cell adjusted for BCV.

TrueCounts The simulated counts before dropout.

Dropout Logical matrix showing which values have been dropped in which cells.

Values that have been added by Splatter are named using UpperCamelCase in order to differentiate them from the values added by analysis packages which typically use underscore_naming.

Value

SingleCellExperiment object containing the simulated counts and intermediate values.

References

Zappia L, Phipson B, Oshlack A. Splatter: simulation of single-cell RNA sequencing data. *Genome Biology* (2017).

Paper: [10.1186/s13059-017-1305-0](https://doi.org/10.1186/s13059-017-1305-0)

Code: <https://github.com/Oshlack/splatter>

See Also

[splatSimLibSizes](#), [splatSimGeneMeans](#), [splatSimBatchEffects](#), [splatSimBatchCellMeans](#), [splatSimDE](#), [splatSimCellMeans](#), [splatSimBCVMeans](#), [splatSimTrueCounts](#), [splatSimDropout](#)

Examples

```
# Simulation with default parameters
sim <- splatSimulate()
## Not run:
# Simulation with different number of genes
sim <- splatSimulate(nGenes = 1000)
# Simulation with custom parameters
params <- newSplatParams(nGenes = 100, mean.rate = 0.5)
sim <- splatSimulate(params)
```

```
# Simulation with adjusted custom parameters
sim <- splatSimulate(params, mean.rate = 0.6, out.prob = 0.2)
# Simulate groups
sim <- splatSimulate(method = "groups")
# Simulate paths
sim <- splatSimulate(method = "paths")

## End(Not run)
```

splatter*splatter.*

Description

splatter is a package for the well-documented and reproducible simulation of single-cell RNA-seq count data.

Details

As well as it's own simulation model **splatter** provides functions for the estimation of model parameters.

See Also

Zappia L, Phipson B, Oshlack A. Splatter: Simulation Of Single-Cell RNA Sequencing Data. bioRxiv. 2017; doi:10.1101/133173

summariseDiff*Summarise diffSCESs*

Description

Summarise the results of [diffSCES](#). Calculates the Median Absolute Deviation (MAD), Mean Absolute Error (MAE) and Root Mean Squared Error (RMSE) for the various properties and ranks them.

Usage

```
summariseDiff(diff)
```

Arguments

diff Output from [diffSCES](#)

Value

data.frame with MADs, MAEs, RMSEs, scaled statistics and ranks

Examples

```
sim1 <- splatSimulate(nGenes = 1000, batchCells = 20)
sim2 <- simpleSimulate(nGenes = 1000, nCells = 20)
difference <- diffSCEs(list(Splat = sim1, Simple = sim2), ref = "Simple")
summary <- summariseDiff(difference)
head(summary)
```

winsorize

Winsorize vector

Description

Set outliers in a numeric vector to a specified percentile.

Usage

```
winsorize(x, q)
```

Arguments

x	Numeric vector to winsorize
q	Percentile to set from each end

Value

Winsorized numeric vector

zinbEstimate

Estimate ZINB-WaVE simulation parameters

Description

Estimate simulation parameters for the ZINB-WaVE simulation from a real dataset.

Usage

```
zinbEstimate(counts, design.samples = NULL, design.genes = NULL,
  common.disp = TRUE, iter.init = 2, iter.opt = 25, stop.opt = 1e-04,
  params = newZINBParams(), verbose = TRUE, BPPARAM = SerialParam(), ...)

## S3 method for class 'SingleCellExperiment'
zinbEstimate(counts, design.samples = NULL,
  design.genes = NULL, common.disp = TRUE, iter.init = 2, iter.opt = 25,
  stop.opt = 1e-04, params = newZINBParams(), verbose = TRUE,
  BPPARAM = SerialParam(), ...)

## S3 method for class 'matrix'
zinbEstimate(counts, design.samples = NULL,
  design.genes = NULL, common.disp = TRUE, iter.init = 2, iter.opt = 25,
  stop.opt = 1e-04, params = newZINBParams(), verbose = TRUE,
  BPPARAM = SerialParam(), ...)
```

Arguments

counts	either a counts matrix or a SingleCellExperiment object containing count data to estimate parameters from.
design.samples	design matrix of sample-level covariates.
design.genes	design matrix of gene-level covariates.
common.disp	logical. Whether or not a single dispersion for all features is estimated.
iter.init	number of iterations to use for initialization.
iter.opt	number of iterations to use for optimization.
stop.opt	stopping criterion for optimization.
params	ZINBParams object to store estimated values in.
verbose	logical. Whether to print progress messages.
BPPARAM	A BiocParallelParam instance giving the parallel back-end to be used. Default is SerialParam which uses a single core.
...	additional arguments passes to zinbFit .

Details

The function is a wrapper around [zinbFit](#) that takes the fitted model and inserts it into a [ZINBParams](#) object. See [ZINBParams](#) for more details on the parameters and [zinbFit](#) for details of the estimation procedure.

Value

ZINBParams object containing the estimated parameters.

Examples

```
## Not run:
data("sc_example_counts")
params <- zinbEstimate(sc_example_counts)
params

## End(Not run)
```

Description

S4 class that holds parameters for the ZINB-WaVE simulation.

Parameters

The ZINB-WaVE simulation uses the following parameters:

- nGenes The number of genes to simulate.
- nCells The number of cells to simulate.
- [seed] Seed to use for generating random numbers.

`model` Object describing a ZINB model.

The majority of the parameters for this simulation are stored in a `ZinbModel` object. Please refer to the documentation for this class and its constructor(`zinbModel`) for details about all the parameters.

The parameters not shown in brackets can be estimated from real data using `zinbEstimate`. For details of the ZINB-WaVE simulation see `zinbSimulate`.

`zinbSimulate`

ZINB-WaVE simulation

Description

Simulate counts using the ZINB-WaVE method.

Usage

```
zinbSimulate(params = newZINBParams(), verbose = TRUE, ...)
```

Arguments

<code>params</code>	ZINBParams object containing simulation parameters.
<code>verbose</code>	logical. Whether to print progress messages
<code>...</code>	any additional parameter settings to override what is provided in <code>params</code> .

Details

This function is just a wrapper around `zinbSim` that takes a `ZINBParams`, runs the simulation then converts the output to a `SingleCellExperiment` object. See `zinbSim` and the ZINB-WaVE paper for more details about how the simulation works.

Value

`SingleCellExperiment` containing simulated counts

References

Campbell K, Yau C. Uncovering genomic trajectories with heterogeneous genetic and environmental backgrounds across single-cells and populations. bioRxiv (2017).

Risso D, Perraudeau F, Gribkova S, Dudoit S, Vert J-P. ZINB-WaVE: A general and flexible method for signal extraction from single-cell RNA-seq data bioRxiv (2017).

Paper: [10.1101/125112](https://doi.org/10.1101/125112)

Code: <https://github.com/drisso/zinbwave>

Examples

```
sim <- zinbSimulate()
```

Index

addFeatureStats, 3
addGeneLengths, 4
assays, 45

BASiCS_MCMC, 5
BASiCS_Sim, 7
BASiCSEstimate, 5, 6
BASiCSParams, 6, 7
BASiCSParams-class (BASiCSParams), 6
BASiCSSimulate, 6, 7
BiocParallelParam, 15, 28, 30, 49
bridge, 8

colData, 45
compareSCEs, 8, 19, 21
create_synthetic, 23

diffSCEs, 9, 20, 21, 47

empirical_lambda, 22
estimateDisp, 36
expandParams, 11
expandParams, BASiCSParams-method
 (expandParams), 11
expandParams, LunParams-method
 (expandParams), 11
expandParams, SplatParams-method
 (expandParams), 11

fitdist, 34, 37–39

getLNormFactors, 11, 41, 42
getParam, 12
getParam, Params-method (getParam), 12
getParams, 12
getPathOrder, 13
ggplot, 9, 10

listSims, 13
logistic, 14
lun2Estimate, 14, 16
Lun2Params, 15, 15
Lun2Params-class (Lun2Params), 15
lun2Simulate, 16, 16
lunEstimate, 17, 18

LunParams, 17, 18, 19
LunParams-class (LunParams), 18
lunSimulate, 18, 18

makeCompPanel, 19
makeDiffPanel, 20
makeOverallPanel, 21
mfaEstimate, 21, 23
MFAParams, 22, 22, 23
MFAParams-class (MFAParams), 22
mfaSimulate, 23, 23

newBASiCSParams (newParams), 24
newLun2Params (newParams), 24
newLunParams (newParams), 24
newMFAParams (newParams), 24
newParams, 24

newPhenoParams (newParams), 24
newSCDDParams (newParams), 24
newSimpleParams (newParams), 24
newSplatParams (newParams), 24
newZINBParams (newParams), 24
nls, 36

Params, 24
Params-class (Params), 24
phenoEstimate, 25, 26
PhenoParams, 25, 26, 26
PhenoParams-class (PhenoParams), 26
phenoSimulate, 26, 26
preprocess, 28

rbindMatched, 27
rowData, 3, 4, 45

scDD, 28
scDDEstimate, 27, 29
SCDDParams, 29, 30
SCDDParams-class (SCDDParams), 29
scDDSimulate, 29, 29

SCESet, 7
SerialParam, 15, 28, 30, 49
setParam, 30, 32
setParam, BASiCSParams-method
 (setParam), 30

setParam, Lun2Params-method (setParam), 30
 setParam, LunParams-method (setParam), 30
 setParam, Params-method (setParam), 30
 setParam, PhenoParams-method (setParam), 30
 setParam, SCDDParams-method (setParam), 30
 setParam, SplatParams-method (setParam), 30
 setParam, ZINBParams-method (setParam), 30
 setParams, 24, 31, 45
 setParamsUnchecked, 32
 setParamUnchecked, 33
 setParamUnchecked, Params-method
 (setParamUnchecked), 33
 showPP, 33
 simpleEstimate, 34, 35
 SimpleParams, 34, 34, 35
 SimpleParams-class (SimpleParams), 34
 simpleSimulate, 35, 35
 simulate_phenopath, 26
 simulateSet, 29, 30
 SingleCellExperiment, 4, 23, 26, 29, 30, 45, 50
 splatEstBCV, 36, 37
 splatEstDropout, 36, 37
 splatEstimate, 37, 40
 splatEstLib, 37, 37
 splatEstMean, 37, 38
 splatEstOutlier, 37, 38
 SplatParams, 39, 45
 SplatParams-class (SplatParams), 39
 splatSimBatchCellMeans, 40, 46
 splatSimBatchEffects, 41, 46
 splatSimBCVMeans, 41, 46
 splatSimCellMeans, 42, 46
 splatSimDE, 42, 46
 splatSimDropout, 43, 46
 splatSimGeneMeans, 43, 46
 splatSimGroupCellMeans
 (splatSimCellMeans), 42
 splatSimGroupDE (splatSimDE), 42
 splatSimLibSizes, 44, 46
 splatSimPathCellMeans
 (splatSimCellMeans), 42
 splatSimPathDE (splatSimDE), 42
 splatSimSingleCellMeans
 (splatSimCellMeans), 42
 splatSimTrueCounts, 44, 46
 splatSimulate, 40, 45
 splatSimulateGroups (splatSimulate), 45
 splatSimulatePaths (splatSimulate), 45
 splatSimulateSingle (splatSimulate), 45
 splatter, 47
 splatter-package (splatter), 47
 summariseDiff, 47
 winsorize, 48
 zinbEstimate, 48, 50
 zinbFit, 49
 ZinbModel, 50
 zinbModel, 50
 ZINBParams, 49, 49, 50
 ZINBParams-class (ZINBParams), 49
 zinbSim, 50
 zinbSimulate, 50, 50