

Package ‘cancR’

October 16, 2019

Type Package

Title A Graphical User Interface for accessing and modeling the Cancer Genomics Data of MSKCC

Version 1.18.6

Date 2019-06-17

Author Karim Mezhoud.

Nuclear Safety & Security Department.
Nuclear Science Center of Tunisia.

Maintainer Karim Mezhoud <kmezhoud@gmail.com>

Description The package is user friendly interface based on the cgdsr and other modeling packages to explore, compare, and analyse all available Cancer Data (Clinical data, Gene Mutation, Gene Methylation, Gene Expression, Protein Phosphorylation, Copy Number Alteration) hosted by the Computational Biology Center at Memorial-Sloan-Kettering Cancer Center (MSKCC).

License GPL-2

LazyLoad yes

Depends R (>= 3.4), tcltk, tcltk2, cgdsr

Imports GSEABase, tkplot, geNetClassifier, RUnit, Formula, rpart, survival, Biobase, phenoTest, circlize, plyr, graphics, stats, utils, grDevices

Suggests testthat (>= 0.10.0), R.rsp

VignetteBuilder R.rsp

biocViews GUI, GeneExpression, Software

RoxygenNote 6.1.1

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/cancR>

git_branch RELEASE_3_9

git_last_commit 8557fdf

git_last_commit_date 2019-06-17

Date/Publication 2019-10-15

R topics documented:

about	3
canceR	4
canceRHelp	4
canceR_Vignette	5
cbind.na	5
dialogGeneClassifier	6
dialoggetGeneListMSigDB	7
dialogMetOption	7
dialogMut	8
dialogOptionCircos	9
dialogOptionGSEAlm	9
dialogOptionPhenoTest	10
dialogPlotOption_SkinCor	10
dialogSamplingGSEA	11
dialogSelectFiles_GSEA	12
dialogSpecificMut	12
dialogSummary_GSEA	13
displayInTable	13
getCases	14
getCasesGenProfs	15
getCircos	15
getClinicalDataMatrix	16
getClinicData_MultipleCases	16
getCor_ExpCNAMet	17
geteSet	18
getGCTCLSEExample	18
getGCT_CLSfiles	19
getGeneExpMatrix	19
getGeneList	20
getGeneListExample	20
getGeneListFromMSigDB	21
getGenesClassifier	21
getGenesTree_MultipleCases	22
getGenesTree_SingleCase	22
getGenProfs	23
getGSEAlm_Diseases	23
getGSEAlm_Variables	24
getInTable	24
getListProfData	25
getMegaProfData	25
getMetaDataMultipleGenes	26
getMSigDB	26
getMSigDBExample	27
getMSigDBfile	27
getMutData	28
getPhenoTest	28
getProfilesDataMultipleGenes	29
getProfilesDataSingleGene	29
getSpecificMut	30
getSummaryGSEA	31

<i>about</i>	3
--------------	---

getSurvival	31
getTextWin	32
GSEA	32
GSEA.Analyze.Sets	33
GSEA.ConsPlot	34
GSEA.EnrichmentScore	34
GSEA.EnrichmentScore2	35
GSEA.Gct2Frame	36
GSEA.Gct2Frame2	36
GSEA.GeneRanking	37
GSEA.HeatMapPlot	38
GSEA.HeatMapPlot2	38
GSEA.NormalizeCols	39
GSEA.NormalizeRows	39
GSEA.ReadClsFile	40
GSEA.Res2Frame	40
GSEA.Threshold	41
GSEA.VarFilter	42
GSEA.write.gct	42
Match_GeneList_MSigDB	43
modalDialog	43
myGlobalEnv	44
OLD.GSEA.EnrichmentScore	44
plotModel	45
plot_1Gene_2GenProfs	45
plot_2Genes_1GenProf	46
rbind.na	46
Run.GSEA	47
setWorkspace	47
testCheckedCaseGenProf	48

Index	49
--------------	----

<i>about</i>	<i>about cancerR</i>
--------------	----------------------

Description

about cancerR

Usage

about()

Value

dialog box with text

Examples

```
## Not run:
about()

## End(Not run)
```

canceR

*main function***Description**

main function

Usage

```
canceR()
```

Value

open the starting windows with cancer studies

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
## Not run:
canceR()

## End(Not run)
```

canceRHelp

*canceR Help***Description**

canceR Help

Usage

```
canceRHelp()
```

Value

html file with tutorial

Examples

```
## Not run:
canceRHelp()

## End(Not run)
```

canceR_Vignette *open pdf vignette*

Description

open pdf vignette

Usage

canceR_Vignette()

Value

open pdf vignette

Examples

```
## Not run:  
canceR_Vignette()  
  
## End(Not run)
```

cbind.na *bind non equal column*

Description

bind non equal column

Usage

cbind.na(..., deparse.level = 1)

Arguments

... (generalized) vectors or matrices.
deparse.level integer controlling the construction of labels in the case of non-matrix-like arguments (for the default method): deparse.level = 0 constructs no labels; the default, deparse.level = 1 or 2 constructs labels from the argument names.

Value

a data frame with merged columns

Examples

```
## Not run:
col1 <- c("a", "b", "c", "d")
col2 <- c("A", "B", "C")
col3 <- cbind.na(col1, col2)

## End(Not run)
```

dialogGeneClassifier *Dialogue Box for gene classifier setting: sample size and postprob threshold*

Description

Dialogue Box for gene classifier setting: sample size and postprob threshold

Usage

```
dialogGeneClassifier(Lchecked_Cases, entryWidth = 10, returnValOnCancel = "ID_CANCEL")
```

Arguments

Lchecked_Cases	integer with a number of checked cases
entryWidth	integer default 10
returnValOnCancel	"ID_CANCEL"

Value

a dataframe with genes classes

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
getGenesClassifier()
dialogGeneClassifier(1,10,returnValOnCancel = "ID_CANCEL")

## End(Not run)
```

`dialoggetGeneListMSigDB`

Multi-select choice of gene sets from loaded MSigDB

Description

Multi-select choice of gene sets from loaded MSigDB

Usage

`dialoggetGeneListMSigDB(MSigDB)`

Arguments

`MSigDB` object with MSigDB. A list of genesets

Value

a dataframe with genes classes

Examples

```
z <- 7
## Not run:
##MSigDB <- readLines(paste(.libPaths(),"/canceR/extdata/MSigDB/c5.bp.v4.0.symbols.gmt", sep=""))
dialoggetGeneListMSigDB(MSigDB)

## End(Not run)
```

`dialogMetOption`

Dialog Box to set methylation options

Description

Dialog Box to set methylation options

Usage

`dialogMetOption(ProfData, k)`

Arguments

`ProfData` adataframe with methylation data
`k` threshold of silencing gene 0:1

Value

a dialog box to set methylation option (threshold of silencing gene)

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getMetDataMultipleGenes()
#dialogMutOption(ProfData, 0.7)

## End(Not run)
```

dialogMut*Dialog bos to set returned Mutation information***Description**

Dialog bos to set returned Mutation information

Usage

```
dialogMut(title, question, entryInit, entryWidth = 40, returnValOnCancel = "ID_CANCEL")
```

Arguments

<code>title</code>	title of the table
<code>question</code>	question
<code>entryInit</code>	entryInit
<code>entryWidth</code>	40
<code>returnValOnCancel</code>	"ID_CANCEL"

Value

a check box with mutations variables

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
dialogMut("title", "question", "entryInit", entryWidth = 40, returnValOnCancel = "ID_CANCEL")

## End(Not run)
```

dialogOptionCircos *Checkbox to select dimensions*

Description

Checkbox to select dimensions

Usage

```
dialogOptionCircos()
```

Value

a checkbox with all dimensions

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/Circos.rds", sep=""))
## Not run:
dialogOptionCircos()
#getCircos(dimension ="All")

## End(Not run)
```

dialogOptionGSEAlm *Dialogbox to select variables from Clinical data*

Description

Dialogbox to select variables from Clinical data

Usage

```
dialogOptionGSEAlm(k,ClinicalData)
```

Arguments

k integer 1
ClinicalData datafram with clinical variables

Value

permutaion value, p-value, coVariables

Examples

```
#data(ClinicalData)
## Not run:
getOptionGSEAlm()

## End(Not run)
```

dialogOptionPhenoTest *Checkbox to select variables from clinical data*

Description

Checkbox to select variables from clinical data

Usage

```
dialogOptionPhenoTest(eSet)
```

Arguments

eSet	Expression Set
------	----------------

Value

vectors: variables to test Survival status, AGE, p-value

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
dialogOptionPhenoTest(myGlobalEnv$eSet)

## End(Not run)
```

dialogPlotOption_SkinCor
Checkbox to select variables for plotting

Description

Checkbox to select variables for plotting

Usage

```
dialogPlotOption_SkinCor(s)
```

Arguments

s	integer number of Studies
---	---------------------------

Value

Dialog box with setting of correlation method

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
dialogPlotOption_SkinCor(1)

## End(Not run)
```

dialogSamplingGSEA

Dialog Box for Sampling patients from expression profile data used for GSEA-R (Broad Institute)

Description

Dialog Box for Sampling patients from expression profile data used for GSEA-R (Broad Institute)

Usage

```
dialogSamplingGSEA( Lchecked_Cases, entryWidth = 10, returnValOnCancel = "ID_CANCEL")
```

Arguments

Lchecked_Cases	Number of checked Cases
entryWidth	10
returnValOnCancel	"ID_CANCEL"

Value

A vector with sampling size

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
Run.GSEA()
#dialogSamplingGSEA(1,entryWidth=10,returnValOnCancel = "ID_CANCEL")

## End(Not run)
```

dialogSelectFiles_GSEA

*Dialog Box to Select GCT, CLS, GMT and output Files for GSEA-R
(Broad Institute)*

Description

Dialog Box to Select GCT, CLS, GMT and output Files for GSEA-R (Broad Institute)

Usage

```
dialogSelectFiles_GSEA()
```

Value

A vector with files paths

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
dialogSelectFiles_GSEA()

## End(Not run)
```

dialogSpecificMut

dialog box to Specify Mutation using Regular Expression. Search specific mutation using regular expression.

Description

dialog box to Specify Mutation using Regular Expression. Search specific mutation using regular expression.

Usage

```
getSpecificMut()
```

Value

a a dataframe with specific mutation informations

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getSpecificMut()

## End(Not run)
```

dialogSummary_GSEA	<i>Dialog Box to specify phenotype (variable) used in last GSEA-R to get Summary Results. This function ask the user to specify the phenotype (variable).</i>
--------------------	---

Description

Dialog Box to specify phenotype (variable) used in last GSEA-R to get Summary Results. This function ask the user to specify the phenotype (variable).

Usage

```
dialogSummary_GSEA(Variable,returnValOnCancel ="ID_CANCEL")
```

Arguments

Variable	phenotype
returnValOnCancel	"ID_CANCEL"

Value

variables

Examples

```
readRDS(paste(path.package("cancER"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
#Run.GSEA()
#getSummaryGSEA()

## End(Not run)
```

displayInTable	<i>Display matrix in tcltk table</i>
----------------	--------------------------------------

Description

Display matrix in tcltk table

Usage

```
displayInTable(tclarray,title="",height=-1,width=-1,nrow=-1,ncol=-1)
```

Arguments

tclarray	a dataframe
title	title of the table
height	-1
width	-1
nrow	-1
ncol	-1

Value

display a Table

Examples

```
#data(ClinicalData)
## Not run:
getInTable(Table= ClinicalData, title= "Clinical Data")

## End(Not run)
```

getCases

Get cases for selected Studies. The Cases are the description of the samples from patients. The samples can be subdivided by the type of assays as, sequencing, CNA, Mutation, Methylation.

Description

Get cases for selected Studies. The Cases are the description of the samples from patients. The samples can be subdivided by the type of assays as, sequencing, CNA, Mutation, Methylation.

Usage

```
getCases()
```

Value

a dataframe with cases

Examples

```
# Create CGDS object
cgds<-CGDS("http://www.cbioportal.org/")
# Get list of cancer studies at server
Studies <- getStudies(cgds)[,2]
# Get available case lists (collection of samples) for a given cancer study
mycancerstudy <- getStudies(cgds)[2,1]
mycaselist <- getCaseLists(cgds,mycancerstudy)[1,1]
## Not run:
##getCases()

## End(Not run)
```

getCasesGenProfs	<i>get Cases and Genetic Profiles of selected Studies.</i>
------------------	--

Description

get Cases and Genetic Profiles of selected Studies.

Usage

```
getCasesGenProfs()
```

Value

This function is run by the "Get Cases and Genetic Profiles for selected Studies in starting window. This function needs to select at least one study and display Cases and genetic profiles in the main window.

Examples

```
##Load Session
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## load Cases and Genetic Profiles
## Not run:
getCasesGenProfs()

## End(Not run)
```

getCircos	<i>get Circos Layout for selected studies and selected dimensions</i>
-----------	---

Description

get Circos Layout for selected studies and selected dimensions

Usage

```
getCircos(dimension)
```

Arguments

dimension	string (All,mRNA, CNA, Met,RPPA, miRNA, Mut)
-----------	--

Value

a plot with Circos style

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/Circos.rds", sep=""))
## Not run:
getCircos(dimension ="All")

## End(Not run)
```

`getClinicalDataMatrix` *get matrix with clinical from file*

Description

get matrix with clinical from file

Usage

```
getClinicalDataMatrix()
```

Value

dataframe of clinicaldata

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getClinicalDataMatrix()

## End(Not run)
```

`getClinicData_MultipleCases`

get Clinical Data for Multiple Cases. User needs to select at least one case to run this function. Get clinical data for more one or multiple cases.

Description

get Clinical Data for Multiple Cases. User needs to select at least one case to run this function. Get clinical data for more one or multiple cases.

Usage

```
getClinicData_MultipleCases(getSummaryGSEAExists)
```

Arguments

`getSummaryGSEAExists`

if equal to 0, the clinical data is displayed in table. if the argument is equal to 1, the clinical data is used to summarise GSEA analysis results.

Value

dataframe with clinical data

Examples

```

##Load Session
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 2
## get Clinical data
## Not run:
getClinicData_MultipleCases(getSummaryGSEAExists = 0)

## End(Not run)

```

getCor_ExpCNAMet *Get gene correlation for multiple dimensions.*

Description

Get gene correlation for multiple dimensions.

Usage

```
getCor_ExpCNAMet(ListMatrix, dimension)
```

Arguments

ListMatrix	is a List of numeric matrices
dimension	Exp,CNA, Met , miRNA , RPPA

Value

correlation matrix

Examples

```

readRDS(paste(path.package("canceR"), "/extdata/rdata/Circos.rds", sep=""))
## Not run:
getListProfData()
getCor_ExpCNAMet(myGlobalEnv$ListProfData$Expression, dimension="mRNA")
head(myGlobalEnv$Cor_Exp)

## End(Not run)

```

`geteSet`*Built Expression Set (eSet) from profile data.***Description**

Built Expression Set (eSet) from profile data.

Usage`geteSet()`**Value**

ExpressionSet

Examples

```
f <- 9
## Not run:
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
geteSet()

## End(Not run)
```

`getGCTCLSEExample`*get GCT and CLS example files.***Description**

get GCT and CLS example files.

Usage`getGCTCLSEExample()`**Value**

GCT and CLS files

Examples

```
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGCTCLSEExample()

## End(Not run)
```

getGCT_CLSfiles *get Profile (GCT file) and Phenotype (CLS file) Data from Disease.*

Description

get Profile (GCT file) and Phenotype (CLS file) Data from Disease.

Usage

```
getGCT_CLSfiles()
```

Value

GCT and CLS files paths

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGCT_CLSfiles()

## End(Not run)
```

getGeneExpMatrix *get matrix with gene expression from file*

Description

get matrix with gene expression from file

Usage

```
getGeneExpMatrix()
```

Value

dataframe of gene expression

getGeneList

User needs to specify which gene is interesting to get genomic cancer data. The gene must be with Symbol and one gene by line.

Description

User needs to specify which gene is interesting to get genomic cancer data. The gene must be with Symbol and one gene by line.

Usage

```
getGeneList()
```

Value

Gene list path of file

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
## Not run:
getGeneList()

## End(Not run)
```

getGeneListExample

get Gene List from examples. User can select one from available gene list

Description

get Gene List from examples. User can select one from available gene list

Usage

```
getGeneListExample()
```

Value

Gene list path of file

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
## Not run:
getGeneListExample()

## End(Not run)
```

getGeneListFromMSigDB *get gene list from MSigDB*

Description

get gene list from MSigDB

Usage

getGeneListFromMSigDB()

Value

a vector with gene list

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcgaGSEAlm1021.rds", sep=""))
## Not run:
getGeneListFromMSigDB()

## End(Not run)
```

getGenesClassifier *get Genes Classifier*

Description

get Genes Classifier

Usage

getGenesClassifier()

Value

a data frma with genes classes

Examples

```
x <- 0
## Not run:
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
getGenesClassifier()

## End(Not run)
```

getGenesTree_MultipleCases*Get successively trees of genes list for multiple cases***Description**

Get successively trees of genes list for multiple cases

Usage`getGenesTree_MultipleCases(entryWidth = 10)`**Arguments**

entryWidth 10

Value

plot tree

Examples

```
q <- readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
readRDS(paste(.libPaths(), "/canceR/data/brca_tcga73genes.rds", sep=""))
getGenesTree_MultipleCases(entryWidth = 10)

## End(Not run)
```

getGenesTree_SingleCase*classify genes in tree for two phenotypes in the same case(disease).***Description**

classify genes in tree for two phenotypes in the same case(disease).

Usage`getGenesTree_SingleCase()`**Value**

tree plot

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getGenesTree_SingleCase()

## End(Not run)
```

getGenProfs

*Get Genetic Profile from selected Studies***Description**

Get Genetic Profile from selected Studies

Usage

getGenProfs()

Value

dataframe with genetic profil

Examples

```
cgds<-CGDS("http://www.cbioportal.org/")
# Get list of cancer studies at server
Studies <- getStudies(cgds)[,2]
# Get available case lists (collection of samples) for a given cancer study
mycancerstudy <- getStudies(cgds)[2,1]
mycaselist <- getCaseLists(cgds,mycancerstudy)[1,1]
# Get available genetic profiles
mygeneticprofile <- getGeneticProfiles(cgds,mycancerstudy)[4,1]
## Not run:
getGenProfs()

## End(Not run)
```

getGSEAlm_Diseases

*get GSEA linear modeling by studies (diseases)***Description**

get GSEA linear modeling by studies (diseases)

Usage

getGSEAlm_Diseases()

Value

a dataframe with annotation (GO, BP)

Examples

```
readRDS(paste(path.package("cancer"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getGSEAlm_Diseases

## End(Not run)
```

`getGSEAlm_Variables` *get GSEA linear modeling by variables (phenotype)*

Description

get GSEA linear modeling by variables (phenotype)

Usage

```
getGSEAlm_Variables()
```

Value

a dataframe with annotation (GO, BP)

Examples

```
x <- 3
## Not run:
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
getGSEAlm_Variables()

## End(Not run)
```

`getInTable` *get dataframe in TK/TCL table*

Description

get dataframe in TK/TCL table

Usage

```
getInTable(table, title)
```

Arguments

table	Dataframe
title	string a title of the table

Value

display a Table

Examples

```
#data(ClinicalData)
## Not run:
getInTable(Table= ClinicalData, title= "Clinical Data")

## End(Not run)
```

getListProfData	<i>get a list of Profile Data of every available dimensions. This function load matrices of every dimension (Exp, CNA, Met, RPPA,miRNA,Mut) and save them in a list for every disease.</i>
-----------------	--

Description

get a list of Profile Data of every available dimensions. This function load matrices of every dimension (Exp, CNA, Met, RPPA,miRNA,Mut) and save them in a list for every disease.

Usage

```
getListProfData()
```

Value

a list of data frame with Profiles Data

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getListProfData()
head(myGlobalEnv$ProfData$Expression)

## End(Not run)
```

getMegaProfData	<i>Get profile data for more than 500 genes list.</i>
-----------------	---

Description

Get profile data for more than 500 genes list.

Usage

```
getMegaProfData(MegaGeneList,k)
```

Arguments

MegaGeneList	Genelist >500
k	integer number of studies

Value

dataframe with profile data

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcgaGSEAlm1021.rds", sep=""))
## Not run:
getMegaProfData(myGlobalEnv$MegaGeneList, 1)

## End(Not run)
```

getMetDataMultipleGenes

get Methylation data for multiple genes

Description

get Methylation data for multiple genes

Usage

```
getMetDataMultipleGenes()
```

Value

a a dataframe with mean and median of methylation rate (threshold of silencing gene)

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getMetDataMultipleGenes()

## End(Not run)
```

getMSigDB

Reduce MSigDB size for only gene list

Description

Reduce MSigDB size for only gene list

Usage

```
getMSigDB(eSet, k)
```

Arguments

eSet	Expression Set
k	integer Number of studies

Value

MSigDB for user gene List

Examples

```
d <- 7
## Not run:
setWorkspace()
getMSigDB(eSet = myGlobalEnv$eSetClassifier,k = 1)

## End(Not run)
```

getMSigDBExample

get example of .gmt file from MSigDB (Broad Institute)

Description

get example of .gmt file from MSigDB (Broad Institute)

Usage

```
getMSigDBExample()
```

Value

path of GMT file

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
getMSigDBExample()

## End(Not run)
```

getMSigDBfile

Dialog Box to Select MSigDB Files from drive

Description

Dialog Box to Select MSigDB Files from drive

Usage

```
getMSigDBfile()
```

Value

A path of MSigDB file

Examples

```
f <- 5+2
## Not run:
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
geteSet()
getMSigDBfile()

## End(Not run)
```

getMutData

*get Mutation data for multiple genes***Description**

get Mutation data for multiple genes

Usage

```
getMutData()
```

Value

a a dataframe with mutation informations

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getMutData()

## End(Not run)
```

getPhenoTest

*Associate phenotype to Studies (cancers)***Description**

Associate phenotype to Studies (cancers)

Usage

```
getPhenoTest()
```

Value

a dataframe with disease/ variables association

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getPhenoTest(myGlobalEnv$eSet)

## End(Not run)
```

getProfilesDataMultipleGenes

get Profiles Data of multiple genes

Description

get Profiles Data of multiple genes

Usage

```
getProfilesDataMultipleGenes(getSummaryGSEAExists)
```

Arguments

`getSummaryGSEAExists`

if equal to 0, the clinical data is displayed in table. if the argument is equal to 1, the clinical data is used to summarise GSEA analysis results.

Value

a file with a dataframe of profile data

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
getProfilesDataMultipleGenes(getSummaryGSEAExists = 0)

## End(Not run)
```

getProfilesDataSingleGene

get Profiles Data for a Single Gene.

Description

get Profiles Data for a Single Gene.

Usage

```
getProfilesDataSingleGene()
```

Value

dataframe with profiles data for a single gene

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case from Breast Cancer
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 9
##Select Genetic Profile from Breast Cancer
myGlobalEnv$curselectGenProfs <- 4
## get Specific Mutation data for 73 Genes list
## Not run:
getProfilesDataSingleGene()

## End(Not run)
```

getSpecificMut

get specific Mutation data for multiple genes

Description

get specific Mutation data for multiple genes

Usage

`getSpecificMut()`

Value

a a dataframe with specific mutation informations

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata//ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
getSpecificMut()

## End(Not run)
```

getSummaryGSEA

*get Summary results from GSEA-R (Broad Institute)***Description**

get Summary results from GSEA-R (Broad Institute)

Usage

```
getSummaryGSEA()
```

Value

Dataframe with summary results

Examples

```
readRDS(paste(path.package("cancER"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
Run.GSEA()
getSummaryGSEA()

## End(Not run)
```

getSurvival

*Survival plot***Description**

Survival plot

Usage

```
getSurvival(Coxph)
```

Arguments

Coxph	if Coxph = 0 : plot Kaplan-Meier curves else Coxph= 1 : plot Cox Proportional Hazard Model
-------	--

Value

Survival plot

Examples

```
surv <- 11
## Not run:
readRDS(paste(path.package("cancER"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
getSurvival(Coxph = 1)

## End(Not run)
```

<code>getTextWin</code>	<i>get text in tcltk windows</i>
-------------------------	----------------------------------

Description

get text in tcltk windows

Usage

```
getTextWin(text)
```

Arguments

<code>text</code>	string
-------------------	--------

Value

tcltk windows with text

Examples

```
text <- "mytext"
## Not run:
getTextWin(text)

## End(Not run)
```

<code>GSEA</code>	<i>GSEA-R (Broad Institute)</i>
-------------------	---------------------------------

Description

See http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/R-GSEA_Readme

Value

GSEA

Author(s)

Subramanian, Tamayo, et al. (2005, PNAS 102, 15545-15550) and Mootha, Lindgren, et al. (2003, Nat Genet 34, 267-273)

Examples

```
## Not run:
library(cancceR)
## Load workspace
readRDS(paste(path.package("cancceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.Analyze.Sets *GSEA.Analyze.Sets*

Description

http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/R-GSEA_Readme

Usage

```
GSEA.Analyze.Sets(directory,topgs="",non.interactive.run= FALSE,height=12,width=17)
```

Arguments

directory	directory= fname.Output
topgs	topgs = 20
non.interactive.run	non.interactive.run= FALSE
height	height=16
width	width=16

Value

GSEA.Analyze.Sets

Author(s)

Subramanian, Tamayo, et al. (2005, PNAS 102, 15545-15550) and Mootha, Lindgren, et al. (2003, Nat Genet 34, 267-273)

References

http://www.broadinstitute.org/cancer/software/gsea/wiki/index.php/Main_Page.

Examples

```
## Not run:  
## Load workspace  
readRDS(paste(path.package("cancER"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.ConsPlot

*GSEA.ConsPlot***Description**

GSEA.ConsPlot

Usage

```
GSEA.ConsPlot(V, col.names, main = " ", sub = " ", xlab = " ", ylab = " ")
```

Arguments

V	V="Itable"
col.names	col.names = colnames
main	main= " "
sub	sub = " "
xlab	xlab= " "
ylab	ylab = " "

Value

GSEA.ConsPlot

Examples

```
## Not run:
library(canceR)
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.EnrichmentScore

*GSEA.EnrichmentScore***Description**

GSEA.EnrichmentScore

Usage

```
GSEA.EnrichmentScore(gene.list, gene.set, weighted.score.type = 1, correl.vector = NULL)
```

Arguments

```
gene.list  
gene.set  
weighted.score.type  
  
correl.vector
```

Value

GSEA.EnrichmentScore

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.EnrichmentScore2 *GSEA.EnrichmentScore2*

Description

GSEA.EnrichmentScore2

Usage

```
GSEA.EnrichmentScore2(gene.list, gene.set, weighted.score.type = 1, correl.vector = NULL)
```

Arguments

```
gene.list  
gene.set  
weighted.score.type  
  
correl.vector
```

Value

GSEA.EnrichmentScore2

Examples

```
## Not run:  
library(canceR)  
## Load workspace  
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.Gct2Frame

*GSEA.Gct2Frame***Description**

GSEA.Gct2Frame

Usage

GSEA.Gct2Frame(filename = "NULL")

Arguments

filename

Value

GSEA.GCT2Frame

Examples

```
## Not run:
library(canceR)
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.Gct2Frame2

*GSEA.Gct2Frame2***Description**

GSEA.Gct2Frame2

Usage

GSEA.Gct2Frame2(filename = "NULL")

Arguments

filename

Value

GSEA.GCT2Frame2

Examples

```
## Not run:  
library(cancceR)  
## Load workspace  
readRDS(paste(path.package("cancceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.GeneRanking

GSEA.GeneRanking

Description

GSEA.GeneRanking

Arguments

```
A  
class.labels  
gene.labels  
nperm  
permutation.type  
  
sigma.correction  
  
fraction  
replace  
reverse.sign
```

Value

GSEA.GeneRanking

Examples

```
## Not run:  
library(cancceR)  
## Load workspace  
readRDS(paste(path.package("cancceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.HeatMapPlot *GSEA.HeatMapPlot*

Description

GSEA.HeatMapPlot

Value

GSEA.HeatMapPlot

Examples

```
## Not run:  
library(cancR)  
## Load workspace  
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.HeatMapPlot2 *GSEA.HeatMapPlot2*

Description

GSEA.HeatMapPlot2

Value

GSEA.HeatMapPlot2

Examples

```
## Not run:  
library(cancR)  
## Load workspace  
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))  
##Run.GSEA()  
  
## End(Not run)
```

GSEA.NormalizeCols *GSEA.NormalizeCols*

Description

GSEA.NormalizeCols

Usage

GSEA.NormalizeCols(V)

Arguments

V

Value

GSEA.NormalizeCols

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
## Load workspace
##Run.GSEA()

## End(Not run)
```

GSEA.NormalizeRows *GSEA.NormalizeRows*

Description

GSEA.NormalizeRows

Usage

GSEA.NormalizeRows(V)

Arguments

V

Value

GSEA.NormalizeRows

Examples

```
## Not run:
library(cancR)
## Load workspace
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
##Run.GSEA()

## End(Not run)
```

GSEA.ReadClsFile

*GSEA.ReadClsFile***Description**

GSEA.ReadClsFile

Usage

GSEA.ReadClsFile(file = "NULL")

Arguments

file

Value

GSEA.ReadClsFile

Examples

```
readRDS(paste(path.package("cancR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
##Run.GSEA()

## End(Not run)
```

GSEA.Res2Frame

*GSEA.Res2Frame***Description**

GSEA.Res2Frame

Usage

GSEA.Res2Frame(filename = "NULL")

Arguments

filename

Value

`GSEA.NormalizeCols`

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
##Run.GSEA()

## End(Not run)
```

`GSEA.Threshold`

GSEA.Threshold

Description

`GSEA.Threshold`

Usage

```
GSEA.Threshold(V, thres, ceil)
```

Arguments

`V`
`thres`
`ceil`

Value

`GSEA.Threshold`

Examples

```
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:

##Run.GSEA()

## End(Not run)
```

GSEA.VarFilter

*GSEA.VarFilter***Description**

GSEA.VarFilter

Usage

GSEA.VarFilter(V, fold, delta, gene.names = "NULL")

Arguments

V
fold
delta
gene.names

Value

GSEA.VarFilter

Examples

```
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
##Run.GSEA()

## End(Not run)
```

GSEA.write.gct

*GSEA.write.gct***Description**

GSEA.write.gct

Usage

GSEA.write.gct(gct, filename)

Arguments

gct
filename

Value

GSEA.Write.gct

Examples

```
## Load workspace
readRDS(paste(path.package("canceR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:

##Run.GSEA()

## End(Not run)
```

Match_GeneList_MSigDB *Search MSigDb that overlap gene list*

Description

Search MSigDb that overlap gene list

Usage

```
Match_GeneList_MSigDB
```

Value

GeneList

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/prad_michPhenoTest1021.rds", sep=""))
## Not run:
Match_GeneList_MSigDB()

## End(Not run)
```

modalDialog

Dialog box to specify Gene Symbol.

Description

Dialog box to specify Gene Symbol.

Usage

```
modalDialog(title, question, entryInit, entryWidth = 40, returnValOnCancel = "ID_CANCEL")
```

Arguments

title	string
question	string
entryInit	entryInit
entryWidth	40
returnValOnCancel	"ID_CANCEL"

Value

dialog box

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Select Case from Breast Cancer
myGlobalEnv <- new.env(parent = emptyenv())
myGlobalEnv$curselectCases <- 9
##Select Genetic Profile from Breast Cancer
myGlobalEnv$curselectGenProfs <- 4
## get Specific Mutation data for 73 Genes list
## Not run:
getProfilesDataSingleGene()

## End(Not run)
```

myGlobalEnv

myGlobalEnv

Description

Global environment to store canceR variables.

Format

The format is: <environment: 0xb3eb240>

Examples

```
myGlobalEnv <- new.env(parent = emptyenv())
```

OLD.GSEA.EnrichmentScore

OLD.GSEA.EnrichmentScore

Description

OLD.GSEA.EnrichmentScore

Arguments

```
gene.list
gene.set
```

Value

OLD.GSEA.EnchmentScore

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
##Run.GSEA()

## End(Not run)
```

plotModel*model plotting with tcltk*

Description

model plotting with tcltk

Usage

```
plotModel(plotCommand, title= "TITLE", hscale=1, vscale=1 )
```

Arguments

plotCommand	plotcommand
title	title of plot
hscale	horizontal scale
vscale	vertical scale

Value

plot

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
plot_1Gene_2GenProfs()

## End(Not run)
```

plot_1Gene_2GenProfs *Plotting two genetic profiles for one Gene*

Description

Plotting two genetic profiles for one Gene

Usage

```
plot_1Gene_2GenProfs()
```

Value

plot

Examples

```
readRDS(paste(path.package("cancER"), "/extdata/rdata/gbm_tcgaPlotTwoGenProf.rds", sep=""))
## Not run:
plot_1Gene_2GenProfs()

## End(Not run)
```

plot_2Genes_1GenProf *plot correlation of two genes expressions.*

Description

plot correlation of two genes expressions.

Usage

```
plot_2Genes_1GenProf()
```

Value

plot

Examples

```
readRDS(paste(path.package("cancER"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
plot_2Genes_1GenProf()

## End(Not run)
```

rbind.na

bind non equal row

Description

bind non equal row

Usage

```
rbind.na(..., deparse.level = 1)
```

Arguments

- ... (generalized) vectors or matrices.
- deparse.level integer controlling the construction of labels in the case of non-matrix-like arguments (for the default method): deparse.level = 0 constructs no labels; the default, deparse.level = 1 or 2 constructs labels from the argument names.

Value

a data frame with merged rows

Examples

```
## Not run:
row1 <- c("a", "b", "c", "d")
row2 <- c("A", "B", "C")
row3 <- rbind.na(row1, row2)

## End(Not run)
```

Run.GSEA

The main function to run GSEA-R from Broad Institute

Description

The main function to run GSEA-R from Broad Institute

Usage

```
Run.GSEA()
```

Value

A vector with sampling size

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/ucec_tcga_pubGSEA1021.rds", sep=""))
## Not run:
Run.GSEA()

## End(Not run)
```

setWorkspace

Setting work Directory and output folders. At starting window, user needs to set work directory for output data. The function is found in File menu.

Description

Setting work Directory and output folders. At starting window, user needs to set work directory for output data. The function is found in File menu.

Usage

```
setWorkspace()
```

Value

paths of output files

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
setWorkspace()

## End(Not run)
```

testCheckedCaseGenProf

Testing checked appropriate Cases for appropriate Genetic profiles.

Description

Testing checked appropriate Cases for appropriate Genetic profiles.

Usage

```
testCheckedCaseGenProf()
```

Value

dialog box with warning message

Examples

```
readRDS(paste(path.package("canceR"), "/extdata/rdata/brca_tcga73genes.rds", sep=""))
## Not run:
testCheckedCaseGenProf()

## End(Not run)
```

Index

*Topic **datasets**
 myGlobalEnv, 44

about, 3

cancer, 4
cancer_Vignette, 5
cancerHelp, 4
cbind.na, 5

dialogGeneClassifier, 6
dialoggetGeneListMSigDB, 7
dialogMetOption, 7
dialogMut, 8
dialogOptionCircos, 9
dialogOptionGSEAlm, 9
dialogOptionPhenoTest, 10
dialogPlotOption_SkinCor, 10
dialogSamplingGSEA, 11
dialogSelectFiles_GSEA, 12
dialogSpecificMut, 12
dialogSummary_GSEA, 13
displayInTable, 13

getCases, 14
getCasesGenProfs, 15
getCircos, 15
getClinicalDataMatrix, 16
getClinicData_MultipleCases, 16
getCor_ExpCNAMet, 17
geteSet, 18
getGCT_CLSfiles, 19
getGCTCLSEExample, 18
getGeneExpMatrix, 19
getGeneList, 20
getGeneListExample, 20
getGeneListFromMSigDB, 21
getGenesClassifier, 21
getGenesTree_MultipleCases, 22
getGenesTree_SingleCase, 22
getGenProfs, 23
getGSEAlm_Diseases, 23
getGSEAlm_Variables, 24
getInTable, 24

getListProfData, 25
getMegaProfData, 25
getMetDataMultipleGenes, 26
getMSigDB, 26
getMSigDBExample, 27
getMSigDBfile, 27
getMutData, 28
getPhenoTest, 28
getProfilesDataMultipleGenes, 29
getProfilesDataSingleGene, 29
getSpecificMut, 30
getSummaryGSEA, 31
getSurvival, 31
getTextWin, 32
GSEA, 32
GSEA.Analyze.Sets, 33
GSEA.ConsPlot, 34
GSEA.EnrichmentScore, 34
GSEA.EnrichmentScore2, 35
GSEA.Gct2Frame, 36
GSEA.Gct2Frame2, 36
GSEA.GeneRanking, 37
GSEA.HeatMapPlot, 38
GSEA.HeatMapPlot2, 38
GSEA.NormalizeCols, 39
GSEA.NormalizeRows, 39
GSEA.ReadClsFile, 40
GSEA.Res2Frame, 40
GSEA.Threshold, 41
GSEA.VarFilter, 42
GSEA.write.gct, 42

Match_GeneList_MSigDB, 43
modalDialog, 43
myGlobalEnv, 44

OLD.GSEA.EnrichmentScore, 44

plot_1Gene_2GenProfs, 45
plot_2Genes_1GenProf, 46
plotModel, 45

rbind.na, 46
Run.GSEA, 47

[setWorkspace](#), [47](#)
[testCheckedCaseGenProf](#), [48](#)