

Package ‘RnBeads.hg19’

June 19, 2025

Title RnBeads.hg19

Description Automatically generated RnBeads annotation package for the assembly hg19.

Author RnBeadsAnnotationCreator

Maintainer RnBeadsAnnotationCreator <rnbeads@mpi-inf.mpg.de>

Date 2021-11-21

License GPL-3

Version 1.41.0

Depends R (>= 3.0.0), GenomicRanges

Suggests RnBeads

NeedsCompilation no

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/RnBeads.hg19>

git_branch devel

git_last_commit cf3cea1

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-06-19

Contents

hg19	2
regions	2
rnb.set.example	3
sites	3
Index	4

hg19	<i>HG19 - Annotation tables</i>
------	---------------------------------

Description

Scaffold of annotation tables for HG19. This structure is automatically loaded upon initialization of the annotation, that is, by the first valid call to any of the following functions: [rnb.get.assemblies](#), [rnb.get.chromosomes](#), [rnb.get.annotation](#), [rnb.set.annotation](#), [rnb.get.mapping](#), [rnb.annotation.size](#). Adding an annotation amounts to attaching its table(s) and mapping structures to this scaffold.

Format

list of four elements - "regions", "sites", "controls" and "mappings". These elements are described below.

"regions" list of NULLs; the names of the elements correspond to the built-in region annotation tables. Once the default annotations are loaded, the attribute "builtin" is a logical vector storing, for each region annotation, whether it is the default (built-in) or custom.

"sites" list of NULLs; the names of the elements correspond to the site and probe annotation tables.

"controls" list of NULLs; the names of the elements correspond to the control probe annotation tables. The attribute "sites" is a character vector pointing to the site annotation that encompasses the respective control probes.

"mappings" list of NULLs; the names of the elements correspond to the built-in region annotation tables.

Author(s)

Yassen Assenov

regions	<i>Names of the regions</i>
---------	-----------------------------

Description

This a a list of all regions available for the annotation.

Usage

```
regions
```

Format

list of NULLs; the names of the elements correspond to the built-in region annotation tables. Once the default annotations are loaded, the attribute "builtin" is a logical vector storing, for each region annotation, whether it is the default (built-in) or custom.

Author(s)

Michael Scherer

`rnb.set.example`*Example Data Set*

Description

A small example dataset for testing RnBeads' basic functionality.

Usage

```
data(small.example.object)
```

Format

`RnBeadRawSet-class` object with 12 samples and 1,736 sites. It is an example object obtained from Illumina Infinium 450K BeadChip and contains coverage, intensity, and detection p-values. No preprocessing steps have been performed.

Author(s)

Michael Scherer

`sites`*Names of the sites*

Description

This a a list of all sites available for the annotation.

Usage

```
sites
```

Format

list of NULLs; the names of the elements correspond to the site and probe annotation tables.

Author(s)

Michael Scherer

Index

*** datasets**

- hg19, [2](#)
- regions, [2](#)
- rnb.set.example, [3](#)
- sites, [3](#)

hg19, [2](#)

- regions, [2](#)
- rnb.annotation.size, [2](#)
- rnb.get.annotation, [2](#)
- rnb.get.assemblies, [2](#)
- rnb.get.chromosomes, [2](#)
- rnb.get.mapping, [2](#)
- rnb.set.annotation, [2](#)
- rnb.set.example, [3](#)

sites, [3](#)