

Package ‘chipenrich.data’

April 8, 2015

Type Package

Title Gene set enrichment analysis for ChIP-seq data

Version 1.1.8

Date 2014-10-03

Depends R (>= 2.15.0)

Imports methods, GenomicRanges (>= 1.10.0), IRanges (>= 1.16.0),
BiocGenerics (>= 0.2.0)

biocViews ExperimentData

Description Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

License GPL-3

LazyLoad yes

Author Ryan P. Welch [aut, cre, cph],
Chee Lee [aut, cre],
Raymond G. Cavalcante [aut, cre],
Laura J. Scott [ths],
Maureen A. Sartor [ths]

Maintainer Ryan P. Welch <welchr@umich.edu>, Chee Lee <cheelee@umich.edu>, Raymond G. Cavalcante <rcavalca@umich.edu>

R topics documented:

chipenrich.data-package	6
example_datasets	8
genes.dme	8
genes.hsa	9
genes.mmu	9
genes.rno	10
GeneSet-class	11
geneset.biocarta_pathway.hsa	12
geneset.biocarta_pathway.mmu	12
geneset.biocarta_pathway.rno	13

geneset.cytoband.hsa	13
geneset.drug_bank.hsa	14
geneset.drug_bank.mmu	14
geneset.drug_bank.rno	15
geneset.ehmn_pathway_gene.hsa	15
geneset.ehmn_pathway_gene.mmu	16
geneset.ehmn_pathway_gene.rno	16
geneset.gene_expression.hsa	17
geneset.gene_expression.mmu	17
geneset.GOBP.dme	18
geneset.GOBP.hsa	18
geneset.GOBP.mmu	19
geneset.GOBP.rno	19
geneset.GOCC.dme	20
geneset.GOCC.hsa	20
geneset.GOCC.mmu	21
geneset.GOCC.rno	21
geneset.GOMF.dme	22
geneset.GOMF.hsa	22
geneset.GOMF.mmu	23
geneset.GOMF.rno	23
geneset.kegg_pathway.hsa	24
geneset.kegg_pathway.mmu	24
geneset.kegg_pathway.rno	25
geneset.mesh.hsa	25
geneset.mesh.mmu	26
geneset.mesh.rno	26
geneset.metabolite.hsa	27
geneset.metabolite.mmu	27
geneset.metabolite.rno	28
geneset.mirbase.hsa	28
geneset.mirbase.mmu	29
geneset.mirbase.rno	29
geneset.panther_pathway.hsa	30
geneset.panther_pathway.mmu	30
geneset.panther_pathway.rno	31
geneset(pfam.hsa	31
geneset(pfam.mmu	32
geneset(pfam.rno	32
geneset.protein_interaction_mimi.hsa	33
geneset.protein_interaction_mimi.mmu	33
geneset.protein_interaction_mimi.rno	34
geneset.reactome.hsa	34
geneset.reactome.mmu	35
geneset.reactome.rno	35
geneset.transcription_factors.hsa	36
geneset.transcription_factors.mmu	36
geneset.transcription_factors.rno	37

locusdef.dm3.10kb	37
locusdef.dm3.10kb_and_more_upstream	38
locusdef.dm3.1kb	38
locusdef.dm3.5kb	39
locusdef.dm3.exon	39
locusdef.dm3.intron	40
locusdef.dm3.nearest_gene	40
locusdef.dm3.nearest_tss	41
locusdef.hg19.10kb	41
locusdef.hg19.10kb_and_more_upstream	42
locusdef.hg19.1kb	42
locusdef.hg19.5kb	43
locusdef.hg19.exon	43
locusdef.hg19.intron	44
locusdef.hg19.nearest_gene	44
locusdef.hg19.nearest_tss	45
locusdef.mm10.10kb	45
locusdef.mm10.10kb_and_more_upstream	46
locusdef.mm10.1kb	46
locusdef.mm10.5kb	47
locusdef.mm10.exon	47
locusdef.mm10.intron	48
locusdef.mm10.nearest_gene	48
locusdef.mm10.nearest_tss	49
locusdef.mm9.10kb	49
locusdef.mm9.10kb_and_more_upstream	50
locusdef.mm9.1kb	50
locusdef.mm9.5kb	51
locusdef.mm9.exon	51
locusdef.mm9.intron	52
locusdef.mm9.nearest_gene	52
locusdef.mm9.nearest_tss	53
locusdef.rn4.10kb	53
locusdef.rn4.10kb_and_more_upstream	54
locusdef.rn4.1kb	54
locusdef.rn4.5kb	55
locusdef.rn4.exon	55
locusdef.rn4.intron	56
locusdef.rn4.nearest_gene	56
locusdef.rn4.nearest_tss	57
LocusDefinition-class	57
mappa.hg19.10kb.100mer	58
mappa.hg19.10kb.24mer	59
mappa.hg19.10kb.36mer	59
mappa.hg19.10kb.40mer	60
mappa.hg19.10kb.50mer	61
mappa.hg19.10kb.75mer	61
mappa.hg19.10kb_and_more_upstream.100mer	62

mappa.hg19.10kb_and_more_upstream.24mer	63
mappa.hg19.10kb_and_more_upstream.36mer	63
mappa.hg19.10kb_and_more_upstream.40mer	64
mappa.hg19.10kb_and_more_upstream.50mer	65
mappa.hg19.10kb_and_more_upstream.75mer	65
mappa.hg19.1kb.100mer	66
mappa.hg19.1kb.24mer	67
mappa.hg19.1kb.36mer	67
mappa.hg19.1kb.40mer	68
mappa.hg19.1kb.50mer	69
mappa.hg19.1kb.75mer	69
mappa.hg19.5kb.100mer	70
mappa.hg19.5kb.24mer	71
mappa.hg19.5kb.36mer	71
mappa.hg19.5kb.40mer	72
mappa.hg19.5kb.50mer	73
mappa.hg19.5kb.75mer	73
mappa.hg19.exon.100mer	74
mappa.hg19.exon.24mer	75
mappa.hg19.exon.36mer	75
mappa.hg19.exon.40mer	76
mappa.hg19.exon.50mer	77
mappa.hg19.exon.75mer	77
mappa.hg19.intron.100mer	78
mappa.hg19.intron.24mer	79
mappa.hg19.intron.36mer	79
mappa.hg19.intron.40mer	80
mappa.hg19.intron.50mer	81
mappa.hg19.intron.75mer	81
mappa.hg19.nearest_gene.100mer	82
mappa.hg19.nearest_gene.24mer	83
mappa.hg19.nearest_gene.36mer	83
mappa.hg19.nearest_gene.40mer	84
mappa.hg19.nearest_gene.50mer	85
mappa.hg19.nearest_gene.75mer	85
mappa.hg19.nearest_tss.100mer	86
mappa.hg19.nearest_tss.24mer	87
mappa.hg19.nearest_tss.36mer	87
mappa.hg19.nearest_tss.40mer	88
mappa.hg19.nearest_tss.50mer	89
mappa.hg19.nearest_tss.75mer	89
mappa.mm9.10kb.100mer	90
mappa.mm9.10kb.36mer	91
mappa.mm9.10kb.40mer	91
mappa.mm9.10kb.50mer	92
mappa.mm9.10kb.75mer	93
mappa.mm9.10kb_and_more_upstream.100mer	93
mappa.mm9.10kb_and_more_upstream.36mer	94

mappa.mm9.10kb_and_more_upstream.40mer	95
mappa.mm9.10kb_and_more_upstream.50mer	95
mappa.mm9.10kb_and_more_upstream.75mer	96
mappa.mm9.1kb.100mer	97
mappa.mm9.1kb.36mer	97
mappa.mm9.1kb.40mer	98
mappa.mm9.1kb.50mer	99
mappa.mm9.1kb.75mer	99
mappa.mm9.5kb.100mer	100
mappa.mm9.5kb.36mer	101
mappa.mm9.5kb.40mer	101
mappa.mm9.5kb.50mer	102
mappa.mm9.5kb.75mer	103
mappa.mm9.exon.100mer	103
mappa.mm9.exon.36mer	104
mappa.mm9.exon.40mer	105
mappa.mm9.exon.50mer	105
mappa.mm9.exon.75mer	106
mappa.mm9.intron.100mer	107
mappa.mm9.intron.36mer	107
mappa.mm9.intron.40mer	108
mappa.mm9.intron.50mer	109
mappa.mm9.intron.75mer	109
mappa.mm9.nearest_gene.100mer	110
mappa.mm9.nearest_gene.36mer	111
mappa.mm9.nearest_gene.40mer	111
mappa.mm9.nearest_gene.50mer	112
mappa.mm9.nearest_gene.75mer	113
mappa.mm9.nearest_tss.100mer	113
mappa.mm9.nearest_tss.36mer	114
mappa.mm9.nearest_tss.40mer	115
mappa.mm9.nearest_tss.50mer	115
mappa.mm9.nearest_tss.75mer	116
peaks_E2F4	117
peaks_H3K4me3_GM12878	117
tss.dm3	118
tss.hg19	119
tss.mm10	119
tss.mm9	120
tss.rn4	121

chipenrich.data-package

Datasets required for the chipenrich package

Description

This package includes genesets (KEGG, GO, etc.), gene locus definitions, gene locus mappabilities, and other required data for the chipenrich package. It also includes example ChIP-seq peak datasets for use with chipenrich.

Details

Almost all of the datasets within this package, with the exception of the example ChIP-seq peak datasets, are not intended for direct use by the user. They are automatically used by the chipenrich package itself. This help file attempts to document each data source should a user wish to understand how each is computed, where it came from, etc.

Genesets are exactly that - sets of genes - as defined in various databases such as KEGG, Gene Ontology, and others.

Each geneset is stored per genome in the format "geneset.<name of geneset>.<genome build>", use `data(package="chipenrich.data")` for a full list.

Each geneset and the description for how it was generated can be found at:

http://sartorlab.ccmb.med.umich.edu/sites/default/files/pdf/geneset_information.pdf.

Gene locus definitions define regions in which peaks are assigned to genes. If a peak falls into a particular gene locus, it is assigned to that gene. Within the package, locus definitions are stored per genome and per definition in the format "locusdef.<genome>.<definition code>". We support multiple definitions currently:

- `nearest_tss`: assigns peaks to the gene with the closest transcription start site (TSS). Each gene locus stretches from the midpoint upstream between TSSs, and the midpoint downstream between TSSs.
- `nearest_gene`: assigns peaks to the nearest gene. Each gene locus stretches from the upstream midpoint between genes and the downstream midpoint between genes.
- `1kb`: each gene locus is defined as the region 1KB up- and down-stream of the TSS.
- `5kb`: each gene locus is defined as the region 5KB up- and down-stream of the TSS.
- `10kb`: each gene locus is defined as the region 10KB up- and down-stream of the TSS.
- `10kb_and_more_upstream`: each gene locus is defined as the region greater than 10KB upstream of the TSS.
- `exon`: each gene locus is defined as the exonic regions of each gene. In the case where exons from multiple transcripts of the same gene may overlap, the region was reduced to one non-overlapping region.
- `intron`: each gene locus is defined as the intronic regions of each gene, that is, the region between two non-overlapping exons of transcripts belonging to the same gene.

The mappability datasets stored within this package represent the average mappability per locus definition (above.) They are stored in the following format: "mappa.<genome build>.<locus definition code>.<read length>". Each dataset is simply an entrez ID, and the mappability score computed for the gene under the given locus definition and read length. For more information regarding how mappability is included, please see (Welch & Lee, 2014.)

Example ChIP-seq peak datasets are also included, and can be used for running chipenrich. Each dataset is stored as "peaks_<name of protein/transcription factor>". Use `example_datasets` or `data(package="chipenrich.data")` for a list.

Author(s)

Ryan Welch <welchr@umich.edu>

References

R.P. Welch*, C. Lee*, R.A. Smith, P. Imbriano, S. Patil, T. Weymouth, L.J. Scott, M.A. Sartor. "ChIP-Enrich: gene set enrichment testing for ChIP-seq data." Nucl. Acids Res. (2014) 42(13):e105. doi:10.1093/nar/gku463

Examples

```
# Get a list of all ChIP-seq peak example datasets.  
example_datasets();  
  
# Inspect an example geneset.  
data("geneset.kegg_pathway.hsa");  
str(geneset.kegg_pathway.hsa);  
  
# Get the mappings from geneset ID to genes for KEGG (loaded above)  
kegg_to_genes = as.list(geneset.kegg_pathway.hsa@set.gene);  
  
# Get the mappings from geneset ID to geneset descriptions for KEGG  
kegg_to_names = as.list(geneset.kegg_pathway.hsa@set.name);  
  
# List all genes within KEGG pathways (as Entrez IDs.)  
kegg_genes = geneset.kegg_pathway.hsa@all.genes;  
  
# Inspect an example locus definition.  
data(locusdef.hg19.nearest_tss);  
str(locusdef.hg19.nearest_tss);  
  
# Get a data frame specifying each gene locus, its chromosome, and start/end positions.  
ldef = locusdef.hg19.nearest_tss@dframe;  
  
# Get a GRanges object containing each locus definition for fast lookups.  
granges = locusdef.hg19.nearest_tss@granges;
```

example_datasets *List ChIP-seq peak example datasets*

Description

Convenience function to list the example ChIP-seq peak datasets available for use with chipenrich.

Usage

```
example_datasets()
```

Details

Prints a list of all example datasets, and a tip on how to load them.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
library(chipenrich.data)
example_datasets()
```

genes.dme *genes.dme*

Description

Entrez Gene IDs for *D. melanogaster* and their corresponding gene symbols.

This is used internally by the chipenrich package.

Usage

```
data(genes.hsa)
```

Format

A data frame with 6790 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Chee Lee <cheelee@umich.edu>

See Also[chipenrich.data](#)

*genes.hsa**genes.hsa*

Description

Entrez Gene IDs for H. sapiens and their corresponding gene symbols.

This is used internally by the `chipenrich` package.

Usage

```
data(genes.hsa)
```

Format

A data frame with 19781 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also[chipenrich.data](#)

*genes.mmu**genes.mmu*

Description

Entrez Gene IDs for M. musculus and their corresponding gene symbols.

This is used internally by the `chipenrich` package.

Usage

```
data(genes.mmu)
```

Format

A data frame with 21388 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

genes.rno

genes.rno

Description

Entrez Gene IDs for *R. norvegicus* and their corresponding gene symbols.

This is used internally by the `chipenrich` package.

Usage

`data(genes.rno)`

Format

A data frame with 19746 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

GeneSet-class *Class "GeneSet"*

Description

Class for storing sets of genes and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("GeneSet")`.

These objects are used internally by the `chipenrich` package and users will not likely need to create these.

Slots

`set.gene`: Object of class "environment". Maps from geneset IDs to lists of Entrez gene IDs.
`type`: Object of class "character". The formal name for this collection of genesets.
`set.name`: Object of class "environment". Maps from geneset IDs to their descriptions/names.
`all.genes`: Object of class "character". A set of all genes present across every geneset.
`organism`: Object of class "character". Organism code for gene IDs.
`dburl`: Object of class "character". Web URL for this collection of genesets.

Note

Not typically accessed by the user - this is used internally by the `chipenrich` package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
library(chipenrich.data)

# Show information about class.
showClass("GeneSet")

# What is stored inside a geneset object?
data("geneset.metabolite.hsa");
str(geneset.metabolite.hsa);

# How are the mappings from geneset IDs to gene IDs stored?
ls.str(geneset.metabolite.hsa@set.gene);
```

`geneset.biocarta_pathway.hsa`
geneset.biocarta_pathway.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.biocarta_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.biocarta_pathway.mmu`
geneset.biocarta_pathway.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.biocarta_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.biocarta_pathway.rno
geneset.biocarta_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.biocarta_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.cytoband.hsa *geneset.cytoband.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.cytoband.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.hsa` *geneset.drug_bank.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.drug_bank.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.mmu` *geneset.drug_bank.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.drug_bank.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.drug_bank.rno *geneset.drug_bank.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.ehmn_pathway_gene.hsa
geneset.ehmn_pathway_gene.hsa

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.mmu  
geneset.ehmn_pathway_gene.mm
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.ehmn_pathway_gene.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.rno  
geneset.ehmn_pathway_gene.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.ehmn_pathway_gene.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.gene_expression.hsa  
      geneset.gene_expression.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.gene_expression.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.gene_expression.mmu  
      geneset.gene_expression.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.gene_expression.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.dme` *geneset.GOBP.dme*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOBP.dme)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.hsa` *geneset.GOBP.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOBP.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.mmu` *geneset.GOBP.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOBP.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.rno` *geneset.GOBP.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOBP.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOCC.dme` *geneset.GOCC.dme*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOCC.dme)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOCC.hsa` *geneset.GOCC.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOCC.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOCC.mmu` *geneset.GOCC.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOCC.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOCC.rno` *geneset.GOCC.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOCC.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOMF.dme` *geneset.GOMF.dme*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOMF.dme)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOMF.hsa` *geneset.GOMF.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOMF.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOMF.mmu` *geneset.GOMF.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOMF.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOMF.rno` *geneset.GOMFrno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.GOMF.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.kegg_pathway.hsa`
geneset.kegg_pathway.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.kegg_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.kegg_pathway.mmu`
geneset.kegg_pathway.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.kegg_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.kegg_pathway.rno
geneset.kegg_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.kegg_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.hsa *geneset.mesh.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mesh.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mesh.mmu` *geneset.mesh.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mesh.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mesh.rno` *geneset.mesh.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mesh.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.metabolite.hsa  
geneset.metabolite.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.metabolite.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.metabolite.mmu  
geneset.metabolite.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.metabolite.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.metabolite.rno`
geneset.metabolite.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.metabolite.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mirbase.hsa` *geneset.mirbase.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mirbase.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mirbase.mmu *geneset.mirbase.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mirbase.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mirbase.rno *geneset.mirbase.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.mirbase.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.panther_pathway.hsa`
geneset.panther_pathway.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.panther_pathway.mmu`
geneset.panther_pathway.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.panther_pathway.rno
geneset.panther_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.panther_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.pfam.hsa *geneset.pfam.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.pfam.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.pfam.mmu` *geneset.pfam.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.pfam.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.pfam.rno` *geneset.pfam.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.pfam.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_mimi.hsa  
geneset.protein_interaction_mimi.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.protein_interaction_mimi.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_mimi.mmu  
geneset.protein_interaction_mimi.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.protein_interaction_mimi.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_mimi.rno  
geneset.protein_interaction_mimi.rno
```

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.protein_interaction_mimi.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.reactome.hsa    geneset.reactome.hsa
```

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.reactome.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.reactome.mmu *geneset.reactome.mmu*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.reactome.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.reactome.rno *geneset.reactome.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.reactome.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.transcription_factors.hsa`
geneset.transcription_factors.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.transcription_factors.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.transcription_factors.mmu`
geneset.transcription_factors.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.transcription_factors.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.transcription_factors.rno  
geneset.transcription_factors.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.transcription_factors.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
locusdef.dm3.10kb      locusdef.dm3.10kb
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.10kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.10kb_and_more_upstream`
locusdef.dm3.10kb_and_more_upstream

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.10kb_and_more_upstream)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.1kb` *locusdef.dm3.1kb*

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.5kb` *locusdef.dm3.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.exon` *locusdef.dm3.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.intron` *locusdef.dm3.intron*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.intron)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.dm3.nearest_gene`
 locusdef.dm3.nearest_gene

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.dm3.nearest_tss  
      locusdef.dm3.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.dm3.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.10kb      locusdef.hg19.10kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.10kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.10kb_and_more_upstream  
      locusdef.hg19.10kb_and_more_upstream
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.10kb_and_more_upstream)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.1kb      locusdef.hg19.1kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.hg19.5kb` *locusdef.hg19.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.hg19.exon` *locusdef.hg19.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.hg19.intron` *locusdef.hg19.intron*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.intron)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.hg19.nearest_gene`
 locusdef.hg19.nearest_gene

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.nearest_tss  
      locusdef.hg19.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.hg19.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm10.10kb      locusdef.mm10.10kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.10kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm10.10kb_and_more_upstream  
locusdef.mm10.10kb_and_more_upstream
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.10kb_and_more_upstream)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm10.1kb      locusdef.mm10.1kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm10.5kb *locusdef.mm10.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm10.exon *locusdef.mm10.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm10.intron` *locusdef.mm10.intron*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.intron)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm10.nearest_gene`
locusdef.mm10.nearest_gene

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm10.nearest_tss  
      locusdef.mm10.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm10.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm9.10kb      locusdef.mm9.10kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.10kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.10kb_and_more_upstream`
locusdef.mm9.10kb_and_more_upstream

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.10kb_and_more_upstream)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.1kb` *locusdef.mm9.1kb*

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.5kb` *locusdef.mm9.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.exon` *locusdef.mm9.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.intron` *locusdef.mm9.intron*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.intron)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.mm9.nearest_gene`
 locusdef.mm9.nearest_gene

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm9.nearest_tss  
      locusdef.mm9.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.mm9.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.10kb      locusdef.rn4.10kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.10kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.10kb_and_more_upstream  
      locusdef.rn4.10kb_and_more_upstream
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.10kb_and_more_upstream)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.1kb      locusdef.rn4.1kb
```

Description

LocusDefinition object which stores information about gene locus definitions.

These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.rn4.5kb` *locusdef.rn4.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.rn4.exon` *locusdef.rn4.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.rn4.intron` *locusdef.rn4.intron*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.intron)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`locusdef.rn4.nearest_gene`
 locusdef.rn4.nearest_gene

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the `chipenrich` package.

Usage

```
data(locusdef.rn4.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.nearest_tss  
  locusdef.rn4.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.rn4.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

LocusDefinition-class *Class "LocusDefinition"*

Description

A storage class representing gene locus definitions and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("LocusDefinition")`. These objects are used internally by the chipenrich package and users will not likely need to create these.

Slots

dframe: Object of class "data.frame". Each row represents a locus for a particular geneid.
granges: Object of class "GenomicRanges". Locus definitions stored as a GenomicRanges object.
chrom2iranges: Object of class "list". List mapping chromosomes to IRanges objects.
genome.build: Object of class "character". Genome build these definitions were generated from.
organism: Object of class "character". Organism code.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
library(chipenrich.data)

# Show info about the class.
showClass("LocusDefinition");

# Example of what a locus definition object looks like.
data(locusdef.mm9.nearest_tss);
str(locusdef.mm9.nearest_tss);
```

mappa.hg19.10kb.100mer

mappa.hg19.10kb.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.100mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.10kb.24mer mappa.hg19.10kb.24mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.24mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.10kb.36mer mappa.hg19.10kb.36mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.10kb.40mer` *mappa.hg19.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.50mer mappa.hg19.10kb.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.75mer mappa.hg19.10kb.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb_and_more_upstream.100mer

mappa.hg19.10kb_and_more_upstream.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb_and_more_upstream.24mer
mappa.hg19.10kb_and_more_upstream.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb_and_more_upstream.36mer
mappa.hg19.10kb_and_more_upstream.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb_and_more_upstream.40mer

mappa.hg19.10kb_and_more_upstream.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.10kb_and_more_upstream.50mer  
mappa.hg19.10kb_and_more_upstream.50mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.10kb_and_more_upstream.75mer  
mappa.hg19.10kb_and_more_upstream.75mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.10kb_and_more_upstream.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.100mer` *mappa.hg19.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.24mer` *mappa.hg19.1kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.36mer` *mappa.hg19.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.40mer` *mappa.hg19.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.50mer` *mappa.hg19.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.75mer` *mappa.hg19.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.100mer` *mappa.hg19.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.24mer` *mappa.hg19.5kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.36mer` *mappa.hg19.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.40mer` *mappa.hg19.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.50mer` *mappa.hg19.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.75mer` *mappa.hg19.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.100mer

mappa.hg19.exon.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.24mer` *mappa.hg19.exon.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.36mer` *mappa.hg19.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.40mer mappa.hg19.exon.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.50mer mappa.hg19.exon.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.75mer mappa.hg19.exon.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.100mer

mappa.hg19.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.intron.24mer`
mappa.hg19.intron.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.intron.36mer`
mappa.hg19.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.40mer

mappa.hg19.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.intron.50mer`
mappa.hg19.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.intron.75mer`
mappa.hg19.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.100mer

mappa.hg19.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.24mer`
mappa.hg19.nearest_gene.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.24mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.36mer`
mappa.hg19.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.40mer

mappa.hg19.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.50mer`
mappa.hg19.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.75mer`
mappa.hg19.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.100mer

mappa.hg19.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_tss.24mer  
mappa.hg19.nearest_tss.24mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.24mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_tss.36mer  
mappa.hg19.nearest_tss.36mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.40mer

mappa.hg19.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_tss.50mer  
mappa.hg19.nearest_tss.50mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.50mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_tss.75mer  
mappa.hg19.nearest_tss.75mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.100mer mappa.mm9.10kb.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.10kb.36mer` *mappa.mm9.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.10kb.40mer` *mappa.mm9.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.50mer *mappa.mm9.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.75mer mappa.mm9.10kb.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb.75mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb_and_more_upstream.100mer
mappa.mm9.10kb_and_more_upstream.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb_and_more_upstream.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb_and_more_upstream.36mer

mappa.mm9.10kb_and_more_upstream.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 36mer

These objects are used internally by the *chipenrich* package.

Usage

```
data(mappa.mm9.10kb_and_more_upstream.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb_and_more_upstream.40mer
mappa.mm9.10kb_and_more_upstream.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb_and_more_upstream.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb_and_more_upstream.50mer
mappa.mm9.10kb_and_more_upstream.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.10kb_and_more_upstream.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb_and_more_upstream.75mer

mappa.mm9.10kb_and_more_upstream.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb_and_more_upstream
- K-Mer Reads: 75mer

These objects are used internally by the *chipenrich* package.

Usage

```
data(mappa.mm9.10kb_and_more_upstream.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.100mer` *mappa.mm9.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.36mer` *mappa.mm9.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.40mer *mappa.mm9.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.50mer` *mappa.mm9.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.75mer` *mappa.mm9.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.100mer *mappa.mm9.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.36mer` *mappa.mm9.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.40mer` *mappa.mm9.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.50mer *mappa.mm9.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.75mer` *mappa.mm9.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.100mer` *mappa.mm9.exon.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.36mer *mappa.mm9.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.40mer` *mappa.mm9.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.50mer` *mappa.mm9.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.75mer *mappa.mm9.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.intron.100mer  
mappa.mm9.intron.100mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.100mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.intron.36mer  
mappa.mm9.intron.36mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.40mer

mappa.mm9.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.intron.50mer`
mappa.mm9.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.intron.75mer`
mappa.mm9.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.100mer

mappa.mm9.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_gene.36mer`
mappa.mm9.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_gene.40mer`
mappa.mm9.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.50mer

mappa.mm9.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_gene.75mer`
mappa.mm9.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_gene.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs
`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_tss.100mer`
mappa.mm9.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.36mer
mappa.mm9.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_tss.40mer  
mappa.mm9.nearest_tss.40mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.40mer)
```

Format

A data frame containing:

```
geneid Entrez Gene IDs  
mappa Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_tss.50mer  
mappa.mm9.nearest_tss.50mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.75mer
mappa.mm9.nearest_tss.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

peaks_E2F4

ChIP-seq Peaks for the E2F4 Transcription Factor

Description

A dataset containing the binding locations (peaks) of the transcription factor E2F4 called from a ChIP-seq experiment

Usage

```
peaks_E2F4
```

Format

A data frame containing 16,245 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found in the following publication:

Lee, B. K., A. A. Bhinge, et al. (2011). "Wide-ranging functions of E2F4 in transcriptional activation and repression revealed by genome-wide analysis." Nucleic Acids Res 39(9): 3558-3573.

Examples

```
library(chipenrich.data)

# Load E2F4 peak data.
data(peaks_E2F4)

# Print the first 10 peaks in the dataset.
print(head(peaks_E2F4))
```

peaks_H3K4me3_GM12878 *ChIP-seq Peaks for the Histone Modification H3K4me3 in GM12878*

Description

A dataset containing the binding locations (peaks) of the histone modification H3K4me3 called from a ChIP-seq experiment in the GM12878 cell line

Usage

```
peaks_H3K4me3_GM12878
```

Format

A data frame containing 57,476 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found at the following ENCODE URL:

<http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeBroadHistone/wgEncodeBroadHistoneGm12878H>

Examples

```
library(chipenrich.data)

# Load H3K4me3 in GM12878 peak data.
data(peaks_H3K4me3_GM12878)

# Print the first 10 peaks in the dataset.
print(head(peaks_H3K4me3_GM12878))
```

tss.dm3

tss.dm3

Description

Transcription start site information for dm3.

This is used internally by the `chipenrich` package.

Usage

```
data(tss.dm3)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Chee Lee <cheelee@umich.edu>

See Also

[chipenrich.data](#)

tss.hg19

tss.hg19

Description

Transcription start site information for hg19.

This is used internally by the `chipenrich` package.

Usage

```
data(tss.hg19)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

tss.mm10

tss.mm10

Description

Transcription start site information for mm10.

This is used internally by the `chipenrich` package.

Usage

```
data(tss.mm10)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

tss.mm9

tss.mm9

Description

Transcription start site information for mm9.

This is used internally by the `chipenrich` package.

Usage

```
data(tss.mm9)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

*tss.rn4**tss.rn4*

Description

Transcription start site information for rn4.

This is used internally by the `chipenrich` package.

Usage

```
data(tss.rn4)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

Index

*Topic **classes**

GeneSet-class, 11
LocusDefinition-class, 57

*Topic **datasets**

genes.dme, 8
genes.hsa, 9
genes.mmu, 9
genes.rno, 10
geneset.biocarta_pathway.hsa, 12
geneset.biocarta_pathway.mmu, 12
geneset.biocarta_pathway.rno, 13
geneset.cytoband.hsa, 13
geneset.drug_bank.hsa, 14
geneset.drug_bank.mmu, 14
geneset.drug_bank.rno, 15
geneset.ehmn_pathway_gene.hsa, 15
geneset.ehmn_pathway_gene.mmu, 16
geneset.ehmn_pathway_gene.rno, 16
geneset.gene_expression.hsa, 17
geneset.gene_expression.mmu, 17
geneset.GOBP.dme, 18
geneset.GOBP.hsa, 18
geneset.GOBP.mmu, 19
geneset.GOBP.rno, 19
geneset.GOCC.dme, 20
geneset.GOCC.hsa, 20
geneset.GOCC.mmu, 21
geneset.GOCC.rno, 21
geneset.GOMF.dme, 22
geneset.GOMF.hsa, 22
geneset.GOMF.mmu, 23
geneset.GOMF.rno, 23
geneset.kegg_pathway.hsa, 24
geneset.kegg_pathway.mmu, 24
geneset.kegg_pathway.rno, 25
geneset.mesh.hsa, 25
geneset.mesh.mmu, 26
geneset.mesh.rno, 26
geneset.metabolite.hsa, 27
geneset.metabolite.mmu, 27
geneset.metabolite.rno, 28
geneset.mirbase.hsa, 28
geneset.mirbase.mmu, 29
geneset.mirbase.rno, 29
geneset.panther_pathway.hsa, 30
geneset.panther_pathway.mmu, 30
geneset.panther_pathway.rno, 31
geneset.pfam.hsa, 31
geneset.pfam.mmu, 32
geneset.pfam.rno, 32
geneset.protein_interaction_mimi.hsa,
33
geneset.protein_interaction_mimi.mmu,
33
geneset.protein_interaction_mimi.rno,
34
geneset.reactome.hsa, 34
geneset.reactome.mmu, 35
geneset.reactome.rno, 35
geneset.transcription_factors.hsa,
36
geneset.transcription_factors.mmu,
36
geneset.transcription_factors.rno,
37
locusdef.dm3.10kb, 37
locusdef.dm3.10kb_and_more_upstream,
38
locusdef.dm3.1kb, 38
locusdef.dm3.5kb, 39
locusdef.dm3.exon, 39
locusdef.dm3.intron, 40
locusdef.dm3.nearest_gene, 40
locusdef.dm3.nearest_tss, 41
locusdef.hg19.10kb, 41
locusdef.hg19.10kb_and_more_upstream,
42
locusdef.hg19.1kb, 42

- locusdef.hg19.5kb, 43
locusdef.hg19.exon, 43
locusdef.hg19.intron, 44
locusdef.hg19.nearest_gene, 44
locusdef.hg19.nearest_tss, 45
locusdef.mm10.10kb, 45
locusdef.mm10.10kb_and_more_upstream,
 46
locusdef.mm10.1kb, 46
locusdef.mm10.5kb, 47
locusdef.mm10.exon, 47
locusdef.mm10.intron, 48
locusdef.mm10.nearest_gene, 48
locusdef.mm10.nearest_tss, 49
locusdef.mm9.10kb, 49
locusdef.mm9.10kb_and_more_upstream,
 50
locusdef.mm9.1kb, 50
locusdef.mm9.5kb, 51
locusdef.mm9.exon, 51
locusdef.mm9.intron, 52
locusdef.mm9.nearest_gene, 52
locusdef.mm9.nearest_tss, 53
locusdef.rn4.10kb, 53
locusdef.rn4.10kb_and_more_upstream,
 54
locusdef.rn4.1kb, 54
locusdef.rn4.5kb, 55
locusdef.rn4.exon, 55
locusdef.rn4.intron, 56
locusdef.rn4.nearest_gene, 56
locusdef.rn4.nearest_tss, 57
mappa.hg19.10kb.100mer, 58
mappa.hg19.10kb.24mer, 59
mappa.hg19.10kb.36mer, 59
mappa.hg19.10kb.40mer, 60
mappa.hg19.10kb.50mer, 61
mappa.hg19.10kb.75mer, 61
mappa.hg19.10kb_and_more_upstream.100mer,
 62
mappa.hg19.10kb_and_more_upstream.24mer,
 63
mappa.hg19.10kb_and_more_upstream.36mer,
 63
mappa.hg19.10kb_and_more_upstream.40mer,
 64
mappa.hg19.10kb_and_more_upstream.50mer,
 65
mappa.hg19.10kb_and_more_upstream.75mer,
 65
mappa.hg19.1kb.100mer, 66
mappa.hg19.1kb.24mer, 67
mappa.hg19.1kb.36mer, 67
mappa.hg19.1kb.40mer, 68
mappa.hg19.1kb.50mer, 69
mappa.hg19.1kb.75mer, 69
mappa.hg19.5kb.100mer, 70
mappa.hg19.5kb.24mer, 71
mappa.hg19.5kb.36mer, 71
mappa.hg19.5kb.40mer, 72
mappa.hg19.5kb.50mer, 73
mappa.hg19.5kb.75mer, 73
mappa.hg19.exon.100mer, 74
mappa.hg19.exon.24mer, 75
mappa.hg19.exon.36mer, 75
mappa.hg19.exon.40mer, 76
mappa.hg19.exon.50mer, 77
mappa.hg19.exon.75mer, 77
mappa.hg19.intron.100mer, 78
mappa.hg19.intron.24mer, 79
mappa.hg19.intron.36mer, 79
mappa.hg19.intron.40mer, 80
mappa.hg19.intron.50mer, 81
mappa.hg19.intron.75mer, 81
mappa.hg19.nearest_gene.100mer, 82
mappa.hg19.nearest_gene.24mer, 83
mappa.hg19.nearest_gene.36mer, 83
mappa.hg19.nearest_gene.40mer, 84
mappa.hg19.nearest_gene.50mer, 85
mappa.hg19.nearest_gene.75mer, 85
mappa.hg19.nearest_tss.100mer, 86
mappa.hg19.nearest_tss.24mer, 87
mappa.hg19.nearest_tss.36mer, 87
mappa.hg19.nearest_tss.40mer, 88
mappa.hg19.nearest_tss.50mer, 89
mappa.hg19.nearest_tss.75mer, 89
mappa.mm9.10kb.100mer, 90
mappa.mm9.10kb.36mer, 91
mappa.mm9.10kb.40mer, 91
mappa.mm9.10kb.50mer, 92
mappa.mm9.10kb.75mer, 93
mappa.mm9.10kb_and_more_upstream.100mer,
 93
mappa.mm9.10kb_and_more_upstream.36mer,
 94
mappa.mm9.10kb_and_more_upstream.40mer,

- 95
 mappa.mm9.10kb_and_more_upstream.50mer, 95
 mappa.mm9.10kb_and_more_upstream.75mer, 96
 mappa.mm9.1kb.100mer, 97
 mappa.mm9.1kb.36mer, 97
 mappa.mm9.1kb.40mer, 98
 mappa.mm9.1kb.50mer, 99
 mappa.mm9.1kb.75mer, 99
 mappa.mm9.5kb.100mer, 100
 mappa.mm9.5kb.36mer, 101
 mappa.mm9.5kb.40mer, 101
 mappa.mm9.5kb.50mer, 102
 mappa.mm9.5kb.75mer, 103
 mappa.mm9.exon.100mer, 103
 mappa.mm9.exon.36mer, 104
 mappa.mm9.exon.40mer, 105
 mappa.mm9.exon.50mer, 105
 mappa.mm9.exon.75mer, 106
 mappa.mm9.intron.100mer, 107
 mappa.mm9.intron.36mer, 107
 mappa.mm9.intron.40mer, 108
 mappa.mm9.intron.50mer, 109
 mappa.mm9.intron.75mer, 109
 mappa.mm9.nearest_gene.100mer, 110
 mappa.mm9.nearest_gene.36mer, 111
 mappa.mm9.nearest_gene.40mer, 111
 mappa.mm9.nearest_gene.50mer, 112
 mappa.mm9.nearest_gene.75mer, 113
 mappa.mm9.nearest_tss.100mer, 113
 mappa.mm9.nearest_tss.36mer, 114
 mappa.mm9.nearest_tss.40mer, 115
 mappa.mm9.nearest_tss.50mer, 115
 mappa.mm9.nearest_tss.75mer, 116
 peaks_E2F4, 117
 peaks_H3K4me3_GM12878, 117
 tss.dm3, 118
 tss.hg19, 119
 tss.mm10, 119
 tss.mm9, 120
 tss.rn4, 121
- chipenrich.data, 9, 10, 12–116, 118–121
 chipenrich.data
 (chipenrich.data-package), 6
 chipenrich.data-package, 6
- example_datasets, 7, 8
- genes.dme, 8
 genes.hsa, 9
 genes.mmu, 9
 genes.rno, 10
 GeneSet-class, 11
 geneset.biocarta_pathway.hsa, 12
 geneset.biocarta_pathway.mmu, 12
 geneset.biocarta_pathway.rno, 13
 geneset.cytoband.hsa, 13
 geneset.drug_bank.hsa, 14
 geneset.drug_bank.mmu, 14
 geneset.drug_bank.rno, 15
 geneset.ehmn_pathway_gene.hsa, 15
 geneset.ehmn_pathway_gene.mmu, 16
 geneset.ehmn_pathway_gene.rno, 16
 geneset.gene_expression.hsa, 17
 geneset.gene_expression.mmu, 17
 geneset.GOBP.dme, 18
 geneset.GOBP.hsa, 18
 geneset.GOBP.mmu, 19
 geneset.GOBP.rno, 19
 geneset.GOCC.dme, 20
 geneset.GOCC.hsa, 20
 geneset.GOCC.mmu, 21
 geneset.GOCC.rno, 21
 geneset.GOMF.dme, 22
 geneset.GOMF.hsa, 22
 geneset.GOMF.mmu, 23
 geneset.GOMF.rno, 23
 geneset.kegg_pathway.hsa, 24
 geneset.kegg_pathway.mmu, 24
 geneset.kegg_pathway.rno, 25
 geneset.mesh.hsa, 25
 geneset.mesh.mmu, 26
 geneset.mesh.rno, 26
 geneset.metabolite.hsa, 27
 geneset.metabolite.mmu, 27
 geneset.metabolite.rno, 28
 geneset.mirbase.hsa, 28
 geneset.mirbase.mmu, 29
 geneset.mirbase.rno, 29
 geneset.panther_pathway.hsa, 30
 geneset.panther_pathway.mmu, 30
 geneset.panther_pathway.rno, 31
 geneset.pfam.hsa, 31
 geneset.pfam.mmu, 32
 geneset.pfam.rno, 32
 geneset.protein_interaction_mimi.hsa,

- geneset.protein_interaction_mimi.mmu,
33
geneset.protein_interaction_mimi.rno,
34
geneset.reactome.hsa, 34
geneset.reactome.mmu, 35
geneset.reactome.rno, 35
geneset.transcription_factors.hsa, 36
geneset.transcription_factors.mmu, 36
geneset.transcription_factors.rno, 37
- locusdef.dm3.10kb, 37
locusdef.dm3.10kb_and_more_upstream,
38
locusdef.dm3.1kb, 38
locusdef.dm3.5kb, 39
locusdef.dm3.exon, 39
locusdef.dm3.intron, 40
locusdef.dm3.nearest_gene, 40
locusdef.dm3.nearest_tss, 41
locusdef.hg19.10kb, 41
locusdef.hg19.10kb_and_more_upstream,
42
locusdef.hg19.1kb, 42
locusdef.hg19.5kb, 43
locusdef.hg19.exon, 43
locusdef.hg19.intron, 44
locusdef.hg19.nearest_gene, 44
locusdef.hg19.nearest_tss, 45
locusdef.mm10.10kb, 45
locusdef.mm10.10kb_and_more_upstream,
46
locusdef.mm10.1kb, 46
locusdef.mm10.5kb, 47
locusdef.mm10.exon, 47
locusdef.mm10.intron, 48
locusdef.mm10.nearest_gene, 48
locusdef.mm10.nearest_tss, 49
locusdef.mm9.10kb, 49
locusdef.mm9.10kb_and_more_upstream,
50
locusdef.mm9.1kb, 50
locusdef.mm9.5kb, 51
locusdef.mm9.exon, 51
locusdef.mm9.intron, 52
locusdef.mm9.nearest_gene, 52
locusdef.mm9.nearest_tss, 53
locusdef.rn4.10kb, 53
- locusdef.rn4.10kb_and_more_upstream,
54
locusdef.rn4.1kb, 54
locusdef.rn4.5kb, 55
locusdef.rn4.exon, 55
locusdef.rn4.intron, 56
locusdef.rn4.nearest_gene, 56
locusdef.rn4.nearest_tss, 57
LocusDefinition-class, 57
- mappa.hg19.10kb.100mer, 58
mappa.hg19.10kb.24mer, 59
mappa.hg19.10kb.36mer, 59
mappa.hg19.10kb.40mer, 60
mappa.hg19.10kb.50mer, 61
mappa.hg19.10kb.75mer, 61
mappa.hg19.10kb_and_more_upstream.100mer,
62
mappa.hg19.10kb_and_more_upstream.24mer,
63
mappa.hg19.10kb_and_more_upstream.36mer,
63
mappa.hg19.10kb_and_more_upstream.40mer,
64
mappa.hg19.10kb_and_more_upstream.50mer,
65
mappa.hg19.10kb_and_more_upstream.75mer,
65
mappa.hg19.1kb.100mer, 66
mappa.hg19.1kb.24mer, 67
mappa.hg19.1kb.36mer, 67
mappa.hg19.1kb.40mer, 68
mappa.hg19.1kb.50mer, 69
mappa.hg19.1kb.75mer, 69
mappa.hg19.5kb.100mer, 70
mappa.hg19.5kb.24mer, 71
mappa.hg19.5kb.36mer, 71
mappa.hg19.5kb.40mer, 72
mappa.hg19.5kb.50mer, 73
mappa.hg19.5kb.75mer, 73
mappa.hg19.exon.100mer, 74
mappa.hg19.exon.24mer, 75
mappa.hg19.exon.36mer, 75
mappa.hg19.exon.40mer, 76
mappa.hg19.exon.50mer, 77
mappa.hg19.exon.75mer, 77
mappa.hg19.intron.100mer, 78
mappa.hg19.intron.24mer, 79
mappa.hg19.intron.36mer, 79

- mappa.hg19.intron.40mer, 80
 mappa.hg19.intron.50mer, 81
 mappa.hg19.intron.75mer, 81
 mappa.hg19.nearest_gene.100mer, 82
 mappa.hg19.nearest_gene.24mer, 83
 mappa.hg19.nearest_gene.36mer, 83
 mappa.hg19.nearest_gene.40mer, 84
 mappa.hg19.nearest_gene.50mer, 85
 mappa.hg19.nearest_gene.75mer, 85
 mappa.hg19.nearest_tss.100mer, 86
 mappa.hg19.nearest_tss.24mer, 87
 mappa.hg19.nearest_tss.36mer, 87
 mappa.hg19.nearest_tss.40mer, 88
 mappa.hg19.nearest_tss.50mer, 89
 mappa.hg19.nearest_tss.75mer, 89
 mappa.mm9.10kb.100mer, 90
 mappa.mm9.10kb.36mer, 91
 mappa.mm9.10kb.40mer, 91
 mappa.mm9.10kb.50mer, 92
 mappa.mm9.10kb.75mer, 93
 mappa.mm9.10kb_and_more_upstream.100mer,
 93
 mappa.mm9.10kb_and_more_upstream.36mer,
 94
 mappa.mm9.10kb_and_more_upstream.40mer,
 95
 mappa.mm9.10kb_and_more_upstream.50mer,
 95
 mappa.mm9.10kb_and_more_upstream.75mer,
 96
 mappa.mm9.1kb.100mer, 97
 mappa.mm9.1kb.36mer, 97
 mappa.mm9.1kb.40mer, 98
 mappa.mm9.1kb.50mer, 99
 mappa.mm9.1kb.75mer, 99
 mappa.mm9.5kb.100mer, 100
 mappa.mm9.5kb.36mer, 101
 mappa.mm9.5kb.40mer, 101
 mappa.mm9.5kb.50mer, 102
 mappa.mm9.5kb.75mer, 103
 mappa.mm9.exon.100mer, 103
 mappa.mm9.exon.36mer, 104
 mappa.mm9.exon.40mer, 105
 mappa.mm9.exon.50mer, 105
 mappa.mm9.exon.75mer, 106
 mappa.mm9.intron.100mer, 107
 mappa.mm9.intron.36mer, 107
 mappa.mm9.intron.40mer, 108
 mappa.mm9.intron.50mer, 109
 mappa.mm9.intron.75mer, 109
 mappa.mm9.nearest_gene.100mer, 110
 mappa.mm9.nearest_gene.36mer, 111
 mappa.mm9.nearest_gene.40mer, 111
 mappa.mm9.nearest_gene.50mer, 112
 mappa.mm9.nearest_gene.75mer, 113
 mappa.mm9.nearest_tss.100mer, 113
 mappa.mm9.nearest_tss.36mer, 114
 mappa.mm9.nearest_tss.40mer, 115
 mappa.mm9.nearest_tss.50mer, 115
 mappa.mm9.nearest_tss.75mer, 116
 peaks_E2F4, 117
 peaks_H3K4me3_GM12878, 117
 tss.dm3, 118
 tss.hg19, 119
 tss.mm10, 119
 tss.mm9, 120
 tss.rn4, 121