

Package ‘CoreGx’

October 14, 2021

Type Package

Title Classes and Functions to Serve as the Basis for Other 'Gx' Packages

Version 1.4.2

Date 2021-09-28

Description A collection of functions and classes which serve as the foundation for our lab's suite of R packages, such as 'PharmacoGx' and 'RadioGx'. This package was created to abstract shared functionality from other lab package releases to increase ease of maintainability and reduce code repetition in current and future 'Gx' suite programs. Major features include a 'CoreSet' class, from which 'RadioSet' and 'PharmacoSet' are derived, along with get and set methods for each respective slot. Additional functions related to fitting and plotting dose response curves, quantifying statistical correlation and calculating area under the curve (AUC) or survival fraction (SF) are included. For more details please see the included documentation, as well as:

Smirnov, P., Safikhani, Z., El-Hachem, N., Wang, D., She, A., Olsen, C., Freeman, M., Selby, H., Gendoo, D., Grossman, P., Beck, A., Aerts, H., Lupien, M., Goldenberg, A. (2015) <[doi:10.1093/bioinformatics/btv723](https://doi.org/10.1093/bioinformatics/btv723)>. Manem, V., Labie, M., Smirnov, P., Kofia, V., Freeman, M., Koritzinksy, M., Abazeed, M., Haibe-Kains, B., Bratman, S. (2018) <[doi:10.1101/449793](https://doi.org/10.1101/449793)>.

VignetteBuilder knitr

VignetteEngine knitr::rmarkdown

biocViews Software, Pharmacogenomics, Classification, Survival

Encoding UTF-8

LazyData true

Depends R (>= 4.1), BiocGenerics, SummarizedExperiment

Imports Biobase, S4Vectors, MultiAssayExperiment, MatrixGenerics, piano, BiocParallel, methods, stats, utils, graphics, grDevices, lsq, data.table, crayon, glue, rlang

Suggests pandoc, markdown, BiocStyle, rmarkdown, knitr, formatR, testthat

License GPL-3

Roxxygen list(markdown = TRUE, r6=FALSE)

RoxxygenNote 7.1.1

```
Collate 'allGenerics.R' 'LongTable-class.R' 'CoreSet-class.R'
  'CoreSet-accessors.R' 'DataMapper-class.R'
  'LongTable-accessors.R' 'LongTableDataMapper-class.R'
  'adaptiveMatthewCor.R' 'callingWaterfall.R'
  'connectivityScore.R' 'cosinePerm.R' 'datasets.R' 'globals.R'
  'gwc.R' 'matthewCor.R' 'methods-$.R' 'methods-[.R'
  'methods-[.R' 'methods-assay.R' 'methods-assayNames.R'
  'methods-assays.R' 'methods-buildLongTable.R'
  'methods-coerce.R' 'methods-colData.R' 'methods-dim.R'
  'methods-dimnames.R' 'methods-drugSensitivitySig.R'
  'methods-getIntern.R' 'methods-guessMapping.R'
  'methods-intersect.R' 'methods-metaConstruct.R'
  'methods-metadata.R' 'methods-reindex.R' 'methods-rowData.R'
  'methods-subset.R' 'methods-subsetTo.R' 'utilities.R'
  'utils-iteration.R' 'utils-messages.R' 'utils-updateS4.R'
```

git_url <https://git.bioconductor.org/packages/CoreGx>

git_branch RELEASE_3_13

git_last_commit 32dc73a

git_last_commit_date 2021-09-28

Date/Publication 2021-10-14

Author Petr Smirnov [aut],

Ian Smith [aut],

Christopher Eeles [aut],

Benjamin Haibe-Kains [aut, cre]

Maintainer Benjamin Haibe-Kains <benjamin.haibe.kains@utoronto.ca>

R topics documented:

.....	4
amcc	4
as	5
as.data.frame.LongTable	6
as.data.table.LongTable	7
as.long.table	7
assayCols	8
buildLongTable	8
buildLongTable,list-method	9
checkColumnCardinality	10
checkCsetStructure	11
clevelandSmall_cSet	11
colIDs	12
colMeta	12

connectivityScore	13
CoreSet	14
CoreSet-accessors	15
CoreSet-class	24
cosinePerm	25
DataMapper-accessors	26
DataMapper-class	27
exampleDataMapper	27
getIntern	27
guessMapping	28
guessMapping,LongTableDataMapper-method	29
gwc	30
idCols	31
idCols,LongTable-method	31
is.items	32
lapply,MultiAssayExperiment-method	33
list_or_LongTable-class	33
LongTable	33
LongTableDataMapper	34
LongTableDataMapper-accessors	36
LongTableDataMapper-class	38
mcc	39
merckLongTable	40
metaConstruct	41
metadata,LongTable-method	42
metadata<-,LongTable-method	42
reindex	43
reindex,LongTable-method	43
rowIDs	44
rowMeta	44
sensitivityInfo	45
sensitivityInfo<-	46
sensitivityMeasures	46
sensitivityMeasures<-	47
sensitivityProfiles	47
sensitivityProfiles<-	48
sensitivityRaw	48
sensitivityRaw<-	49
sensitivitySlotToLongTable	49
show,CoreSet-method	50
show,LongTable-method	50
showSigAnnot	51
subset,LongTable-method	52
summarizeMolecularProfiles	53
summarizeSensitivityProfiles	53
[,LongTable,ANY,ANY,ANY-method	54
[[<,LongTable,ANY,ANY-method	55
\$,LongTable-method	56

\$<-,LongTable-method	57
-----------------------	----

. Convenience function for converting R code to a call

Description

This is used to pass through unevaluated R expressions into subset and [, where they will be evaluated in the correct context.

Usage

$\dots(\dots)$

Arguments

... pairlist One or more R expressions to convert to calls.

Value

`call` An R call object containing the quoted expression.

Examples

```
.(cell line1 == 'A2058')
```

amcc

Calculate an Adaptive Matthews Correlation Coefficient

Description

This function calculates an Adaptive Matthews Correlation Coefficient (AMCC) for two vectors of values of the same length. It assumes the entries in the two vectors are paired. The Adaptive Matthews Correlation Coefficient for two vectors of values is defined as the Maximum Matthews Coefficient over all possible binary splits of the ranks of the two vectors. In this way, it calculates the best possible agreement of a binary classifier on the two vectors of data. If the AMCC is low, then it is impossible to find any binary classification of the two vectors with a high degree of concordance.

Usage

```
amcc(x, y, step.prct = 0, min.cat = 3, nperm = 1000, nthread = 1, ...)
```

Arguments

x, y	Two paired vectors of values. Could be replicates of observations for the same experiments for example.
step.prct	Instead of testing all possible splits of the data, it is possible to test steps of a percentage size of the total number of ranks in x/y. If this variable is 0, function defaults to testing all possible splits.
min.cat	The minimum number of members per category. Classifications with less members fitting into both categories will not be considered.
nperm	The number of permutation to use for estimating significance. If 0, then no p-value is calculated.
nthread	Number of threads to parallelize over. Both the AMCC calculation and the permutation testing is done in parallel.
...	Additional arguments

Value

Returns a list with two elements. \$amcc contains the highest 'mcc' value over all the splits, the p value, as well as the rank at which the split was done.

Examples

```
x <- c(1,2,3,4,5,6,7)
y <- c(1,3,5,4,2,7,6)
amcc(x,y, min.cat=2)
```

as

*LongTable to data.table conversion***Description**

Coerce a LongTable into a data.table.

Currently only supports coercing to data.table or data.frame

Coerce a data.table with the proper configuration attributes back to a LongTable

Arguments

to	character Class name to coerce to, currently only 'data.table' and 'data.frame' are supported
from	A data.table with the 'LongTable.config' attribute, containing three lists named assayCols, rowDataCols and colDataCols. This attribute is automatically created when coercing from a LongTable to a data.table.

Value

A `data.table` with the data from a `LongTable`.
`data.table` containing the data from the `LongTable`, with the ‘`LongTable.config`’ attribute containing the metadata needed to reverse the coercing operation.
`LongTable` object configured with the `LongTable.config`

Examples

```
as(merckLongTable, 'data.table')

dataTable <- as(merckLongTable, 'data.table')
print(attr(dataTable, 'LongTable.config')) # Method doesn't work without this
as(dataTable, 'LongTable')
```

as.data.frame.LongTable

Coerce a LongTable to a data.frame

Description

S3 version of coerce method for convenience.

Usage

```
## S3 method for class 'LongTable'
as.data.frame(x, row.names, optional = TRUE, ...)
```

Arguments

<code>x</code>	LongTable to coerce to <code>data.frame</code> .
<code>row.names</code>	An optional character vector of rownames. We do not recommend using this parameter, it is included for S3 method consistency with <code>as.data.frame</code> .
<code>optional</code>	<code>logical</code> Is it optional for row and column names to be valid R names? If <code>FALSE</code> will use the <code>make.names</code> function to ensure the row and column names are valid R names. Defaults to <code>TRUE</code> .
<code>...</code>	Does nothing.

Value

`data.frame` containing the data from the `LongTable`, with the ‘`LongTable.config`’ attribute containing the metadata needed to reverse the coercion operation.

Examples

```
as(merckLongTable, 'data.frame')
```

```
as.data.table.LongTable
```

Coerce a LongTable into a data.table

Description

S3 version of coerce method for convenience.

Usage

```
## S3 method for class 'LongTable'  
as.data.table(x)
```

Arguments

x LongTable to coerce to a data.table

Value

A data.table containing the data from the LongTable, as well as the ‘LongTable.config’ attribute which contains the data needed to reverse the coercion.

```
as.long.table
```

Coerce from data.table to LongTable

Description

Coerce a data.table with the proper configuration attributes back to a LongTable

Usage

```
as.long.table(x)
```

Arguments

x A data.frame with the ‘LongTable.config’ attribute, containing three lists named assayCols, rowDataCols and colDataCols. This attribute is automatically created when coercing from a LongTable to a data.table.

Value

LongTable object configured with the LongTable.config

Examples

```
dataTable <- as(merckLongTable, 'data.table')
print(attr(dataTable, 'LongTable.config')) # Method doesn't work without this
as.long.table(dataTable)
```

assayCols

Generic to access the assay columns of a rectangular object.

Description

Generic to access the assay columns of a rectangular object.

Usage

```
assayCols(object, ...)
```

Arguments

- | | |
|--------|--------------------------------------|
| object | S4 An object to get assay ids from. |
| ... | Allow new arguments to this generic. |

Value

Depends on the implemented method.

Examples

```
print("Generics shouldn't need examples?")
```

buildLongTable

Build a LongTable object

Description

Build a LongTable object

Usage

```
buildLongTable(from, ...)
```

Arguments

- | | |
|------|--|
| from | What to build the LongTable from? |
| ... | pairlist Allow definition of new parameters for implementations of this generic. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

buildLongTable, list-method

LongTable build method from list

Description

LongTable build method from list

Usage

```
## S4 method for signature 'list'  
buildLongTable(from, rowDataCols, colDataCols, assayCols)
```

Arguments

- | | |
|-------------|--|
| from | list A list containing any combination of character file paths, data.tables and data.frames which will be used to construct the LongTable. |
| rowDataCols | list List with two character vectors, the first specifying one or more columns to be used as cell identifiers (e.g., cell-line name columns) and the second containing any additional metadata columns related to the cell identifiers. |
| colDataCols | list List with two character vectors, the first specifying one or more columns to be used as column identifiers (e.g., drug name columns) and the second containing any additional metadata columns related to the column identifiers. |
| assayCols | list A named list of character vectors specifying how to parse assay columns into a list of data.tables. Each list data.table will be named for the name of corresponding list item and contain the columns specified in the character vector of column names in each list item. |

Value

A LongTable object constructed with the data in `from`.

Functions

- `buildLongTable, list-method`: a LongTable object from a list containing file paths, data.frames and data.tables.

Examples

```
assayList <- assays(merckLongTable, withDimnames=TRUE)
rowDataCols <- list(rowIDs(merckLongTable), rowMeta(merckLongTable))
colDataCols <- list(colIDs(merckLongTable), colMeta(merckLongTable))
assayCols <- assayCols(merckLongTable)
longTable <- buildLongTable(from=assayList, rowDataCols, colDataCols, assayCols)
```

checkColumnCardinality

Search a data.frame for 1:cardinality relationships between a group of columns (your identifiers) and all other columns.

Description

Search a data.frame for 1:cardinality relationships between a group of columns (your identifiers) and all other columns.

Usage

```
checkColumnCardinality(df, group, cardinality = 1, ...)
```

Arguments

df	A data.frame to search for 1:cardinality mappings with the columns in group.
group	A character vector of one or more column names to check the cardinality of other columns against.
cardinality	The cardinality of to search for (i.e., 1:cardinality) relationships with the combination of columns in group. Defaults to 1 (i.e., 1:1 mappings).
...	Fall through arguments to data.table::[. For developer use. One use case is setting verbose=TRUE to diagnose slow data.table operations.

Value

A character vector with the names of the columns with cardinality of 1:cardinality with the columns listed in group.

Examples

```
df <- rawdata(exampleDataMapper)
checkColumnCardinality(df, group='drug_id')
```

checkCsetStructure *A function to verify the structure of a CoreSet*

Description

This function checks the structure of a PharamcoSet, ensuring that the correct annotations are in place and all the required slots are filled so that matching of cells and drugs can be properly done across different types of data and with other studies.

Usage

```
checkCsetStructure(cSet, plotDist = FALSE, result.dir = ".")
```

Arguments

cSet	A CoreSet to be verified
plotDist	Should the function also plot the distribution of molecular data?
result.dir	The path to the directory for saving the plots as a string

Value

Prints out messages whenever describing the errors found in the structure of the cSet object passed in.

Examples

```
checkCsetStructure(clevelandSmall_cSet)
```

clevelandSmall_cSet *Cleaveland_mut RadioSet subsetted and cast as CoreSet*

Description

This dataset is just a dummy object derived from the Cleveland_mut RadioSet in the RadioGx R package. It's contents should not be interpreted and it is only present to test the functions in this package and provide examples

Usage

```
data(clevelandSmall_cSet)
```

Format

CoreSet object

References

Lamb et al. The Connectivity Map: using gene-expression signatures to connect small molecules, genes, and disease. *Science*, 2006.

colIDs

Generic to access the row identifiers for an object.

Description

Generic to access the row identifiers for an object.

Usage

```
colIDs(object, ...)
```

Arguments

- | | |
|--------|---|
| object | S4 An object to get column id columns from. |
| ... | Allow new arguments to this generic |

Value

Depends on the implemented method.

Examples

```
print("Generics shouldn't need examples?")
```

colMeta

Generic to access the column identifiers for a rectangular object.

Description

Generic to access the column identifiers for a rectangular object.

Usage

```
colMeta(object, ...)
```

Arguments

- | | |
|--------|---|
| object | S4 An object to get column metadata columns from. |
| ... | Allow new arguments to this generic |

Value

Depends on impemented method.

Examples

```
print("Generics shouldn't need examples?")
```

connectivityScore

Function computing connectivity scores between two signatures

Description

A function for finding the connectivity between two signatures, using either the GSEA method based on the KS statistic, or the gwc method based on a weighted spearman statistic. The GSEA analysis is implemented in the piano package.

Usage

```
connectivityScore(
  x,
  y,
  method = c("fgsea", "gwc"),
  nperm = 10000,
  nthread = 1,
  gwc.method = c("spearman", "pearson"),
  ...
)
```

Arguments

x	A matrix with the first gene signature. In the case of GSEA the vector of values per gene for GSEA in which we are looking for an enrichment. In the case of gwc, this should be a matrix, with the per gene responses in the first column, and the significance values in the second.
y	A matrix with the second signature. In the case of GSEA, this is the vector of up and down regulated genes we are looking for in our signature, with the direction being determined from the sign. In the case of gwc, this should be a matrix of identical size to x, once again with the per gene responses in the first column, and their significance in the second.
method	character string identifying which method to use, out of 'fgsea' and 'gwc'
nperm	numeric, how many permutations should be done to determine significance through permutation testing? The minimum is 100, default is 1e4.
nthread	numeric, how many cores to run parallel processing on.
gwc.method	character, should gwc use a weighted spearman or pearson statistic?
...	Additional arguments passed down to gsea and gwc functions

Value

numeric a numeric vector with the score and the p-value associated with it

References

F. Pozzi, T. Di Matteo, T. Aste, 'Exponential smoothing weighted correlations', The European Physical Journal B, Vol. 85, No 6, 2012. DOI: 10.1140/epjb/e2012-20697-x

Varemo, L., Nielsen, J. and Nookaew, I. (2013) Enriching the gene set analysis of genome-wide data by incorporating directionality of gene expression and combining statistical hypotheses and methods. Nucleic Acids Research. 41 (8), 4378-4391. doi: 10.1093/nar/gkt111

Examples

```
xValue <- c(1,5,23,4,8,9,2,19,11,12,13)
xSig <- c(0.01, 0.001, .97, 0.01,0.01,0.28,0.7,0.01,0.01,0.01,0.01)
yValue <- c(1,5,10,4,8,19,22,19,11,12,13)
ySig <- c(0.01, 0.001, .97,0.01, 0.01,0.78,0.9,0.01,0.01,0.01,0.01)
xx <- cbind(xValue, xSig)
yy <- cbind(yValue, ySig)
rownames(xx) <- rownames(yy) <- c('1','2','3','4','5','6','7','8','9','10','11')
data.cor <- connectivityScore(xx,yy,method='gwc', gwc.method='spearman', nperm=300)
```

CoreSet

*CoreSet constructor***Description**

A constructor that simplifies the process of creating CoreSets, as well as creates empty objects for data not provided to the constructor. Only objects returned by this constructor are expected to work with the CoreSet methods.

Usage

```
CoreSet(
  name,
  molecularProfiles = list(),
  cell = data.frame(),
  sensitivityInfo = data.frame(),
  sensitivityRaw = array(dim = c(0, 0, 0)),
  sensitivityProfiles = matrix(),
  sensitivityN = matrix(nrow = 0, ncol = 0),
  perturbationN = array(NA, dim = c(0, 0, 0)),
  curationCell = data.frame(),
  curationTissue = data.frame(),
  datasetType = c("sensitivity", "perturbation", "both"),
  verify = TRUE
)
```

Arguments

<code>name</code>	A character string detailing the name of the dataset
<code>molecularProfiles</code>	A list of SummarizedExperiment objects containing molecular profiles for each molecular data type.
<code>cell</code>	A <code>data.frame</code> containing the annotations for all the cell lines profiled in the data set, across all data types
<code>sensitivityInfo</code>	A <code>data.frame</code> containing the information for the sensitivity experiments
<code>sensitivityRaw</code>	A 3 Dimensional array containing the raw drug dose response data for the sensitivity experiments
<code>sensitivityProfiles</code>	<code>data.frame</code> containing drug sensitivity profile statistics such as IC50 and AUC
<code>sensitivityN, perturbationN</code>	A <code>data.frame</code> summarizing the available sensitivity/perturbation data
<code>curationCell, curationTissue</code>	A <code>data.frame</code> mapping the names for cells and tissues used in the data set to universal identifiers used between different CoreSet objects
<code>datasetType</code>	A character string of 'sensitivity', 'perturbation', or both detailing what type of data can be found in the CoreSet, for proper processing of the data
<code>verify</code>	boolean Should the function verify the CoreSet and print out any errors it finds after construction?

Value

An object of class CoreSet

Description

Documentation for the various setters and getters which allow manipulation of data in the slots of a CoreSet object.

Usage

```
## S4 method for signature 'CoreSet'
annotation(object)

## S4 replacement method for signature 'CoreSet,list'
annotation(object) <- value

## S4 method for signature 'CoreSet'
```

```
dateCreated(object)

## S4 replacement method for signature 'CoreSet,character'
dateCreated(object) <- value

## S4 method for signature 'CoreSet'
name(object)

## S4 replacement method for signature 'CoreSet'
name(object) <- value

## S4 method for signature 'CoreSet'
cellInfo(object)

## S4 replacement method for signature 'CoreSet,data.frame'
cellInfo(object) <- value

## S4 method for signature 'CoreSet'
cellNames(object)

## S4 replacement method for signature 'CoreSet,character'
cellNames(object) <- value

## S4 method for signature 'CoreSet'
curation(object)

## S4 replacement method for signature 'CoreSet,list'
curation(object) <- value

## S4 method for signature 'CoreSet'
datasetType(object)

## S4 replacement method for signature 'CoreSet,character'
datasetType(object) <- value

## S4 method for signature 'CoreSet'
molecularProfiles(object, mDataType, assay)

## S4 replacement method for signature 'CoreSet,character,character,matrix'
molecularProfiles(object, mDataType, assay) <- value

## S4 method for signature 'CoreSet'
featureInfo(object, mDataType)

## S4 replacement method for signature 'CoreSet,character,data.frame'
featureInfo(object, mDataType) <- value

## S4 method for signature 'CoreSet,character'
```

```
phenoInfo(object, mDataType)

## S4 replacement method for signature 'CoreSet,character,data.frame'
phenoInfo(object, mDataType) <- value

## S4 method for signature 'CoreSet,character'
fNames(object, mDataType)

## S4 replacement method for signature 'CoreSet,character,character'
fNames(object, mDataType) <- value

## S4 method for signature 'CoreSet'
mDataNames(object)

## S4 replacement method for signature 'CoreSet'
mDataNames(object) <- value

## S4 method for signature 'CoreSet'
molecularProfilesSlot(object)

## S4 replacement method for signature 'CoreSet,list_or_MAE'
molecularProfilesSlot(object) <- value

## S4 method for signature 'CoreSet'
sensitivityInfo(object, dimension, ...)

## S4 replacement method for signature 'CoreSet,data.frame'
sensitivityInfo(object, dimension, ...) <- value

## S4 method for signature 'CoreSet'
sensitivityMeasures(object)

## S4 replacement method for signature 'CoreSet,character'
sensitivityMeasures(object) <- value

## S4 method for signature 'CoreSet'
sensitivityProfiles(object)

## S4 replacement method for signature 'CoreSet,data.frame'
sensitivityProfiles(object) <- value

## S4 method for signature 'CoreSet'
sensitivityRaw(object)

## S4 replacement method for signature 'CoreSet,array'
sensitivityRaw(object) <- value

## S4 method for signature 'CoreSet'
```

```
sensitivitySlot(object)

## S4 replacement method for signature 'CoreSet,list_or_LongTable'
sensitivitySlot(object) <- value

## S4 method for signature 'CoreSet'
sensNumber(object)

## S4 replacement method for signature 'CoreSet,matrix'
sensNumber(object) <- value

## S4 method for signature 'CoreSet'
pertNumber(object)

## S4 replacement method for signature 'CoreSet,array'
pertNumber(object) <- value
```

Arguments

object	A CoreSet object.
value	See details.
mDataType	character(1) The name of a molecular datatype to access from the molecularProfiles of a CoreSet object.
assay	character(1) A valid assay name in the SummarizedExperiment of @molecularProfiles of a CoreSet object for data type mDataType.
dimension	See details.
...	See details.

Details

@annotation:

annotation: A list of CoreSet annotations with items: 'name', the name of the object; 'dateCreated', date the object was created; 'sessionInfo', the sessionInfo() when the object was created; 'call', the R constructor call; and 'version', the object version.

annotation<-: Setter method for the annotation slot. Arguments:

- value: a list of annotations to update the CoreSet with.

@dateCreated:

dateCreated: character(1) The date the CoreSet object was created, as returned by the date() function.

dateCreated<-: Update the 'dateCreated' item in the annotation slot of a CoreSet object. Arguments:

- value: A character(1) vector, as returned by the date() function.

name: character(1) The name of the CoreSet, retrieved from the @annotation slot.

name<-: Update the @annotation\$name value in a CoreSet object.

- value: character(1) The name of the CoreSet object.

cellInfo: data.frame Metadata for all cell-lines in a CoreSet object.

cellInfo<-: assign updated cell-line annotations to the CoreSet object. Arguments:

- value: a data.frame object.

cellNames: character Retrieve the rownames of the data.frame in the cell slot from a CoreSet object.

cellNames<-: assign new rownames to the cellInfo slot data.frame for a CoreSet object. Arguments:

- value: character vector of rownames for the cellInfo(object) data.frame.

@curation:

curation: A list of curated mappings between identifiers in the CoreSet object and the original data publication. Contains two data.frames, 'cell' with cell-line ids and 'tissue' with tissue ids.

curation<-: Update the curation slot of a CoreSet object. Arugments:

- value: A list of data.frames, one for each type of curated identifier. For a CoreSet object the slot should contain tissue and cell-line id data.frames.

datasetType slot:

datasetType: character(1) The type treatment response in the sensitivity slot. Valid values are 'sensitivity', 'perturbation' or 'both'.

datasetType<-: Update the datasetType slot of a CoreSet object. Arguments:

- value: A character(1) vector with one of 'sensitivity', 'perturbation' or 'both'

@molecularProfiles:

molecularProfiles: matrix() Retrieve an assay in a SummarizedExperiment from the molecularProfiles slot of a CoreSet object with the specified mDataType. Valid mDataType arguments can be found with mDataNames(object). Arguments:

- assay: Optional character(1) vector specifying an assay in the SummarizedExperiment of the molecularProfiles slot of the CoreSet object for the specified mDataType. If excluded, defaults to modifying the first assay in the SummarizedExperiment for the given mDataType.

molecularProfiles<-: Update an assay in a SummarizedExperiment from the molecularProfiles slot of a CoreSet object with the specified mDataType. Valid mDataType arguments can be found with mDataNames(object).

- assay: Optional character(1) vector specifying an assay in the SummarizedExperiment of the molecularProfiles slot of the CoreSet object for the specified mDataType. If excluded, defaults to modifying the first assay in the SummarizedExperiment for the given mDataType.
- value: A matrix of values to assign to the assay slot of the SummarizedExperiment for the selected mDataType. The rownames and column names must match the associated SummarizedExperiment.

featureInfo: Retrieve a DataFrame of feature metadata for the specified mDataType from the molecularProfiles slot of a CoreSet object. More specifically, retrieve the @rowData slot from the SummarizedExperiment from the @molecularProfiles of a CoreSet object with the name mDataType.

featureInfo<-: Update the featureInfo(object,mDataType) DataFrame with new feature metadata. Arguments:

- value: A data.frame or DataFrame with updated feature metadata for the specified molecular profile in the molecularProfiles slot of a CoreSet object.

phenoInfo: Return the @colData slot from the SummarizedExperiment of mDataType, containing sample-level metadata, from a CoreSet object.

phenoInfo<-: Update the @colData slot of the SummarizedExperiment of mDataType in the @molecularProfiles slot of a CoreSet object. This updates the sample-level metadata in-place.

- value: A data.frame or DataFrame object where rows are samples and columns are sample metadata.

fNames: character() The features names from the rowData slot of a SummarizedExperiment of mDataType within a CoreSet object.

fNames: Updates the rownames of the feature metadata (i.e., rowData) for a SummarizedExperiment of mDataType within a CoreSet object.

- value: character() A character vector of new features names for the rowData of the SummarizedExperiment of mDataType in the @molecularProfiles slot of a CoreSet object. Must be the same length as nrow(featureInfo(object,mDataType)), the number of rows in the feature metadata.

mDataNames: character Retrieve the names of the molecular data types available in the molecularProfiles slot of a CoreSet object. These are the options which can be used in the mDataType parameter of various molecularProfiles slot accessors methods.

mDataNames: Update the molecular data type names of the molecularProfiles slot of a CoreSet object. Arguments:

- value: character vector of molecular datatype names, with length equal to length(molecularProfilesSlot(object))

molecularProfilesSlot: Return the contents of the @molecularProfiles slot of a CoreSet object. This will either be a list or MultiAssayExperiment of SummarizedExperiments.

molecularProfilesSlot<-: Update the contents of the @molecularProfiles slot of a CoreSet object. Arguemnts:

- value: A list or MultiAssayExperiment of SummarizedExperiments. The list and assays should be named for the molecular datatype in each SummarizedExperiment.

@sensitivity:

Arguments::

- dimension: Optional character(1) One of 'drug', 'cell' or 'assay' to retrieve rowData, colData or the 'assay_metadata' assay from the CoreSet @sensitivity LongTable object, respectively. Ignored with warning if @sensitivity is not a LongTable object.

- ...: Additional arguments to the `rowData` or `colData`. `LongTable` methods. Only used if the `sensitivity` slot contains a `LongTable` object instead of a list and the `dimension` argument is specified.

Methods::

sensitivityInfo: `DataFrame` or `data.frame` of sensitivity drug combo by cell-line metadata for the `CoreSet` object. When the `dimension` parameter is used, it allows retrieval of the dimension specific metadata from the `LongTable` object in `@sensitivity` of a `CoreSet` object.

sensitivityInfo<-: Update the `@sensitivity` slot metadata for a `CoreSet` object. When used without the `dimension` argument it behaves similar to the old `CoreSet` implementation, where the `@sensitivity` slot contained a list with a `$info` `data.frame` item. When the `dimension` argument is used, more complicated assignments can occur where 'cell' modifies the `@sensitivity` `LongTable` `colData`, 'drug' the `rowData` and 'assay' the 'assay_metadata' assay. Arguments:

- `value`: A `data.frame` of treatment response experiment metadata, documenting experiment level metadata (mapping to drugs and cells). If the `@sensitivity` slot doesn't contain a `LongTable` and `dimension` is not specified, you can only modify existing columns as returned by `sensitivityInfo(object)`.

sensitivityMeasures: Get the 'sensitivityMeasures' available in a `CoreSet` object. Each measure represents some summary of cell-line sensitivity to a given drug, such as `ic50`, `ec50`, `AUC`, `AAC`, etc. The results are returned as a character vector with all available metrics for the `PSet` object.

sensitivityMeasures: Update the sensitivity measure in a `CoreSet` object. These values are the column names of the 'profiles' assay and represent various computed sensitivity metrics such as `ic50`, `ec50`, `AUC`, `AAC`, etc.

- `value`: A character vector of new sensitivity measure names, the length of the character vector must match the number of columns of the 'profiles' assay, excluding metadata and key columns.

sensitivityProfiles: Return the sensitivity profile summaries from the `sensitivity` slot. This `data.frame` contains various sensitivity summary metrics, such as `ic50`, `amax`, `EC50`, `aac`, `HS`, etc as columns, with rows as drug by sample experiments.

sensitivityProfiles<-: Update the sensitivity profile summaries the `sensitivity` slot. Arguments: - `value`: A `data.frame` with the same number of rows as returned by `sensitivityProfiles(object)`, but potentially modified columns, such as the computation of additional summary metrics.

sensitivityRaw: Access the raw sensitivity measurements for a `CoreSet` object. A 3D array where rows are `experiment_ids`, columns are doses and the third dimension is metric, either 'Dose' for the doses used or 'Viability' for the cell-line viability at that dose.

sensitivityRaw<-: Update the raw dose and viability data in a `CoreSet`.

- `value`: A 3D array object where rows are `experiment_ids`, columns are replicates and pages are c('Dose', 'Viability'), with the corresponding dose or viability measurement for that `experiment_id` and replicate.

sensNumber: Return a count of viability observations in a `CoreSet` object for each drug-combo by cell-line combination.

sensNumber<-: Update the 'n' item, which holds a matrix with a count of drug by cell-line experiment counts, in the list in `@sensitivity` slot of a `CoreSet` object. Will error when `@sensitivity` contains a `LongTable` object, since the counts are computed on the fly. Arguments:

- **value:** A matrix where rows are cells and columns are drugs, with a count of the number of experiments for each combination as the values.

pertNumber: array Summary of available perturbation experiments from in a CoreSet object. Returns a 3D array with the number of perturbation experiments per drug and cell line, and data type.

pertNumber<-: Update the @perturbation\$n value in a CoreSet object, which stores a summary of the available perturbation experiments. Arguments:

- **value:** A new 3D array with the number of perturbation experiments per drug and cell line, and data type

Value

Accessors: See details.

Setters: An updated CoreSet object, returned invisibly.

Examples

```
data(clevelandSmall_cSet)

## @annotation

annotation(clevelandSmall_cSet)

annotation(clevelandSmall_cSet) <- annotation(clevelandSmall_cSet)

dateCreated(clevelandSmall_cSet)

## dateCreated
dateCreated(clevelandSmall_cSet) <- date()

name(clevelandSmall_cSet)

name(clevelandSmall_cSet) <- 'new_name'

cellInfo(clevelandSmall_cSet) <- cellInfo(clevelandSmall_cSet)

cellNames(clevelandSmall_cSet)

cellNames(clevelandSmall_cSet) <- cellNames(clevelandSmall_cSet)

## curation
curation(clevelandSmall_cSet)

curation(clevelandSmall_cSet) <- curation(clevelandSmall_cSet)

datasetType(clevelandSmall_cSet)

datasetType(clevelandSmall_cSet) <- 'both'

# No assay specified
```

```
molecularProfiles(clevelandSmall_cSet, 'rna') <- molecularProfiles(clevelandSmall_cSet, 'rna')

# Specific assay
molecularProfiles(clevelandSmall_cSet, 'rna', 'exprs') <-
  molecularProfiles(clevelandSmall_cSet, 'rna', 'exprs')

featureInfo(clevelandSmall_cSet, 'rna')

featureInfo(clevelandSmall_cSet, 'rna') <- featureInfo(clevelandSmall_cSet, 'rna')

phenoInfo(clevelandSmall_cSet, 'rna')

phenoInfo(clevelandSmall_cSet, 'rna') <- phenoInfo(clevelandSmall_cSet, 'rna')

fNames(clevelandSmall_cSet, 'rna')

fNames(clevelandSmall_cSet, 'rna') <- fNames(clevelandSmall_cSet, 'rna')

mDataNames(clevelandSmall_cSet)

mDataNames(clevelandSmall_cSet) <- mDataNames(clevelandSmall_cSet)

molecularProfilesSlot(clevelandSmall_cSet)

molecularProfilesSlot(clevelandSmall_cSet) <- molecularProfilesSlot(clevelandSmall_cSet)

sensitivityInfo(clevelandSmall_cSet)

sensitivityInfo(clevelandSmall_cSet) <- sensitivityInfo(clevelandSmall_cSet)

sensitivityMeasures(clevelandSmall_cSet) <- sensitivityMeasures(clevelandSmall_cSet)

sensitivityMeasures(clevelandSmall_cSet) <- sensitivityMeasures(clevelandSmall_cSet)

sensitivityProfiles(clevelandSmall_cSet)

sensitivityProfiles(clevelandSmall_cSet) <- sensitivityProfiles(clevelandSmall_cSet)

head(sensitivityRaw(clevelandSmall_cSet))

sensitivityRaw(clevelandSmall_cSet) <- sensitivityRaw(clevelandSmall_cSet)

sensitivitySlot(clevelandSmall_cSet)

sensitivitySlot(clevelandSmall_cSet) <- sensitivitySlot(clevelandSmall_cSet)

sensNumber(clevelandSmall_cSet)

sensNumber(clevelandSmall_cSet) <- sensNumber(clevelandSmall_cSet)

pertNumber(clevelandSmall_cSet)

pertNumber(clevelandSmall_cSet) <- pertNumber(clevelandSmall_cSet)
```

CoreSet-class	<i>CoreSet - A generic data container for molecular profiles and treatment response data</i>
---------------	--

Description

CoreSet - A generic data container for molecular profiles and treatment response data

Details

The CoreSet (CSet) class was developed as a superclass for pSets in the Pharmacogenomic and RadioGx packages to contain the data generated in screens of cancer cell lines for their genetic profile and sensitivities to therapy (Pharmacological or Radiation). This class is meant to be a superclass which is contained within the Pharmacogenomic (pSet) and RadioSet (RSet) objects exported by Pharmacogenomic and RadioGx. The format of the data is similar for both pSets and rSets, allowing much of the code to be abstracted into the CoreSet super-class. However, the models involved with quantifying cellular response to Pharmacological and Radiation therapy are widely different, and extension of the cSet class allows the packages to apply the correct model for the given data.

Slots

annotation See Slots section.
 molecularProfiles See Slots section.
 cell See Slots section.
 curation See Slots section.
 sensitivity See Slots section.
 perturbation See Slots section.
 curation See Slots section.
 datasetType See Slots section.

Slots

- annotation: A list of annotation data about the CoreSet, including the \$name and the session information for how the object was created, detailing the exact versions of R and all the packages used.
- molecularProfiles: A list or MultiAssayExperiment containing CoreSet object.
- cell: A data.frame containing the annotations for all the cell lines profiled in the data set, across all molecular data types and treatment response experiments.
- sensitivity: A list or LongTable containing all the data for the sensitivity experiments, including \$info, a data.frame containing the experimental info, \$raw a 3D array containing raw data, \$profiles, a data.frame containing sensitivity profiles statistics, and \$n, a data.frame detailing the number of experiments for each cell-drug/radiationInfo pair

- perturbation: list containing \$n, a data.frame summarizing the available perturbation data. This slot is currently being deprecated.
- curation: list containing mappings for cell, tissue names used in the data set to universal identifiers used between different CoreSet objects
- datasetType: character string of 'sensitivity', 'perturbation', or both detailing what type of data can be found in the CoreSet, for proper processing of the data

See Also

[CoreSet-accessors](#)

cosinePerm

Cosine Permutations

Description

Computes the cosine similarity and significance using permutation test. This function uses random numbers, to ensure reproducibility please call `set.seed()` before running the function.

Usage

```
cosinePerm(
  x,
  y,
  nperm = 1000,
  alternative = c("two.sided", "less", "greater"),
  include.perm = FALSE,
  nthread = 1,
  ...
)
```

Arguments

x	factor is the factors for the first variable
y	factor is the factors for the second variable
nperm	integer is the number of permutations to compute the null distribution of MCC estimates
alternative	string indicates the alternative hypothesis and must be one of "two.sided", "greater" or "less". You can specify just the initial letter. "greater" corresponds to positive association, "less" to negative association. Options are 'two.sided', 'less', or 'greater'
include.perm	boolean indicates whether the estimates for the null distribution should be returned. Default set to 'FALSE'
nthread	integer is the number of threads to be used to perform the permutations in parallel
...	A list of fallthrough parameters

Value

A list estimate of the cosine similarity, p-value and estimates after random permutations (null distribution) in include.perm is set to 'TRUE'

Examples

```
x <- factor(c(1,2,1,2,1))
y <- factor(c(2,2,1,1,1))
cosinePerm(x, y)
```

DataMapper-accessors *Accessing and modifying data in a DataMapper object.*

Description

Documentation for the various setters and getters which allow manipulation of data in the slots of a DataMapper object.

Usage

```
## S4 method for signature 'DataMapper'
rawdata(object)
```

Arguments

object A DataMapper object to get or set data from.

Details

rawdata: Get the raw data slot from a DataMapper object. Returns a list-like containing one or more raw data inputs to the DataMapper object.

Value

Accessors: See details

Setters: An update DataMapper object, returned invisibly.

See Also

Other DataMapper-accessors: [LongTableDataMapper-accessors](#)

DataMapper-class

An S4 Class For Mapping from Raw Experimental Data to a Specific S4 Object

Description

This object will be used as a way to abstract away data preprocessing.

Slots

- rawdata: A list-like object containing one or more pieces of raw data that will be processed and mapped to the slots of an S4 object.
 - metadata: A List of object level metadata.
-

exampleDataMapper

Example LongTableDataMapper

Description

A dummy LongTableDataMapper object to be used in package examples.

Usage

```
data(exampleDataMapper)
```

Format

LongTableDataMapper object

getIntern

Retrieve the symbol for the object@.intern slot

Description

Internal slot for storing metadata relevant to the internal operation of an S4 object.

Usage

```
getIntern(object, x, ...)
```

Arguments

- object S4 An object with an @.intern slot containing an environment.
- x character One or more symbol names to retrieve from the object@.intern environment.
- ... Allow new parameters to be defined for this generic.

Details

Warning: This method is intended for developer use and can be ignored by users.

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

guessMapping

Generic for Guessing the Mapping Between Some Raw Data and an S4 Object

Description

Generic for Guessing the Mapping Between Some Raw Data and an S4 Object

Usage

```
guessMapping(object, ...)
```

Arguments

- object An S4 object containing some raw data to guess data to object slot mappings for.
- ... Allow new arguments to be defined for this generic.

Value

A list with mapping guesses as items.

guessMapping,LongTableDataMapper-method

Guess which columns in raw experiment data map to which dimensions.

Description

Checks for columns which are uniquely identified by a group of identifiers. This should be used to help identify the columns required to uniquely identify the rows, columns, assays and metadata of a DataMapper class object.

Usage

```
## S4 method for signature 'LongTableDataMapper'
guessMapping(object, groups, subset, data = FALSE)
```

Arguments

object	A LongTableDataMapper object.
groups	A list containing one or more vector of column names to group-by. The function uses these to determine 1:1 mappings between the combination of columns in each vector and unique values in the raw data columns.
subset	A logical vector indicating whether to subset out mapped columns after each grouping. Must be a single TRUE or FALSE or have the same length as groups, indicating whether to subset out mapped columns after each grouping. This will prevent mapping a column to two different groups.
data	A logical vector indicating whether you would like the data for mapped columns to be returned instead of their column names. Defaults to FALSE for easy use assigning mapped columns to a DataMapper object.

Details

Any unmapped columns will be added to the end of the returned list in an item called unmapped. The function automatically guesses metadata by checking if any columns have only a single value. This is returned as an additional item in the list.

Value

A list, where each item is named for the associated groups item the guess is for. The character vector in each item are columns which are uniquely identified by the identifiers from that group.

Examples

```
guessMapping(exampleDataMapper, groups=list(rows='drug_id', cols='cell_id'),
subset=FALSE)
```

gwc	<i>GWC Score</i>
-----	------------------

Description

Calculate the gwc score between two vectors, using either a weighted spearman or pearson correlation

Usage

```
gwc(
  x1,
  p1,
  x2,
  p2,
  method.cor = c("pearson", "spearman"),
  nperm = 10000,
  truncate.p = 1e-16,
  ...
)
```

Arguments

x1	numeric vector of effect sizes (e.g., fold change or t statitics) for the first experiment
p1	numeric vector of p-values for each corresponding effect size for the first experiment
x2	numeric effect size (e.g., fold change or t statitics) for the second experiment
p2	numeric vector of p-values for each corresponding effect size for the second experiment
method.cor	character string identifying if a pearson or spearman correlation should be used
nperm	numeric how many permutations should be done to determine
truncate.p	numeric Truncation value for extremely low p-values
...	Other passed down to internal functions

Value

numeric a vector of two values, the correlation and associated p-value.

Examples

```
data(clevelandSmall_cSet)
x <- molecularProfiles(clevelandSmall_cSet, 'rna')[,1]
y <- molecularProfiles(clevelandSmall_cSet, 'rna')[,2]
```

```
x_p <- rep(0.05, times=length(x))
y_p <- rep(0.05, times=length(y))
names(x_p) <- names(x)
names(y_p) <- names(y)
gwc(x,x_p,y,y_p, nperm=100)
```

idCols

Generic to access the unique id columns in an S4 object used to

Description

Generic to access the unique id columns in an S4 object used to

Usage

```
idCols(object, ...)
```

Arguments

object	An S4 object to get id columns from.
...	Allow new arguments to this generic.

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

idCols,LongTable-method

Retrieve the unique identifier columns used for primary keys in rowData and colData.

Description

Retrieve the unique identifier columns used for primary keys in rowData and colData.

Usage

```
## S4 method for signature 'LongTable'
idCols(object)
```

Arguments

object	LongTable
--------	-----------

Value

character A character vector containing the unique rowIDs and colIDs in a LongTable object.

Examples

```
idCols(merckLongTable)
```

<i>is.items</i>	<i>Get the types of all items in a list</i>
-----------------	---

Description

Get the types of all items in a list

Usage

```
is.items(list, ..., FUN = is)
```

Arguments

list	A list to get the types from
...	pairlist Additional arguments to FUN
FUN	function or character Either a function, or the name of a function which returns a single logical value. The default function uses <code>is</code> , specify the desired type in You can also use other type checking functions such as <code>is.character</code> , <code>is.numeric</code> , or <code>is.data.frame</code> .

Value

logical A vector indicating if the list item is the specified type.

Examples

```
list <- list(c(1,2,3), c('a','b','c'))
is.items(list, 'character')
```

lapply,MultiAssayExperiment-method
lapply lapply method for MultiAssayExperiment

Description

`lapply` `lapply` method for `MultiAssayExperiment`

Usage

```
## S4 method for signature 'MultiAssayExperiment'
lapply(X, FUN, ...)
```

Arguments

X	A <code>MultiAssayExperiment</code> object.
FUN	A function to be applied to each <code>SummarizedExperiment</code> in a in X.
...	Fall through parameters to FUN

Value

A `MultiAssayExperiment` object, modified such that `experiments(X) <- endoapply(experiments(X), FUN, ...).s`

list_or_LongTable-class
A class union to allow multiple types in a CoreSet slot

Description

A class union to allow multiple types in a CoreSet slot

LongTable	<i>LongTable constructor method</i>
------------------	-------------------------------------

Description

Builds a `LongTable` object from rectangular objects. The `rowData` argument should contain row level metadata, while the `colData` argument should contain column level metadata, for the experimental assays in the assays list. The `rowIDs` and `colIDs` lists are used to configure the internal keys mapping rows or columns to rows in the assays. Each list should contain at minimum one character vector, specifying which columns in `rowData` or `colData` are required to uniquely identify each row. An optional second character vector can be included, specifying any metadata columns for either dimension. These should contain information about each row but NOT be required to uniquely identify a row in the `colData` or `rowData` objects. Additional metadata can be attached to a `LongTable` by passing a list to the `metadata` argument.

Usage

```
LongTable(
  rowData,
  rowIDs,
  colData,
  colIDs,
  assays,
  metadata = list(),
  keep.rownames = FALSE
)
```

Arguments

rowData	<code>data.table, data.frame, matrix</code> A table like object coercible to a <code>data.table</code> containing the a unique <code>rowID</code> column which is used to key assays, as well as additional row metadata to subset on.
rowIDs	<code>character, integer</code> A vector specifying the names or integer indexes of the row data identifier columns. These columns will be pasted together to make up the <code>row.names</code> of the <code>LongTable</code> object.
colData	<code>data.table, data.frame, matrix</code> A table like object coercible to a <code>data.table</code> containing the a unique <code>colID</code> column which is used to key assays, as well as additional column metadata to subset on.
colIDs	<code>character, integer</code> A vector specifying the names or integer indexes of the col data identifier columns. These columns will be pasted together to make up the <code>col.names</code> of the <code>LongTable</code> object.
assays	A list containing one or more objects coercible to a <code>data.table</code> , and keyed by <code>rowID</code> and <code>colID</code> corresponding to the <code>rowID</code> and <code>colID</code> columns in <code>colData</code> and <code>rowData</code> .
metadata	A list of metadata associated with the <code>LongTable</code> object being constructed
keep.rownames	<code>logical</code> or <code>character</code> Logical: whether <code>rownames</code> should be added as a column if coercing to a <code>data.table</code> , default is <code>FALSE</code> . If <code>TRUE</code> , <code>rownames</code> are added to the column ' <code>rn</code> '. Character: specify a custom column name to store the <code>rownames</code> in.

Value

A `LongTable` object containing the data for a treatment response experiment and configured according to the `rowIDs` and `colIDs` arguments.

<code>LongTableDataMapper</code>	<i>Constructor for the <code>LongTableDataMapper</code> class, which maps from one or more raw experimental data files to the slots of a <code>LongTable</code> object.</i>
----------------------------------	---

Description

Constructor for the LongTableDataMapper class, which maps from one or more raw experimental data files to the slots of a LongTable object.

Usage

```
LongTableDataMapper(  
  rawdata,  
  rowDataMap = list(),  
  colDataMap = list(),  
  assayMap = list(),  
  metadataMap = list()  
)
```

Arguments

rawdata	A <code>data.frame</code> of raw data from a treatment response experiment. This will be coerced to a <code>data.table</code> internally. We recommend using joins to aggregate your raw data if it is not present in a single file.
rowDataMap	A list-like object containing two character vectors. The first is column names in <code>rawdata</code> needed to uniquely identify each row, the second is additional columns which map to rows, but are not required to uniquely identify them. Rows should be drugs.
colDataMap	A list-like object containing two character vectors. The first is column names in <code>rawdata</code> needed to uniquely identify each column, the second is additional columns which map to rows, but are not required to uniquely identify them. Columns should be samples.
assayMap	A list-like where each item is a character vector of <code>rawdata</code> column names to assign to an assay, where the name of that assay is the name of the list item. If names are omitted, assays will be numbered by their index in the list
metadataMap	A list-like where each item is a character vector of <code>rawdata</code> column names to assign to the <code>@metadata</code> of the <code>LongTable</code> , where the name of that assay is the name of the list item. If names are omitted, assays will be numbered by their index in the list.

Details

The `guessMapping` method can be used to test hypotheses about the cardinality of one or more sets of identifier columns. This is helpful to determine the id columns for `rowDataMap` and `colDataMap`, as well as identify columns mapping to assays or metadata.

To attach metadata not associated with `rawdata`, please use the `metadata` assignment method on your `LongTableDataMapper`. This metadata will be merge with any metadata from `metadataMap` and added to the `LongTable` which this object ultimately constructs.

Value

A `LongTable` object, with columns mapped to its slots according to the various maps in the `LongTableDataMapper` object.

See Also

[guessMapping](#)

LongTableDataMapper-accessors

Accessing and modifying data in a LongTableDataMapper object.

Description

Documentation for the various setters and getters which allow manipulation of data in the slots of a LongTableDataMapper object.

Usage

```
## S4 method for signature 'LongTableDataMapper'
rowDataMap(object)

## S4 replacement method for signature 'LongTableDataMapper, list_or_List'
rowDataMap(object) <- value

## S4 method for signature 'LongTableDataMapper'
colDataMap(object)

## S4 replacement method for signature 'LongTableDataMapper, list_or_List'
colDataMap(object) <- value

## S4 method for signature 'LongTableDataMapper'
assayMap(object)

## S4 replacement method for signature 'LongTableDataMapper, list_or_List'
assayMap(object) <- value

## S4 method for signature 'LongTableDataMapper'
metadataMap(object)

## S4 replacement method for signature 'LongTableDataMapper, list_or_List'
metadataMap(object) <- value
```

Arguments

- | | |
|--------|---|
| object | A LongTableDataMapper object to get or set data from. |
| value | See details. |

Details

rawdata: Get the raw data slot from a LongTableDataMapper object. Returns a list-like containing one or more raw data inputs to the LongTableDataMapper object.

rowDataMap: list of two character vectors, the first are the columns required to uniquely identify each row of a LongTableDataMapper and the second any additional row-level metadata. If the character vectors have names, the resulting columns are automatically renamed to the item name of the specified column.

rowDataMap<-: Update the @rowDataMap slot of a LongTableDataMapper object, returning an invisible NULL. Arguments:

- value: A list or List where the first item is the names of the identifier columns – columns needed to uniquely identify each row in rowData – and the second item is the metadata associated with those the identifier columns, but not required to uniquely identify rows in the object rowData.

colDataMap: list of two character vectors, the first are the columns required to uniquely identify each row of a LongTableDataMapper and the second any additional col-level metadata. If the character vectors have names, the resulting columns are automatically renamed to the item name of the specified column.

colDataMap<-: Update the @colDataMap slot of a LongTableDataMapper object, returning an invisible NULL. Arguments:

- value: A list or List where the first item is the names of the identifier columns – columns needed to uniquely identify each row in colData – and the second item is the metadata associated with those the identifier columns, but not required to uniquely identify rows in the object rowData.

assayMap: A list of character vectors. The name of each list item will be the assay in a LongTableDataMapper object that the columns in the character vector will be assigned to. Column renaming occurs automatically when the character vectors have names (from the value to the name).

assayMap<-: Updates the @assayMap slot of a LongTableDataMapper object, returning an invisible NULL. Arguments:

- value: A list of character vectors, where the name of each list item is the name of an assay and the values of each character vector specify the columns mapping to the assay in the S4 object the LongTableDataMapper constructs.

metadataMap: A list of character vectors. Each item is an element of the constructed objects @metadata slot.

metadataMap<-: Updates LongTableDataMapper object in-place, then returns an invisible(NULL). Arguments:

- value: A list of character vectors. The name of each list item is the name of the item in the @metadata slot of the LongTableDataMapper object created when metaConstruct is called on the DataMapper, and a character vector specifies the columns of @rawdata to assign to each item.

Value

Accessors: See details

Setters: An update LongTableDataMapper object, returned invisibly.

See Also

Other DataMapper-accessors: [DataMapper-accessors](#)

Examples

```
rowDataMap(exampleDataMapper)

rowDataMap(exampleDataMapper) <- list(c('drug_id'), c())

colDataMap(exampleDataMapper)

colDataMap(exampleDataMapper) <- list(c('cell_id'), c())

assayMap(exampleDataMapper)

assayMap(exampleDataMapper) <- list(sensitivity=c(viability='viability'))

metadataMap(exampleDataMapper)

metadataMap(exampleDataMapper) <- list(object_metadata=c('metadata'))
```

LongTableDataMapper-class

A Class for Mapping Between Raw Data and an LongTable Object

Description

A Class for Mapping Between Raw Data and an LongTable Object

Usage

```
## S4 method for signature 'LongTableDataMapper'
show(object)
```

Arguments

object	A LongTableDataMapper to display in the console.
--------	--

Value

invisible Prints to console.

Functions

- `show`, `LongTableDataMapper`-method: Show method for `LongTableDataMapper`. Determines how the object is displayed in the console.

Slots

`rowDataMap` See Slots section.
`colDataMap` See Slots section.
`assayMap` See Slots section.
`metadataMap` See Slots section.

Slots

- `rowDataMap`: A list-like object containing two character vectors. The first is column names in `rawdata` needed to uniquely identify each row, the second is additional columns which map to rows, but are not required to uniquely identify them. Rows should be drugs.
- `colDataMap`: A list-like object containing two character vectors. The first is column names in `rawdata` needed to uniquely identify each column, the second is additional columns which map to rows, but are not required to uniquely identify them. Columns should be samples.
- `assayMap`: A list-like where each item is a character vector of `rawdata` column names to assign to an assay, where the name of that assay is the name of the list item. If names are omitted, assays will be numbered by their index in the list.
- `metadataMap`: A list-like where each item is a character vector of `rawdata` column names to assign to the `@metadata` of the `LongTable`, where the name of that assay is the name of the list item. If names are omitted, assays will be numbered by their index in the list.
- `rawdata`: A list-like object containing one or more pieces of raw data that will be processed and mapped to the slots of an S4 object.
- `metadata`: A List of object level metadata.

Examples

```
show(exampleDataMapper)
```

mcc

Compute a Mathews Correlation Coefficient

Description

The function computes a Matthews correlation coefficient for two factors provided to the function. It assumes each factor is a factor of class labels, and the entries are paired in order of the vectors.

Usage

```
mcc(x, y, nperm = 1000, nthread = 1, ...)
```

Arguments

<code>x, y</code>	factor of the same length with the same number of levels
<code>nperm</code>	numeric number of permutations for significance estimation. If 0, no permutation testing is done
<code>nthread</code>	numeric can parallelize permutation testing using BiocParallel's <code>bplapply</code>
<code>...</code>	list Additional arguments

Details

Please note: we recommend you call `set.seed()` before using this function to ensure the reproducibility of your results. Write down the seed number or save it in a script if you intend to use the results in a publication.

Value

A list with the MCC as the `$estimate`, and p value as `$p.value`

Examples

```
x <- factor(c(1,2,1,2,3,1))
y <- factor(c(2,1,1,1,2,2))
mcc(x,y)
```

Description

This is a LongTable object created from some drug combination data provided to our lab by Merck.

Usage

```
data(merckLongTable)
```

Format

LongTable object

References

TODO:: Include a reference

metaConstruct	<i>Generic for preprocessing complex data before being used in the constructor of an S4 container object.</i>
---------------	---

Description

This method is intended to abstract away complex constructor arguments and data preprocessing steps needed to transform raw data, such as that produced in a treatment-response or next-gen sequencing experiment, and automate building of the appropriate S4 container object. This is intended to allow mapping between different experimental designs, in the form of an S4 configuration object, and various S4 class containers in the Bioconductor community and beyond.

Usage

```
metaConstruct(mapper, ...)

## S4 method for signature 'LongTableDataMapper'
metaConstruct(mapper)
```

Arguments

- | | |
|--------|--|
| mapper | An LongTableDataMapper object abstracting arguments to an the LongTable constructor. |
| ... | Allow new arguments to be defined for this generic. |

Value

An S4 object for which the class corresponds to the type of the build configuration object passed to this method.

A LongTable object, as specified in the mapper.

Examples

```
data(exampleDataMapper)
rowDataMap(exampleDataMapper) <- list(c('drug_id'), c())
colDataMap(exampleDataMapper) <- list(c('cell_id'), c())
assayMap(exampleDataMapper) <- list(sensitivity=c('viability'))
metadataMap(exampleDataMapper) <- list(study_metadata=c('metadata'))
longTable <- metaConstruct(exampleDataMapper)
longTable
```

metadata,LongTable-method*Getter method for the metadata slot of a LongTable object***Description**

Getter method for the metadata slot of a LongTable object

Usage

```
## S4 method for signature 'LongTable'
metadata(x)
```

Arguments

x The LongTable object from which to retrieve the metadata list.

Value

list The contents of the metadata slot of the LongTable object.

metadata<-,LongTable-method*Setter method for the metadata slot of a LongTable object***Description**

Setter method for the metadata slot of a LongTable object

Usage

```
## S4 replacement method for signature 'LongTable'
metadata(x) <- value
```

Arguments

x LongTable The LongTable to update

value list A list of new metadata associated with a LongTable object.

Value

LongTable A copy of the LongTable object with the value in the metadata slot.

reindex*Generic method for resetting indexing in an S4 object*

Description

This method allows integer indexes used to maintain referential integrity internal to an S4 object to be reset. This is useful particularly after subsetting an object, as certain indexes may no longer be present in the object data. Reindexing removes gaps integer indexes and ensures that the smallest contiguous integer values are used in an objects indexes.

Usage

```
reindex(object, ...)
```

Arguments

object	S4 An object to redo indexing for
...	pairlist Allow definition of new parameters to this generic.

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

reindex,LongTable-method*Redo indexing for a LongTable object to remove any gaps in integer indexes*

Description

After subsetting a LongTable, it is possible that values of rowKey or colKey could no longer be present in the object. As a result there the indexes will no longer be contiguous integers. This method will calculate a new set of rowKey and colKey values such that integer indexes are the smallest set of contiguous integers possible for the data.

Usage

```
## S4 method for signature 'LongTable'  
reindex(object)
```

Arguments

object The LongTable object to recalculalte indexes (rowKey and colKey values) for.

Value

A copy of the LongTable with all keys as the smallest set of contiguous integers possible given the current data.

rowIDs	<i>Generic to access the row identifiers from</i>
---------------	---

Description

Generic to access the row identifiers from

Usage

```
rowIDs(object, ...)
```

Arguments

object S4 An object to get row id columns from.
... Allow new arguments to this generic.

Value

Depends on the implemented method.

Examples

```
print("Generics shouldn't need examples?")
```

rowMeta	<i>Generic to access the row identifiers from</i>
----------------	---

Description

Generic to access the row identifiers from

Usage

```
rowMeta(object, ...)
```

Arguments

- | | |
|--------|--|
| object | S4 An object to get row metadata columns from. |
| ... | Allow new arguments to this generic. |

Value

Depends on the implemented method.

Examples

```
print("Generics shouldn't need examples?")
```

sensitivityInfo	<i>Generic function to get the annotations for a treatment response experiment from an S4 class</i>
-----------------	---

Description

Generic function to get the annotations for a treatment response experiment from an S4 class

Usage

```
sensitivityInfo(object, ...)
```

Arguments

- | | |
|--------|---|
| object | An S4 object to get treatment response experiment annotations from. |
| ... | Allow new arguments to be defined for this generic. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

`sensitivityInfo<-` *sensitivityInfo<- Generic Method*

Description

Generic function to get the annotations for a treatment response experiment from an S4 class.

Usage

```
sensitivityInfo(object, ...) <- value
```

Arguments

- | | |
|---------------------|--|
| <code>object</code> | An S4 object to set treatment response experiment annotations for. |
| <code>...</code> | Allow new arguments to be defined for this generic. |
| <code>value</code> | The new treatment response experiment annotations. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

`sensitivityMeasures` *sensitivityMeasures Generic*

Description

Get the names of the sensitivity summary metrics available in an S4 object.

Usage

```
sensitivityMeasures(object, ...)
```

Arguments

- | | |
|---------------------|---|
| <code>object</code> | An S4 object to retrieve the names of sensitivity summary measurements for. |
| <code>...</code> | Fallthrough arguments for defining new methods |

Value

Depends on the implemented method

Examples

```
sensitivityMeasures(clevelandSmall_cSet)
```

```
sensitivityMeasures<- sensitivityMeasures<- Generic
```

Description

Set the names of the sensitivity summary metrics available in an S4 object.

Usage

```
sensitivityMeasures(object, ...) <- value
```

Arguments

- | | |
|--------|---|
| object | An S4 object to update. |
| ... | Allow new methods to be defined for this generic. |
| value | A set of names for sensitivity measures to use to update the object with. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

```
sensitivityProfiles    sensitivityProfiles Generic
```

Description

A generic for sensitivityProfiles getter method

Usage

```
sensitivityProfiles(object, ...)
```

Arguments

- | | |
|--------|---|
| object | The S4 object to retrieve sensitivity profile summaries from. |
| ... | pairlist Allow defining new arguments for this generic. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

```
sensitivityProfiles<- sensitivityProfiles<- Generic
```

Description

A generic for the sensitivityProfiles replacement method

Usage

```
sensitivityProfiles(object, ...) <- value
```

Arguments

- | | |
|--------|---|
| object | An S4 object to update the sensitivity profile summaries for. |
| ... | Fallthrough arguments for defining new methods |
| value | An object with the new sensitivity profiles. If a matrix object is passed in, converted to data.frame before assignment |

Value

Updated CoreSet

```
sensitivityRaw      sensitivityRaw Generic Method
```

Description

Generic function to get the raw data array for a treatment response experiment from an S4 class.

Usage

```
sensitivityRaw(object, ...)
```

Arguments

- | | |
|--------|---|
| object | An S4 object to extract the raw sensitivity experiment data from. |
| ... | pairlist Allow new parameters to be defined for this generic. |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

```
sensitivityRaw<-      sensitivityRaw<- Generic
```

Description

Generic function to set the raw data array for a treatment response experiment in an S4 class.

Usage

```
sensitivityRaw(object, ...) <- value
```

Arguments

- | | |
|--------|--|
| object | An S4 object to extract the raw sensitivity data from. |
| ... | pairlist Allow new parameters to be defined for this generic. |
| value | An object containing dose and viability metrics to update the object with. |

Value

Depends on the implemented method

```
sensitivitySlotToLongTable
      sensitivitySlotToLongTable Generic
```

Description

Convert the sensitivity slot in an object inheriting from a CoreSet from a list to a LongTable.

Usage

```
sensitivitySlotToLongTable(object, ...)
```

Arguments

- | | |
|--------|--|
| object | CoreSet Object inheriting from CoreSet. |
| ... | Allow new arguments to be defined on this generic. |

Value

A LongTable object containing the data in the sensitivity slot.

Examples

```
print("Generics shouldn't need examples?")
```

show,CoreSet-method *Show a CoreSet*

Description

Show a CoreSet

Usage

```
## S4 method for signature 'CoreSet'
show(object)
```

Arguments

object	CoreSet
--------	---------

Value

Prints the CoreSet object to the output stream, and returns invisible NULL.

Examples

```
show(clevelandSmall_cSet)
```

show,LongTable-method *Show method for the LongTable class*

Description

Show method for the LongTable class

Usage

```
## S4 method for signature 'LongTable'
show(object)
```

Arguments

object A LongTable object to print the results for.

Value

invisible Prints to console.

Examples

```
show(merckLongTable)
```

showSigAnnot

Get the annotations for a Signature class object, as returned by drugSensitivitysig or radSensitivitySig functions available in PharmacoGx and RadioGx, respectively.

Description

Get the annotations for a Signature class object, as returned by drugSensitivitysig or radSensitivitySig functions available in PharmacoGx and RadioGx, respectively.

Usage

```
showSigAnnot(object, ...)
```

Arguments

object A Signature class object
... Allow definition of new arguments to this generic

Value

NULL Prints the signature annotations to console

Examples

```
print("Generics shouldn't need examples?")
```

subset,LongTable-method

Subset method for a LongTable object.

Description

Allows use of the colData and rowData data.table objects to query based on rowID and colID, which is then used to subset all value data.tables stored in the dataList slot. This function is endomorphic, it always returns a LongTable object.

Usage

```
## S4 method for signature 'LongTable'  
subset(x, i, j, assays, reindex = TRUE)
```

Arguments

- x LongTable The object to subset.
- i character, numeric, logical or expression Character: pass in a character vector of drug names, which will subset the object on all row id columns matching the vector. Numeric or Logical: these select based on the rowKey from the rowData method for the LongTable. Call: Accepts valid query statements to the data.table i parameter, this can be used to make complex queries using the data.table API for the rowData data.table.
- j character, numeric, logical or expression Character: pass in a character vector of drug names, which will subset the object on all drug id columns matching the vector. Numeric or Logical: these select based on the rowID from the rowData method for the LongTable. Call: Accepts valid query statements to the data.table i parameter, this can be used to make complex queries using the data.table API for the colData data.table.
- assays character, numeric or logical Optional list of assay names to subset. Can be used to subset the assays list further, returning only the selected items in the new LongTable.
- reindex logical Should the col/rowKeys be remapped after subsetting. defaults to TRUE. For chained subsetting you may be able to get performance gains by setting to FALSE and calling reindex() manually after subsetting is finished.

Value

LongTable A new LongTable object subset based on the specified parameters.

Examples

```
# Character  
subset(merckLongTable, 'ABT-888', 'CAOV3')  
# Numeric
```

```
subset(merckLongTable, 1, c(1, 2))
# Logical
subset(merckLongTable, , colData(merckLongTable)$cellid == 'A2058')
# Call
subset(merckLongTable, drug1id == 'Dasatinib' & drug2id != '5-FU',
       cellid == 'A2058')
```

summarizeMolecularProfiles

Summarize molecular profile data such that there is a single entry for each cell line/treatment combination

Description

Summarize molecular profile data such that there is a single entry for each cell line/treatment combination

Usage

```
summarizeMolecularProfiles(object, ...)
```

Arguments

- | | |
|--------|---|
| object | An S4 object to summarize the molecular profiles for. |
| ... | Allow definition of new arguments to this generic |

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

summarizeSensitivityProfiles

Summarize across replicates for a sensitivity dose-response experiment

Description

Summarize across replicates for a sensitivity dose-response experiment

Usage

```
summarizeSensitivityProfiles(object, ...)
```

Arguments

- object An S4 object to summarize sensitivity profiles for.
 ... Allow definition of new arguments to this generic

Value

Depends on the implemented method

Examples

```
print("Generics shouldn't need examples?")
```

[,LongTable,ANY,ANY,ANY-method
[LongTable Method

Description

Single bracket subsetting for a LongTable object. See subset for more details.

Usage

```
## S4 method for signature 'LongTable,ANY,ANY,ANY'  

x[i, j, assays, ..., drop = FALSE]
```

Arguments

- x LongTable The object to subset.
 i character, numeric, logical or call Character: pass in a character vector of drug names, which will subset the object on all row id columns matching the vector. This parameter also supports valid R regex query strings which will match on the colnames of x. For convenience, * is converted to .* automatically. Colon can be to denote a specific part of the colnames string to query. Numeric or Logical: these select based on the rowKey from the rowData method for the LongTable. Call: Accepts valid query statements to the data.table i parameter as a call object. We have provided the function .() to conveniently convert raw R statements into a call for use in this function.
 j character, numeric, logical or call Character: pass in a character vector of drug names, which will subset the object on all drug id columns matching the vector. This parameter also supports regex queries. Colon can be to denote a specific part of the colnames string to query. Numeric or Logical: these select

based on the rowID from the `rowData` method for the `LongTable`. Call: Accepts valid query statements to the `data.table i` parameter as a call object. We have provided the function `.()` to conveniently convert raw R statements into a call for use in this function.

assays	character Names of assays which should be kept in the <code>LongTable</code> after sub-setting.
...	Included to ensure drop can only be set by name.
drop	logical Included for compatibility with the ' <code>[</code> ' primitive, it defaults to FALSE and changing it does nothing.

Details

This function is endomorphic, it always returns a `LongTable` object.

Value

A `LongTable` containing only the data specified in the function parameters.

Examples

```
# Character
merckLongTable['ABT-888', 'CAOV3']
# Numeric
merckLongTable[1, c(1, 2)]
# Logical
merckLongTable[, colData(merckLongTable)$cellid == 'A2058']
# Call
merckLongTable[
  .(drug1id == 'Dasatinib' & drug2id != '5-FU'),
  .(cellid == 'A2058'),
]
```

[[<,LongTable,ANY,ANY-method
[[<- Method for *LongTable* Class

Description

Just a wrapper around `assay<-` for convenience. See `?assay<-,LongTable,character-method`.

Usage

```
## S4 replacement method for signature 'LongTable,ANY,ANY'
x[[i]] <- value
```

Arguments

- x A LongTable to update.
- i The name of the assay to update, must be in assayNames(object).
- value A data.frame

Value

A LongTable object with the assay i updated using value.

Examples

```
merckLongTable[['sensitivity']] <- merckLongTable[['sensitivity']]
```

\$,LongTable-method Select an assay from a LongTable object

Description

Select an assay from a LongTable object

Usage

```
## S4 method for signature 'LongTable'
x$name
```

Arguments

- x A LongTable object to retrieve an assay from
- name character The name of the assay to get.

Value

data.frame The assay object.

Examples

```
merckLongTable$sensitivity
```

`$<-,LongTable-method` *Update an assay from a LongTable object*

Description

Update an assay from a LongTable object

Usage

```
## S4 replacement method for signature 'LongTable'  
x$name <- value
```

Arguments

x	A LongTable to update an assay for.
name	character(1) The name of the assay to update
value	A data.frame or data.table to update the assay with.

Value

Updates the assay name in x with value, returning an invisible NULL.

Examples

```
merckLongTable$sensitivity <- merckLongTable$sensitivity
```

Index

* **DataMapper-accessors**
 DataMapper-accessors, 26
 LongTableDataMapper-accessors, 36

* **datasets**
 clevelandSmall_cSet, 11
 exampleDataMapper, 27
 merckLongTable, 40

.., 4

.CoreSet (CoreSet-class), 24

.DataMapper (DataMapper-class), 27

.LongTableDataMapper
 (LongTableDataMapper-class), 38

[, LongTable, ANY, ANY, ANY-method, 54

[[<-, LongTable, ANY, ANY-method, 55

\$, LongTable-method, 56

\$<-, LongTable-method, 57

amcc, 4

annotation (CoreSet-accessors), 15

annotation, CoreSet-method
 (CoreSet-accessors), 15

annotation<- (CoreSet-accessors), 15

annotation<-, CoreSet, list-method
 (CoreSet-accessors), 15

as, 5

as.data.frame.LongTable, 6

as.data.table.LongTable, 7

as.long.table, 7

assayCols, 8

assayMap
 (LongTableDataMapper-accessors),
 36

assayMap, LongTableDataMapper, List-method
 (LongTableDataMapper-accessors),
 36

assayMap, LongTableDataMapper, list-method
 (LongTableDataMapper-accessors),
 36

assayMap, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36

36

assayMap<-,
 (LongTableDataMapper-accessors),
 36

assayMap<-, LongTableDataMapper, List-methhod
 (LongTableDataMapper-accessors),
 36

assayMap<-, LongTableDataMapper, list-method
 (LongTableDataMapper-accessors),
 36

assayMap<-, LongTableDataMapper, list_or_List-method
 (LongTableDataMapper-accessors),
 36

buildLongTable, 8

buildLongTable, list-method, 9

cardinality (checkColumnCardinality), 10

cellInfo (CoreSet-accessors), 15

cellInfo, CoreSet-method
 (CoreSet-accessors), 15

cellInfo<- (CoreSet-accessors), 15

cellInfo<-, CoreSet, data.frame-method
 (CoreSet-accessors), 15

cellName, CoreSet-method
 (CoreSet-accessors), 15

cellNames (CoreSet-accessors), 15

cellNames, CoreSet-method
 (CoreSet-accessors), 15

cellNames<- (CoreSet-accessors), 15

cellNames<-, CoreSet, character-method
 (CoreSet-accessors), 15

cellNames<-, CoreSet, list-method
 (CoreSet-accessors), 15

checkColumnCardinality, 10

checkCsetStructure, 11

clevelandSmall_cSet, 11

colDataMap
 (LongTableDataMapper-accessors),
 36

colDataMap, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36
colDataMap<-
 (LongTableDataMapper-accessors),
 36
colDataMap<-, LongTableDataMapper, list_or_List-method
 (LongTableDataMapper-accessors),
 36
colDataMap<-LongTableDataMapper, List-method
 (LongTableDataMapper-accessors),
 36
colIDs, 12
colMeta, 12
connectivityScore, 13
CoreSet, 14
CoreSet-accessors, 15
CoreSet-class, 24
cosinePerm, 25
curation (CoreSet-accessors), 15
curation, CoreSet-method
 (CoreSet-accessors), 15
curation<- (CoreSet-accessors), 15
curation<-, CoreSet, list-method
 (CoreSet-accessors), 15

DataMapper-accessors, 26
DataMapper-class, 27
datasetType (CoreSet-accessors), 15
datasetType, CoreSet-method
 (CoreSet-accessors), 15
datasetType<- (CoreSet-accessors), 15
datasetType<-, CoreSet, character-method
 (CoreSet-accessors), 15
dateCreated (CoreSet-accessors), 15
dateCreated, CoreSet-method
 (CoreSet-accessors), 15
dateCreated<- (CoreSet-accessors), 15
dateCreated<-, CoreSet, character-method
 (CoreSet-accessors), 15
dateCreated<-, CoreSet-method
 (CoreSet-accessors), 15

exampleDataMapper, 27

featureInfo (CoreSet-accessors), 15
featureInfo, CoreSet-method
 (CoreSet-accessors), 15
featureInfo<- (CoreSet-accessors), 15

featureInfo<-, CoreSet, character, data.frame-method
 (CoreSet-accessors), 15
featureInfo<-, CoreSet, character, DataFrame-method
 (CoreSet-accessors), 15
fNames (CoreSet-accessors), 15
fNames, CoreSet, character-method
 (CoreSet-accessors), 15
fNames<- (CoreSet-accessors), 15
fNames<-, CoreSet, character, character-method
 (CoreSet-accessors), 15

getIntern, 27
guessMapping, 28, 36
guessMapping, LongTableDataMapper-method,
 29
gwc, 30

idCols, 31
idCols, LongTable-method, 31
is.items, 32

lapply, MultiAssayExperiment-method, 33
list_or_LongTable-class, 33
LongTable, 33
LongTableDataMapper, 34
LongTableDataMapper-accessors, 36
LongTableDataMapper-class, 38

mcc, 39
mDataNames (CoreSet-accessors), 15
mDataNames, CoreSet-method
 (CoreSet-accessors), 15
mDataNames<- (CoreSet-accessors), 15
mDataNames<-, CoreSet, ANY-method
 (CoreSet-accessors), 15
mDataNames<-, CoreSet-method
 (CoreSet-accessors), 15
merckLongTable, 40
metaConstruct, 41
metaConstruct, LongTableDataMapper-method
 (metaConstruct), 41
metadata, LongTable-method, 42
metadata<- , LongTable-method, 42
metadataMap
 (LongTableDataMapper-accessors),
 36
metadataMap, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36

metadataMap<-
 (LongTableDataMapper-accessors),
 36
 metadataMap<-, LongTableDataMapper, list_or_List
 (LongTableDataMapper-accessors),
 36
 metadataMap<-, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36
 molecularProfiles (CoreSet-accessors),
 15
 molecularProfiles, CoreSet-method
 (CoreSet-accessors), 15
 molecularProfiles<-
 (CoreSet-accessors), 15
 molecularProfiles<-, CoreSet, character, character
 (CoreSet-accessors), 15
 molecularProfiles<-, CoreSet, character, missing
 (CoreSet-accessors), 15
 molecularProfilesSlot
 (CoreSet-accessors), 15
 molecularProfilesSlot, CoreSet-method
 (CoreSet-accessors), 15
 molecularProfilesSlot<-
 (CoreSet-accessors), 15
 molecularProfilesSlot<-, CoreSet, list-method
 (CoreSet-accessors), 15
 molecularProfilesSlot<-, CoreSet, list_or_MAE-method
 (CoreSet-accessors), 15
 molecularProfilesSlot<-CoreSet, MultiAssayExperiment-method
 (CoreSet-accessors), 15
 molecularProfilesSlot, CoreSet-method
 (CoreSet-accessors), 15
 name (CoreSet-accessors), 15
 name, CoreSet-method
 (CoreSet-accessors), 15
 name<- (CoreSet-accessors), 15
 name<-, CoreSet, character-method
 (CoreSet-accessors), 15
 name<-, CoreSet-method
 (CoreSet-accessors), 15
 pertNumber (CoreSet-accessors), 15
 pertNumber, CoreSet-method
 (CoreSet-accessors), 15
 pertNumber<- (CoreSet-accessors), 15
 pertNumber<-, CoreSet, array-method
 (CoreSet-accessors), 15

phenoInfo (CoreSet-accessors), 15
 phenoInfo, CoreSet, character-method
 (CoreSet-accessors), 15
 phenoInfo<- (CoreSet-accessors), 15
 phenoInfo<-, CoreSet, character, data.frame-method
 (CoreSet-accessors), 15
 phenoInfo<-, CoreSet, character, DataFrame-method
 (CoreSet-accessors), 15

rawdata (DataMapper-accessors), 26
 rawdata, DataMapper-method
 (DataMapper-accessors), 26
 rawdata, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36
 reindex, 43
 reindex, LongTable-method, 43
 rowDataMap
 (LongTableDataMapper-accessors),
 36
 rowDataMap, LongTableDataMapper-method
 (LongTableDataMapper-accessors),
 36
 rowDataMap<-
 (LongTableDataMapper-accessors),
 36
 rowDataMap<-, LongTableDataMapper, list-method
 (LongTableDataMapper-accessors),
 36
 rowDataMap<-, LongTableDataMapper, list_or_List-method
 (LongTableDataMapper-accessors),
 36
 rowDataMap<-LongTableDataMapper, List-method
 (LongTableDataMapper-accessors),
 36
 rowIDs, 44
 rowMeta, 44

sensitivityInfo, 45
 sensitivityInfo, CoreSet, character-method
 (CoreSet-accessors), 15
 sensitivityInfo, CoreSet, missing-method
 (CoreSet-accessors), 15
 sensitivityInfo, CoreSet-method
 (CoreSet-accessors), 15
 sensitivityInfo<-, 46
 sensitivityInfo<-, CoreSet, data.frame-method
 (CoreSet-accessors), 15

sensitivityInfo<, CoreSet, missing, data.frame-method
 (CoreSet-accessors), 15
sensitivityMeasures, 46
sensitivityMeasures, CoreSet-method
 (CoreSet-accessors), 15
sensitivityMeasures<, 47
sensitivityMeasures<, CoreSet, character-method
 (CoreSet-accessors), 15
sensitivityProfiles, 47
sensitivityProfiles, CoreSet-method
 (CoreSet-accessors), 15
sensitivityProfiles<, 48
sensitivityProfiles<, CoreSet, data.frame-method
 (CoreSet-accessors), 15
sensitivityRaw, 48
sensitivityRaw, CoreSet-method
 (CoreSet-accessors), 15
sensitivityRaw<, 49
sensitivityRaw<, CoreSet, array-method
 (CoreSet-accessors), 15
sensitivitySlot (CoreSet-accessors), 15
sensitivitySlot, CoreSet-method
 (CoreSet-accessors), 15
sensitivitySlot< (CoreSet-accessors),
 15
sensitivitySlot<, CoreSet, list-method
 (CoreSet-accessors), 15
sensitivitySlot<, CoreSet, list_or_LongTable-method
 (CoreSet-accessors), 15
sensitivitySlot<, CoreSet, LongTable-method
 (CoreSet-accessors), 15
sensitivitySlotToLongTable, 49
sensitivityInfo<, CoreSet, character, data.frame-method
 (CoreSet-accessors), 15
sensNumber (CoreSet-accessors), 15
sensNumber, CoreSet-method
 (CoreSet-accessors), 15
sensNumber< (CoreSet-accessors), 15
sensNumber<, CoreSet, matrix-method
 (CoreSet-accessors), 15
show, CoreSet-method, 50
show, LongTable-method, 50
show, LongTableDataMapper-method
 (LongTableDataMapper-class), 38
showSigAnnot, 51
subset, LongTable-method, 52
summarizeMolecularProfiles, 53
summarizeSensitivityProfiles, 53