

Package ‘leeBamViews’

April 1, 2025

Title leeBamViews -- multiple yeast RNAseq samples excerpted from Lee
2009

Version 1.42.0

Author VJ Carey <stvjc@channing.harvard.edu>

Description data from PMID 19096707; prototype for managing multiple NGS samples

Depends R (>= 2.15.0), Biobase, Rsamtools (>= 0.1.50), BSgenome

Imports GenomicRanges, GenomicAlignments, methods, S4Vectors,
parallel, IRanges

Suggests biomaRt, org.Sc.sgd.db, edgeR

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic 2.0

LazyLoad yes

biocViews ExperimentData, Saccharomyces_cerevisiae_Data,
SequencingData, RNASeqData, SNPData

RxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/leeBamViews>

git_branch RELEASE_3_20

git_last_commit c223e2c

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-04-01

Contents

bs1	2
leeRPKM	4
leeUnn	5
tabulateReads	6
totalReadCounts	7

Index

8

Description

BamViews instance construction related to yeast RNA-seq

Format

The format is: Formal class 'BamViews' [package "Rsamtools"] with 5 slots

```

..@ bamPaths : chr [1:8] "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt5_13e.bam"
"/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt6_13e.bam" "/Users/stvjc/ExternalSoft/R-
-devel/library/leeBamViews/bam/rlp5_13e.bam" "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/rlp6_13e.

...
..@ bamIndices : chr [1:8] "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt5_13e.bam"
"/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/isowt6_13e.bam" "/Users/stvjc/ExternalSoft/R-
-devel/library/leeBamViews/bam/rlp5_13e.bam" "/Users/stvjc/ExternalSoft/R-devel/library/leeBamViews/bam/rlp6_13e.

...
..@ bamSamples :Formal class 'DataFrame' [package "IRanges"] with 6 slots
... ..@ rownames : chr [1:8] "isowt.5" "isowt.6" "rlp.5" "rlp.6" ...
... ..@ nrows : int 8
... ..@ elementMetadata: NULL
... ..@ elementType : chr "ANY"
" ... ..@ metadata : list()
... ..@ listData :List of 2
... .. .$.geno: chr [1:8] "isowt" "isowt" "rlp" "rlp" ...
... .. .$.lane: chr [1:8] "5" "6" "5" "6" ...
..@ bamRanges :Formal class 'GRanges' [package "GenomicRanges"] with 7 slots
... ..@ seqnames :Formal class 'Rle' [package "IRanges"] with 5 slots
... .. .@ values : Factor w/ 1 level "Scchr13": 1
... .. .@ lengths : int 27
... .. .@ elementMetadata: NULL
... .. .@ elementType : chr "ANY"
... .. .@ metadata : list()
... ..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
... .. . .@ start : int [1:27] 798517 801771 804455 808999 810465 811088 818826 820255
822762 832338 ...
... .. . .@ width : int [1:27] 2862 933 636 234 114 108 1122 2199 1869 915 ...
... .. . .@ NAMES : NULL
... .. . .@ elementMetadata: NULL
... .. . .@ elementType : chr "integer"
... .. . .@ metadata : list()
... .. .@ strand :Formal class 'Rle' [package "IRanges"] with 5 slots
... .. . .@ values : Factor w/ 3 levels "+","-","*": 1
... .. . .@ lengths : int 27
... .. . .@ elementMetadata: NULL
... .. . .@ elementType : chr "ANY"
... .. . .@ metadata : list()
... .. .@ seqlengths : Named int NA
... .. . .- attr(*, "names")= chr "Scchr13"
... .. .@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots

```

```

... . . . . .@ rownames : NULL
... . . . . .@ nrows : int 27
... . . . . .@ elementMetadata: NULL
... . . . . .@ elementType : chr "ANY"
... . . . . .@ metadata : list()
... . . . . .@ listData :List of 1
... . . . . .$. name: chr [1:27] "YMR266W" "YMR267W" "YMR269W" "YMRWdelta20" ...
... . . . . .@ elementType : chr "ANY"
... . . . . .@ metadata : list()
... @ bamExperiment:List of 1
... $. annotation: chr "org.Sc.sgd.db"

```

Details

Illumina short reads from a very small segment of yeast chr XIII have been collected

Source

FASTQ data available at <ftp://ftp.ncbi.nlm.nih.gov/sra/Studies/SRP000/SRP000632/>

References

Albert Lee and Kasper Daniel Hansen and James Bullard and Sandrine Dudoit and Gavin Sherlock, Novel Low Abundance and Transient RNAs in Yeast Revealed by Tiling Microarrays and Ultra High-Throughput Sequencing Are Not Conserved Across Closely Related Yeast Species, PLoS Genet, v4, e1000299, Dec 2008

Examples

```

library(leeBamViews) # bam files stored in package
bpaths = dir(system.file("bam", package="leeBamViews"), full=TRUE, patt="bam$")
#
# extract genotype and lane information from filenames
#
gt = gsub("./", "", bpaths)
gt = gsub("_.*", "", gt)
lane = gsub(".*(.)$", "\\\1", gt)
geno = gsub(".", "", gt)
#
# format the sample-level information appropriately
#
pd = DataFrame(geno=geno, lane=lane, row.names=paste(geno, lane, sep="."))
prd = new("DFrame") # protocol data could go here
#
# create the views object, adding some arbitrary experiment-level information
#
bs1 = BamViews(bamPaths=bpaths, bamSamples=pd,
               bamExperiment=list(annotation="org.Sc.sgd.db"))
bs1
# add ranges and tabulate reads

START=c(861250, 863000)
END=c(862750, 864000)
exc = GRanges(IRanges(start=START, end=END), seqnames="Scchr13", strand="+")

```

```

values(exc)$name = c("intv1", "intv2") # necessary
bamRanges(bs1) = exc
bs1
tabulateReads(bs1, "+")

```

leeRPKM

*supplemental data extract on RNA seq results in yeast***Description**

supplemental data extract on RNA seq results in yeast

Usage

```
data(leeRPKM)
```

Format

A data frame with 6291 observations on the following 16 variables.

chr	a numeric vector
strand	a numeric vector
start	a numeric vector
end	a numeric vector
name	a factor with levels LSR1 NME1 YAL001C YAL002W YAL003W ...
feature	a factor with levels CDS CDS_unchar snRNA snoRNA
orf_classification	a factor with levels Uncharacterized Verified silenced_gene3A Verified
gene	a factor with levels AAC1 AAC3 AAD10 AAD14 AAD15 AAD16 AAD3 AAD4 ...
wt.reads	a numeric vector
rrp.reads	a numeric vector
ski.reads	a numeric vector
xrn.reads	a numeric vector
wt.rpkm	a numeric vector
rrp.rpkm	a numeric vector
ski.rpkm	a numeric vector
xrn.rpkm	a numeric vector

Source

imported from supplemental data

References

Lee et al PLOS genetics December 2008 ; Volume 4 ; Issue 12 ; e1000299

Examples

```

data(leeRPKM)
leeRPKM[1:5,]

```

leeUnn	<i>supplemental data extracts on existing evidence of transcription in yeast</i>
--------	--

Description

supplemental data extracts on existing evidence of transcription in yeast

Usage

```
data(leeUnn)
```

Format

A data frame with 54822 observations on the following 11 variables.

chr a numeric vector
start a numeric vector
end a numeric vector
strand a numeric vector
lengthWithoutMask a numeric vector
length a numeric vector
lambda a numeric vector
background5 a logical vector
background20 a logical vector
reads a numeric vector
study a factor with levels David Davis Miura Nagalakshmi

Source

from Lee et al PLoS genetics December 2008 Volume 4 Issue 12 e1000299 supplemental data information on unannotated transcripts for which some evidence of transcription was obtained in this experiment

Examples

```
data(leeUnn)  
leeUnn[1:5,]
```

tabulateReads*tabulate counts of alignments occurring in specified genomic regions***Description**

tabulate counts of alignments occurring in specified genomic regions

Usage

```
tabulateReads(bv, strandmarker=NULL, as.GRanges=FALSE, applier=lapply)
```

Arguments

<code>bv</code>	BamViews-class instance
<code>strandmarker</code>	character atom: ‘+’ or ‘-’; if missing, ignore strand
<code>as.GRanges</code>	logical directive to return a GRanges instance instead of a matrix
<code>applier</code>	lapply-like function; if unspecified and multicore is attached will use mclapply

Details

[readGAlignments](#) is the basic engine for this task

Value

annotated matrix with start, end, and samples as rows, regions as columns, and read counts as cell entries

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
example(bs1)
#
# counts in a partition
#
myrn = GRanges(IRanges(start=seq(861250, 862750, 100), width=100),
  seqnames="Scchr13", strand="+")

values(myrn)$name = paste("til", 1:length(myrn), sep=".")
bamRanges(bs1) = myrn
tabulateReads(bs1, "+")
#
# a related computation based on countBam
lapply(bamPaths(bs1)[1:2], function(x)
  countBam(x, param=ScanBamParam(which=bamRanges(bs1))))
```

<code>totalReadCounts</code>	<i>scan BAM files for total read counts</i>
------------------------------	---

Description

scan BAM files for total read counts

Usage

```
totalReadCounts(x)
```

Arguments

`x` [BamViews-class](#) instance

Details

slow procedure – does lightweight scan of entire file

Value

named integer vector of read counts per sample

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
example(bs1)
totalReadCounts(bs1)
```

Index

- * **datasets**
 - bs1, [2](#)
 - leeRPKM, [4](#)
 - leeUnn, [5](#)
- * **models**
 - tabulateReads, [6](#)
 - totalReadCounts, [7](#)

[bs1, 2](#)

[leeRPKM, 4](#)

[leeUnn, 5](#)

[readGAlignments, 6](#)

[tabulateReads, 6](#)

[tabulateReads, BamViews, character_OR_NULL, logical, function-method \(tabulateReads\), 6](#)

[tabulateReads, BamViews, character_OR_NULL, missing, missing-method \(tabulateReads\), 6](#)

[tabulateReads, BamViews, missing, missing, missing-method \(tabulateReads\), 6](#)

[totalReadCounts, 7](#)

[totalReadCounts, BamViews-method \(totalReadCounts\), 7](#)