

# Package ‘MatrixRider’

June 22, 2025

**Type** Package  
**Title** Obtain total affinity and occupancies for binding site matrices on a given sequence  
**Version** 1.40.0  
**Date** 2015-11-02  
**Author** Elena Grassi  
**Maintainer** Elena Grassi <grassi.e@gmail.com>  
**Description** Calculates a single number for a whole sequence that reflects the propensity of a DNA binding protein to interact with it. The DNA binding protein has to be described with a PFM matrix, for example gotten from Jaspar.  
**biocViews** GeneRegulation, Genetics, MotifAnnotation  
**License** GPL-3  
**Depends** R (>= 3.1.2)  
**Imports** methods, TFBSTools, IRanges, XVector, Biostrings  
**Suggests** RUnit, BiocGenerics, BiocStyle, JASPAR2014  
**LinkingTo** IRanges, XVector, Biostrings, S4Vectors  
**NeedsCompilation** yes  
**git\_url** <https://git.bioconductor.org/packages/MatrixRider>  
**git\_branch** RELEASE\_3\_21  
**git\_last\_commit** e6f4c01  
**git\_last\_commit\_date** 2025-04-15  
**Repository** Bioconductor 3.21  
**Date/Publication** 2025-06-22

## Contents

|                               |          |
|-------------------------------|----------|
| MatrixRider-package . . . . . | 2        |
| getSeqOccupancy . . . . .     | 2        |
| <b>Index</b>                  | <b>4</b> |

---

|                     |                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------|
| MatrixRider-package | <i>Calculate total affinity and occupancies for binding site matrices on a given sequence</i> |
|---------------------|-----------------------------------------------------------------------------------------------|

---

### Description

Calculates a single number for a whole sequence that reflects the propensity of a DNA binding protein to interact with it. The DNA binding protein has to be described with a PFM matrix, for example gotten from Jaspar.

### Author(s)

Elena Grassi <elena.grassi@unito.it>

### Examples

```
library(JASPAR2014)
library(TFBSTools)
library(Biostrings)
pfm <- getMatrixByID(JASPAR2014,"MA0004.1")
## The following sequence has a single perfect match
## thus it gives the same results with all cutoff values.
sequence <- DNAString("CACGTG")
getSeqOccupancy(sequence, pfm, 0.1)
getSeqOccupancy(sequence, pfm, 1)
```

---

|                 |                                                                       |
|-----------------|-----------------------------------------------------------------------|
| getSeqOccupancy | <i>Computes the total affinity or the occupancy at a given cutoff</i> |
|-----------------|-----------------------------------------------------------------------|

---

### Description

The affinity/occupancy is calculated on the given DNAString for the given PFMatrix (or all the ones in the PFMatrix list given).

### Usage

```
getSeqOccupancy(sequence, pfm, cutoff)
```

### Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                             |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sequence | A <a href="#">DNAString</a> object with the sequence for which affinity will be computed.                                                                                                                                                                                                                                                                                   |
| pfm      | A <a href="#">PFMatrix</a> or a <a href="#">PFMatrixList</a> object with the matrixes whose affinity will be calculated. The background ( <a href="#">bg,XMatrix-method</a> ) of the given pfm is used to perform affinity calculations.                                                                                                                                    |
| cutoff   | numeric(1); between 0 and 1 (included): 0 corresponds to total affinity (i.e. summing all the affinities) while 1 to summing only values corresponding to the perfect match for a given <a href="#">PFMatrix</a> . See vignette for details on how scores are calculated. If <b>MatrixRider</b> is installed, open the vignette with <code>vignette("MatrixRider")</code> . |

**Value**

numeric; the resulting total affinity calculated on the given fasta. If a [PFMatrixList](#) has been passed then a named numeric vector with the affinities for all the PFMs. The vignette has all the details on the calculations (such as PFM to PWM conversion and pseudocounts).

**Examples**

```
library(JASPAR2014)
library(TFBSTools)
library(Biostrings)
pfm <- getMatrixByID(JASPAR2014,"MA0004.1")
## The following sequence has a single perfect match
## thus it gives the same results with all cutoff values.
sequence <- DNASTring("CACGTG")
getSeqOccupancy(sequence, pfm, 0.1)
getSeqOccupancy(sequence, pfm, 1)

pfm2 <- getMatrixByID(JASPAR2014,"MA0005.1")
pfms <- PFMatrixList(pfm, pfm2)
names(pfms) <- c(name(pfm), name(pfm2))
## This calculates total affinity for both the PFMatrixes.
getSeqOccupancy(sequence, pfms, 0)
```

# Index

- \* **MatrixRider**

- MatrixRider-package, [2](#)

- \* **getSeqOccupancy**

- getSeqOccupancy, [2](#)

bg, XMatrix-method, [2](#)

DNAString, [2](#)

getSeqOccupancy, [2](#)

getSeqOccupancy, DNAString, PFMatrix, numeric-method  
(getSeqOccupancy), [2](#)

getSeqOccupancy, DNAString, PFMatrixList, numeric-method  
(getSeqOccupancy), [2](#)

getSeqOccupancy-methods  
(getSeqOccupancy), [2](#)

MatrixRider (MatrixRider-package), [2](#)

MatrixRider-package, [2](#)

PFMatrix, [2](#)

PFMatrixList, [2](#), [3](#)