

Package ‘POWSC’

November 7, 2025

Type Package

Title Simulation, power evaluation, and sample size recommendation for single cell RNA-seq

Version 1.19.0

Description Determining the sample size for adequate power to detect statistical significance is a crucial step at the design stage for high-throughput experiments. Even though a number of methods and tools are available for sample size calculation for microarray and RNA-seq in the context of differential expression (DE), this topic in the field of single-cell RNA sequencing is understudied. Moreover, the unique data characteristics present in scRNA-seq such as sparsity and heterogeneity increase the challenge. We propose POWSC, a simulation-based method, to provide power evaluation and sample size recommendation for single-cell RNA sequencing DE analysis. POWSC consists of a data simulator that creates realistic expression data, and a power assessor that provides a comprehensive evaluation and visualization of the power and sample size relationship.

License GPL-2

Encoding UTF-8

LazyData true

biocViews DifferentialExpression, ImmunoOncology, SingleCell, Software

Depends R (>= 4.1), Biobase, SingleCellExperiment, MAST

Imports pheatmap, ggplot2, RColorBrewer, grDevices, SummarizedExperiment, limma

Suggests rmarkdown, knitr, testthat (>= 3.0.0), BiocStyle

VignetteBuilder knitr

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/POWSC>

git_branch devel

git_last_commit b092ca1

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23
Date/Publication 2025-11-06
Author Kenong Su [aut, cre],
Hao Wu [aut]
Maintainer Kenong Su <kenong.su@emory.edu>

Contents

Est2Phase	2
es_mef_sce	3
plot_POWSC	3
Power_Cont	4
Power_Disc	5
runDE	6
runMAST	7
runPOWSC	7
runSC2P	9
sce	9
Simulate2SCE	10
SimulateMultiSCEs	11
summary_POWSC	12
Index	13

Est2Phase	<i>Estimate characterized parameters for a given scRNA-seq data (SingleCellExperiment object or a count matrix).</i>
-----------	--

Description

These parameters include four gene-wise parameters and two cell-wise parameters.

Usage

```
Est2Phase(sce, low.prob = 0.99)
```

Arguments

- sce SingleCellExperiment object with assays(sce)[[1]] is the count matrix or input directly
- low.prob lower bound probability for phase I

Value

a list of needed estimated parameters

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(123)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
estParas = Est2Phase(sce)
```

es_mef_sce	<i>sample data for POWSC</i>
------------	------------------------------

Description

This dataset is obtained from GEO under accession number GSE29087. It is generated to profile the transcriptomes for 92 single cells consisting of mouse embryonic fibroblast (MEF) and embryonic stem (ES) cells (Islam et al., 2011). The average sequencing depth for the dataset is around half a million.

Usage

```
es_mef_sce
```

Format

A singlecellexperiment object contain the expressin data with two cell types

References

Islam, S., Kjällquist, U., Moliner, A., Zajac, P., Fan, J.-B., Lönnerberg, P., and Linnarsson, S. (2011). Characterization of the single-cell transcriptional landscape by highly multiplex RNA-seq. *Genome research*, 21(7), 1160–1167.

plot_POWSC	<i>plot the result use visualization.</i>
------------	---

Description

plot the result use visualization.

Usage

```
plot_POWSC(POWSCobj, Form = c("I", "II"), Cell_Type = c("PW", "Multi"))
```

Arguments

POWSCobj a POWSC object from runPOWSC

Form choose from "I" or "II".

Cell_Type choose from "PW" or "Multi"

Value

for multiple comparison cases, return the pheatmap; for the pairwise comparison, return the ggplot object.

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(12)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
est_Paras = Est2Phase(sce)
sim_size = c(100, 200) # A numeric vector
pow_rslt = runPOWSC(sim_size = sim_size, est_Paras = est_Paras, per_DE=0.05, DE_Method = "MAST", Cell_Type = "PW") #
plot_POWSC(pow_rslt, Form="II", Cell_Type = "PW") # Alternatively, we can use Form="I")
```

Power_Cont	<i>Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.</i>
------------	---

Description

Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.

Usage

```
Power_Cont(
  DErslt,
  simData,
  alpha = 0.1,
  delta = 0.5,
  strata = c(0, 10, 2^(seq_len(4)) * 10, Inf)
)
```

Arguments

Derslt	is from the DE analysis by MAST
simData	is the corresponding simulated scRNA-seq dataset (SingCellExperiment)
alpha	is the cutoff for the fdr which can be modified
delta	or the lfc is the cutoff ($=0.5$) used to determined the high DE genes for Form II
strata	can be modified by the user. By default, it is (0, 10], (10, 20], (20, 40], (40, 80], (80, Inf]

Value

a list of metrics for power analysis such as: stratified targeted power and marginal power.

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(123)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
estParas = Est2Phase(sce)
simData = Simulate2SCE(n=500, estParas1 = estParas, estParas2 = estParas)
Derslt = runDE(simData$sce)
Cont_pow = Power_Cont(Derslt, simData)
```

Power_Disc	<i>Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.</i>
------------	---

Description

Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.

Usage

```
Power_Disc(
  Derslt,
  simData,
  alpha = 0.1,
  delta = 0.1,
  strata = seq(0, 1, by = 0.2)
)
```

Arguments

Derslt	is from the DE analysis by MAST
simData	is the corresponding simulated scRNA-seq dataset (SingCellExperiment)
alpha	is the cutoff for the fdr which can be modified
delta	or the zero ratio change is the cutoff (≈ 0.1) used to determined the high DE genes for Form II
strata	can be modified by the user. By default, it is (0, 0.2], (0.2, 0.4], (0.4, 0.6], (0.6, 0.8], (0.8, 1]

Value

a list of metrics for power analysis such as: stratified targeted power and marginal power.

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(123)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
estParas = Est2Phase(sce)
simData = Simulate2SCE(n=1000, estParas1 = estParas, estParas2 = estParas)
DErslt = runDE(simData$sce)
Disc_pow = Power_Disc(DErslt, simData)
```

runDE	<i>A wrapper function for calling DE genes. This contains two methods: MAST and SC2P</i>
-------	--

Description

A wrapper function for calling DE genes. This contains two methods: MAST and SC2P

Usage

```
runDE(sce, DE_Method = c("MAST", "SC2P"))
```

Arguments

sce	is a simulated scRNA-seq dataset with two-group conditions, e.g., treatment vs control.
DE_Method	is a string chosen from "MAST" or "SC2P".

Value

a list of three tables: the first table summaries the DE result for both forms of DE genes. cont table represents the result for continuous case. disc table shows the result for discontinuous case.

Examples

```

data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(123)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
estParas = Est2Phase(sce)
simData = Simulate2SCE(n=100, estParas1 = estParas, estParas2 = estParas)
sim_sce = simData$sce
DErslt = runDE(sim_sce)

```

runMAST	<i>Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.</i>
---------	---

Description

Run DE analysis by using MAST. Here we output two result tables corresponding to two forms of DE genes. These parameters include four gene-wise parameters and two cell-wise parameters.

Usage

```
runMAST(sce)
```

Arguments

sce	is a simulated scRNA-seq dataset with two-group conditions, e.g., treatment vs control.
-----	---

Value

a list of three tables: the first table summaries the DE result for both forms of DE genes. cont table represents the result for continuous case. disc table shows the result for discontinuous case.

runPOWSC	<i>Estimate characterized parameters for a given scRNA-seq data (SingleCellExperiment object or a count matrix).</i>
----------	--

Description

These parameters include four gene-wise parameters and two cell-wise parameters.

Usage

```
runPOWSC(
  sim_size = c(50, 100, 200, 800, 1000),
  per_DE = 0.05,
  est_Paras,
  DE_Method = c("MAST", "SC2P"),
  Cell_Type = c("PW", "Multi"),
  multi_Prob = NULL,
  alpha = 0.1,
  disc_delta = 0.1,
  cont_delta = 0.5
)
```

Arguments

<code>sim_size</code>	a list of numbers
<code>per_DE</code>	the percentage of the DE genes.
<code>est_Paras</code>	the template parameter estimated from one cell type.
<code>DE_Method</code>	is a string chosen from "MAST" or "SC2P".
<code>Cell_Type</code>	is a string corresponding to the 1st scenario: same cell type comparison, and 2nd scenario: multiple cell types.
<code>multi_Prob</code>	is the mixture cell proportions which sum up to 1. If not summing up to 1, then the package will internally do the normalization procedure.
<code>alpha</code>	is the cutoff for the <i>fdr</i> which can be modified
<code>disc_delta</code>	or the zero ratio change is the cutoff (=0.1) used to determined the high DE genes for Form II.
<code>cont_delta</code>	or the <i>lfc</i> is the cutoff (=0.5) used to determined the high DE genes for Form II.

Value

POWSC object

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(12)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
est_Paras = Est2Phase(sce)
sim_size = c(100, 200) # A numeric vector
pow_rslt = runPOWSC(sim_size = sim_size, est_Paras = est_Paras, per_DE=0.05, DE_Method = "MAST", Cell_Type = "PW") #
```

runSC2P

Run DE analysis by using SC2P. Here we output two result tables corresponding to two forms of DE genes.

Description

Run DE analysis by using SC2P. Here we output two result tables corresponding to two forms of DE genes.

Usage

```
runSC2P(sce)
```

Arguments

sce is a simulated scRNA-seq dataset with two-group conditions, e.g., treatment vs control.

Value

a list of three tables: the first table summaries the DE result for both forms of DE genes. cont table represents the result for continuous case. disc table shows the result for discontinuous case.

sce

sample data for GSE67835

Description

This dataset is obtained from GEO under accession number GSE67835. It includes 7 patients about 466 cells to capture the cellular complexity of the adult and fetal human brain at a whole transcriptome level. Healthy adult temporal lobe tissue was obtained from epileptic patients during temporal lobectomy for medically refractory seizures.

Usage

```
sce
```

Format

A singlecellexperiment object contain the expressions data with three cell types about patient AS_7

Source

<https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE67835>

References

Darmanis, Spyros, et al. "A survey of human brain transcriptome diversity at the single cell level." Proceedings of the National Academy of Sciences 112.23 (2015): 7285-7290.

Simulate2SCE	<i>Simulate the data for two-group comparison; e.g., treatment v.s. control It simulates the DE changes in two forms corresponding two types of DE genes</i>
--------------	--

Description

Simulate the data for two-group comparison; e.g., treatment v.s. control It simulates the DE changes in two forms corresponding two types of DE genes

Usage

```
Simulate2SCE(n = 100, perDE = 0.05, estParas1, estParas2)
```

Arguments

n	the number of total cells for two groups
perDE	percentage of DE genes
estParas1	the set of parameters corresponding to cell type I
estParas2	the set of parameters corresponding to cell type II

Value

a list of metrics recording the changes in the generated data: such as the DE gene indices for Form I and II DE genes, and simulated expression data in singlecellexperiment format.

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(123)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
estParas = Est2Phase(sce)
simData = Simulate2SCE(n=100, estParas1 = estParas, estParas2 = estParas)
```

SimulateMultiSCEs	<i>Simulate the data for multiple-group comparisons; e.g., different cell types in blood It simulates the DE changes in two forms corresponding two types of DE genes</i>
-------------------	---

Description

Simulate the data for multiple-group comparisons; e.g., different cell types in blood It simulates the DE changes in two forms corresponding two types of DE genes

Usage

```
SimulateMultiSCEs(
  n = 1000,
  estParas_set,
  multiProb,
  delta1 = 0.1,
  delta2 = 0.5
)
```

Arguments

n	the number of total cells for multiple groups; e.g., 1000, 2000, and etc.
estParas_set	a set of parameters corresponding to different cell types.
multiProb	a vector of probabilities corresponding to each cell type. It is not necessary to sum up to 1 because POWSC will normalize internally.
delta1	the minimum of expression change used to determine the Form I DE.
delta2	the minimum of log fold change used to determine the Form II DE.

Value

a list of simulated datasets. Each dataset corresponds to a pair-wise comparison including a series of metrics such as the DE gene indices for Form I and II DE genes, and simulated expression data in singlecellexperiment format.

Examples

```
data("es_mef_sce")
set.seed(123)
rix = sample(1:nrow(es_mef_sce), 500)
es_mef_sce = es_mef_sce[rix, ]
sce1 = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
estParas1 = Est2Phase(sce1)
sce2 = es_mef_sce[, colData(es_mef_sce)$cellTypes == "stemCell"]
estParas2 = Est2Phase(sce2)
estParas_set = list(celltype1 = estParas1, celltype2 = estParas1, celltype3 = estParas2)
multiProb = c(0.2, 0.3, 0.5)
simData = SimulateMultiSCEs(n=200, estParas_set = estParas_set, multiProb = multiProb)
```

summary_POWSC	<i>summary of the result</i>
---------------	------------------------------

Description

summary of the result

Usage

```
summary_POWSC(POWSCobj, Form = c("I", "II"), Cell_Type = c("PW", "Multi"))
```

Arguments

- POWSCobj a POWSC object from runPOWSC
- Form choose from "I" or "II".
- Cell_Type choose from "PW" or "Multi".

Value

return the summary of the power including stratified, marginal, and overall power.

Examples

```
data("es_mef_sce")
sce = es_mef_sce[, colData(es_mef_sce)$cellTypes == "fibro"]
set.seed(12)
rix = sample(1:nrow(sce), 500)
sce = sce[rix, ]
est_Paras = Est2Phase(sce)
sim_size = c(100, 200) # A numeric vector
pow_rslt = runPOWSC(sim_size = sim_size, est_Paras = est_Paras, per_DE=0.05, DE_Method = "MAST", Cell_Type = "PW") #
summary_POWSC(pow_rslt, Form="II", Cell_Type = "PW")
```

Index

* datasets

es_mef_sce, [3](#)
sce, [9](#)

es_mef_sce, [3](#)
Est2Phase, [2](#)

plot_POWSC, [3](#)
Power_Cont, [4](#)
Power_Disc, [5](#)

runDE, [6](#)
runMAST, [7](#)
runPOWSC, [7](#)
runSC2P, [9](#)

sce, [9](#)
Simulate2SCE, [10](#)
SimulateMultiSCEs, [11](#)
summary_POWSC, [12](#)