

CURLOPT_PROXY_TRANSFER_MODE(3)curl_easy_setopt optionsCURLOPT_PROXY_TRANSFER_MODE(3)

NAME

CURLOPT_PROXY_TRANSFER_MODE – append FTP transfer mode to URL for proxy

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_PROXY_TRANSFER_MODE, long enabled);
```

DESCRIPTION

Pass a long. If the value is set to 1 (one), it tells libcurl to set the transfer mode (binary or ASCII) for FTP transfers done via a HTTP proxy, by appending ;type=a or ;type=i to the URL. Without this setting, or it being set to 0 (zero, the default), *CURLOPT_TRANSFERTEXT(3)* has no effect when doing FTP via a proxy. Beware that not all proxies support this feature.

DEFAULT

0, disabled

PROTOCOLS

FTP over proxy

EXAMPLE

TODO

AVAILABILITY

Added in 7.18.0

RETURN VALUE

Returns CURLE_OK if the option is supported, and CURLE_UNKNOWN_OPTION if the enabled value is not supported.

SEE ALSO

CURLOPT_PROXY(3), **CURLOPT_HTTPPROXYTUNNEL(3)**,